

The wwwacct Script

Overview

The `/scripts/wwwacct` script

Arguments and inputs

Example

Additional documentation

Overview

This script creates a cPanel account. This script also sets up the new account's domain information.

Note:

You can also create a account with the [WHM API 1 createacct](#) function.

The `/scripts/wwwacct` script

To use the `/scripts/wwwacct` script, run the following command as the `root` user:

```
/usr/local/cpanel/scripts/wwwacct <argument>
```

Arguments and inputs

You can use the following arguments with the `/scripts/wwwacct` script:

Argument	Type	Description	Possible values	Example
<code>domain</code>	<i>string</i>	Required The account's main domain name.	A valid domain name.	<code>example.com</code>
<code>user</code>	<i>string</i>	Required The account's username.	A valid username.	<code>user</code>
<code>pass</code>	<i>string</i>	Required The account's password.	A secure password.	<code>12345luggage</code>
<code>quota</code>	<i>integer</i>	The account's disk space quota. This parameter defaults to 0. (unlimited)	<ul style="list-style-type: none">An integer value between one and 999999 that represents a disk space quota in Megabytes (MB).0 — The account possesses unlimited disk space.	0
<code>cpmod</code>	<i>string</i>	The account's cPanel theme. This parameter defaults to the default package's <i>The me</i> setting.	<ul style="list-style-type: none"><code>paper_lantern</code>Another valid theme on the server.	<code>paper_lantern</code>
<code>ip</code>	<i>string</i>	Whether the account possesses a dedicated IP address. This parameter defaults to <code>n</code> .	<ul style="list-style-type: none"><code>y</code> — The account possesses a dedicated IP address.<code>n</code> — The account does not possess a dedicated IP address.	<code>n</code>

cgi	string	Whether the account has CGI access. This parameter defaults to the default package's <i>CGI Access</i> setting.	<ul style="list-style-type: none"> • y — CGI access. • n — No CGI access. 	y
frontpage	string	Whether Microsoft® FrontPage® Extensions exist on the account.	<ul style="list-style-type: none"> • y — Installed. • n — Not installed. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note: In cPanel & WHM version 11.46 and later, this value is always n.</p> </div>	n
maxftp	string	The account's maximum number of FTP accounts. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxsql	string	The account's maximum number of SQL databases. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxpop	string	The account's maximum number of email addresses. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxlst	string	The account's maximum number of Mailman mailing lists. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxsub	string	The account's maximum number of subdomains. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
bwlimit	string	The account's bandwidth quota. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
hasshell	string	Whether the account has shell access. This parameter defaults to the default package's <i>Shell Access</i> value	<ul style="list-style-type: none"> • y — Shell access. • n — No shell access. 	y
owner	string	The WHM account that owns this account. This parameter defaults to the user who runs the script.	<ul style="list-style-type: none"> • A valid reseller's username. • root 	root
plan	string	The account's hosting plan (package). This parameter defaults to unlimited.	A valid package name.	default

maxpark	string	<p>The account's maximum number of parked domains (aliases).</p> <p>This parameter defaults to the selected package's <i>Maximum Parked Domains</i> value.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited parked domains. 	unlimited
maxaddon	string	<p>The account's maximum number of addon domains.</p> <p>This parameter defaults to the selected package's <i>Maximum Addon Domains</i> value.</p>	<ul style="list-style-type: none"> A positive integer between one and 999,999. 0, unlimited, or null — The account possesses unlimited addon domains. 	unlimited
featurelist	string	<p>The account's feature list.</p> <p>This parameter defaults to the selected package's <i>Feature List</i> value.</p>	A valid feature list name on the server.	default
contactemail	string	<p>The account's contact email address.</p> <p>This parameter defaults to a null value.</p>	A valid email address.	user@example.com
use_registered_nameservers	string	<p>Whether to use the domain's registered nameservers instead of the server's nameservers.</p> <p>This parameter defaults to n.</p>	<ul style="list-style-type: none"> y — Use the domain's nameservers. n — Use the server's nameservers. 	n
language	string	<p>The account's locale.</p> <p>This parameter defaults to the selected package's <i>Locale</i> value.</p>	A valid locale name.	en
spamassassin	string	<p>Whether Apache SpamAssassin™ is enabled on the account.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: We added this parameter in cPanel & WHM version 70.</p> </div> <p>This parameter defaults to y</p>	<ul style="list-style-type: none"> y — Enabled. n — Disabled. 	y
spambox	string	<p>Whether to enable Spam Box on the account.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note:</p> <ul style="list-style-type: none"> You must enable Apache SpamAssassin if you call this parameter. We added this parameter in cPanel & WHM version 80. </div> <p>This parameter defaults to y (enabled).</p>	<ul style="list-style-type: none"> y — Enabled. n — Disabled. 	y

max_emailacct_quota	string	<p>The maximum quota for each email address in MB.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: We added this parameter in cPanel & WHM version 70.</p> </div> <p>This parameter defaults to the selected package's <i>Max Quota per Email Address (MB)</i> value.</p>	<ul style="list-style-type: none"> A positive integer between one and 4,294,967,296. unlimited — Unlimited. 	unlimited
---------------------	--------	---	---	-----------

Example

The following example creates the `example.com` cPanel account:

```
/usr/local/cpanel/scripts/wwwacct example.com user 12345luggage 0
paper_lantern n y n 0 0 0 0 0 0 y root default unlimited unlimited default
user@example.com 0 en y unlimited
```

Additional documentation

Suggested documentation [For cPanel users](#) [For WHM users](#) [For developers](#)

- [The wwwacct Script](#)
- [Create a New Account - Settings](#)
- [Create a New Account](#)
- [Create a New Account - Package](#)
- [Create a New Account - Domain Information](#)

- [User Manager](#)

- [How to Create a WHM Reseller Without An Associated Domain](#)
- [The wwwacct Script](#)
- [How to Create a Demo cPanel Account](#)
- [Create a New Account - Settings](#)
- [Create a New Account](#)

- [WHM API 0 Functions - createacct](#)
- [WHM API 1 Functions - createacct](#)
- [WHM API 1 Functions - setresellerips](#)
- [WHM API 0 Functions - listacIs](#)
- [WHM API 1 Functions - setresellermainip](#)