

WHM API 1 Functions - setresellerlimits

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Use WHM API to Call cPanel API & UAPI](#)

[accountsummary](#)

[applist](#)

[createacct](#)

[domainuserdata](#)

[editquota](#)

[forcepasswordchange](#)

[has_digest_auth](#)

[has_mycnf_for_cpuser](#)

[limitbw](#)

[listaccts](#)

[listlockedaccounts](#)

[listsuspended](#)

[modifyacct](#)

[myprivs](#)

[passwd](#)

[removeacct](#)

[set_digest_auth](#)

[showbw](#)

[suspendacct](#)

[unsuspendacct](#)

[untrack_acct_id](#)

[verify_new_username](#)

Description

This function sets a reseller's bandwidth and disk quotas.

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/setresellerlimits?api.version=1&user=username&enable_account_limit=0
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/setresellerlimits?api.version=1&user=username&enable_account_limit=0
```

```
whmapil setresellerlimits user=username enable_account_limit=0
```



Notes:

- You **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- We introduced this functionality in cPanel & WHM version 11.52.0.8.

```
{  "metadata": {    "version": 1,    "reason": "OK",    "result": 1,    "command": "setresellerlimits"  } }
```

```
<result>  <metadata>    <version>1</version>    <reason>OK</reason>    <result>1</result>    <command>setresellerlimits</command>  </metadata></result>
```



Note:

Use WHM's [API Shell](#) interface (`WHM >> Home >> Development >> API Shell`) to directly test WHM API calls.

Function information

API

Version:

[WHM API 1](#)

Available in:

WHM 11+

Methods:

GET, POST

Required

Parameters:

user

Return Format:

JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

restore_modules_summary

restore_queue_activate

restore_queue_add_task

restore_queue_clear_all_completed_tasks

restore_queue_clear_all_failed_tasks

restore_queue_clear_all_pending_tasks

restore_queue_clear_all_tasks

restore_queue_clear_completed_task

restore_queue_clear_pending_task

restore_queue_is_active

restore_queue_list_active

restore_queue_list_completed

restore_queue_list_pending

restore_queue_state

restoreaccount

verify_new_username_for_restore

convert_addon_fetch_conversion_details

convert_addon_fetch_domain_details





convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_addon_domains

convert_addon_list_conversions

Parameters

Parameter	Type	Description	Possible values	Example
user	string	Required The reseller's username.	A valid username on the server.	username
enable_account_limit	Boolean	Whether to limit the reseller's total number of accounts.  Note: Use this parameter with the <code>account_limit</code> parameter. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Limit. 0 — Do not limit. 	1
account_limit	integer	The reseller's maximum total number of accounts.  Important: The system only enforces this maximum if you set the <code>enable_account_limit</code> value to 1.	A positive integer that represents the maximum number of accounts that the reseller may access.	10
enable_resource_limits	Boolean	Whether to limit the reseller's resources.  Note: Use this parameter with the <code>bandwidthlimit</code> , <code>diskspace_limit</code> , <code>enable_overselling</code> , <code>enable_overselling_bandwidth</code> , <code>enable_overselling_diskspace</code> , <code>enable_package_limits</code> , and <code>enable_package_limit_numbers</code> parameters. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Limit resources. 0 — Do not limit resources. 	1
bandwidth_limit	integer	The reseller's total bandwidth limit.  Important: The system only enforces this limit if you set the <code>enable_resource_limits</code> value to 1.	<ul style="list-style-type: none"> A positive integer that represents the reseller's bandwidth limit, in Megabytes (MB). 0 — The reseller has unlimited bandwidth. 	0

- Some functions and parameters may require that the caller authenticate as the router.

[api_token_create](#)
[api_token_list](#)
[api_token_revoke](#)
[api_token_update](#)
[disable_authentication_provider](#)
[disable_failing_authentication_providers](#)
[enable_authentication_provider](#)
[link_user_authn_provider](#)
[get_available_authentication_providers](#)
[get_login_url](#)
[get_provider_client_configurations](#)
[get_provider_configuration_fields](#)
[get_provider_display_configurations](#)
[get_users_authn_linked_accounts](#)
[set_provider_client_configurations](#)
[set_provider_display_configurations](#)
[twofactorauth_disable_policy](#)
[twofactorauth_enable_policy](#)
[twofactorauth_generate_tfa_config](#)
[twofactorauth_get_issuer](#)
[twofactorauth_get_user_configs](#)
[twofactorauth_policy_status](#)

enable_overselling	<i>Boolean</i>	Whether the reseller can oversell accounts. Important: The system only enforces this limit if you set the <code>enable_resource_limits</code> value to 1.	<ul style="list-style-type: none"> 1 — The reseller can oversell accounts. 0 — The reseller cannot oversell accounts. 	0
enable_overselling_bandwidth	<i>Boolean</i>	Whether the reseller can oversell bandwidth. Important: The system only enforces this limit if you set the <code>enable_resource_limits</code> value to 1.	<ul style="list-style-type: none"> 1 — The reseller can oversell bandwidth. 0 — The reseller cannot oversell bandwidth. 	0
enable_overselling_diskspace	<i>Boolean</i>	Whether the reseller can oversell disk space. Important: The system only enforces this limit if you set the <code>enable_resource_limits</code> value to 1.	<ul style="list-style-type: none"> 1 — The reseller can oversell disk space. 0 — The reseller cannot oversell disk space. 	0
diskspace_limit	<i>integer</i>	The reseller's total disk space usage limit. Important: The system only enforces this limit if you set the <code>enable_resource_limits</code> value to 1.	<ul style="list-style-type: none"> A positive integer that represents the reseller's disk space limit, in Megabytes (MB). 0 — The reseller has unlimited disk space. 	0
enable_package_limits	<i>Boolean</i>	Whether to apply package limits to the reseller.	<ul style="list-style-type: none"> 1 — Enable package limits. 0 — Disable package limits. 	0
enable_package_limit_numbers	<i>Boolean</i>	Whether to apply package limit numbers to the reseller.	<ul style="list-style-type: none"> 1 — Enable package limit numbers. 0 — Disable package limit numbers. 	0

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

[twofactorauth_remove_user_config](#)

[twofactorauth_set_issuer](#)

[twofactorauth_set_tfa_config](#)

[unlink_user_authn_provider](#)

[validate_login_token](#)

[backup_config_get](#)

[backup_config_set](#)

[backup_date_list](#)

[backup_destination_add](#)

[backup_destination_delete](#)

[backup_destination_get](#)

[backup_destination_list](#)

[backup_destination_set](#)

[backup_destination_validate](#)

[backup_set_list](#)

[backup_skip_users_all](#)

[backup_skip_users_all_status](#)

[backup_user_list](#)

[convert_and_migrate_from_legacy_config](#)

[list_cparchive_files](#)

[start_background_pkgacct](#)

[toggle_user_backup_state](#)

[cphulk_status](#)

[create_cphulk_record](#)

[delete_cphulk_record](#)

Returns

This function only returns metadata.

- [WHM API 0 Functions - setresellermainip](#) — This function assigns a main IP address to a reseller's account.
- [WHM API 0 Functions - setresellernameservers](#) — This function assigns nameservers to a reseller's account.
- [WHM API 1 Sections - Resellers](#) — Reseller functions allow you to manage your cPanel and WHM reseller accounts.
- [WHM API 1 Functions - acctcounts](#) — This function lists a reseller's total accounts, suspended accounts, and account creation limit.
- [WHM API 1 Functions - getresellerips](#) — This function lists a reseller's available IP addresses.

disable_cphulk
enable_cphulk
flush_cphulk_login_history
flush_cphulk_login_history_for_ips
get_cphulk_brutes
get_cphulk_excessive_brutes
get_cphulk_failed_logins
load_cphulk_config
read_cphulk_records
save_cphulk_config
background_mysql_upgrade_status
current_mysql_version
installable_mysql_versions
latest_available_mysql_version
list_database_users
list_databases
list_mysql_databases_and_users
remote_mysql_create_profile
remote_mysql_create_profile_via_ssh
remote_mysql_delete_profile
remote_mysql_initiate_profile_activation
remote_mysql_monitor_profile_activation
remote_mysql_read_profile

remote_mysql
l_read_profiles

remote_mysql
l_update_profile

remote_mysql
l_validate_profile

rename_mysql
ql_database

rename_mysql
ql_user

rename_postgresql
database

rename_postgresql
user

set_local_mysql
root_password

set_mysql_password

set_postgresql
password

start_background_mysql
upgrade

adddns

addzonerecord

addzonerecord (Reverse
DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

killdns

listmxs

listzones

lookupnsip

lookupnsips

removezonerecord

resetzone

resolvedomainname

savemxs

setresolvers

ea4_get_currently_installed_packages

ea4_get_ea_pkgs_state

ea4_list_profiles

ea4_pre_migrate_check

ea4_recommendations

ea4_save_profile

cpgreylist_is_server_netblock_trusted

cpgreylist_list_entries_for_common_mail_provider

cpgreylist_load_common_mail_providers_config

cpgreylist_save_common_mail_providers_config

cpgreylist_status

cpgreylist_trusted_entries_for_common_mail_provider

cpgreylist_untrust_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_hosts

save_cpgreylist_config

batch
cpanel
create_integration_group
create_integration_link
get_integration_link_user_config
list_integration_groups
list_integration_links
remove_integration_group
remove_integration_link
update_integration_link_token
addips
delip
get_public_ip
get_shared_ip
ipv6_disable_account
ipv6_enable_account
ipv6_range_add
ipv6_range_edit
ipv6_range_list
ipv6_range_remove
ipv6_range_usage
listips
nat_checkip
nat_set_public_ip
setsiteip
disable_mail_sni
emailtrack_search
emailtrack_stats
emailtrack_user_stats

enable_mail_
sni

exim_configu
ration_check

expunge_mai
lbox_messag
es

expunge_me
ssages_for_
mailbox_guid

fetch_mail_q
ueue

generate_mo
bileconfig

get_mailbox_
status

get_mailbox_
status_list

get_user_em
ail_forward_d
estination

hold_outgoin
g_email

is_sni_suppo
rted

list_pops_for

mail_sni_stat
us

rebuild_mail_
sni_config

release_outg
oing_email

save_spamd_
_config

set_user_em
ail_forward_d
estination

suspend_out
going_email

unsuspend_o
utgoing_email

validate_curr
ent_installed
_exim_config

validate_exi
m_configurati
on_syntax

disable_mark
et_provider

enable_mark
et_provider

get_adjusted
_market_pro
viders_produ
cts

get_market_
providers_co
mmission_co
nfig

get_market_
providers_list

get_market_
providers_pr
oduct_metad
ata

get_market_
providers_pr
oducts

set_market_p
roduct_attri
bute

set_market_p
rovider_com
mission_id

modsec_add
_rule

modsec_add
_vendor

modsec_batc
h_settings

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disc
ard_rule_cha
nges

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_disc
ard_all_rule_
changes

modsec_edit
_rule

modsec_ena
ble_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_update_vendor

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage
create_featurelist
delete_featurelist
delpkgext
editpkg
get_available_featurelists
get_feature_metadata
get_feature_names
get_featurelist_data
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
package_manager_fixcache
package_manager_get_package_info
package_manager_resolve_actions
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature
php_get_handlers
php_get_affected_domains
php_get_installed_versions
php_get_system_default_version

php_get_vho
sts_by_versi
on

php_get_vho
st_versions

php_ini_get_
content

php_ini_get_
directives

php_ini_set_
content

php_ini_set_
directives

php_set_han
dler

php_set_syst
em_default_v
ersion

php_set_vho
st_versions

php_set_old_
fpm_flag

php_get_old_
fpm_flag

get_fpm_cou
nt_and_utiliz
ation

php_get_def
ault_account
s_to_fpm

php_set_defa
ult_accounts
_to_fpm

convert_all_d
omains_to_fpm

get_public_c
ontact

set_public_c
ontact

acctcounts

getresellerips

listacIs

listresellers

resellerstats

saveacllist

setacIs

setresellerips

setresellerlim
its

setresellerma
inip

setresellerna
meservers

setresellerpa
ckagelimit

setupreseller

suspendresel
ler

terminateres
eller

unsetupresell
er

unsuspendre
seller

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

delete_rpm_v
ersion

edit_rpm_ver
sion

enable_monit
or_all_enable
d_services

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_all_conta
ct_importanc
es

get_passwor
d_strength

get_remote_
access_hash

get_rpm_ver
sion_data

get_service_
config

get_service_
config_key

get_update_
availability

get_tweakset
ting

get_users_lin
ks

getdiskusage

gethostname

install_rpm_p
lugin

list_configclu
sterservers

list_rpms

loadavg

nvget

nvset

purchase_a_l
icense

reboot

remove_in_p
rogress_exim
_config_edit

restartservice

run_cpkeyclt

send_test_po
sturl

send_test_pu
shbullet_note

servicestatus

set_applicati
on_contact_e
vent_importa
nce

set_applicati
on_contact_i
mportance

set_primary_
servername

set_service_
config_key

set_tweakset
ting

sethostname

setminimump
asswordstren
gths

systemloada
vg

system_need
s_reboot

uninstall_rpm
_plugin

update_conf
gclusterserver

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushb
ullet_access

disable_auto
ssl

fetch_service
_ssl_compon
ents

fetch_ssl_cer
tificates_for_f
qdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_log

get_autossl_logs_catalog

get_autossl_pending_queue

get_autossl_pending_queue_for_domain

get_autossl_pending_queue_for_user

get_autossl_problems_for_domain

get_autossl_problems_for_user

get_autossl_providers

get_best_ssl_domain_for_service

install_service_ssl_certificate

installssl

listcrts

rebuildinstall_edssldb

rebuilduserssldb

reset_autossl_provider

reset_service_ssl_certificate

set_autossl_metadata

set_autossl_provider

start_autossl_check_for_all_users

start_autossl_check_for_one_user

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_s
upport_agree
ment

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remot
e_user_trans
fer_session

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version