

WHM API 1 Functions - generate_mobileconfig

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Use WHM API to Call cPanel API & UAPI](#)

[accountssummary](#)

[applist](#)

[createacct](#)

[domainuserdata](#)

[editquota](#)

[forcepasswordchange](#)

[has_digest_auth](#)

[has_mycnf_for_cpuser](#)

[limitbw](#)

[listaccts](#)

[listlockedaccounts](#)

[listsuspended](#)

[modifyacct](#)

[myprivs](#)

[passwd](#)

[removeacct](#)

[set_digest_auth](#)

[showbw](#)

[suspendacct](#)

[unsuspendacct](#)

[untrack_acct_id](#)

[verify_new_username](#)

Description

This function generates a mobile configuration profile for an email account.

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/generate_mobileconfig?api.version=1&account=username%40example.com&use_ssl=1
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/generate_mobileconfig?api.version=1&account=username@example.com&use_ssl=1
```

```
whmapil generate_mobileconfig account=username%40example.com use_ssl=1
```



Notes:

- You **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- We introduced this functionality in cPanel & WHM version 11.52.0.8.

```
{
  "data": {
    "payload": "
0\u00119\u0006\t*H\r\u0001\u0007\u0002\u0011*0\u0011&\u0002\u0001\u0001\u000b0\t\u0006\u0005+\u000e\u0003\u0002\u0001a\u0005\u0000\u000b\u0006\t*H\r\u0001\u0007\u0001\u000b3\u0004\u000b/<?xml version=\"1.0\" encoding=\"UTF-8\"?>\r\n<!DOCTYPE plist PUBLIC \"-//Apple//DTD PLIST 1.0//EN\" \"http://www.apple.com/DTDs/PropertyList-1.0.dtd\">\r\n<plist version=\"1.0\">\r\n<dict>\r\n<key>PayloadContent</key>\r\n<array>\r\n<dict>\r\n<key>EmailAccountDescription</key>\r\n<string>mister.bad@example.com</string>\r\n<key>EmailAccountName</key>\r\n<string>mister.bad@example.com</string>\r\n<key>EmailAccountType</key>\r\n<string>EmailTypeIMAP</string>\r\n<key>EmailAddress</key>\r\n<string>mister.bad@example.com</string>\r\n<key>IncomingMailServerAuthentication</key>\r\n<string>EmailAuthPassword</string>\r\n<key>IncomingMailServerHostName</key>\r\n<string>laurence.dev.cpanel.net</string>\r\n<key>IncomingMailServerPortNumber</key>\r\n<integer>993</integer>\r\n<key>IncomingMailServerUseSSL</key>\r\n<true>/>\r\n<key>IncomingMailServerUsername</key>\r\n<string>mister.bad@example.com</string>\r\n<key>OutgoingMailServerAuthentication</key>\r\n<string>EmailAuthPassword</string>\r\n<key>OutgoingMailServerHostName</key>\r\n<string>laurence.dev.cpanel.net</string>\r\n</dict>\r\n</array>\r\n</dict>\r\n</plist>\r\n"
  }
}
```

Function information

API

Version:

[WHM API 1](#)

Available in:

WHM 11.52+

Methods:

GET, POST

Required Parameters:

account, use_ssl

Return Format:

JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

restore_modules_summary
restore_queue_activate
restore_queue_add_task
restore_queue_clear_all_completed_tasks
restore_queue_clear_all_failed_tasks
restore_queue_clear_all_pending_tasks
restore_queue_clear_all_tasks
restore_queue_clear_completed_task
restore_queue_clear_pending_task
restore_queue_is_active
restore_queue_list_active
restore_queue_list_completed
restore_queue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore
convert_addon_fetch_conversion_details
convert_addon_fetch_domain_details
convert_addon_get_conversion_status
convert_addon_initiate_conversion
convert_addon_list_addon_domains
convert_addon_list_conversions

```
/key>\r\n      <string>laurence.dev.cpanel.net<
/strings>\r\n      <key>OutgoingMailServerPortNumber<
/key>\r\n      <integer>465</integer>\r\n
<key>OutgoingMailServerUseSSL</key>\r\n      <true
/>\r\n      <key>OutgoingMailServerUsername<
/key>\r\n      <string>mister.bad@example.com<
/strings>\r\n
<key>OutgoingPasswordSameAsIncomingPassword<
/key>\r\n      <true/>\r\n      <key>PayloadDescription<
/key>\r\n      <string>username@example.com Secure Email
Setup</string>\r\n      <key>PayloadDisplayName<
/key>\r\n      <string>username@example.com Secure Email
Setup</string>\r\n      <key>PayloadIdentifier<
/key>\r\n      <string>cpanel.mail.org.mister.bad.example.
com</string>\r\n      <key>PayloadOrganization<
/key>\r\n      <string>example.com</string>\r\n
<key>PayloadType</key>\r\n      <string>com.apple.mail.
managed</string>\r\n      <key>PayloadUUID</key>\r\n
<string>6de23f78-a548-8c49-b060-4c4dd39c5db0<
/strings>\r\n      <key>PayloadVersion</key>\r\n
<integer>1</integer>\r\n      <key>PreventAppSheet<
/key>\r\n      <false/>\r\n      <key>PreventMove<
/key>\r\n      <false/>\r\n      <key>SMIMEEnabled<
/key>\r\n      <false/>\r\n      </dict>\r\n      </array>\r\n
<key>PayloadDescription</key>\r\n      <string>mister.
bad@example.com Secure Email Setup</string>\r\n
<key>PayloadDisplayName</key>\r\n      <string>mister.
bad@example.com Secure Email Setup</string>\r\n
<key>PayloadIdentifier</key>\r\n      <string>cpanel.mail.org.
mister.bad.example.com</string>\r\n
<key>PayloadOrganization</key>\r\n      <string>cpanel.mail.
org.mister.bad.example.com</string>\r\n
<key>PayloadRemovalDisallowed</key>\r\n      <false/>\r\n
<key>PayloadType</key>\r\n      <string>Configuration<
/strings>\r\n      <key>PayloadUUID</key>\r\n
<string>3e259e6f-8edf-0041-7554-c6f0a4585f87<
/strings>\r\n      <key>PayloadVersion</key>\r\n      <integer>1<
/integer>\r\n</dict>\r\n<
/plist>\r\n\u0003o0\u0003k0\u0002S\u0003\u0002\u0001\u0002
\u0002\u0005\u00022;
`0\r\u0006\t*H\r\u0001\u0001\u0005\u0005\u0000\u0000N1
0\u0001e\u0006\u0003U\u0004\u0003\u0003\u0003f\u0017laurence.dev.
cpanel.net1*0
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.
net0\u001e\u0017\r140811190945Z\u0017\r150811190945Z0N1
0\u0001e\u0006\u0003U\u0004\u0003\u0003f\u0017laurence.dev.
cpanel.net1*0
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.net0\u0001\"
0\r\u0006\t*H\r\u0001\u0001\u0001\u0001\u0005\u0000\u0003\u0001\u0001\u0000
\u000f\u0000\u0001\u0001\u0002\u0001\u0001\u0001\u0000\u0000\u0000\u0000\u0010A)
\u0004%i$`/\u0004a\u0003_\u0017CvGoc\bH##!( *lhfno*.VR-
8\u0001d\u0019\";\rG\u0005:\u0007qH[>!
Ã^\u0015qi\u0006\u0014/\u001a{\u0001YJ0';
k|'GWx\u001c\u0005sRP/\u0018;Kw'\u001d|7zCy^Q|;
\u000e\u001c\u000bQ)\u001c\u001ak\u0018M}
\u0013\u0002\u0003\u0001\u0000\u0001\u0001\u0001\u0001\u001d\u0006\u0003
U\u001d\u000e\u0004\u0016\u0004\u0014V\u0003_\u001eX&vwk0\
u001f\u0006\u0003U\u001d#\u0004\u0018\u0016\u0014V\u0003_
\u001eX&vwk0\u0006\u0003U\u001d\u0013\u0004\u0005\u0003
\u0001\u00010\r\u0006\t*H\r\u0001\u0001\u0005\u0005\u0000\u0000\u0000
\u0003\u0001\u0001\u0000\u0004. ,\b8\u0007`0+RRH\u0016a\u0004H[S2
{-Y=^\" \u0018A1\u0010\u0014e\u0004{`ED|\u000f\u000e%b}AY]
; ]\u000b\u0000D)n\u0014\u000fv23\u001d\u000b\u0016xIGW%
A\u0000j\u0015Vx\u0012#Qe\u0013\u0003?
&FPk\u0013n\u0000SU51#0 :P~f\u0001f-
m\u001a5E<H\u0016ZO\nlD\u0019\u001bY\u0014\u0005iAcagVfLd1
\u0002Y0\u0002U\u0002\u0001\u0001\u00010W0N1
0\u0001e\u0006\u0003U\u0004\u0003\u0003f\u0017laurence.dev.
cpanel.net1*0
```

• S
o
m
e
f
u
n
c
t
i
o
n
s
a
n
d
p
a
r
a
m
e
t
e
r
s
m
a
y
r
e
q
u
i
r
e
t
h
a
t
t
h
e
c
a
l
l
e
r
a
u
t
h
e
n
t
i
c
a
t
e
a
s
t
h
e
r
o
t
u
s
e
r.

api_token_crate

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_authentication_providers

enable_authentication_provider

link_user_authn_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider_display_configurations

get_users_authn_linked_accounts

set_provider_client_configurations

set_provider_display_configurations

twofactorauth_disable_policy

twofactorauth_enable_policy

twofactorauth_generate_tfa_config

twofactorauth_get_issuer

twofactorauth_get_user_configs

twofactorauth_policy_status

```
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.net\u0002\u0005\u00022;
^0\t\u0006\u0005+\u000e\u0003\u0002\u001a\u0005\u0000\u00
18\u0006\t*H\r\u0001\t\u00031\u000b\u0006\t*H\r\u0001\u00
7\u00010\u001c\u0006\t*H\r\u0001\t\u00051\u000f\u0017\r15
602150437Z0#\u0006\t*H\r\u0001\t\u00041\u0016\u0004\u0014n
&\u0010mN\u0002nrA
{0\u001e0y\u0006\t*H\r\u0001\t\u000f110j0\u000b\u0006\t`H\
u0001e\u0003\u0004\u0001*0\u000b\u0006\t`H\u0001e\u0003\u0
004\u0001\u0016\u000b\u0006\t`H\u0001e\u0003\u0004\u0001\
u00020\n\u0006\b*H\r\u0003\u00070\u000e\u0006\b*H\r\u0003\
u0002\u0002\u0002\u0000\r\u0006\b*H\r\u0003\u0002\u0002\u
0001@0\u0007\u0006\u0005+\u000e\u0003\u0002\u00070\r\u0006
\b*H\r\u0003\u0002\u0002\u0001
(0\r\u0006\t*H\r\u0001\u0001\u0001\u0001\u0005\u0000\u0004\u0001
\u0000,ju\u001cCV@OS\r\u0004)x#{vD\u0014x>
[o\u00188\u0000\b)*\u001f(hIO-
^\u001a$\r\u001fn>&$RA\u001eJ+\u0013DC\u000f\u0004\u001a\u
0007L@_J|\u0017f\u0002\u000121'bp6"#i8uX\u0019 \u001c\b!}]
&\u0003G\u000bd[\u0015$_ulN\u0000D\u0018UD\r}*|5$x
/\u001f\f\u0006P}\u0011XN}w\u0011z[z|,lg*WM\u001eU!1"
},
"metadata":{
  "version":1,
  "reason":"OK",
  "result":1,
  "command":"generate_mobileconfig"
}
}
```

```
<result>
  <data>

  <payload>0\u00119\u0006\t*H\r\u0001\u0007\u0002\u0011*0\u0
011&\u0002\u0001\u00011\u000b0\t\u0006\u0005+\u000e\u0003\
u0002\u001a\u0005\u0000\u000b\u0006\t*H\r\u0001\u0007\u00
001\u000b3\u0004\u000b/<?xml version=\"1.0\" encoding=\"
UTF-8\"?>\r\n<!DOCTYPE plist PUBLIC "-//Apple//DTD PLIST
1.0//EN\" \http://www.apple.com/DTDs/PropertyList-1.0.
dtd\">\r\n<plist version=\"1.0\">\r\n<dict>\r\n
<key>PayloadContent</key>\r\n  <array>\r\n
<dict>\r\n    <key>EmailAccountDescription<
/key>\r\n      <string>mister.bad@example.com<
/string>\r\n    <key>EmailAccountName</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>EmailAccountType</key>\r\n
<string>EmailTypeIMAP</string>\r\n      <key>EmailAddress<
/key>\r\n        <string>mister.bad@example.com<
/string>\r\n      <key>IncomingMailServerAuthentication<
/key>\r\n        <string>EmailAuthPassword<
/string>\r\n        <key>IncomingMailServerHostName<
/key>\r\n          <string>laurence.dev.cpanel.net<
/string>\r\n        <key>IncomingMailServerPortNumber<
/key>\r\n          <integer>993</integer>\r\n
<key>IncomingMailServerUseSSL</key>\r\n      <true
/>\r\n      <key>IncomingMailServerUsername<
/key>\r\n        <string>mister.bad@example.com<
/string>\r\n      <key>OutgoingMailServerAuthentication<
/key>\r\n        <string>EmailAuthPassword<
/string>\r\n        <key>OutgoingMailServerHostName<
/key>\r\n          <string>laurence.dev.cpanel.net<
/string>\r\n        <key>OutgoingMailServerPortNumber<
/key>\r\n          <integer>465</integer>\r\n
<key>OutgoingMailServerUseSSL</key>\r\n      <true
/>\r\n      <key>OutgoingMailServerUsername<
/key>\r\n        <string>mister.bad@example.com<
/string>\r\n      <key>OutgoingPasswordSameAsIncomingPassword<
```

• Y
o
u
m
u
s
t
u
s
e
t
h
e
a
p
p
r
o
p
r
i
a
t
e
W
H
M
P
o
r
t
s
(
2
0
8
6
o
r
2
0
8
7
)
to
c
a
l
l
W
H
M
A
P
I
f
u
n
c
t
i
o
n
s.

Find a function

Related functions

twofactorauth_remove_use_r_config

twofactorauth_set_issuer

twofactorauth_set_tfa_config

unlink_user_authn_provider

validate_login_token

backup_config_get

backup_config_set

backup_date_list

backup_destination_add

backup_destination_delete

backup_destination_get

backup_destination_list

backup_destination_set

backup_destination_validate

backup_set_list

backup_skip_users_all

backup_skip_users_all_status

backup_user_list

convert_and_migrate_from_legacy_config

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

cpbulk_status

create_cpbulk_record

delete_cpbulk_record

```

/key>\r\n      <true/>\r\n      <key>PayloadDescription<
/key>\r\n      <string>mister.bad@example.com Secure
Email Setup</string>\r\n      <key>PayloadDisplayName<
/key>\r\n      <string>mister.bad@example.com Secure
Email Setup</string>\r\n      <key>PayloadIdentifier<
/key>\r\n      <string>cpanel.mail.org.mister.bad.example.
com</string>\r\n      <key>PayloadOrganization<
/key>\r\n      <string>example.com</string>\r\n
<key>PayloadType</key>\r\n      <string>com.apple.mail.
managed</string>\r\n      <key>PayloadUUID</key>\r\n
<string>6de23f78-a548-8c49-b060-4c4dd39c5db0<
/string>\r\n      <key>PayloadVersion</key>\r\n
<integer>1</integer>\r\n      <key>PreventAppSheet<
/key>\r\n      <false/>\r\n      <key>PreventMove<
/key>\r\n      <false/>\r\n      <key>SMIMEEnabled<
/key>\r\n      <false/>\r\n      </dict>\r\n      </array>\r\n
<key>PayloadDescription</key>\r\n      <string>mister.
bad@example.com Secure Email Setup</string>\r\n
<key>PayloadDisplayName</key>\r\n      <string>mister.
bad@example.com Secure Email Setup</string>\r\n
<key>PayloadIdentifier</key>\r\n      <string>cpanel.mail.org.
mister.bad.example.com</string>\r\n
<key>PayloadOrganization</key>\r\n      <string>cpanel.mail.
org.mister.bad.example.com</string>\r\n
<key>PayloadRemovalDisallowed</key>\r\n      <false/>\r\n
<key>PayloadType</key>\r\n      <string>Configuration<
/string>\r\n      <key>PayloadUUID</key>\r\n
<string>3e259e6f-8edf-0041-7554-c6f0a4585f87<
/string>\r\n      <key>PayloadVersion</key>\r\n      <integer>1<
/integer>\r\n</dict>\r\n<
/plist>\r\n\u0003o0\u0003k0\u0002S\u0003\u0002\u0001\u0002
\u0002\u0005\u00022;
`0\r\u0006\t*H\r\u0001\u0001\u0005\u0005\u00000N1
0\u0001e\u0006\u0003U\u0004\u0003f\u0017laurence.dev.
cpanel.net1*0
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.
net0\u001e\u0017\r140811190945Z\u0017\r150811190945Z0N1
0\u0001e\u0006\u0003U\u0004\u0003f\u0017laurence.dev.
cpanel.net1*0
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.net0\u0001"
0\r\u0006\t*H\r\u0001\u0001\u0001\u0005\u0000\u0003\u0001\
\u000f\u0000\u0001\u0002\u0001\u0001\u0000\u0000zVvY%#\u0010A)
\u0004%i$}`/\u0004a\u0003_\u0017CvGoc\bH##!( *lhfn0* .VR-
8\u001d\u0019" ;\rG\u0005:\u0007qH[> !
Ã^\u0015qi\u0006\u0014/\u001a{\u0001YJ0' ;
k| 'GWx\u001e\u0005sRP/\u0018;Kw' \u001d|7zCy^Q| ;
\u000e\u000bQ)\fHg)0\u001ak\u0018M}
\u0013\u0002\u0003\u0001\u0000\u0001P0N0\u001d\u0006\u0003
U\u001d\u000e\u0004\u0016\u0004\u0014V\u0003_\u001eX&vWk0\
\u001f\u0006\u0003U\u001d#\u0004\u0018\u0016\u0014V\u0003_
\u001eX&vWk0f\u0006\u0003U\u001d\u0013\u0004\u00050\u0003
\u0001\u00010\r\u0006\t*H\r\u0001\u0001\u0005\u0005\u0000\
\u0003\u0001\u0001\u0004. , \b8\u0007`0+RRH\u0016a\u0004H[S2
{-Y=^"\u0018A1\u0010\u0014e\u0004{ `ED|\u000f\u000e%b}AY]
; ]\u000b\u0000D)n\u0014\u000fV23\u001d\u000b\u0016xIGW%
A\u0000j\u0015Vx\u0012#Qe\fvn\u0013\u0003?
&FPk\u0013n\u0000SU51#0 :P~f\u0001f-
m\u001a5E<H\u0016ZO\ndl\u0019\u001bY\u0014\u0005iAcagVfLd1
\u0002Y0\u0002U\u0002\u0001\u00010W0N1
0\u001e\u0006\u0003U\u0004\u0003f\u0017laurence.dev.
cpanel.net1*0
(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.
cpanel.net\u0002\u0005\u00022;
`0\t\u0006\u0005+\u000e\u0003\u0002\u001a\u0005\u00000\u00
18\u0006\t*H\r\u0001\t\u00031\u000b\u0006\t*H\r\u0001\u000
7\u00010\u001c\u0006\t*H\r\u0001\t\u00051\u000f\u0017\r150
602150437Z0#\u0006\t*H\r\u0001\t\u00041\u0016\u0004\u0014n
&\u0010mN\u0002nrA
{o\u001e0y\u0006\t*H\r\u0001\t\u000f110j0\u000b\u0006\t`H\

```

- WHM API 1 Sections - Mail — Mail functions manage your server's mail configurations.
- WHM API 1 Functions - emailtrack_search — This function retrieves email delivery records.
- WHM API 1 Functions - emailtrack_stats — This function retrieves email tracking statistics.
- WHM API 1 Functions - emailtrack_user_stats — This function retrieves email tracking statistics for each user.
- WHM API 1 Functions - expunge_messages_for_mailbox_guid — This function removes mail messages from a cPanel account.

[disable_cphulk](#)
[enable_cphulk](#)
[flush_cphulk_login_history](#)
[flush_cphulk_login_history_for_ips](#)
[get_cphulk_rules](#)
[get_cphulk_excessive_brutes](#)
[get_cphulk_failed_logins](#)
[load_cphulk_config](#)
[read_cphulk_records](#)
[save_cphulk_config](#)
[background_mysql_upgrade_status](#)
[current_mysql_version](#)
[installable_mysql_versions](#)
[latest_available_mysql_version](#)
[list_database_users](#)
[list_databases](#)
[list_mysql_databases_and_users](#)
[remote_mysql_create_profile](#)
[remote_mysql_create_profile_via_ssh](#)
[remote_mysql_delete_profile](#)
[remote_mysql_initiate_profile_activation](#)
[remote_mysql_monitor_profile_activation](#)
[remote_mysql_read_profile](#)

```

u0001e\u0003\u0004\u0001*0\u000b\u0006\t`H\u0001e\u0003\u0004\u0001\u0001\u0016\u000b\u0006\t`H\u0001e\u0003\u0004\u0001\u0002\u0002\u0006\b*H\r\u0003\u0007\u000e\u0006\b*H\r\u0003\u0002\u0002\u0000\r\u0006\b*H\r\u0003\u0002\u0002\u0001@0\u0007\u0006\u0005+\u000e\u0003\u0002\u0007\u0006\b*H\r\u0003\u0002\u0002\u0001
(0\r\u0006\t`H\r\u0001\u0001\u0001\u0005\u0000\u0004\u0001\u0000,ju\u001cCV@OS\r\u0004)x#{vD\u0014x>
[o\u00188\u0000\b)*\u001f(hIO-
^\u001a$\r\u001fn>&$RA\u001eJ+\u0013DC\u000f\u0004\u001a\u0007L@_J|\u0017f\u0002\u0002121'bp6\"#i8uX\u0019 \u001c\b!}]&\u0003G'\u000bd[\" \u0015$_ulN\u0000D\u0018UD\r}*|5$x
/\u001f\f\u0006P}\u0011XN}w\u0011z[z|,lg*WM\u001eU!1<
/payload>
<metadata>
  <version>1</version>
  <reason>OK</reason>
  <result>1</result>
  <command>generate_mobileconfig</command>
</metadata>
</result>

```



Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
account	<i>string</i>	Required The email account.	A valid email account.	username@example.com
use_ssl	<i>Boolean</i>	Required Whether to use an SSL-encrypted connection.	<ul style="list-style-type: none"> 1 — Use an SSL-encrypted connection. 0 — Do not use an SSL-encrypted connection. 	1

Returns

Return	Type	Description	Possible values	Example
payload	<i>binary</i>	The function's raw output.	A valid binary of an Apple® mobile configuration file that contains a series of sub-tags and keys. For more information, read Apple's key reference .	<pre> 0\u00119\u0006\t`H\r\u0001\u0007\u0002\u0011*0\u0011&\u0002\u0001\u00011\u000b0\t\u0006\u0005+\u000e\u0003\u0002\u001a\u0005\u0000\u000b\u0006\t`H\r\u0001\u0007\u0001\u000b3\u0004\u000b/<?xml version=\"1.0\" encoding=\" UTF-8\"?>\r\n<!DOCTYPE plist PUBLIC \"-//Apple//DTD PLIST 1.0 //EN\" \"http://www.apple.com /DTDs/PropertyList-1.0.dtd\" >\r\n version=\"1.0\" </pre>

remote_mysql_read_profiles				>\r\n<dict>\r\n<key>PayloadContent</key>\r\n <array>\r\n<dict>\r\n<key>EmailAccountDescription</key>\r\n<string>mister.bad@example.com</string>\r\n<key>EmailAccountName</key>\r\n<string>mister.bad@example.com</string>\r\n<key>EmailAccountType</key>\r\n<string>EmailTypeIMAP</string>\r\n<key>EmailAddress</key>\r\n<string>mister.bad@example.com</string>\r\n<key>IncomingMailServerAuthentication</key>\r\n<string>EmailAuthPassword</string>\r\n<key>IncomingMailServerHostName</key>\r\n<string>laurence.dev.cpanel.net</string>\r\n<key>IncomingMailServerPortNumber</key>\r\n<integer>993</integer>\r\n<key>IncomingMailServerUseSSL</key>\r\n<true/>\r\n<key>IncomingMailServerUsername</key>\r\n<string>mister.bad@example.com</string>\r\n<key>OutgoingMailServerAuthentication</key>\r\n<string>EmailAuthPassword</string>\r\n<key>OutgoingMailServerHostName</key>\r\n<string>laurence.dev.cpanel.net</string>\r\n<key>OutgoingMailServerPortNumber</key>\r\n<integer>465</integer>\r\n<key>OutgoingMailServerUseSSL</key>\r\n<true/>\r\n<key>OutgoingMailServerUsername</key>\r\n<string>mister.bad@example.com</string>\r\n<key>OutgoingPasswordSameAsIncomingPassword</key>\r\n<true/>\r\n<key>PayloadDescription</key>\r\n<string>mister.bad@example.com Secure Email Setup</string>\r\n<key>PayloadDisplayName</key>\r\n<string>mister.bad@example.com Secure Email
remote_mysql_update_profile				
remote_mysql_validate_profile				
rename_mysql_database				
rename_mysql_user				
rename_postgresql_database				
rename_postgresql_user				
set_local_mysql_root_password				
set_mysql_password				
set_postgresql_password				
start_background_mysql_upgrade				
adddns				
addzonerecord				
addzonerecord (Reverse DNS)				
dumpzone				
editzonerecord				
get_nameserver_config				
getzonerecord				
killdns				
listmxs				
listzones				
lookupnsip				
lookupnsips				
removezonerecord				
resetzone				
resolvedomainname				
savemxs				
setresolvers				

ea4_get_currently_installed_packages					Setup</string>\r\n
ea4_get_ea_pkgs_state					<key>PayloadIdentifier</key>\r\n
ea4_list_profiles					<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
ea4_pre_migrate_check					<key>PayloadOrganization</key>\r\n
ea4_recommendations					<string>example.com</string>\r\n
ea4_save_profile					<key>PayloadType</key>\r\n
cpgreylist_is_server_netblock_trusted					<string>com.apple.mail.managed</string>\r\n
cpgreylist_list_entries_for_common_mail_provider					<key>PayloadUUID</key>\r\n
cpgreylist_load_common_mail_provider_s_config					<string>6de23f78-a548-8c49-b060-4c4dd39c5db0</string>\r\n
cpgreylist_save_common_mail_provider_s_config					<key>PayloadVersion</key>\r\n
cpgreylist_status					<integer>1</integer>\r\n
cpgreylist_trust_entries_for_common_mail_provider					<key>PreventAppSheet</key>\r\n
cpgreylist_untrust_entries_for_common_mail_provider					<false>\r\n
create_cpgreylist_trusted_host					<key>PreventMove</key>\r\n
delete_cpgreylist_trusted_host					<false>\r\n
disable_cpgreylist					<key>SMIMEEnabled</key>\r\n
enable_cpgreylist					<false>\r\n
load_cpgreylist_config					</dict>\r\n </array>\r\n
read_cpgreylist_deferred_entries					<key>PayloadDescription</key>\r\n
read_cpgreylist_trusted_host					<string>mister.bad@example.com Secure Email Setup</string>\r\n
save_cpgreylist_config					<key>PayloadDisplayName</key>\r\n
					<string>mister.bad@example.com Secure Email Setup</string>\r\n
					<key>PayloadIdentifier</key>\r\n
					<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
					<key>PayloadOrganization</key>\r\n
					<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
					<key>PayloadRemovalDisallowed</key>\r\n
					<false>\r\n
					<key>PayloadType</key>\r\n
					<string>Configuration</string>\r\n
					<key>PayloadUUID</key>\r\n
					<string>3e259e6f-8edf-0041-7554-c6f0a4585f87</string>\r\n
					<key>PayloadVersion</key>\r\n
					<integer>1</integer>\r\n
					</dict>\r\n
					</plist>\r\n\u0003o0\u0003k0\u0002S\u0003\u0002\u0001\u0002\u0002\u0005\u00022;

batch				<pre> `0\r\u0006\t*H\r\u0001\u0001\ u0005\u0005\u00000N1 0\u001e\u0006\u0003U\u0004\u0 003\f\u0017laurence.dev. cpanel.net1*0 (\u0006\t*H\r\u0001\t\u0001\u 0016\u001bssl@laurence.dev. cpanel. net0\u001e\u0017\r14081119094 5Z\u0017\r150811190945Z0N1 0\u001e\u0006\u0003U\u0004\u0 003\f \u0017laurence.dev.cpanel. net1*0 (\u0006\t*H\r\u0001\t\u0001\u 0016 \u001bssl@laurence.dev. cpanel.net0\u0001\" 0\r\u0006\t*H\r\u0001 \u0001\u0001\u0005\u0000\u000 3\u0001\u000f\u0000\u0001\n\ u0002\u0001 \u0001\u0000UzVy#%\u0010A) \u0004%i\$}`/ \u0004a\u0003_\u0017Cv Goc\bH##!(*lhfn0* .VR-8 \u001d\u0019\"; \rG\u0005: \u0007qH[>! Ã^\u0015qi\u0006\u0014/\u001a {\u0001YJ0'; k 'GWx\u001c\u0005sRP/\u0018; Kw'\u001d 7zCy^Q ; \u000e\FP^\u000bQ)\fHg) 0\u001ak\u0018M} \u0013\u0002\u0003\u0001\u000 0\u0001P0N0\u001d\u0006\u0003 U\u001d\u000e\u0004\u0016\u00 04\u0014V\u0003_\u001eX&vwk0\ u001f\u0006\u0003U\u001d#\u00 04\u00180\u0016\u0014V\u0003_ \u001eX&vwk0\f\u0006\u0003U\u 001d\u0013\u0004\u00050\u0003 \u0001\u00010\r\u0006\t*H\r\u 0001\u0001\u0005\u0005\u0000\ u0003\u0001\u0001\u00004. , \b8\u0007`0+RRH\u0016a\u0004H [S2{-Y=^\" \u0018A1\u0010\u0014e\u0004 {`ED \u000f\u000e%b]AY];} \u000b\u0000D) n\u0014\u000fv23\u001d\u000b\ u0016xIGW% A\u0000j\u0015Vx\u0012#Qe\fvn \u0013\u0003? &FPk\u0013n\u0000SU51#0 :P~f\u001f- m\u001a5E<H\u0016ZO\n1D\u0019 \u001by\u0014\u0005iAcagVfLd1 \u0002Y0\u0002U\u0002\u0001\ 00010W0N1 0\u001e\u0006\u0003U\u0004\u0 003\f \u0017laurence.dev.cpanel. net1*0 (\u0006\t*H\r\u0001\t\u0001\u 0016 \u001bssl@laurence.dev. </pre>
cpanel				
create_integr ation_group				
create_integr ation_link				
get_integratio n_link_user_ config				
list_integratio n_groups				
list_integratio n_links				
remove_integr ation_group				
remove_integr ation_link				
update_integr ation_link_to ken				
addips				
delip				
get_public_ip				
get_shared_ip				
ipv6_disable_ account				
ipv6_enable_ account				
ipv6_range_a dd				
ipv6_range_e dit				
ipv6_range_li st				
ipv6_range_r emove				
ipv6_range_u sage				
listips				
nat_checkip				
nat_set_publi c_ip				
setsiteip				
disable_mail_ sni				
emailtrack_s earch				
emailtrack_st ats				
emailtrack_u ser_stats				

enable_mail_sni					cpanel. net\u0002\u0005\u00022; `0\t\u0006\u0005+ \u000e\u0003\u0002\u001a\u0005 5\u00000\u0018\u0006\t*H\r\u0001\t \u00031\u000b\u0006\t*H\r\u0001 01\u0007\u00010\u001c\u0006\t*H\r \u0001\t\u00051\u000f\u0017\r 150602150437Z0#\u0006\t*H\r\u0001\t \u00041\u0016\u0004\u0014n&\u0010mN\u0002nrA {o\u001e0y\u0006 \t*H\r\u0001\t\u000f110j0\u000b\u0006\t`H\u0001e\u0003\u0004\u0001*0 \u000b\u0006\t`H\u0001e\u0003\u0004\u0001\u00160\u000b\u0006\t`H \u0001e\u0003\u0004\u0001\u0020\n\u0006\b*H\r\u0003\u00070\u000e \u0006\b*H\r\u0003\u0002\u0002\u0002\u00000\r\u0006\b*H\r\u0003 \u0002\u0002\u0001@0\u0007\u0006\u0005+\u000e\u0003\u0002\u00070\r\u0006 \b*H\r\u0003\u0002\u0002\u0001 (0\r\u0006\t*H\r\u0001\u0001\u0001 \u0005\u0000\u0004\u0001\u0000,]\u001cCV@OS\r\u0004)x#{vD\u0014x>[o\u00188\u0000\b)*\u001f(hIO- ^\u001a\$\r\u001fn>&\$RA\u001eJ+\u0013DC\u000f\u0004\u001a\u0007L@_J \u0017f\u0002\u000121'bp6\"#i8uX\u0019 \u001c\b!]}&\u0003G` \u000bd [\" \u0015\$_u1N\u0000D\u0018UD\r} * 5\$x/\u001f\f\u0006P} \u0011XN}w\u0011z[z , lg*WM\u001eU!1
exim_configuration_check					
expunge_mailbox_messages					
expunge_messages_for_mailbox_guid					
fetch_mail_queue					
generate_mailconfig					
get_mailbox_status					
get_mailbox_status_list					
get_user_email_forward_destination					
hold_outgoing_email					
is_sni_supported					
list_pops_for					
mail_sni_status					
rebuild_mail_sni_config					
release_outgoing_email					
save_spamd_config					
set_user_email_forward_destination					
suspend_outgoing_email					
unsuspend_outgoing_email					
validate_current_installed_exim_config					
validate_exim_configuration_syntax					
disable_mail_provider					
enable_mail_provider					
get_adjusted_market_providers_products					

get_market_
providers_co
mmission_co
nfig

get_market_
providers_list

get_market_
providers_pr
oduct_metad
ata

get_market_
providers_pr
oducts

set_market_p
roduct_attrib
ute

set_market_p
rovider_com
mission_id

modsec_add
_rule

modsec_add
_vendor

modsec_batc
h_settings

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disc
ard_rule_cha
nges

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_disc
ard_all_rule_
changes

modsec_edit
_rule

modsec_ena
ble_vendor

modsec_ena
ble_vendor_c
onfigs

modsec_ena
ble_vendor_u
pdates

modsec_get_
config_text

modsec_get_
configs

modsec_get_
configs_with_
changes_pen
ding

modsec_get_
log

modsec_get_
rules

modsec_get_
settings

modsec_get_
vendors

modsec_is_i
nstalled

modsec_mak
e_config_acti
ve

modsec_mak
e_config_ina
ctive

modsec_prev
iew_vendor

modsec_rem
ove_rule

modsec_rem
ove_setting

modsec_rem
ove_vendor

modsec_repo
rt_rule

modsec_set_
config_text

modsec_set_
setting

modsec_undi
sable_rule

modsec_upd
ate_vendor

_getpkgexten
sionform

add_override
_features_for
_user

addpkg

addpkgext

changepackage
create_featurelist
delete_featurelist
delpkgext
editpkg
get_available_featurelists
get_feature_metadata
get_feature_names
get_featurelist_data
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
package_manager_fixcache
package_manager_get_package_info
package_manager_resolve_actions
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature
php_get_handlers
php_get_affected_domains
php_get_installed_versions
php_get_system_default_version

php_get_vho
sts_by_versi
on

php_get_vho
st_versions

php_ini_get_
content

php_ini_get_
directives

php_ini_set_
content

php_ini_set_
directives

php_set_han
dler

php_set_syst
em_default_v
ersion

php_set_vho
st_versions

php_set_old_
fpm_flag

php_get_old_
fpm_flag

get_fpm_cou
nt_and_utiliz
ation

php_get_def
ault_account
s_to_fpm

php_set_defa
ult_accounts
_to_fpm

convert_all_d
omains_to_fpm

get_public_c
ontact

set_public_c
ontact

acctcounts

getresellerips

listacIs

listresellers

resellerstats

saveacllist

setacIs

setresellerips

setresellerlim
its

setresellerma
inip

setresellerna
meservers

setresellerpa
ckagelimit

setupreseller

suspendresel
ler

terminateres
eller

unsetupresell
er

unsuspendre
seller

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

delete_rpm_v
ersion

edit_rpm_ver
sion

enable_monit
or_all_enable
d_services

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_all_conta
ct_importanc
es

get_passwor
d_strength

get_remote_
access_hash

get_rpm_ver
sion_data

get_service_
config

get_service_
config_key

get_update_
availability

get_tweakset
ting

get_users_lin
ks

getdiskusage

gethostname

install_rpm_p
lugin

list_configclu
sterservers

list_rpms

loadavg

nvget

nvset

purchase_a_l
icense

reboot

remove_in_p
rogress_exim
_config_edit

restartservice

run_cpkeyclt

send_test_po
sturl

send_test_pu
shbullet_note

servicestatus

set_applicati
on_contact_e
vent_importa
nce

set_applicati
on_contact_i
mportance

set_primary_
servername

set_service_
config_key

set_tweakset
ting

sethostname

setminimump
asswordstren
gths

systemloada
vg

system_need
s_reboot

uninstall_rpm
_plugin

update_conf
gclusterserver

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushb
ullet_access

disable_auto
ssl

fetch_service
_ssl_compon
ents

fetch_ssl_cer
tificates_for_f
qdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_log

get_autossl_logs_catalog

get_autossl_pending_queue

get_autossl_pending_queue_for_domain

get_autossl_pending_queue_for_user

get_autossl_problems_for_domain

get_autossl_problems_for_user

get_autossl_providers

get_best_ssl_domain_for_service

install_service_ssl_certificate

installssl

listcrts

rebuildinstall_edssldb

rebuilduserssldb

reset_autossl_provider

reset_service_ssl_certificate

set_autossl_metadata

set_autossl_provider

start_autossl_check_for_all_users

start_autossl_check_for_one_user

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_s
upport_agree
ment

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remot
e_user_trans
fer_session

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version