

# UAPI Functions - LangPHP::php\_get\_vhost\_versions

## Guide to UAPI

- [Return Data](#)
- [Filter Output](#)
- [Sort Output](#)
- [Paginate Output](#)
- [Output Columns](#)
- [Calls from the WHM API](#)
- [Custom UAPI Modules](#)

- Backup:: [fullbackup\\_to\\_ftp](#)
- Backup:: [fullbackup\\_to\\_homedir](#)
- Backup:: [fullbackup\\_to\\_scp\\_with\\_key](#)
- Backup:: [fullbackup\\_to\\_scp\\_with\\_password](#)
- Backup:: [list\\_backups](#)
- Backup:: [restore\\_databases](#)
- Bandwidth:: [get\\_enabled\\_protocols](#)
- Bandwidth:: [get\\_retention\\_periods](#)
- Bandwidth:: [query](#)
- Batch:: [strict](#)
- BoxTrapper:: [blacklist\\_messages](#)
- BoxTrapper:: [delete\\_messages](#)
- BoxTrapper:: [deliver\\_messages](#)
- BoxTrapper:: [get\\_configuration](#)
- BoxTrapper:: [get\\_email\\_template](#)
- BoxTrapper:: [get\\_log](#)
- BoxTrapper:: [get\\_message](#)
- BoxTrapper:: [get\\_status](#)
- BoxTrapper:: [ignore\\_messages](#)

## Description

This function returns the PHP version of every virtual host that a reseller controls.



### Note:

This document **only** applies to systems that run EasyApache 4.



### Important:

In cPanel & WHM version 76 and later, when you disable the `webServer` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

```
https://hostname.example.com:2083/cpsess#####/execute/LangPHP/php_get_vhost_versions
```



### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.
```

```
// List the user's virtual hosts and PHP versions.  
$get_vhost_versions = $cpanel->uapi(  
    'LangPHP', 'php_get_vhost_versions',  
);
```



### Note:

For more information, read our [Guide to the LiveAPI System](#).

```
my $cpliveapi = Cpanel::LiveAPI->new(); # Connect to cPanel - only do this once.
```

```
# List the user's virtual hosts and PHP versions.  
my $get_vhost_versions = $cpliveapi->uapi(  
    'LangPHP', 'php_get_vhost_versions',  
);
```



### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Function information

**Module:** LangPHP  
**API Version:** UAPI  
**Available in:** cPanel 11.52+  
**Methods:** GET, POST  
**Required Parameters:** (none)  
**Return Formats:** JSON, XML  
**Legacy Equivalents:** (none)

## About this module

The LangPHP module manages multi-PHP functionality.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.



### Notes:

BoxTrapper:: [list\\_email\\_templates](#)

BoxTrapper:: [list\\_queued\\_messages](#)

BoxTrapper:: [process\\_messages](#)

BoxTrapper:: [reset\\_email\\_template](#)

BoxTrapper:: [save\\_configuration](#)

BoxTrapper:: [save\\_email\\_template](#)

BoxTrapper:: [set\\_status](#)

BoxTrapper:: [whitelist\\_messages](#)

Brand:: [read](#)

Branding:: [file](#)

Branding:: [get\\_applications](#)

Branding:: [get\\_application\\_information](#)

Branding:: [get\\_available\\_applications](#)

Branding:: [get\\_information\\_for\\_applications](#)

Branding:: [image](#)

Branding:: [include](#)

Branding:: [spritelist](#)

CacheBuster:: [read](#)

CacheBuster:: [update](#)

Chkservd:: [get\\_exim\\_ports](#)

Chkservd:: [get\\_exim\\_ports\\_ssl](#)

Chrome:: [get\\_dom](#)

Contactus:: [is\\_enabled](#)

cPAddons:: [get\\_available\\_addons](#)

cPAddons:: [get\\_instance\\_settings](#)

cPAddons:: [list\\_addon\\_instances](#)

cPGreyList:: [disable\\_all\\_domains](#)

cPGreyList:: [disable\\_domains](#)

cPGreyList:: [enable\\_all\\_domains](#)

```
uapi --user=username LangPHP php_get_vhost_versions
```



#### Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local/cpanel/bin/uapi
```

- These functions may require specific features.
- To enable or disable features, use WHM's [Feature Manager](#) interface.
- Unless you call this API via the WHM

cPGreyList: enable\_domains

cPGreyList: has\_greylisting\_enabled

cPGreyList: list\_domains

DAV:: disable\_shared\_global\_addressbook

DAV:: enable\_shared\_global\_addressbook

DAV:: get\_calendar\_contacts\_config

DAV:: has\_shared\_global\_addressbook

DAV:: is\_dav\_service\_enabled

DAV:: is\_horde\_enabled

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

DomainInfo: domains\_data

DomainInfo: list\_domains

DomainInfo: main\_domain\_builtin\_subdomain\_aliases

DomainInfo: single\_domain\_data

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

DNSSEC:: activate\_zone\_key

DNSSEC:: add\_zone\_key

DNSSEC:: deactivate\_zone\_key

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: export\_zone\_key

DNSSEC:: fetch\_ds\_records

```
{
  "errors":null,
  "status":1,
  "messages":null,
  "data":[
    {
      "main_domain":1,
      "vhost":"blee.com",
      "version":"ea-php70",
      "account_owner":"root",
      "account":"blee",
      "documentroot":"/home/blee/public_html",
      "php_fpm":1,
      "phpversion_source":{
        "domain":"blee.com"
      },
      "homedir":"/home/blee",
      "php_fpm_pool_parms":{
        "pm_process_idle_timeout":10,
        "pm_max_requests":20,
        "pm_max_children":5
      }
    },
    {
      "php_fpm":0,
      "account":"blee",
      "documentroot":"/home/blee/first.blee.com",
      "php_fpm_pool_parms":{
      },
      "phpversion_source":{
        "domain":"first.blee.com"
      },
      "homedir":"/home/blee",
      "version":"ea-php70",
      "main_domain":0,
      "vhost":"first.blee.com",
      "account_owner":"root"
    },
    {
      "account_owner":"root",
      "vhost":"second.blee.com",
      "main_domain":0,
      "version":"ea-php56",
      "phpversion_source":{
        "system_default":1
      },
      "homedir":"/home/blee",
      "php_fpm_pool_parms":{
      },
      "php_fpm":0,
      "documentroot":"/home/blee/second.blee.com",
      "account":"blee"
    }
  ],
  "metadata":{
    "transformed":1
  },
  "warnings":null
}
```



**Note:**

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

M  
A  
P  
I  
,  
y  
o  
u  
m  
u  
s  
t  
u  
s  
e  
t  
h  
e  
a  
p  
p  
r  
o  
p  
r  
i  
e  
c  
P  
a  
n  
e  
l  
p  
o  
r  
t  
s  
(  
2  
0  
8  
2  
o  
r  
2  
0  
0  
8  
3  
).  
Y  
o  
u  
c  
a  
n  
a  
l  
s  
o  
c  
a  
l  
l  
s  
o  
m  
e  
f  
u  
n  
c  
t  
i  
o  
n  
s  
v  
i  
a  
c  
P  
a  
n  
e  
l's  
W  
e  
b  
m  
a  
i  
l  
p  
o  
r  
t  
s  
(  
2  
0  
0  
9  
5  
o  
r  
2  
0  
0  
9  
6  
).

DNSSEC:: import\_zone\_key

DNSSEC:: remove\_zone\_key

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

Email:: add\_spam\_filter

Email:: browse\_mailbox

Email:: change\_mx

Email:: check\_fastmail

Email:: check\_pipe\_forwarder

Email:: count\_auto\_responders

Email:: count\_filters

Email:: count\_forwarders

Email:: count\_lists

Email:: count\_pops

Email:: delete\_auto\_responder

Email:: delete\_domain\_forwarder

Email:: delete\_filter

Email:: delete\_forwarder

Email:: delete\_held\_messages

Email:: delete\_list

Email:: delete\_mx

Email:: delete\_pop

Email:: disable\_filter

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
	<i>array of hashes</i>	An array of hashes of the virtual host's suspended status, versions, virtual hosts, and accounts.	An array of hashes that contains the documentroot, main_domain, homedir, account, account_owner, php_fpm, version, and vhost returns, the phpversion_source array, and the php_fpm_pool_params hash.	
documentroot	<i>string</i>	The virtual host's document root. <div data-bbox="646 724 803 1039" style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"><p><b>Note:</b> We introduced this return in cPanel &amp; WHM version 54.</p></div>	A valid document root path.	/home/blee/public_html
version	<i>string</i>	The virtual host's PHP version. The function returns this value in the unnamed array.	<ul style="list-style-type: none"><li>ea-php54</li><li>ea-php55</li><li>ea-php56</li><li>ea-php70</li><li>ea-php71</li><li>ea-php72</li><li>inherit</li><li>Any custom PHP package name.</li></ul>	ea-php70
vhost	<i>string</i>	The virtual host's name. The function returns this value in the unnamed array.	A valid hostname.	blee.com
account	<i>string</i>	The account's name. The function returns this value in the unnamed array.	A valid cPanel account on the server.	blee
account_owner	<i>string</i>	The account's owner. The function returns this value in the unnamed array.	A valid cPanel account on the server.	blee

## Find a function

## Related functions

- [UAPI Modules - LangPHP](#) — The LangPHP module manages multi-PHP functionality.
- [UAPI Functions - LangPHP:: php\\_get\\_impacted\\_domains](#) — This function lists domains that obtain their PHP version from a specified PHP configuration.
- [UAPI Functions - LangPHP:: php\\_get\\_installed\\_versions](#) — This function lists the system's PHP versions.
- [UAPI Functions - LangPHP:: php\\_get\\_system\\_default\\_version](#) — This function lists the system's default PHP version.
- [UAPI Functions - LangPHP:: php\\_get\\_vhost\\_versions](#) — This function returns the PHP version of every virtual host that a reseller controls.

Email: [disable\\_mail\\_box\\_autocreate](#)

Email: [disable\\_spam\\_assassin](#)

Email: [disable\\_spam\\_autodelete](#)

Email: [disable\\_spam\\_box](#)

Email: [dispatch\\_client\\_settings](#)

Email: [edit\\_pop\\_quota](#)

Email: [enable\\_filter](#)

Email: [enable\\_mail\\_box\\_autocreate](#)

Email: [enable\\_spam\\_assassin](#)

Email: [enable\\_spam\\_box](#)

Email: [fetch\\_charmaps](#)

Email: [fts\\_rescan\\_mailbox](#)

Email: [generate\\_mailman\\_otp](#)

Email: [get\\_auto\\_responder](#)

Email: [get\\_charsets](#)

Email: [get\\_client\\_settings](#)

Email: [get\\_default\\_email\\_quota](#)

Email: [get\\_default\\_email\\_quota\\_mib](#)

Email: [get\\_disk\\_usage](#)

Email: [get\\_filter](#)

Email: [get\\_held\\_message\\_count](#)

Email: [get\\_lists\\_total\\_disk\\_usage](#)





Email: [get\\_mailbox\\_autocreate](#)

Email: [get\\_mailman\\_delegates](#)

Email: [get\\_main\\_account\\_disk\\_usage](#)

Email: [get\\_main\\_account\\_disk\\_usage\\_bytes](#)

Email: [get\\_max\\_email\\_quota](#)

main_domain	<i>Boolean</i>	<p>Whether the virtual host is the primary domain.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px;">  <b>Note:</b> We introduced this return in cPanel &amp; WHM version 54. </div> <p>The function returns this value in the unnamed array.</p>	<ul style="list-style-type: none"> <li>• <b>True</b> — The primary domain.</li> <li>• <b>False</b> — Not the primary domain.</li> </ul> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  <b>Note:</b> In cPanel &amp; WHM version 60 and earlier, this function returns the following possible values: <ul style="list-style-type: none"> <li>• 1 — The primary domain.</li> <li>• 0 — Not the primary domain.</li> </ul> </div>	True
homedir	<i>string</i>	<p>The virtual host's home directory.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px;">  <b>Note:</b> We introduced this return in cPanel &amp; WHM version 54. </div> <p>The function returns this value in the unnamed array.</p>	A valid home directory.	/home/blee
php_fpm_pool_params	<i>hash</i>	<p>A hash that contains the domain's PHP-FPM parameters.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 10px;">  <b>Note:</b> We introduced this return in cPanel &amp; WHM version 58. </div> <p>The function returns this value in the unnamed array.</p>	A hash that contains the pm_max_children, pm_process_idle_timeout, and pm_max_requests returns.	

<p>Email: <a href="#">get_max_email_quota_mib</a></p> <p>Email: <a href="#">get_pop_quota</a></p> <p>Email: <a href="#">get_spam_settings</a></p> <p>Email: <a href="#">get_webmail_settings</a></p> <p>Email: <a href="#">has_delegated_mailman_lists</a></p>	<p>m a x c h i l d r e n</p>	<p><i>integer</i></p>	<p>The maximum number of child pages per pool.</p> <p>The function returns this value in the <code>php_fpm_pool_params</code> hash.</p>	<p>A valid number of child pages.</p>	<p>5</p>
<p>Email: <a href="#">has_plaintext_authentication</a></p> <p>Email: <a href="#">hold_outgoing</a></p> <p>Email: <a href="#">is_integer</a></p> <p>Email: <a href="#">list_auto_responders</a></p> <p>Email: <a href="#">list_default_address</a></p> <p>Email: <a href="#">list_domain_forwarders</a></p> <p>Email: <a href="#">list_filters</a></p> <p>Email: <a href="#">list_filters_backups</a></p>	<p>p r o c e s s i d l e t i m e o u t</p>	<p><i>integer</i></p>	<p>A specified time of idleness before the system kills an FPM child process.</p> <p>The function returns this value in the <code>php_fpm_pool_params</code> hash.</p>	<p>A valid timeout value.</p>	<p>10</p>
<p>Email: <a href="#">list_forwards</a></p> <p>Email: <a href="#">list_forwards_backups</a></p> <p>Email: <a href="#">list_lists</a></p> <p>Email: <a href="#">list_mail_domains</a></p> <p>Email: <a href="#">list_mxns</a></p>	<p>m a x r e q u e s t s</p>	<p><i>integer</i></p>	<p>The maximum number of requests per pool.</p> <p>The function returns this value in the <code>php_fpm_pool_params</code> hash.</p>	<p>A valid number of requests.</p>	<p>20</p>
<p>Email: <a href="#">list_pops</a></p> <p>Email: <a href="#">list_pops_with_disk</a></p> <p>Email: <a href="#">list_system_filter_info</a></p> <p>Email: <a href="#">passwd_list</a></p> <p>Email: <a href="#">passwd_pop</a></p> <p>Email: <a href="#">release_outgoing</a></p> <p>Email: <a href="#">remove_mailman_delegates</a></p> <p>Email: <a href="#">reorder_filters</a></p> <p>Email: <a href="#">set_always_accept</a></p> <p>Email: <a href="#">set_default_address</a></p> <p>Email: <a href="#">set_list_privacy_options</a></p> <p>Email: <a href="#">stats_db_status</a></p>	<p>php_fpm</p>	<p><i>Boolean</i></p>	<p>Whether FPM is enabled on the virtual host.</p> <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"> <p><b>Note:</b></p> <p>We introduced this return in cPanel &amp; WHM version 60.</p> </div> <p>The function returns this value in the unnamed array.</p>	<ul style="list-style-type: none"> <li>• True — PHP-FPM enabled.</li> <li>• False — PHP-FPM not enabled.</li> </ul> <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"> <p><b>Note:</b></p> <p>In cPanel &amp; WHM version 60 and earlier, this function returns the following possible values:</p> <ul style="list-style-type: none"> <li>• 1 — PHP-FPM enabled.</li> <li>• 0 — PHP-FPM not enabled.</li> </ul> </div>	<p>1</p>

Email:: [store\\_filter](#)

Email:: [suspend\\_incoming](#)

Email:: [suspend\\_login](#)

Email:: [suspend\\_outgoing](#)

Email:: [trace\\_delivery](#)

Email:: [trace\\_filter](#)

Email:: [unsuspend\\_incoming](#)

Email:: [unsuspend\\_login](#)

Email:: [unsuspend\\_outgoing](#)

Email:: [verify\\_password](#)

EmailAuth:: [disable\\_dkim](#)

EmailAuth:: [enable\\_dkim](#)

EmailAuth:: [ensure\\_dkim\\_keys\\_exist](#)

EmailAuth:: [fetch\\_dkim\\_private\\_keys](#)

EmailAuth:: [install\\_dkim\\_private\\_keys](#)

EmailAuth:: [install\\_spf\\_records](#)

EmailAuth:: [validate\\_current\\_dkims](#)

EmailAuth:: [validate\\_current\\_ptrs](#)

EmailAuth:: [validate\\_current\\_spfs](#)

ExternalAuthentication:: [add\\_authn\\_link](#)

ExternalAuthentication:: [configured\\_modules](#)

ExternalAuthentication:: [get\\_authn\\_links](#)

ExternalAuthentication:: [has\\_external\\_auth\\_modules\\_configured](#)

ExternalAuthentication:: [remove\\_authn\\_link](#)

Features:: [get\\_feature\\_metadata](#)

Features:: [has\\_feature](#)

phpversion\_source

array

How the virtual host determines its PHP version.

An array that contains either the `system_default` or `domain` return.



**Notes:**

- **W**e **i**n **t**r **o** **d** **u** **c** **e** **d** **t** **i** **s** **r** **e** **t** **u** **r** **n** **i** **n** **c** **P** **a** **n** **e** **l** **&** **W** **H** **M** **v** **e** **r** **s** **i** **o** **n** **6** **2**.
- **I**n **c** **P** **a** **n** **e** **l** **&** **W** **H** **M** **v** **e** **r** **s** **i** **o** **n** **6** **4** **a** **n** **d** **l** **a** **t** **e** **r**, **t** **i** **s** **v** **a** **l** **u** **e** **r** **e** **t** **u** **r** **n** **s** **a** **n** **a** **r** **r** **a** **y**.



**Note:**

In cPanel & WHM version 62, this function returns one of the following values:

- `system:default`
- Any valid domain name, in `domain:example.com` format.

The function returns this value in the unnamed array.

Features:: [list\\_features](#)

Fileman:: [autocomplete\\_dir](#)

Fileman:: [empty\\_trash](#)

Fileman:: [get\\_file\\_content](#)

Fileman:: [get\\_file\\_information](#)

Fileman:: [list\\_files](#)

Fileman:: [save\\_file\\_content](#)

Fileman:: [transcode](#)

Fileman:: [upload\\_files](#)

Ftp:: [add\\_ftp](#)

Ftp:: [allows\\_anonymous\\_ftp](#)

Ftp:: [allows\\_anonymous\\_ftp\\_incoming](#)

Ftp:: [delete\\_ftp](#)

Ftp:: [ftp\\_exists](#)

Ftp:: [get\\_ftp\\_daemon\\_info](#)

Ftp:: [get\\_port](#)

Ftp:: [get\\_quota](#)

Ftp:: [get\\_welcome\\_message](#)

Ftp:: [kill\\_session](#)

Ftp:: [list\\_ftp](#)

Ftp:: [list\\_ftp\\_with\\_disk](#)

Ftp:: [list\\_sessions](#)

Ftp:: [passwd](#)

Ftp:: [server\\_name](#)

Ftp:: [set\\_anonymous\\_ftp](#)

Ftp:: [set\\_anonymous\\_ftp\\_incoming](#)

Ftp:: [set\\_homedir](#)


Ftp:: [set\\_quota](#)

Ftp:: [set\\_welcome\\_message](#)

Gpg:: [delete\\_keypair](#)

Gpg:: [export\\_public\\_key](#)

Gpg:: [export\\_secret\\_key](#)

	<code>domain</code>	<i>string</i>	<p>The domain the virtual host inherits its PHP version from.</p> <p>The function returns this value in the <code>phpversions_source</code> array.</p>	<p>Any valid domain name on the system.</p>	<code>blee.com</code>
	<code>system_default</code>	<i>integer</i>	<p>Whether the virtual host uses the system's default PHP version.</p> <p>The function returns this value in the <code>phpversions_source</code> array.</p>	<ul style="list-style-type: none"><li>1 — Uses the system default PHP version.</li></ul> <div style="border: 1px solid #f0e68c; padding: 5px;"><p> <b>Note:</b></p><p>The function <b>only</b> returns this value if true.</p></div>	<code>1</code>



Gpg:: [generate\\_key](#)

Gpg:: [import\\_key](#)

Gpg:: [list\\_public\\_keys](#)

Gpg:: [list\\_secret\\_keys](#)

ImageManager:: [convert\\_file](#)

ImageManager:: [create\\_thumbnails](#)

ImageManager:: [get\\_dimensions](#)

ImageManager:: [resize\\_image](#)

Integration:: [fetch\\_url](#)

KnownHosts:: [create](#)

KnownHosts:: [delete](#)

KnownHosts:: [update](#)

KnownHosts:: [verify](#)

LangPHP:: [php\\_get\\_domain\\_handler](#)

LangPHP:: [php\\_get\\_impacted\\_domains](#)

LangPHP:: [php\\_get\\_installed\\_versions](#)

LangPHP:: [php\\_get\\_system\\_default\\_version](#)

LangPHP:: [php\\_get\\_vhost\\_versions](#)

LangPHP:: [php\\_ini\\_get\\_user\\_basic\\_directives](#)

LangPHP:: [php\\_ini\\_get\\_user\\_content](#)

LangPHP:: [php\\_ini\\_get\\_user\\_paths](#)

LangPHP:: [php\\_ini\\_set\\_user\\_basic\\_directives](#)

LangPHP:: [php\\_ini\\_set\\_user\\_content](#)

LangPHP:: [php\\_set\\_vhost\\_versions](#)

LastLogin:: [get\\_last\\_or\\_current\\_logged\\_in\\_ip](#)

Locale:: [get\\_attributes](#)

Locale:: [list\\_locales](#)

Locale:: [set\\_locale](#)

LogManager:: [get\\_settings](#)

LogManager:: [list\\_archives](#)

LogManager:: [set\\_settings](#)

Mailboxes:: [expunge\\_mailbox\\_messages](#)

Mailboxes:: [expunge\\_messages\\_for\\_mailbox\\_guid](#)

Mailboxes:: [get\\_mailbox\\_status\\_list](#)

Mailboxes:: [has\\_utf8\\_mailbox\\_names](#)

Mailboxes:: [set\\_utf8\\_mailbox\\_names](#)

Market:: [cancel\\_pending\\_ssl\\_certificate](#)

Market:: [create\\_shopping\\_cart](#)

Market:: [get\\_all\\_products](#)

Market:: [get\\_certificate\\_status\\_details](#)

Market:: [get\\_login\\_url](#)

Market:: [get\\_pending\\_ssl\\_certificates](#)

Market:: [get\\_provider\\_specific\\_dcv\\_constraints](#)

Market:: [get\\_providers\\_list](#)

Market:: [get\\_ssl\\_certificate\\_if\\_available](#)

Market:: [process\\_ssl\\_pending\\_queue](#)

Market:: [request\\_ssl\\_certificates](#)

Market:: [set\\_status\\_of\\_pending\\_queue\\_items](#)

Market:: [set\\_url\\_after\\_checkout](#)

Market:: [validate\\_login\\_token](#)

Mime:: [add\\_handler](#)

Mime:: [add\\_hotlink](#)

Mime:: [add\\_mime](#)

Mime:: [add\\_redirect](#)

Mime:: [delete\\_handler](#)

Mime:: [delete\\_hotlink](#)

Mime:: [delete\\_mime](#)

Mime:: [delete\\_redirect](#)

Mime:: [list\\_handlers](#)

Mime:: [list\\_hotlinks](#)

Mime:: [list\\_mime](#)

Mime:: [list\\_redirects](#)

Mime:: [redirect\\_info](#)

ModSecurity:: [disable\\_all\\_domains](#)

ModSecurity:: [disable\\_domains](#)

ModSecurity:: [enable\\_all\\_domains](#)

ModSecurity:: [enable\\_domains](#)

ModSecurity:: [has\\_modsecurity\\_installed](#)

ModSecurity:: [list\\_domains](#)

Mysql:: [add\\_host](#)

Mysql:: [add\\_host\\_note](#)

Mysql:: [check\\_database](#)

Mysql:: [create\\_database](#)

Mysql:: [create\\_user](#)

Mysql:: [delete\\_database](#)

Mysql:: [delete\\_host](#)

Mysql:: [delete\\_user](#)

Mysql:: [dump\\_database\\_schema](#)

Mysql:: [get\\_host\\_notes](#)

Mysql:: [get\\_privileges\\_on\\_database](#)

Mysql:: [get\\_restrictions](#)

Mysql:: [get\\_server\\_information](#)

Mysql:: [list\\_databases](#)

Mysql:: [list\\_routines](#)

Mysql:: [list\\_users](#)

Mysql:: [locate\\_server](#)

Mysql:: rename\_data  
base

Mysql:: rename\_user

Mysql:: repair\_data  
base

Mysql:: revoke\_acc  
ess\_to\_database

Mysql:: set\_password

Mysql:: set\_privilege  
s\_on\_database

Mysql:: update\_privi  
leges

Notifications:: get\_n  
otifications\_count

NVData:: get

NVData:: set

Parser:: firstfile\_rela  
tive\_uri

PassengerApps:: di  
sable\_application

PassengerApps:: ed  
it\_application

PassengerApps:: en  
able\_application

PassengerApps:: en  
sure\_deps

PassengerApps:: lis  
t\_applications

PassengerApps:: re  
gister\_application

PassengerApps:: un  
register\_application

PasswdStrength:: g  
et\_required\_strength

Personalization::set

Personalization ::get

Postgresql:: create\_  
database

Postgresql:: create\_  
user

Postgresql:: delete\_  
database

Postgresql:: delete\_  
user

Postgresql:: get\_res  
trictions

Postgresql:: grant\_a  
ll\_privileges

Postgresql:: list\_dat  
abases

Postgresql:: list\_use  
rs

Postgresql:: rename  
\_database

Postgresql:: rename  
\_user

Postgresql:: rename  
\_user\_no\_password

Postgresql:: revoke  
\_all\_privileges

Postgresql:: set\_pas  
sword

Pushbullet:: send\_te  
st\_message

Quota:: get\_quota\_i  
nfo

Resellers:: list\_acc  
ounts

ResourceUsage:: g  
et\_usages

Restore:: directory\_l  
isting

Restore:: get\_users

Restore:: query\_file  
\_info

Restore:: restore\_file

ServerInformation::  
get\_information

Session:: create\_te  
mp\_user

SiteTemplates:: list\_  
site\_templates

SiteTemplates:: list\_  
user\_settings

SiteTemplates:: pub  
lish

SpamAssassin :: cle  
ar\_spam\_box

SpamAssassin:: get  
\_symbolic\_test\_na  
mes

SpamAssassin:: get  
\_user\_preferences

SpamAssassin:: up  
date\_user\_preferen  
ce

SSH:: get\_port

SSL:: add\_autossl\_  
excluded\_domains

SSL:: can\_ssl\_redir  
ect

SSL:: check\_shared\_  
\_cert

SSL:: delete\_cert

SSL:: delete\_csr

SSL:: delete\_key  
SSL:: delete\_ssl  
SSL:: disable\_mail\_sni  
SSL:: enable\_mail\_sni  
SSL:: fetch\_best\_for\_domain  
SSL:: fetch\_cert\_info  
SSL:: fetch\_certificates\_for\_fqdns  
SSL:: fetch\_key\_and\_cabundle\_for\_certificate  
SSL:: find\_certificates\_for\_key  
SSL:: find\_csrs\_for\_key  
SSL:: generate\_cert  
SSL:: generate\_csr  
SSL:: generate\_key  
SSL:: get\_autossl\_excluded\_domains  
SSL:: get\_autossl\_pending\_queue  
SSL:: get\_autossl\_problems  
SSL:: get\_cabundle  
SSL:: get\_cn\_name  
SSL:: install\_ssl  
SSL:: installed\_host  
SSL:: installed\_hosts  
SSL:: is\_autossl\_check\_in\_progress  
SSL:: is\_mail\_sni\_supported  
SSL:: is\_sni\_supported  
SSL:: list\_certs  
SSL:: list\_csrs  
SSL:: list\_keys  
SSL:: list\_ssl\_items  
SSL:: mail\_sni\_status  
SSL:: rebuild\_mail\_sni\_config  
SSL:: rebuildssldb

SSL:: remove\_autossl\_excluded\_domains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csr\_friendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: toggle\_ssl\_rejects\_for\_domains

SSL:: upload\_cert

SSL:: upload\_key

StatsBar:: get\_stats

Stats:: get\_bandwidth

Stats:: get\_site\_errors

Stats:: list\_analog\_by\_month

Stats:: list\_sites

Stats:: list\_stats\_by\_domain

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

SubDomain:: addsubdomain

Themes:: get\_theme\_base

Themes:: list

Themes:: update

Tokens:: create\_full\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

UserTasks:: delete

UserTasks:: retrieve

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

WebDisk:: delete\_user

WebDisk:: set\_home\_dir

WebDisk:: set\_password

WebDisk:: set\_permissions



WebmailApps:: [listw  
ebmailapps](#)

WebVhost:: [list\\_do  
mains](#)

WebVhost:: [list\\_ssl\\_  
capable\\_domains](#)

WordPressBackup::  
[any\\_running](#)

WordPressBackup::  
[cancel](#)

WordPressBackup::  
[cleanup](#)

WordPressBackup::  
[get\\_available\\_back  
ups](#)

WordPressBackup::  
[is\\_running](#)

WordPressBackup::  
[start](#)

WordPressInstance  
Manager:: [cancel\\_s  
can](#)

WordPressInstance  
Manager:: [cleanup\\_  
scan](#)

WordPressInstance  
Manager:: [change\\_  
admin\\_password](#)

WordPressInstance  
Manager:: [configure\\_  
autoupdate](#)

WordPressInstance  
Manager:: [get\\_api\\_  
version](#)

WordPressInstance  
Manager:: [get\\_insta  
nce\\_by\\_id](#)

WordPressInstance  
Manager:: [get\\_insta  
nces](#)

WordPressInstance  
Manager:: [get\\_lates  
t\\_wordpress\\_versio  
n\\_from\\_wordpress\\_  
org](#)

WordPressInstance  
Manager:: [get\\_scan  
\\_results](#)

WordPressInstance  
Manager:: [is\\_install  
able\\_addon\\_availab  
le](#)

WordPressInstance  
Manager:: [start\\_scan](#)

WordPressRestore::  
[any\\_running](#)

WordPressRestore::  
[cleanup](#)

WordPressRestore::

start