

WHM API 1 Functions - disable_autossl

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Call cPanel API 2 and UAPI](#)

Description

This function disables the AutoSSL feature.

[restore_modules_summary](#)

[restore_queue_activate](#)

[restore_queue_add_task](#)

[restore_queue_clear_all_completed_tasks](#)

[restore_queue_clear_all_failed_tasks](#)

[restore_queue_clear_all_pending_tasks](#)

[restore_queue_clear_all_tasks](#)

[restore_queue_clear_completed_task](#)

[restore_queue_clear_pending_task](#)

[restore_queue_is_active](#)

[restore_queue_list_active](#)

[restore_queue_list_completed](#)

[restore_queue_list_pending](#)

[restore_queue_state](#)

[restoreaccount](#)

[verify_new_username_for_restore](#)

Function information

API Version:
[WHM API 1](#)
Available in:
WHM 58+
Methods:
GET, POST
Required Parameters:
(none)
Return Format:
JSON, XML

Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

[accountsummary](#)
[applist](#)
[createacct](#)
[domainuserdata](#)
[editquota](#)
[forcepasswordchange](#)
[get_current_users_count](#)
[get_disk_usage](#)
[get_domain_info](#)
[getdomainowner](#)
[get_maximum_users](#)
[getminimumpasswordstrengths](#)
[has_digest_auth](#)
[has_mycnf_for_cpuser](#)
[limitbw](#)
[list_users](#)
[listaccts](#)
[listlockedaccounts](#)
[listsuspended](#)
[modifyacct](#)
[myprivs](#)
[passwd](#)
[quota_enabled](#)
[removeacct](#)
[set_digest_auth](#)
[showbw](#)
[suspendacct](#)
[unsuspendacct](#)
[untrack_acct_id](#)
[verify_new_username](#)
[convert_addon_fetch_conversion_details](#)

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/disable_autossl?api.version=1
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/disable_autossl?api.version=1
```

```
whmapil disable_autossl
```



Notes:

- Unless otherwise noted, you **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

```
{
  "metadata": {
    "reason": "OK",
    "command": "disable_autossl",
    "result": 1,
    "version": 1
  }
}
```

```
<result>
  <metadata>
    <version>1</version>
    <result>1</result>
    <reason>OK</reason>
    <command>disable_autossl</command>
  </metadata>
</result>
```



Note:

Use WHM's [API Shell](#) interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

- Some functions and parameters may require that you authenticate as the root user.

[convert_addon_fetch_domain_details](#)

This function does not accept parameters.

[convert_addon_get_conversion_status](#)

Returns

This function only returns metadata.

[convert_addon_initiate_conversion](#)

[convert_addon_list_addon_domains](#)

[convert_addon_list_conversions](#)

[api_token_create](#)

[api_token_list](#)

[api_token_revoke](#)

[api_token_update](#)

[disable_authentication_provider](#)

[disable_failing_authentication_providers](#)

[enable_authentication_provider](#)

[get_available_authentication_providers](#)

[get_login_url](#)

[get_provider_client_configurations](#)

[get_provider_configuration_fields](#)

[get_provider_display_configurations](#)

[get_users_authn_linked_accounts](#)

[link_user_authn_provider](#)

[set_provider_client_configurations](#)

[set_provider_display_configurations](#)

[twofactorauth_disable_policy](#)

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

[twofactorauth
_enable_policy](#)

[twofactorauth
_generate_tfa_config](#)

[twofactorauth
_get_issuer](#)

[twofactorauth
_get_user_configs](#)

[twofactorauth
_policy_status](#)

[twofactorauth
_remove_user_config](#)

[twofactorauth
_set_issuer](#)

[twofactorauth
_set_tfa_config](#)

[unlink_user_authn_provider](#)

[validate_login_token](#)

[backup_config_get](#)

[backup_config_set](#)

[backup_date_list](#)

[backup_destination_add](#)

[backup_destination_delete](#)

[backup_destination_get](#)

[backup_destination_list](#)

[backup_destination_set](#)

[backup_destination_validate](#)

[backup_get_transport_status](#)

[backup_list_transported](#)

[backup_set_list](#)

[backup_set_list_combined](#)

[backup_skip_users_all](#)

- [WHM API 1 Functions - is_sni_supported](#) — This function checks whether the server supports SNI (Server Name Indication).
- [WHM API 1 Sections - Security](#) — Security functions allow you to manage system security services.
- [WHM API 1 Functions - authorizesshkey](#) — This function authorizes a key to access the server via SSH.
- [WHM API 1 Functions - check_remote_ssh_connection](#) — This function tests an SSH connection to another server.
- [WHM API 1 Functions - convertopenssh_oputty](#) — This function converts an OpenSSH private key to a PuTTY key.

backup_skip
_users_all_status

backup_user
_list

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

participate_in_analytics

cphulk_status

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk_login_history

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brutes

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_user_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

background_mysql_upgrade_status

current_mysql
_version

installable_m
ysql_versions

latest_availa
ble_mysql_v
ersion

list_database
_users

list_databases

list_mysql_da
tabases_and
_users

remote_mysql
_create_profi
le

remote_mysql
_create_profi
le_via_ssh

remote_mysql
_delete_profi
le

remote_mysql
_initiate_prof
ile_activation

remote_mysql
_monitor_pr
ofile_activation

remote_mysql
_read_profile

remote_mysql
_read_profiles

remote_mysql
_update_pro
file

remote_mysql
_validate_pr
ofile

rename_mys
ql_database

rename_mys
ql_user

rename_post
gresql_datab
ase

rename_post
gresql_user

set_local_my
sql_root_pas
sword

set_mysql_p
assword

set_postgres
ql_password

start_backgro
und_mysql_u
pgrade

adddns

addzonereco
rd

addzonereco
rd (Reverse
DNS)

create_parke
d_domain_fo
r_user

dumpzone

editzonerecord

get_nameser
ver_config

getzonerecord

has_local_au
thority

killdns

listmxs

listzones

lookupnsip

lookupnsips

removezoner
ecord

resetzone

resolvedomai
nname

savemxs

setresolvers

update_nam
eservers_con
fig

ea4_get_curr
ently_installe
d_packages

ea4_get_ea_
pkgs_state

ea4_list_profi
les

ea4_metainfo

ea4_migration

ea4_pre_mig
rate_check

ea4_recomm
endations

ea4_save_pr
ofile

ea4_tomcat8
5_add

ea4_tomcat8
5_list

ea4_tomcat8
5_rem

cpgreylist_is_
server_netblo
ck_trusted

cpgreylist_list
_entries_for_
common_mai
l_provider

cpgreylist_lo
ad_common_
mail_provide
r_s_config

cpgreylist_sa
ve_common_
mail_provide
r_s_config

cpgreylist_st
atus

cpgreylist_tru
st_entries_for
_common_m
ail_provider

cpgreylist_un
trust_entries_
for_common_
_mail_provid
er

create_cpgre
ylist_trusted_
host

delete_cpgre
ylist_trusted_
host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyli
st_config

read_cpgreyli
st_deferred_
entries

read_cpgreyli
st_trusted_ho
st

save_cpgreyli
st_config

batch

cpanel

create_integr
ation_group

create_integr
ation_link

get_integratio
n_link_user_
config

list_integratio
n_groups

list_integratio
n_links

remove_integ
ration_group

remove_integ
ration_link

update_integ
ration_link_to
ken

addips

delip

get_public_ip

get_shared_ip

ipv6_disable_
_account

ipv6_enable_
account

ipv6_range_a
dd

ipv6_range_e
dit

ipv6_range_li
st

ipv6_range_r
emove

ipv6_range_u
sage

listips

nat_checkip

nat_set_publi
c_ip

setsiteip

block_incomi
ng_email_fro
m_country

block_incomi
ng_email_fro
m_domain

disable_dkim

disable_mail
_sni

emailtrack_s
earch

emailtrack_st
ats

emailtrack_u
ser_stats

enable_dkim
enable_mail_sni
ensure_dkim_keys_exist
exim_configuration_check
expunge_mailbox_messages
expunge_messages_for_mailbox_guid
fetch_dkim_private_keys
fetch_mail_queue
generate_mobileconfig
get_mailbox_status
get_mailbox_status_list
get_unique_recipient_count_per_sender_for_user
get_unique_sender_recipient_count_per_user
get_user_email_forward_destination
hold_outgoing_email
install_dkim_private_keys
install_spf_records
is_sni_supported
list_blocked_incoming_email_countries
list_blocked_incoming_email_domains
list_pops_for
mail_sni_status
rebuild_mail_sni_config
release_outgoing_email

save_spamd
_config

set_user_email_forward_destination

suspend_outgoing_email

unblock_incoming_email_from_country

unblock_incoming_email_from_domain

unsuspend_outgoing_email

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

modsec_add_rule

modsec_add_vendor

modsec_asse
mble_config
_text

modsec_batc
h_settings

modsec_che
ck_rule

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_disc
ard_all_rule_
changes

modsec_disc
ard_rule_cha
nges

modsec_edit
_rule

modsec_ena
ble_vendor

modsec_ena
ble_vendor_c
onfigs

modsec_ena
ble_vendor_u
pdates

modsec_get_
config_text

modsec_get_
configs

modsec_get_
configs_with_
changes_pen
ding

modsec_get_
log

modsec_get_
rules

modsec_get_
settings

modsec_get_
vendors

modsec_is_i
nstalled

modsec_mak
e_config_acti
ve

modsec_mak
e_config_ina
ctive

modsec_prev
iew_vendor

modsec_rem
ove_rule

modsec_rem
ove_setting

modsec_rem
ove_vendor

modsec_repo
rt_rule

modsec_set_
config_text

modsec_set_
setting

modsec_undi
sable_rule

modsec_upd
ate_vendor

_getpkgexten
sionform

add_override
_features_for
_user

addpkg

addpkgext

changepacka
ge

create_featur
elist

delete_featur
elist

delpkgext

editpkg

get_available
_applications

get_available
_featurelists

get_feature_
metadata

get_feature_
names

get_featurelis
t_data

get_featurelis
ts

get_users_fe
atures_settin
gs

getfeaturelist

getpkginfo

killpkg

listpkgs

manage_feat
ures

matchpkgs

read_featurel
ist

remove_over
ride_features
_for_user

update_featu
relist

verify_user_h
as_feature

convert_all_d
omains_to_fpm

get_fpm_cou
nt_and_utiliz
ation

is_conversio
n_in_progress

php_get_def
ault_account
s_to_fpm

php_get_han
dlers

php_get_imp
acted_domai
ns

php_get_inst
alled_versions

php_get_old_
fpm_flag

php_get_syst
em_default_v
ersion

php_get_vho
sts_by_versi
on

php_get_vho
st_versions

php_ini_get_
content

php_ini_get_
directives

php_ini_set_
content

php_ini_set_
directives

php_fpm_con
fig_get

php_fpm_con
fig_set

php_set_defa
ult_accounts
_to_fpm

php_set_han
dler

php_set_old_
fpm_flag

php_set_ses
sion_save_p
ath

php_set_syst
em_default_v
ersion

php_set_vho
st_versions

acctcounts

get_public_c
ontact

getresellerips

listacis

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacis

setresellerips

setresellerlim
its

setresellerma
inip

setresellerna
meservers

setresellerpa
ckagelimit

setupreseller

suspendresel
ler

terminateres
eller

unsetupresell
er

unsuspendre
seller

delete_rpm_v
ersion

edit_rpm_ver
sion

get_rpm_ver
sion_data

install_rpm_p
lugin

list_rpms

package_ma
nager_fixcac
he

package_ma
nager_get_b
uild_log

package_ma
nager_get_p
ackage_info

package_ma
nager_is_per
forming_actio
ns

package_ma
nager_list_pa
ckages

package_ma
nager_resolv
e_actions

package_ma
nager_submit
_actions

package_ma
nager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accesshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys
add_configcl
usterserver
configurebac
kgroundproc
esskiller
configureserv
ice
cors_proxy_g
et
create_user_
session
delete_config
clusterserver
enable_monit
or_all_enable
d_services
get_all_conta
ct_importanc
es
get_appconfi
g_application
_list
get_applicati
on_contact_e
vent_importa
nce
get_applicati
on_contact_i
mportance
get_available
_profiles
get_current_
profile
get_passwor
d_strength
get_remote_
access_hash
get_service_
config
get_service_
config_key
get_tcp4_soc
kets
get_tcp6_soc
kets
get_tweakset
ting
get_udp4_so
ckets
get_udp6_so
ckets
get_update_
availability

get_users_links

getdiskusage

gethostname

is_role_enabled

list_configclusterservers

loadavg

nvget

nvset

personalization_get

personalization_set

purchase_application_license

reboot

remove_in_progress_exit_config_edit

restartservice

restore_config_from_file

restore_config_from_upload

run_cpkeyctl

send_test_posturl

send_test_pushbullet_note

servicestatus

set_application_contact_event_importance

set_application_contact_importance

set_primary_servername

set_service_config_key

set_tweaksetting

sethostname

setminimumpasswordstrengths

start_profile_activation

system_need
s_reboot

systemloada
vg

update_confi
gclusterserver

update_conta
ct_email

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushb
ullet_access

delete_ssl_v
host

disable_auto
ssl

fetch_service
_ssl_compon
ents

fetch_ssl_cer
tificates_for_f
qdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_
log

get_autossl_
ogs_catalog

get_autossl_
metadata

get_autossl_
pending_que
ue

get_autossl_
pending_que
ue_for_doma
in

get_autossl_
pending_que
ue_for_user

get_autossl_
problems_for
_domain

get_autossl_
problems_for
_user

get_autossl_
providers

get_best_ssl
domain_for_s
ervice

install_servic
e_ssl_certific
ate

installssl

listcrts

rebuildinstall
edssldb

rebuilduserss
ldb

reset_autossl_
_provider

reset_service
_ssl_certificate

set_autossl_
metadata

set_autossl_
metadata_key

set_autossl_
provider

start_autossl_
_check_for_a
ll_users

start_autossl_
_check_for_o
ne_user

generate_cp
anel_plugin

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_su
pport_agree
ment

ticket_get_su
pport_info

ticket_grant

ticket_list

ticket_remove_closed
ticket_revoke
ticket_ssh_test
ticket_ssh_test_start
ticket_update_service_agreement_approval
ticket_validate_oauth2_code
ticket_whitelist_check
ticket_whitelist_setup
ticket_whitelist_unsetup
abort_transfer_session
analyze_transfer_session_remote
available_transfer_modules
create_remote_root_transfer_session
create_remote_user_transfer_session
delete_account_archives
enqueue_transfer_item
fetch_transfer_session_log
get_transfer_session_state
pause_transfer_session
remote_basic_credential_check
retrieve_transfer_session_remote_analysis
start_transfer_session
transfer_module_schema
validate_system_user

accept_eula

get_available_tiers

get_current_lts_expiration_status

get_lts_expire

getlongtermsupport

installed_versions

set_cpanel_updates

set_tier

update_updateconf

version