

WHM API 1 Functions - matchpkgs

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Use WHM API to Call cPanel API & UAPI](#)

[accountsummary](#)

[applist](#)

[createacct](#)

[domainuserdata](#)

[editquota](#)

[forcepasswordchange](#)

[has_digest_auth](#)

[has_mycnf_for_cpuser](#)

[limitbw](#)

[listaccts](#)

[listlockedaccounts](#)

[listsuspended](#)

[modifyacct](#)

[myprivs](#)

[passwd](#)

[removeacct](#)

[set_digest_auth](#)

[showbw](#)

[suspendacct](#)

[unsuspendacct](#)

[untrack_acct_id](#)

[verify_new_username](#)

Description

This function matches the server's hosting plans (packages) against your criteria.

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/matchpkgs?api.version=1&FEATURELIST=default
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/matchpkgs?api.version=1&FEATURELIST=default
```

```
whmapil matchpkgs FEATURELIST=default
```



Notes:

- You **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- We introduced this functionality in cPanel & WHM version 11.52.0.8.

```
{
  "data": {
    "pkg": {
      "FEATURELIST": "default",
      "QUOTA": "100",
      "MAXSUB": "5",
      "MAXADDON": "1",
      "MAX_DEFER_FAIL_PERCENTAGE": "10",
      "CGI": 1,
      "HASSHELL": 1,
      "DIGESTAUTH": "y",
      "MAX_EMAIL_PER_HOUR": "100",
      "LANG": "en",
      "MAXFTP": "2",
      "CPMOD": "paper_lantern",
      "MAXLST": "5",
      "MAXPARK": "1",
      "BWLIMIT": null,
      "FRONTPAGE": 0,
      "IP": 0,
      "MAXPOP": "20",
      "MAXSQL": "1"
    }
  },
  "metadata": {
    "version": 1,
    "reason": "OK",
    "result": 1,
    "command": "matchpkgs"
  }
}
```

Function information

API

Version:

[WHM API 1](#)

Available in:

WHM 11+

Methods:

GET, POST

Required

Parameters:

(none)

Return Format

s:

JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

[restore_modules_summary](#)
[restore_queue_activate](#)
[restore_queue_add_task](#)
[restore_queue_clear_all_completed_tasks](#)
[restore_queue_clear_all_failed_tasks](#)
[restore_queue_clear_all_pending_tasks](#)
[restore_queue_clear_all_tasks](#)
[restore_queue_clear_completed_task](#)
[restore_queue_clear_pending_task](#)
[restore_queue_is_active](#)
[restore_queue_list_active](#)
[restore_queue_list_completed](#)
[restore_queue_list_pending](#)
[restore_queue_state](#)
[restoreaccount](#)
[verify_new_username_for_restore](#)
[convert_addon_fetch_conversion_details](#)
[convert_addon_fetch_domain_details](#)
[convert_addon_get_conversion_status](#)
[convert_addon_initiate_conversion](#)
[convert_addon_list_addon_domains](#)
[convert_addon_list_conversions](#)

```

<result>
  <data>
    <pkg>
      <FEATURELIST>default</FEATURELIST>
      <QUOTA>100</QUOTA>
      <MAXSUB>5</MAXSUB>
      <MAXADDON>1</MAXADDON>
      <MAX_DEFER_FAIL_PERCENTAGE>10<
/MAX_DEFER_FAIL_PERCENTAGE>
      <CGI>1</CGI>
      <HASSHELL>1</HASSHELL>
      <DIGESTAUTH>y</DIGESTAUTH>
      <MAX_EMAIL_PER_HOUR>100</MAX_EMAIL_PER_HOUR>
      <LANG>en</LANG>
      <MAXFTP>2</MAXFTP>
      <CPMOD>paper_lantern</CPMOD>
      <MAXLST>5</MAXLST>
      <MAXPARK>1</MAXPARK>
      <BWLIMIT/>
      <FRONTPAGE>0</FRONTPAGE>
      <IP>0</IP>
      <MAXPOP>20</MAXPOP>
      <MAXSQL>1</MAXSQL>
    </pkg>
  </data>
  <metadata>
    <version>1</version>
    <reason>OK</reason>
    <result>1</result>
    <command>matchpkgs</command>
  </metadata>
</result>

```

Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Note:

If you do not include **any** input parameters, the function lists **all** of the server's packages.

| Parameter | Type | Description | Possible values | Example |
|-----------|---------------|--|---|-----------|
| MAXSUB | <i>string</i> | The hosting plan's maximum number of subdomains. | <ul style="list-style-type: none"> unlimited An integer that represents a number of subdomains. | unlimited |

• Some functions and parameters may require that the caller authenticate as the router.

[api_token_create](#)
[api_token_list](#)
[api_token_revoke](#)
[api_token_update](#)
[disable_authentication_provider](#)
[disable_failing_authentication_providers](#)
[enable_authentication_provider](#)
[link_user_authn_provider](#)
[get_available_authentication_providers](#)
[get_login_url](#)
[get_provider_client_configurations](#)
[get_provider_configuration_fields](#)
[get_provider_display_configurations](#)
[get_users_authn_linked_accounts](#)
[set_provider_client_configurations](#)
[set_provider_display_configurations](#)
[twofactorauth_disable_policy](#)
[twofactorauth_enable_policy](#)
[twofactorauth_generate_tfa_config](#)
[twofactorauth_get_issuer](#)
[twofactorauth_get_user_configs](#)
[twofactorauth_policy_status](#)

| | | | | |
|---------------------------|---------------|---|---|-------------------|
| MAXADDON | <i>string</i> | The hosting plan's maximum number of addon domains. | <ul style="list-style-type: none"> unlimited An integer that represents a number of addon domains. | unlimited |
| MAX_DEFER_FAIL_PERCENTAGE | <i>string</i> | The percentage of failed or deferred email messages that the hosting plan can send per hour before outgoing mail is rate-limited. | <ul style="list-style-type: none"> unlimited An integer that represents a percentage of messages. | unlimited |
| _PACKAGE_EXTENSIONS | <i>string</i> | The hosting plan's package extensions. | A space-separated list of one or more package extension names. | ext1 ext2 ext3 |
| CPMOD | <i>string</i> | The hosting plan's cPanel interface theme. | <ul style="list-style-type: none"> paper_lantern Another valid theme on the server. | paper_lantern |
| MAX_EMAIL_PER_HOUR | <i>string</i> | The maximum number of emails that the hosting plan can send in one hour. | <ul style="list-style-type: none"> unlimited An integer that represents a number of sent emails. | unlimited |
| LANG | <i>string</i> | The hosting plan's locale. | The ISO code for any locale on the server. | en |
| MAXLST | <i>string</i> | The hosting plan's maximum number of mailing lists. | <ul style="list-style-type: none"> unlimited An integer that represents a number of mailing lists. | unlimited |
| MAXPARK | <i>string</i> | The hosting plan's maximum number of parked domains (aliases). | <ul style="list-style-type: none"> unlimited An integer that represents a number of parked domains. | unlimited |
| MAXSQL | <i>string</i> | The hosting plan's maximum number of SQL databases. | <ul style="list-style-type: none"> unlimited An integer that represents a number of SQL databases. | unlimited |

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

[twofactorauth_remove_user_config](#)
[twofactorauth_set_issuer](#)
[twofactorauth_set_tfa_config](#)
[unlink_user_authn_provider](#)
[validate_login_token](#)
[backup_config_get](#)
[backup_config_set](#)
[backup_date_list](#)
[backup_destination_add](#)
[backup_destination_delete](#)
[backup_destination_get](#)
[backup_destination_list](#)
[backup_destination_set](#)
[backup_destination_validate](#)
[backup_set_list](#)
[backup_skip_users_all](#)
[backup_skip_users_all_status](#)
[backup_user_list](#)
[convert_and_migrate_from_legacy_config](#)
[list_cparchive_files](#)
[start_background_pkgacct](#)
[toggle_user_backup_state](#)
[cphulk_status](#)
[create_cphulk_record](#)
[delete_cphulk_record](#)

| | | | | |
|-------------|----------------|--|---|-----------|
| FEATURELIST | <i>string</i> | The hosting plan's featurerlist. | A valid feature list name. | default |
| CGI | <i>Boolean</i> | Whether CGI is enabled for the hosting plan. | <ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. | 1 |
| MAXFTP | <i>string</i> | The hosting plan's maximum number of FTP accounts. | <ul style="list-style-type: none"> unlimited An integer that represents a number of FTP accounts. | unlimited |
| BWLIMIT | <i>string</i> | The hosting plan's bandwidth limit. | <ul style="list-style-type: none"> unlimited A maximum amount of bandwidth, in Megabytes (MB). | unlimited |
| QUOTA | <i>string</i> | The hosting plan's disk space limit. | <ul style="list-style-type: none"> unlimited A maximum amount of disk space, in Megabytes (MB). | unlimited |
| DIGESTAUTH | <i>string</i> | Whether the hosting plan enables Digest Authentication. | <ul style="list-style-type: none"> y — Enable. n — Disable. | n |
| IP | <i>string</i> | Whether the hosting plan grants accounts a dedicated IP address. | <ul style="list-style-type: none"> y — Dedicated IP address. n — Shared IP address. | n |

- [WHM API 1 Functions - addpkg](#) — This function creates a hosting plan (package).
- [WHM API 1 Functions - changepackage](#) — This function changes a cPanel account's hosting plan (package).
- [WHM API 1 Functions - listpkgs](#) — This function lists the authenticated user's available hosting plans (packages).
- [WHM API 1 Functions - killpkg](#) — This function deletes a hosting plan (package).
- [WHM API 1 Functions - getpkgextensionform](#) — This function retrieves a hosting plan's package extension templates.

Returns

| Return | Type | Description | Possible values | Example |
|--------|------|-------------|-----------------|---------|
|--------|------|-------------|-----------------|---------|

| | | | | | |
|---|---|---|---|---|--|
| <p>disable_cphulk</p> <p>enable_cphulk</p> <p>flush_cphulk_login_history</p> <p>flush_cphulk_login_history_for_ips</p> <p>get_cphulk_brules</p> <p>get_cphulk_excessive_brules</p> <p>get_cphulk_failed_logins</p> <p>load_cphulk_config</p> <p>read_cphulk_records</p> <p>save_cphulk_config</p> <p>background_mysql_upgrade_status</p> <p>current_mysql_version</p> <p>installable_mysql_versions</p> <p>latest_available_mysql_version</p> <p>list_database_users</p> <p>list_databases</p> <p>list_mysql_databases_and_users</p> <p>remote_mysql_create_profile</p> <p>remote_mysql_create_profile_via_ssh</p> <p>remote_mysql_delete_profile</p> <p>remote_mysql_initiate_profile_activation</p> <p>remote_mysql_monitor_profile_activation</p> <p>remote_mysql_read_profile</p> | <p>pkg</p> <p>MA XS UB</p> <p>MA XA DD ON</p> <p>MA X_DEFERRED_INSTALLABLE_EXTENSIONS</p> <p>_PACKAGE_EXTENSIONS</p> <p>CP MOD</p> <p>MA X_EMAIL_SENT_PER_HOUR</p> <p>LA NG</p> | <p><i>hash</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> <p><i>string</i></p> | <p>A hash of hosting plan settings.</p> <p>The hosting plan's maximum number of subdomains.</p> <p>The function returns this value in the pkg hash.</p> <p>The hosting plan's maximum number of addon domains.</p> <p>The function returns this value in the pkg hash.</p> <p>The percentage of failed or deferred email messages that the hosting plan can send per hour before outgoing mail is rate-limited.</p> <p>The function returns this value in the pkg hash.</p> <p>The hosting plan's package extensions.</p> <p>The function returns this value in the pkg hash.</p> <p>The hosting plan's cPanel interface theme.</p> <p>The function returns this value in the pkg hash.</p> <p>The maximum number of emails that the hosting plan can send in one hour.</p> <p>The function returns this value in the pkg hash.</p> <p>The hosting plan's locale.</p> <p>The function returns this value in the pkg hash.</p> | <p>This function contains one or more of the following returns: name, MAXSUB, MAXADDON, MAX_DEFER_FAIL_PERCENTAGE, _PACKAGE_EXTENSIONS, CPMOD, MAX_EMAIL_PER_HOUR, LANG, MAXLIST, MAXPARK, MAXSQL, FEATURELIST, CGI, MAXFTP, BWLIMIT, QUOTA, DIGESTAUTH, IP.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p> Note:</p> <p>If the hosting plan uses package extensions, the pkg hash will also include the extension's variables.</p> </div> <ul style="list-style-type: none"> unlimited An integer that represents a number of subdomains. <ul style="list-style-type: none"> unlimited An integer that represents a number of addon domains. <ul style="list-style-type: none"> unlimited An integer that represents a percentage of messages. <p>A space-separated list of one or more package extension names.</p> <ul style="list-style-type: none"> paper_lantern Another valid theme on the server. <ul style="list-style-type: none"> unlimited An integer that represents a number of sent emails. <p>The ISO code for any locale on the server.</p> | <p>unlimited</p> <p>unlimited</p> <p>unlimited</p> <p>ext1 ext2 ext3</p> <p>paper_lantern</p> <p>unlimited</p> <p>en</p> |
|---|---|---|---|---|--|

[remote_mysql_read_profiles](#)
[remote_mysql_update_profile](#)
[remote_mysql_validate_profile](#)
[rename_mysql_database](#)
[rename_mysql_user](#)
[rename_postgresql_database](#)
[rename_postgresql_user](#)
[set_local_mysql_root_password](#)
[set_mysql_password](#)
[set_postgresql_password](#)
[start_background_mysql_upgrade](#)
[adddns](#)
[addzonerecord](#)
[addzonerecord \(Reverse DNS\)](#)
[dumpzone](#)
[editzonerecord](#)
[get_nameserver_config](#)
[getzonerecord](#)
[killdns](#)
[listmxs](#)
[listzones](#)
[lookupnspip](#)
[lookupnspips](#)
[removezonerecord](#)
[resetzone](#)
[resolvedomainname](#)
[savemxs](#)
[setresolvers](#)

| | | | | |
|-----------------------------|----------------|---|---|-----------|
| MA XL ST | <i>string</i> | The hosting plan's maximum number of mailing lists. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited An integer that represents a number of mailing lists. | unlimited |
| MA XP ARK | <i>string</i> | The hosting plan's maximum number of parked domains. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited An integer that represents a number of parked domains. | unlimited |
| MA XS QL | <i>string</i> | The hosting plan's maximum number of SQL databases. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited An integer that represents a number of SQL databases. | unlimited |
| FE AT UR EL IST | <i>string</i> | The hosting plan's featurelist. The function returns this value in the <code>pkg</code> hash. | A valid feature list name. | default |
| CGI | <i>Boolean</i> | Whether CGI is enabled for the hosting plan. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. | 1 |
| MA XF TP | <i>string</i> | The hosting plan's maximum number of FTP accounts. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited An integer that represents a number of FTP accounts. | unlimited |
| BW LI MIT | <i>string</i> | The hosting plan's bandwidth limit. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited A maximum amount of bandwidth, in Megabytes (MB). | unlimited |
| QU OTA | <i>string</i> | The hosting plan's disk space limit. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> unlimited A maximum amount of disk space, in Megabytes (MB). | unlimited |
| DI GE ST AU TH | <i>string</i> | Whether the hosting plan enables Digest Authentication. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> y — Enable. n — Disable. | n |
| IP | <i>string</i> | Whether the hosting plan grants accounts a dedicated IP address. The function returns this value in the <code>pkg</code> hash. | <ul style="list-style-type: none"> y — Dedicated IP address. n — Shared IP address. | n |

ea4_get_currently_installed_packages

ea4_get_ea_pkgs_state

ea4_list_profiles

ea4_pre_migrate_check

ea4_recommendations

ea4_save_profile

cpgreylist_is_server_netblock_trusted

cpgreylist_list_entries_for_common_mail_provider

cpgreylist_load_common_mail_providers_config

cpgreylist_save_common_mail_providers_config

cpgreylist_status

cpgreylist_trusted_entries_for_common_mail_provider

cpgreylist_untrust_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_hosts

save_cpgreylist_config

batch
cpanel
create_integration_group
create_integration_link
get_integration_link_user_config
list_integration_groups
list_integration_links
remove_integration_group
remove_integration_link
update_integration_link_token
addips
delip
get_public_ip
get_shared_ip
ipv6_disable_account
ipv6_enable_account
ipv6_range_add
ipv6_range_edit
ipv6_range_list
ipv6_range_remove
ipv6_range_usage
listips
nat_checkip
nat_set_public_ip
setsiteip
disable_mail_sni
emailtrack_search
emailtrack_stats
emailtrack_user_stats

enable_mail_
sni

exim_configu
ration_check

expunge_mai
lbox_messag
es

expunge_me
ssages_for_
mailbox_guid

fetch_mail_q
ueue

generate_mo
bileconfig

get_mailbox_
status

get_mailbox_
status_list

get_user_em
ail_forward_d
estination

hold_outgoin
g_email

is_sni_suppo
rted

list_pops_for

mail_sni_stat
us

rebuild_mail_
sni_config

release_outg
oing_email

save_spamd_
_config

set_user_em
ail_forward_d
estination

suspend_out
going_email

unsuspend_o
utgoing_email

validate_curr
ent_installed
_exim_config

validate_exi
m_configurati
on_syntax

disable_mark
et_provider

enable_mark
et_provider

get_adjusted
_market_pro
viders_produ
cts

get_market_
providers_co
mmission_co
nfig

get_market_
providers_list

get_market_
providers_pr
oduct_metad
ata

get_market_
providers_pr
oducts

set_market_p
roduct_attrib
ute

set_market_p
rovider_com
mission_id

modsec_add
_rule

modsec_add
_vendor

modsec_batc
h_settings

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disc
ard_rule_cha
nges

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_disc
ard_all_rule_
changes

modsec_edit
_rule

modsec_ena
ble_vendor

modsec_ena
ble_vendor_c
onfigs

modsec_ena
ble_vendor_u
pdates

modsec_get_
config_text

modsec_get_
configs

modsec_get_
configs_with_
changes_pen
ding

modsec_get_
log

modsec_get_
rules

modsec_get_
settings

modsec_get_
vendors

modsec_is_i
nstalled

modsec_mak
e_config_acti
ve

modsec_mak
e_config_ina
ctive

modsec_prev
iew_vendor

modsec_rem
ove_rule

modsec_rem
ove_setting

modsec_rem
ove_vendor

modsec_repo
rt_rule

modsec_set_
config_text

modsec_set_
setting

modsec_undi
sable_rule

modsec_upd
ate_vendor

_getpkgexten
sionform

add_override
_features_for
_user

addpkg

addpkgext

changepackage
create_featurelist
delete_featurelist
delpkgext
editpkg
get_available_featurelists
get_feature_metadata
get_feature_names
get_featurelist_data
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
package_manager_fixcache
package_manager_get_package_info
package_manager_resolve_actions
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature
php_get_handlers
php_get_affected_domains
php_get_installed_versions
php_get_system_default_version

php_get_vho
sts_by_versi
on

php_get_vho
st_versions

php_ini_get_
content

php_ini_get_
directives

php_ini_set_
content

php_ini_set_
directives

php_set_han
dler

php_set_syst
em_default_v
ersion

php_set_vho
st_versions

php_set_old_
fpm_flag

php_get_old_
fpm_flag

get_fpm_cou
nt_and_utiliz
ation

php_get_def
ault_account
s_to_fpm

php_set_defa
ult_accounts
_to_fpm

convert_all_d
omains_to_fpm

get_public_c
ontact

set_public_c
ontact

acctcounts

getresellerips

listacIs

listresellers

resellerstats

saveacllist

setacIs

setresellerips

setresellerlim
its

setresellerma
inip

setresellerna
meservers

setresellerpa
ckagelimit

setupreseller

suspendresel
ler

terminateres
eller

unsetupresell
er

unsuspendre
seller

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

delete_rpm_v
ersion

edit_rpm_ver
sion

enable_monit
or_all_enable
d_services

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_all_conta
ct_importanc
es

get_passwor
d_strength

get_remote_
access_hash

get_rpm_ver
sion_data

get_service_
config

get_service_
config_key

get_update_
availability

get_tweakset
ting

get_users_lin
ks

getdiskusage

gethostname

install_rpm_p
lugin

list_configclu
sterservers

list_rpms

loadavg

nvget

nvset

purchase_a_l
icense

reboot

remove_in_p
rogress_exim
_config_edit

restartservice

run_cpkeyclt

send_test_po
sturl

send_test_pu
shbullet_note

servicestatus

set_applicati
on_contact_e
vent_importa
nce

set_applicati
on_contact_i
mportance

set_primary_
servername

set_service_
config_key

set_tweakset
ting

sethostname

setminimump
asswordstren
gths

systemloada
vg

system_need
s_reboot

uninstall_rpm
_plugin

update_confi
gclusterserver

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushb
ullet_access

disable_auto
ssl

fetch_service
_ssl_compon
ents

fetch_ssl_cer
tificates_for_f
qdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_log

get_autossl_logs_catalog

get_autossl_pending_queue

get_autossl_pending_queue_for_domain

get_autossl_pending_queue_for_user

get_autossl_problems_for_domain

get_autossl_problems_for_user

get_autossl_providers

get_best_ssl_domain_for_service

install_service_ssl_certificate

installssl

listcrts

rebuildinstall_edssldb

rebuilduserssldb

reset_autossl_provider

reset_service_ssl_certificate

set_autossl_metadata

set_autossl_provider

start_autossl_check_for_all_users

start_autossl_check_for_one_user

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_s
upport_agree
ment

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remot
e_user_trans
fer_session

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version