

cPanel API 1 Functions - Branding::file

Guide to cPanel API 1

Return Data

cPanel Tags
(deprecated)

Bandwidth:
display
bandwidth

er

Bandwidth:
display
bandwidth

Bandwidth:
display
bandwidth

Bandwidth:
display
bandwidth

▼ BoxTrapper

BoxTrapper:
change
status

BoxTrapper:
clean
config
filelist

BoxTrapper:
edit
msg

BoxTrapper:
fetch
config
file

BoxTrapper:
get
boxconf
dir

BoxTrapper:
list
msg
sgs

BoxTrapper:
log
control
sgs

BoxTrapper:
mess
ageaction

BoxTrapper:
multi
messageaction

BoxTrapper:
reset
msg

BoxTrapper:
save
config
file

BoxTrapper:
save
conf

BoxTrapper:
show
autowhite
list

BoxTrapper:
show
emails

BoxTrapper:
show
fromname

BoxTrapper:
show

Description

This function searches for a file within a theme and returns its URL.

Warning:

cPanel API 1 is **deprecated**. Do not use this function. Instead, we **strongly** recommend that you use the following newer functions:

- **UAPI (recommended)** — `Branding::file` — This function retrieves a branding file's path.
- **cPanel API 2** — `Branding::resolve_file` — This function returns a file's path.

Examples

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
$branding_file =  
$cpanel->api('Brandi  
ng', 'file',  
array('mythemes',  
'/0', 'my_theme',  
'1', '0', '0' '1') );  
// Call the function.
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Func tion infor mati on

About this mod ule

The Branding module accesses cPanel's theming system.

About cPan el API 1

log

BoxTrapper:: show
message

BoxTrapper:: show
queue

BoxTrapper:: show
queuesearch

BoxTrapper:: show
queuetime

BoxTrapper:: statu
s

BoxTrapper:: statu
sbutton

▼ Branding

Branding:: file

Branding:: image

Branding:: killing

Branding:: setbran
dingpkg

Branding:: setmya
cctspkg

Branding:: setupdir
s

Branding:: tempset
brandingpkg

▼ Cgi

Cgi:: backuplink

Cgi:: displayurchin

Cgi:: phpmyadminl
ink

▼ Chkserverd

Chkserverd:: getxi
mport

Chkserverd:: getxi
mport_ssl

▼ ClamScanner

ClamScanner:: bar
s

▼ cPAddons

cPAddons:: mainp
g

▼ Cron

Cron:: crontab_per
ms

▼ CustInfo

CustInfo:: getemail

▼ Denylp

Denylp:: adddenyi
p

Denylp:: deldenyip

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
my $branding_file =  
$cpliveapi->apil('Bra  
nding', file,  
['mythemes', '/0',  
'my_theme', '1', '0',  
'0', '1'] ); # Call  
the function.
```

Note:
For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Tag System (deprecated)

Warning:
In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We provide this example to help developers move from the old cPanel tag system to our [LiveAPI](#) system. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs.

```
<cpanel  
Module="Branding::fil  
e( $FORM(  
'file','isvar','pkg',  
'inline',  
'needfile','skipdefau  
lt','checkmain') )">
```

cPanel API 1 accesses information about cPanel accounts.

Warning:
cPanel API **deprecated**. We **strongly** recommend [cPanel API](#) or [UAPI](#) instead.

Notes:

- Th
Fe
- Ur
mi
us
20
or
20
)`
20
or
20
)

Find a function

- Denylp:: listdenyips
- DiskUsage:: showmanager
- Email:: addautoresponder
 - Email:: addforward
 - Email:: addfilter
 - Email:: addlist
 - Email:: addmx
 - Email:: addpop
 - Email:: addspam
 - Email:: addspambox
 - Email:: addspamfilter
 - Email:: changemx
 - Email:: checkfastmail
 - Email:: checkpipewd
 - Email:: clearspambox
 - Email:: delautoresponder
 - Email:: delforward
 - Email:: delfilter
 - Email:: dellist
 - Email:: delmx
 - Email:: delpop
 - Email:: delspam
 - Email:: delspambox
 - Email:: disable_spam_autodelete
 - Email:: editquota
 - Email:: enable_spam_autodelete
 - Email:: getaging
 - Email:: getarsbody
 - Email:: getarscharset
 - Email:: getarsfrom
 - Email:: getarshtml

Command Line

```
cpapil
--user=username
Branding file
mythemes 0 my_theme 1
0 0 1
```

Notes:

- You **must** URI-encode these values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to cPanel API 1](#) documentation or run the `cpapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapil` command:

```
/usr/local
/cpanel/bin/cpapil
```

Output (URL)

```
/cPanel_magic_revision_1267840609/branding/contactinfo_include.html
```

Parameters

Parameter	Type	Description	Possible values	Example
file	string	Required The file's name.	Any valid filename.	mythemes

- cPanel API 1 Modules - Bandwidth — The Bandwidth module accesses a cPanel account's bandwidth usage data.
- cPanel API 1 Functions - Bandwidth::display — This function generates bandwidth data for the specified day.

- Email:: getarsinter val
- Email:: getarsstart
- Email:: getarsstop
- Email:: getarssubject
- Email:: getmailserver
- Email:: getmailserveruser
- Email:: getpopquota
- Email:: has_spam_as_acl
- Email:: has_spam_autodelete
- Email:: listmaildomains
- Email:: listmaildomainsopt
- Email:: listmaildomainsoptndef
- Email:: mainacctdiskused
- Email:: passwdlist
- Email:: passwdpop
- Email:: setmxaccept
- Email:: spamboxstatus
- Email:: spamstatus
- Email:: tracefilter
- ▼ **Fileman**
- Fileman:: changeperm
- Fileman:: delfile
- Fileman:: dofileop
- Fileman:: emptytrash
- Fileman:: extractfile
- Fileman:: fileimg
- Fileman:: fmmkdir
- Fileman:: fmmkfile
- Fileman:: fmpushfile
- Fileman:: fmrename
- Fileman:: fmsavefil

isvar	<i>Boolean</i>	Required This is a legacy parameter.	<ul style="list-style-type: none"> • 0 • null <div style="border: 1px solid red; padding: 5px; margin-top: 5px;"> <p>Warning: Always set this value to 0 or null.</p> </div>	0
pkg	<i>string</i>	Required The style for which to search.	Any valid style name.	my_theme
inline	<i>Boolean</i>	Required Whether to print the file's contents.	<ul style="list-style-type: none"> • 1 — Print the file's contents. • 0 — Do not print the file's contents. 	1
needfile	<i>Boolean</i>	Required This is a legacy parameter.	<ul style="list-style-type: none"> • 0 • null <div style="border: 1px solid red; padding: 5px; margin-top: 5px;"> <p>Warning: Always set this value to 0 or null.</p> </div>	0
skipdefault	<i>Boolean</i>	Required This is a legacy parameter.	<ul style="list-style-type: none"> • 0 • null <div style="border: 1px solid red; padding: 5px; margin-top: 5px;"> <p>Warning: Always set this value to 0 or null.</p> </div>	0
checkmain	<i>Boolean</i>	Required Whether the function should search the account's /cpanelbranding directory.	<ul style="list-style-type: none"> • 1 — Search the directory. • 0 — Do not search the directory. 	1

- cPanel API 1 Functions - Bandwidth::displayheader — This function generates a monthly bandwidth graph.
- cPanel API 1 Functions - Bandwidth::display — This function generates bandwidth graphs for the specified day.

e

Fileman:: fmsavehtmlfile

Fileman:: fullbackup

Fileman:: getfile

Fileman:: htmleditor

Fileman:: killdir

Fileman:: listfiles

Fileman:: listfullbackups

Fileman:: listtemplates

Fileman:: restoreaf

Fileman:: restoredb

Fileman:: restorefile

Fileman:: restorefiles

Fileman:: savehtmlfile

Fileman:: showperm

Fileman:: uploadfiles

Fileman:: viewfile

▼ Frontpage

FrontPage:: addfp

FrontPage:: delfp

FrontPage:: fpstatus

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: ftpquota

Ftp:: ftpservername

Ftp:: ftpstatslogin

Ftp:: get_anonftp

Ftp:: get_anonftpin

Ftp:: get_welcomemsg

Ftp:: getftpquota

Ftp:: kill_ftp_session

Ftp:: listftpstatsurl

Returns

This function's output depends on the values of the input parameters.

- cPanel API 1 Functions - Bandwidth::displaybandwidthheader — This function generates bandwidth graphs for the current day, week, and year.

Ftp:: passwdftp

Ftp:: set_anonftp

Ftp:: set_anonftpin

Ftp:: set_welcome
msg

▼ Gpg

Gpg:: deletekey

Gpg:: exportkey

Gpg:: exportsecret
key

Gpg:: genkey

Gpg:: importkeys

▼ Htaccess

Htaccess:: checkpr
otected

Htaccess:: del_use
r

Htaccess:: getinde
x

Htaccess:: htdirls

Htaccess:: number
_of_users

Htaccess:: phpsele
ctable

Htaccess:: resnam
e

Htaccess:: set_pas
s

Htaccess:: set_pro
tect

Htaccess:: setinde
x

Htaccess:: setphpr
eference

Htaccess:: showus
ers

▼ ImageManager

ImageManager:: c
onvert

ImageManager:: di
mensions

ImageManager:: h
dimension

ImageManager:: s
cale

ImageManager:: th
umbnail

ImageManager:: w
dimension

▼ LastLogin

LastLogin:: lastlogi
n

▼ LeechProtect

LeechProtect:: dis
able

LeechProtect:: ena
ble

LeechProtect:: set
up

LeechProtect:: sho
wpasswdfile

LeechProtect:: stat
us

▼ LogManager

LogManager:: listd
ownloads

LogManager:: sav
esettings

LogManager:: sho
wsettings

▼ MagicRevision

MagicRevision:: uri

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: del_handler

Mime:: del_hotlink

Mime:: del_mime

Mime:: del_redirect

Mime:: linkallownul
l

Mime:: linkenable

Mime:: linkexts

Mime:: linkrurl

Mime:: linkurIs

▼ Mysql

Mysql:: adddb

Mysql:: addhost

Mysql:: adduser

Mysql:: adduserdb

Mysql:: checkdb

Mysql:: deldb

Mysql:: delhost

Mysql:: deluser

Mysql:: deluserdb

Mysql:: gethost

Mysql:: initcache

Mysql:: listdbs

Mysql:: listdbsopt

Mysql:: listusers

Mysql:: listusersopt

Mysql:: number_of
_dbs

Mysql:: number_of
_users

Mysql:: repairdb

Mysql:: routines

Mysql:: updatepriv
s

▼ Net

Net:: dnslookup

Net:: dnszone

Net:: sethastracero
ute

▼ News

News:: displaynew
s

▼ NVData

NVData:: set

▼ OptimizeWS

OptimizeWS:: load
optimizesettings

OptimizeWS:: load
optimizesettings (b
ytes)

OptimizeWS:: opti
mizews

▼ Park

Park:: disabledir
ect

Park:: getredirectu
rl

Park:: park

Park:: setredirectur
l

Park:: unpark

▼ Postgres

Postgres:: adddb

Postgres:: adduser

Postgres:: adduser
db

Postgres:: deldb

Postgres:: deluser

Postgres:: deluser
db

Postgres:: initcach
e

Postgres:: listdbso
pt

Postgres:: listusers
opt

Postgres:: number
_of_dbs

Postgres:: number
_of_users

▼ ProxyUtils

ProxyUtils:: proxya
ddress

▼ Resellers

Resellers:: accoun
tlistopt

Resellers:: themeli
stopt

▼ Serverinfo

Serverinfo:: servic
estatus

▼ SetLang

SetLang:: listlangs
opt

SetLang:: setlang

▼ SpamAssassin

SpamAssassin:: co
nfig

SpamAssassin:: sa
veconfig

▼ SSH

SSH:: getport

▼ SSL

SSL:: delete

SSL:: deletecrt

SSL:: deletecsr

SSL:: deletekey

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcabundle

SSL:: getcnname

SSL:: install

SSL:: installedhost

SSL:: listkeysopt

SSL:: showcrt

SSL:: showcsr

SSL:: showkey

SSL:: sslsharedsta
tus

SSL:: uploadcrt

SSL:: uploadkey

▼ StatManager

StatManager:: doF
orm

StatManager:: upd
ateUserConfig

▼ Stats

Stats:: analoglist

Stats:: awstats

Stats:: bwbar

Stats:: errlog

Stats:: lastvisitors

Stats:: showbandw
idth

Stats:: webalizer

Stats:: webalizerftp

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: cplist
subdomains

SubDomain:: disab
lesubrd

SubDomain:: listsu
bdomainsop

SubDomain:: setsu
burl

▼ UI

UI:: confirm

UI:: redirect

UI:: showresult