

UAPI Functions - cPAddons::list_addon_instances

Description

This function lists an account's deployed cPAddons instances.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/cPAddons/list_addon_instances?addon=cPanel%3A%3ABlogs%3A%3AWordPressX
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI documentation](#).

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::fullbackup

p_to_ftp

Backup::fullbackup_to_homedir

Backup::fullbackup_to_scp_with_key

Backup::fullbackup_to_scp_with_password

Backup::list_backups

▼ Bandwidth

Bandwidth::get_enabled_protocols

Bandwidth::get_retention_periods

Bandwidth::query

▼ Batch

Batch::strict

▼ Brand

Brand::read

▼ Branding

Branding::file

Branding::get_applications

Branding::get_application_information

Branding::get_available_applications

Branding::get_info

Function information

About this module

The cPAddons module accesses cPanel's cPAddon system.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkserverd

Chkserverd:: get_exit_ports

Chkserverd:: get_exit_ports_ssl

▼ Chrome

Chrome:: get_domain

▼ Contactus

Contactus:: is_enabled

▼ cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

▼ cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

▼ DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// List the account's  
cPAddons instances.  
$instances =  
$cpanel->uapi(  
    'cPAddons',  
    'list_addon_instances'  
,  
    array(  
        'addon'  
=>'cPanel::Blogs::WordPress'  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Notes:

- The *Fe*
- Ur **mt** us 20 or 20).\ 20 or 20).

Find a function

•
cPaddons module accesses cPanel's cPAddon system.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# List the account's  
cPAddons instances.  
my $instances =  
$cpliveapi->uapi(  
  'cPAddons',  
  'list_addon_instances'  
,  
  {  
    'addon'  
=>'cPanel::Blogs::WordPress'  
  }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Template Toolkit

```
<!-- List the  
account's cPAddons  
instances. -->  
[% data = execute(  
  'cPAddons',  
  'list_addon_instances'  
, { 'addon' =>  
  'cPanel::Blogs::WordPress' } ); %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Functions - cPAddons::get_available_addons — This function lists an account's available cPAddons.
- UAPI Functions - cPAddons::list_addon_instances — This function lists an account's deployed cPAddons instances.

Email:: add_spam_filter

Email:: browse_mailbox

Email:: change_mx

Email:: check_fastmail

Email:: check_pipe_forwarder

Email:: delete_auto_responder

Email:: delete_domain_forwarder

Email:: delete_filter

Email:: delete_forwarder

Email:: delete_help_messages

Email:: delete_list

Email:: delete_mx

Email:: delete_pop

Email:: disable_filter

Email:: disable_mailbox_autocreate

Email:: disable_spam_assassin

Email:: disable_spam_autodelete

Email:: disable_spam_box

Email:: dispatch_client_settings

Email:: edit_pop_quota

Email:: enable_filter

Email:: enable_mailbox_autocreate

Email:: enable_spam_assassin

Email:: enable_spam_box

Email:: fetch_charmaps

Email:: fts_rescan_mailbox

Email:: generate_mailman_otp

Email:: get_auto_r

Command Line

```
uapi --user=username
cPAddons
list_addon_instances
addon='cPanel::Blogs:
:WordPressX'
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

Output (JSON)

```
{
  "data": [{
    "installdir":
    "/home/example/public_html/wordpress",
    "addon":
    "cPanel::Blogs::WordPressX",
    "unique_id":
    "cPanel::Blogs::WordPressX.0.1486754861",
    "instance":
    "cPanel::Blogs::WordPressX.0"
  }],
  "status": 1,
  "metadata": {
    "transformed": 1
  },
  "messages": null,
  "errors": null
}
```

- UAPI Functions - cPAddons::get_instance_settings - This function lists a cPAddons instance's settings.
- UAPI Functions - cPAddons::get_available_addons - This function lists an account's available cPAddons.

esponder

Email: `get_charts`

Email: `get_client_settings`

Email: `get_default_email_quota`

Email: `get_default_email_quota_mib`

Email: `get_disk_usage`

Email: `get_filter`

Email: `get_held_message_count`

Email: `get_mailbox_autocreate`

Email: `get_mailman_delegates`

Email: `get_main_account_disk_usage`

Email: `get_main_account_disk_usage_bytes`

Email: `get_max_email_quota`

Email: `get_max_email_quota_mib`

Email: `get_pop_quota`

Email: `get_spam_settings`

Email: `get_webmail_settings`

Email: `has_delegated_mailman_lists`

Email: `has_plaintext_authentication`

Email: `hold_outgoing`

Email: `is_integer`

Email: `list_auto_responders`

Email: `list_default_address`

Email: `list_domain_forwarders`

Email: `list_filters`

Email: `list_filters_backups`

Email: `list_forward`

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Examples
addon	string	The cPAddon for which to return the instances data.	<Vendor>::<Category>::<Application>	cPanel::Blogs::WordPressX

Returns

Return	Type	Description	Possible values	Example
addon	string	The name of the cPAddon in double colon-delimited form.	<Vendor>::<Category>::<Application>	cPanel::Blogs::WordPressX
installdir	string	The full path of the directory in which the system deployed the cPAddon.	A valid directory path.	/home/example/public_html/wordpress
instance	string	The name of the instance and the number suffix.	A cPAddons module name that precedes an integer.	cPanel::Blogs::WordPressX.0

ers	unique_id	string	The unique identifier for the cPAddon.	A unique identifier.	cPanel::Blog s::WordPress X.0.14867548 61
Email:: list_forward_ers_backups			<p>Note : This identifier will not change when you change the cPAddon's settings. However, if a new instance reuses a cPAddon's instance name, the system updates the unique identifier. You can use this identifier to select a specific instance to modify.</p>		
Email:: list_lists					
Email:: list_mail_domains					
Email:: list_mx					
Email:: list_pops					
Email:: list_pops_with_disk					
Email:: list_system_filter_info					
Email:: passwd_list					
Email:: passwd_pop					
Email:: release_outgoing					
Email:: remove_mailman_delegates					
Email:: reorder_filters					
Email:: set_always_accept					
Email:: set_default_address					
Email:: set_list_privacy_options					
Email:: stats_db_status					
Email:: store_filter					
Email:: suspend_incoming					
Email:: suspend_login					
Email:: suspend_outgoing					
Email:: trace_filter					
Email:: unsuspend_incoming					
Email:: unsuspend_login					
Email:: unsuspend_outgoing					
Email:: verify_password					

▼ EmailAuth

EmailAuth:: disable_dkim
EmailAuth:: enable_dkim

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat ion

ExternalAuthentic
ation:: add_authn_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_authn_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

▼ Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_version

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

ModSecurity:: enable_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server
_information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_acc

ounts

▼ ResourceUsage

ResourceUsage::
get_usages

▼ Restore

Restore:: directory
_listing

Restore:: get_user
s

Restore:: query_fil
e_info

Restore:: restore_f
ile

▼ Session

Session:: create_t
emp_user

▼ SiteTemplates

SiteTemplates:: list
_site_templates

SiteTemplates:: list
_user_settings

SiteTemplates:: pu
blish

▼ SpamAssassin

SpamAssassin :: cl
ear_spam_box

SpamAssassin:: g
et_symbolic_test_
names

SpamAssassin:: g
et_user_preferenc
es

SpamAssassin:: u
pdate_user_prefer
ence

▼ SSH

SSH:: get_port

▼ SSL

SSL:: add_autossl
_excluded_domain
s

SSL:: check_share
d_cert

SSL:: delete_cert

SSL:: delete_csr

SSL:: delete_key

SSL:: delete_ssl

SSL :: disable_mai
l_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f

or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do

mains

SSL:: set_autossl_excluded_domains

SSL:: set_cert_friendly_name

SSL:: set_csr_friendly_name

SSL:: set_key_friendly_name

SSL:: set_primary_ssl

SSL:: set_ssl_share

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_check

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stats

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: add_subdomain

▼ Themes

Themes:: get_theme_base

Themes:: list

Themes:: update

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps
WebmailApps:: list
webmailapps

▼ WebVhosts
WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup
WordPressBackup
:: any_running

WordPressBackup
:: cancel

WordPressBackup
:: cleanup

WordPressBackup
:: get_available_backups

WordPressBackup
:: is_running

WordPressBackup
:: start

▼ WordPressInstance
Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_instance_by_id

WordPressInstanceManager:: get_instances

WordPressInstanceManager:: get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager:: get_scan_results

WordPressInstanceManager:: is_inst

allable_addon_ava
ilable

WordPressInstanc
eManager:: start_s
can

▼ WordPressRestore

WordPressRestore
:: any_running

WordPressRestore
:: cleanup

WordPressRestore
:: start