

WHM API 1 Functions - get_autossl_pending_queue_for_domain

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Account Restoration
restore_modules_summary

restore_queue_activate

restore_queue_add_task

restore_queue_clear_all_completed_tasks

restore_queue_clear_all_failed_tasks

restore_queue_clear_all_pending_tasks

restore_queue_clear_all_tasks

restore_queue_clear_completed_task

restore_queue_clear_pending_task

restore_queue_is_active

restore_queue_list_active

restore_queue_list_com

Description

This function returns the most recent AutoSSL pending queue information for a specific domain.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/get_autossl_pending_queue_for_domain?api.version=1&domain=example.com
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/get_autossl_pending_queue_for_domain?api.version=1&domain=example.com
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-)t

Find a function

pleted
restore_queue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

▼ Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct_id
verify_new_

▼ Command Line

```
whmapil  
get_autossl_pending_queue_for_domain  
domain=example.com
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

- WHM API 1 Sections - Security — Security functions allow you to manage system security services.
- WHM API 1 Functions - `authorize_sshkey` — This function authorizes a key to access the server via SSH.

username

▼ Addon Domains

convert_addon_fetch_conversion_details

convert_addon_fetch_main_details

convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_addon_domains

convert_addon_list_conversions

▼ Authentication

api_token_create

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_failing_authentication_providers

enable_authentication_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider_display_configurations

get_users_a

▼ Output (JSON)

```
{
  "data" : {
    "queue_by_domain" : [
      {
        "last_poll_time" :
        "2017-08-19T13:27:03Z",
        "domains"
      : [
        "example.com",
        "www.example.com"
      ],
        "dcv_methods" : [
        "http",
        "dns"
      ],
        "request_time" :
        "2017-08-12T21:02:56Z",
        "vhost_name" :
        "example.com",
        "order_item_id" :
        "12345678"
      }
    ],
    "metadata" : {
      "version" : 1,
      "command" :
      "get_autossl_pending_queue_for_domain",
      "result" : 1,
      "reason" : "OK"
    }
  }
}
```

- WHM API 1 Functions - check_remote_ssh_connection — This function tests an SSH connection to another server.
- WHM API 1 Functions - convert_openssh_private_key_to_PuTTY_key.

uthn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer
twofactorauth_get_user_configs
twofactorauth_policy_status
twofactorauth_remove_user_config
twofactorauth_set_issuer
twofactorauth_set_tfa_config
unlink_user_authn_provider
validate_loggin_token

▼ Backups

backup_config_get
backup_config_set
backup_date_list
backup_destination_add
backup_destination_delete
backup_destination_get

▼ Output (XML)

```
<data>
  <queue_by_domain>

  <dcv_methods>http</dcv_methods>

  <dcv_methods>dns</dcv_methods>

  <domains>example.com</domains>

  <domains>www.example.com</domains>

  <last_poll_time>2017-08-19T13:27:03Z</last_poll_time>

  <order_item_id>12345678</order_item_id>

  <request_time>2017-08-12T21:02:56Z</request_time>

  <vhost_name>example.com</vhost_name>
  </queue_by_domain>
</data>
<metadata>

  <command>get_autossl_pending_queue_for_domain</command>
  <reason>OK</reason>
  <result>1</result>

  <version>1</version>
</metadata>
```

Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

backup_dest
ination_list

backup_dest
ination_set

backup_dest
ination_valid
ate

backup_get
_transport_s
tatus

backup_list_
transported

backup_set_
list

backup_skip
_users_all

backup_skip
_users_all_s
tatus

backup_use
r_list

convert_and
_migrate_fro
m_legacy_c
onfig

get_users_w
ith_backup_
metadata

list_cparchiv
e_files

start_backgr
ound_pkgac
t

toggle_user
_backup_sta
te

▼ cPHulk

cphulk_statu
s

create_cphu
lk_record

delete_cphu
lk_record

disable_cph
ulk

enable_cph
ulk

flush_cphulk
_login_histo
ry

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno

Parameters

Parameter	Type	Description	Possible values	Example
domain	string	<p>Required</p> <p>The domain for which to check the AutoSSL pending queue.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : You can only enter one domain when you call this function. To check the most recent list of all AutoSSL queued domains that a user owns, read our get_autossl_pending_domains_gregueu_e_f_or_use_r_documentation.</p> </div>	A valid domain name that the account owns.	example.com

Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

wn_ip_ranges
 get_cphulk_brutes
 get_cphulk_excessive_brutes
 get_cphulk_failed_logins
 get_cphulk_user_brutes
 load_cphulk_config
 read_cphulk_records
 save_cphulk_config
 set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status
 current_mysql_version
 installable_mysql_versions
 latest_available_mysql_version
 list_database_users
 list_databases
 list_mysql_databases_and_users
 remote_mysql_create_profile
 remote_mysql_create_profile_via_ssh
 remote_mysql_delete_profile
 remote_mysql_initiate_profile_activation
 remote_mysql_monitor_profile_activation

queue_by_domain	<i>array of hashes</i>	An array of hashes that contain information about the AutoSSL pending queue for the specific domain.	This array of hashes includes the domains, last_poll_time, order_item_id, request_time, vhost_name, and dcw_methods returns.	
domains	<i>array of strings</i>	An array that contains information about the domains from the certificate's order_item_id parameter. The function returns this array in the queue_by_domain array of hashes.	A valid domain on the server.	www.example.com
last_poll_time	<i>string</i>	The time of the most recent poll of the provider for the DCV status. The function returns this value in the queue_by_domain array of hashes.	A time value, in ISO-8601 format.	2017-08-19T13:27:03Z
order_item_id	<i>string</i>	The provider's order item ID for the certificate. The function returns this value in the queue_by_domain array of hashes.	A valid order item ID.	12345678
request_time	<i>string</i>	When AutoSSL made the request to the provider. The function returns this value in the queue_by_domain array of hashes.	A time value, in ISO-8601 format.	2017-08-12T21:02:56Z
vhost_name	<i>string</i>	The virtual host that contains the domain. The function returns this value in the queue_by_domain array of hashes.	A valid virtual host name.	example.com

remote_mysql_read_profile remote_mysql_read_profiles remote_mysql_update_profile remote_mysql_validate_profile rename_mysql_database rename_mysql_user rename_postgresql_database rename_postgresql_user set_local_mysql_root_password set_mysql_password set_postgresql_password start_background_mysql_upgrade	dcv_methods array of strings	The methods of Domain Control Validation (DCV) that the system requested the Certificate Authority (CA) to perform for the given domains. Note : We introduced this return in cPanel & WHM version 74. The function returns this value in the queue_by_domain array of hashes.	A comma-separated list that may contain http, dns, or both values. Note : This function returns the results from the domains parameter in the same order in which you called them.	http
---	---------------------------------	--	---	------

▼ DNS

- adddns
- addzonerecord
- addzonerecord (Reverse DNS)
- dumpzone
- editzonerecord
- get_nameserver_config
- getzonerecord
- has_local_authority
- killdns
- listmxs
- listzones
- lookupnsip

lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_package
s
ea4_get_ea
_pkgs_state
ea4_list_pro
files
ea4_migrati
on
ea4_pre_mi
grate_check
ea4_recom
mendations
ea4_save_p
rofile
ea4_tomcat
85_add
ea4_tomcat
85_list
ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d
cpgreylist_li
st_entries_f
or_common
_mail_provid
er
cpgreylist_lo
ad_common
_mail_provid
ers_config
cpgreylist_s
ave_commo
n_mail_provi
ders_config
cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyl
ist_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte
gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_ip
get_shared_ip
ipv6_disable_account
ipv6_enable_account
ipv6_range_add
ipv6_range_edit
ipv6_range_list
ipv6_range_remove
ipv6_range_usage
listips
nat_checkip
nat_set_public_ip
setsiteip

▼ Mail

disable_dkim
disable_mail_sni
emailtrack_search
emailtrack_stats
emailtrack_user_stats
enable_dkim
enable_mail_sni
ensure_dkim_keys_exist
exim_configuration_check
expunge_mailbox_messages
expunge_messages_for_mailbox_guid
fetch_dkim_private_keys

fetch_mail_
queue

generate_m
obileconfig

get_mailbox
_status

get_mailbox
_status_list

get_user_e
mail_forwar
d_destinatio
n

hold_outgoi
ng_email

install_dkim
_private_key
s

install_spf_r
ecords

is_sni_supp
orted

list_pops_for

mail_sni_sta
tus

rebuild_mail
_sni_config

release_out
going_email

save_spamd
_config

set_user_e
mail_forwar
d_destinatio
n

suspend_ou
tgoing_email

unsuspend_
outgoing_e
mail

validate_cur
rent_installe
d_exim_conf
ig

validate_cur
rent_dkims

validate_cur
rent_ptrs

validate_cur
rent_spfs

validate_exi
m_configura
tion_syntax

▼ Market

disable_mar
ket_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_deploy_all_rule_changes

modsec_deploy_rule_changes

modsec_deploy_settings_changes

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

modsec_disable_all_rule_changes

modsec_disable_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set
_config_text

modsec_set
_setting

modsec_un
disable_rule

modsec_up
date_vendor

▼ Packages

_getpkgexte
nsionform

add_overrid
e_features_f
or_user

addpkg

addpkgext

changepack
age

create_featu
relist

delete_featu
relist

delpkgext

editpkg

get_availabl
e_applicatio
ns

get_availabl
e_featurelist
s

get_feature_
metadata

get_feature_
names

get_featureli
st_data

get_featureli
sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_override_features_for_user

update_featurelist

verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_default_accounts_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_versions_by_version

php_get_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_set_default_accounts_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_p

ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacts

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacts

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese
ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m

anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
shtoputty

deletesshke
y

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba

ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tweakse
tting

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg
nvget
nvset
personalization_get
personalization_set
purchase_application_license
reboot
remove_in_progress_exim_configuration
restartservice
restore_configuration_from_file
restore_configuration_from_upload
run_cpkeyctl
send_test_posturl
send_test_pushbullet_notification
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_configuration_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
systemneeds_reboot
systemloada

vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl
_check_sch
edule

get_autossl
_log

get_autossl
_logs_catalo
g

get_autossl
_metadata

get_autossl
_pending_q
ueue

get_autossl
_pending_q
ueue_for_do
main

get_autossl
_pending_q
ueue_for_us
er

get_autossl
_problems_f
or_domain

get_autossl
_problems_f
or_user

get_autossl
_providers

get_best_ssl
domain_for_
service

install_servi
ce_ssl_certif
icate

installssl

listcrts

rebuildinstall
edssldb

rebuildusers
sldb

reset_autos
ssl_provider

reset_servic
e_ssl_certifi
cate

set_autossl_
metadata

set_autossl_
metadata_k
ey

set_autossl_
provider

start_autoss
l_check_for_
all_users

start_autoss
l_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version