

WHM API 1 Functions - create_cphulk_record

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function adds a new record or records to cPHulk's whitelist or blacklist.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/create_cphulk_record?api.version=1&list_name=white&ip=192.168.0.1&comment=George%20Wendt%20flying%20through%20the%20air.
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/create_cphulk_record?api.version=1&list_name=white&ip=192.168.0.1&comment=George%20Wendt%20flying%20through%20the%20air.
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-) t

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_domain_info
getdomainowner
has_digest_auth
has_my.cnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct_id
verify_new_username

Addon Domains

Command Line

```
whmapil  
create_cphulk_record  
list_name=white  
ip=192.168.0.1  
comment=George%20Wend  
t%20flying%20through%  
20the%20air.
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Find a function

- WHM API 1 Functions - `cphulk_status` - This function returns the status of the cPanel ulk service.

convert_add
on_fetch_co
nversion_de
tails

convert_add
on_fetch_do
main_details

convert_add
on_get_con
version_stat
us

convert_add
on_initiate_c
onversion

convert_add
on_list_add
on_domains

convert_add
on_list_conv
ersions

Authentication

api_token_c
reate

api_token_li
st

api_token_r
evoke

api_token_u
pdate

disable_aut
hentication_
provider

disable_fail
ing_authenti
cation_provi
ders

enable_auth
entication_p
rovider

get_availabl
e_authentic
ation_provid
ers

get_login_ur
l

get_provider
_client_confi
gurations

get_provider
_configurati
on_fields

get_provider
_display_co
nfigurations

get_users_a
uthn_linked
_accounts

Output (JSON)

```
{
  "data": {
    "comment": "George
Wendt flying through
the air.",
    "ips_failed": {
      },
    "requester_ip": "10.1.
1.1",
    "list_name": "white",
    "ips_added": [
      "192.168.0.1"
    ]
  },
  "metadata": {
    "version": 1,
    "reason": "OK",
    "result": 1,
    "command": "create_cph
ulk_record"
  }
}
```

- WHM API 1 Functions - create_cphulk_record — This function adds a new record or records to cPHulk's white list or black list.
- WHM API 1 Functions - delete_cphulk_record — This function deletes a record or records from cPHulk's white list or black list.

link_user_authn_provider
 set_provider_client_configurations
 set_provider_display_configurations
 twofactorauth_disable_policy
 twofactorauth_enable_policy
 twofactorauth_generate_tfa_config
 twofactorauth_get_issuer
 twofactorauth_get_user_configs
 twofactorauth_policy_status
 twofactorauth_remove_user_config
 twofactorauth_set_issuer
 twofactorauth_set_tfa_config
 unlink_user_authn_provider
 validate_login_token

▼ Backups

backup_config_get
 backup_config_set
 backup_date_list
 backup_destination_add
 backup_destination_delete
 backup_destination_get
 backup_destination_list

▼ Output (XML)

```
<result>
  <data>

  <comment>George Wendt
  flying through the
  air</comment>
    <ips_failed/>

  <list_name>white</list_name>

  <requester_ip>10.1.4.
  228</requester_ip>

  <ips_added>192.168.0
  .1</ips_added>
  </data>
  <metadata>

  <version>1</version>

  <reason>OK</reason>

  <result>1</result>

  <command>create_cphulk_record</command>
  </metadata>
</result>
```

Note:
 Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

- WHM API 1 Functions - disable_cphulk
 — This function disables the cPHulk service.

Parameters

Parameter	Type	Description	Possible values	Example
list_name	string	Required The cPHulk list's name.	<ul style="list-style-type: none"> • black • white 	white

backup_destination_set backup_destination_validate backup_get_transport_status backup_list_transported backup_set_list backup_skip_users_all backup_skip_users_all_status backup_user_list convert_and_migrate_from_legacy_config get_users_with_backup_metadata list_cparchive_files start_background_package toggle_user_backup_status	ip	string	<p>Required</p> <p>The record's IP address, if there is only one IP address to add.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note</p> <p>:</p> <p>To add multiple IP addresses, increment the parameter name. For example, ip-1, ip-2, ip-3</p> </div>	A valid IP address.	192.168.0.1
	comment	string	A comment to include.	A valid string with a maximum length of 255 characters.	George Wendt flying through the air.

▼ cPHulk

- [cphulk_status](#)
- [create_cphulk_record](#)
- [delete_cphulk_record](#)
- [disable_cphulk](#)
- [enable_cphulk](#)
- [flush_cphulk_login_history](#)
- [flush_cphulk_login_history_for_ips](#)
- [get_countries_with_known_ip_ranges](#)

Returns

Return	Type	Description	Possible values	Example
comment	string	The comment that you included when you called the function.	The comment in put parameter's value.	George Wendt flying through the air.
list_name	string	The cPHulk list's name.	<ul style="list-style-type: none"> • black • white 	white
requester_ip	string	The IP address of the user or system that requested the addition.	A valid IP address.	10.1.4.228
ips_added	array of strings	An array of the IP addresses that the function removed from the list.	An array of IP addresses.	192.168.0.1

get_cphulk_brutes
 get_cphulk_excessive_brutes
 get_cphulk_failed_logins
 get_cphulk_user_brutes
 load_cphulk_config
 read_cphulk_records
 save_cphulk_config
 set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status
 current_mysql_version
 installable_mysql_versions
 latest_available_mysql_version
 list_databases_users
 list_databases
 list_mysql_databases_and_users
 remote_mysql_create_profile
 remote_mysql_create_profile_via_ssh
 remote_mysql_delete_profile
 remote_mysql_initiate_profile_activation
 remote_mysql_monitor_profile_activation
 remote_mysql_read_prof

ips_failed	hash	A hash of the IP addresses that the system failed to add to the list.	This hash contains one or more IP addresses returns.	
IP addresses	string	<p>The reason why the system failed to add an IP address to the list.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : The IP address is the return's name.</p> </div> <p>The function returns this value in the ips_failed hash.</p>	A valid string.	Invalid IP address or range: "192.68.0.1"

ile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns

listmxs

listzones

lookupnsip

lookupnsips

removezone
record

resetzone

resolvedom
ainname

savemxs

setresolvers

update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid
ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_

for_common_mail_provider

cpgreylist_untrusted_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_host

save_cpgreylist_config

Integration

batch

cpanel

create_integration_group

create_integration_link

get_integration_link_user_config

list_integration_groups

list_integration_links

remove_integration_group

remove_integration_link

update_integration_link_token

IP Addresses

addips

delip

get_public_i

p

get_shared_
ip

ipv6_disable_
_account

ipv6_enable_
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail_
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail_
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m
ailbox_mess
ages

expunge_m
essages_for
_mailbox_gu
id

fetch_dkim_
private_keys

fetch_mail_

queue
generate_m
obileconfig
get_mailbox
_status
get_mailbox
_status_list
get_user_e
mail_forwar
d_destinatio
n
hold_outgoi
ng_email
install_dkim
_private_key
s
install_spf_r
ecords
is_sni_supp
orted
list_pops_for
mail_sni_sta
tus
rebuild_mail
_sni_config
release_out
going_email
save_spamd
_config
set_user_e
mail_forwar
d_destinatio
n
suspend_ou
tgoing_email
unsuspend_
outgoing_e
mail
validate_cur
rent_installe
d_exim_conf
ig
validate_cur
rent_dkims
validate_cur
rent_ptrs
validate_cur
rent_spfs
validate_exi
m_configura
tion_syntax

▼ Market

disable_mar
ket_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_deploy_all_rule_changes

modsec_deploy_rule_changes

modsec_deploy_settings_changes

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

modsec_disable_all_rule_changes

modsec_disable_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set
_config_text

modsec_set
_setting

modsec_un
disable_rule

modsec_up
date_vendor

▼ Packages

_getpkgexte
nsionform

add_overrid
e_features_f
or_user

addpkg

addpkgext

changepack
age

create_featu
relist

delete_featu
relist

delpkgext

editpkg

get_availabl
e_applicatio
ns

get_availabl
e_featurelist
s

get_feature_
metadata

get_feature_
names

get_featureli
st_data

get_featureli
sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_override_features_for_user

update_featurelist

verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_default_accounts_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_hosts_by_version

php_get_host_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_set_default_accounts_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_p

ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacts

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacts

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese
ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_
rsion

get_rpm_
sion_data

install_rpm_
plugin

list_rpms

package_m

anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
shtoputty

deletesshke
y

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba

ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tweakse
tting

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg
nvget
nvset
personalization_get
personalization_set
purchase_application_license
reboot
remove_in_progress_exim_configuration
restartservice
restore_configuration_from_file
restore_configuration_from_upload
run_cpkeyctl
send_test_posturl
send_test_pushbullet_notification
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_configuration_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
systemneeds_reboot
systemloada

vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl
_check_sch
edule

get_autossl
_log

get_autossl
_logs_catalo
g

get_autossl
_metadata

get_autossl
_pending_q
ueue

get_autossl
_pending_q
ueue_for_do
main

get_autossl
_pending_q
ueue_for_us
er

get_autossl
_problems_f
or_domain

get_autossl
_problems_f
or_user

get_autossl
_providers

get_best_ssl
domain_for_
service

install_servi
ce_ssl_certif
icate

installssl

listcrts

rebuildinstall
edssldb

rebuildusers
sldb

reset_autos
ssl_provider

reset_servic
e_ssl_certifi
cate

set_autossl_
metadata

set_autossl_
metadata_k
ey

set_autossl_
provider

start_autoss
l_check_for_
all_users

start_autoss
l_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version