

The wwwacct Script

Overview

The `/scripts/wwwacct` script

Arguments and inputs

Example

Additional documentation

Overview

This script creates a cPanel account. This script also sets up the new account's domain information.

Note:

You can also create a account with the [WHM API 1 createacct](#) function.

The `/scripts/wwwacct` script

To use the `/scripts/wwwacct` script, run the following command as the `root` user:

```
/usr/local/cpanel/scripts/wwwacct <argument>
```

Arguments and inputs

You can use the following arguments with the `/scripts/wwwacct` script:

Argument	Type	Description	Possible values	Example
domain	<i>string</i>	The account's main domain name.	A valid domain name.	example.com
user	<i>string</i>	The account's username.	A valid username.	user
pass	<i>string</i>	The account's password.	A secure password.	123451uggage
quota	<i>integer</i>	The account's disk space quota.	<ul style="list-style-type: none">An integer value between one and 999999 that represents a disk space quota in Megabytes (MB).0 — The account possesses unlimited disk space.	0
cpmod	<i>string</i>	The account's cPanel theme.	<ul style="list-style-type: none">paper_lanternAnother valid theme on the server.	paper_lantern
ip	<i>string</i>	Whether the account has a dedicated IP address. This parameter defaults to <code>n</code> .	<ul style="list-style-type: none"><code>y</code> — The account possesses a dedicated IP address.<code>n</code> — The account does not possess a dedicated IP address.	<code>n</code>
cgi	<i>string</i>	Whether the account has CGI access.	<ul style="list-style-type: none"><code>y</code> — CGI access.<code>n</code> — No CGI access.	<code>y</code>

frontpage	<i>string</i>	Whether Microsoft® FrontPage® Extensions exist on the account.	<ul style="list-style-type: none"> • y — Installed. • n — Not installed. <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note: In cPanel & WHM version 11.46 and later, this value is always n.</p> </div>	n
maxftp	<i>string</i>	The account's maximum number of FTP accounts.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxsql	<i>string</i>	The account's maximum number of SQL databases	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxpop	<i>string</i>	The account's maximum number of email addresses.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxlst	<i>string</i>	The account's maximum number of Mailman mailing lists.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
maxsub	<i>string</i>	The account's maximum number of subdomains.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
bwlimit	<i>string</i>	The account's bandwidth quota.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — Unlimited. 	0
hasshell	<i>string</i>	Whether the account has shell access.	<ul style="list-style-type: none"> • y — Shell access. • n — No shell access. 	y
owner	<i>string</i>	The WHM account that owns this account.	<ul style="list-style-type: none"> • A valid reseller's username. • root 	root
plan	<i>string</i>	The account's hosting plan (package).	A valid package name.	default
maxpark	<i>string</i>	The account's maximum number of parked domains (aliases). This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — The account possesses unlimited parked domains. 	unlimited
maxaddon	<i>string</i>	The account's maximum number of addon domains. This parameter defaults to unlimited.	<ul style="list-style-type: none"> • A positive integer between one and 999,999. • 0, unlimited, or null — The account possesses unlimited addon domains. 	unlimited

featurelist	string	The account's feature list. If you do not use this parameter, the function assigns the default feature list to the account.	A valid feature list name on the server.	default
contactemail	string	The account's contact email address.	A valid email address.	user@example.com
use_registered_nameservers	string	Whether to use the domain's registered nameservers instead of the server's nameservers.	<ul style="list-style-type: none"> y — Use the domain's nameservers. n — Use the server's nameservers. 	0
language	string	The account's locale.	A valid locale name.	en
spamassassin	string	Whether Apache SpamAssassin™ is enabled on the account. Note: We added this parameter in cPanel & WHM version 70.	<ul style="list-style-type: none"> y — Enabled. n — Disabled. 	y
max_emailacct_quota	string	The maximum quota for each email address in MB. Note: We added this parameter in cPanel & WHM version 70.	<ul style="list-style-type: none"> A positive integer between one and 4,294,967,296. unlimited — Unlimited. 	unlimited

Example

The following example creates the `example.com` cPanel account:

```
/usr/local/cpanel/scripts/wwvacct example.com user 12345luggage 0
paper_lantern n y n 0 0 0 0 0 0 y root default unlimited unlimited default
user@example.com 0 en y unlimited
```

Additional documentation

Suggested documentation [For cPanel users](#) [For WHM users](#) [For developers](#)

- [The wwwacct Script](#)
- [Create a New Account - Settings](#)
- [Create a New Account](#)
- [Create a New Account - Package](#)
- [Create a New Account - Domain Information](#)
- [User Manager](#)
- [How to Create a WHM Reseller Without An Associated Domain](#)

- [The wwwacct Script](#)
- [How to Create a Demo cPanel Account](#)
- [Create a New Account - Settings](#)
- [Create a New Account](#)

- [WHM API 1 Functions - createacct](#)
- [WHM API 0 Functions - createacct](#)
- [WHM API 1 Functions - setresellerips](#)
- [WHM API 0 Functions - listacls](#)
- [WHM API 1 Functions - setresellermainip](#)