

# UAPI Functions - EmailAuth::disable\_dkim

## Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup  
Backup::  
fullbacku

p\_to\_ftp

Backup:: fullbacku  
p\_to\_homedir

Backup:: fullbacku  
p\_to\_scp\_with\_key

Backup:: fullbacku  
p\_to\_scp\_with\_pa  
ssword

Backup:: list\_back  
ups

### Bandwidth

Bandwidth:: get\_e  
nabled\_protocols

Bandwidth:: get\_re  
tention\_periods

Bandwidth:: query

### Batch

Batch:: strict

### Brand

Brand:: read

### Branding

Branding:: file

Branding:: get\_app  
lications

Branding:: get\_app  
lication\_informati  
on

Branding:: get\_ava  
ilable\_applications

Branding:: get\_info  
rmation\_for\_applic  
ations

## Description

This function removes the Domain Keys Identified Mail (DKIM) records on the DNS server for one or more domains.

### Important:

When you disable the `MailSend` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### ▼ cPanel or Webmail Session URL

```
https://hostname.exam  
ple.com:2083/cpsess##  
▼ #####/execute/Emai  
lAuth/disable_dkim?do  
main=example.com&doma  
in=anotherexample.com
```

### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

## Func tion infor mati on

## About this mod ule

The `EmailAuth` mod  
ule manag  
es email  
authent  
ication  
to en  
sure email  
deliv  
erability.

## About t UAPI

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
  - CacheBuster:: read
  - CacheBuster:: update
- Chkserverd
  - Chkserverd:: get\_exim\_ports
  - Chkserverd:: get\_exim\_ports\_ssl
- Chrome
  - Chrome:: get\_dom
- Contactus
  - Contactus:: is\_enabled
- cPAddons
  - cPAddons:: get\_available\_addons
  - cPAddons:: get\_instance\_settings
  - cPAddons:: list\_addon\_instances
- cPGreyList
  - cPGreyList:: disable\_all\_domains
  - cPGreyList:: disable\_domains
  - cPGreyList:: enable\_all\_domains
  - cPGreyList:: enable\_domains
  - cPGreyList:: has\_greylisting\_enabled
  - cPGreyList:: list\_domains
- DAV
  - DAV:: disable\_shared\_global\_addressbook
  - DAV:: enable\_shared\_global\_addressbook
  - DAV:: get\_calendar\_contacts\_config
  - DAV:: has\_shared\_global\_addressbook
  - DAV:: is\_dav\_service\_enabled

### LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Remove a domain's
DKIM records.
$poll =
$cpanel->uapi(
    'EmailAuth',
    'disable_dkim',
    array(
        'domain' =>
        'example.com',
        'domain' =>
        'anotherexample.com'
    )
);

```

**Note:**  
 For more information, read our [Guide to the LiveAPI System](#).

UAPI accesses and modifies data for cPanel accounts.

**Notes:**

- Th
- Fe
- int
- Ur
- mi
- us
- 20
- or
- 20
- ).'
- 20
- or
- 20
- ).

**Find a function**

•

DCV module checks Domain Control Validation (DCV).

DAV:: is\_horde\_enabled

#### ▼ DCV

DCV:: check\_domains\_via\_dns

DCV:: check\_domains\_via\_http

DCV:: ensure\_domains\_can\_pass\_dcv

#### ▼ DomainInfo

DomainInfo:: domains\_data

DomainInfo:: list\_domains

DomainInfo:: main\_domain\_builtin\_subdomain\_aliases

DomainInfo:: single\_domain\_data

#### ▼ DNS

DNS:: ensure\_domains\_reside\_only\_locally

DNS:: has\_local\_authority

#### ▼ DNSSEC

DNSSEC:: disable\_dnssec

DNSSEC:: enable\_dnssec

DNSSEC:: fetch\_dns\_records

DNSSEC:: set\_nsec3

DNSSEC:: unset\_nsec3

#### ▼ Email

Email:: account\_name

Email:: add\_auto\_responder

Email:: add\_domain\_forwarder

Email:: add\_forwarder

Email:: add\_list

Email:: add\_mailman\_delegates

Email:: add\_mx

Email:: add\_pop

Email:: add\_spam\_filter

#### ▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Remove a domain's  
DKIM records.
```

```
my $poll =  
$cpliveapi->uapi(  
  'EmailAuth',  
  'disable_dkim',  
  {  
    'domain' =>  
    'example.com',  
    'domain' =>  
    'anotherexample.com'  
  }  
);
```

#### **Note:**

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions - DCV::check\_domains\_via\_http - This function checks whether the account's domains can pass Domain Control Validation (DCV) via an HTTP request.

Email: browse\_mailbox  
Email: change\_mx  
Email: check\_fastmail  
Email: check\_pipe\_forwarder  
Email: delete\_auto\_responder  
Email: delete\_domain\_forwarder  
Email: delete\_filter  
Email: delete\_forwarder  
Email: delete\_held\_messages  
Email: delete\_list  
Email: delete\_mx  
Email: delete\_pop  
Email: disable\_filter  
Email: disable\_mailbox\_autocreate  
Email: disable\_spam\_assassin  
Email: disable\_spam\_autodelete  
Email: disable\_spam\_box  
Email: dispatch\_client\_settings  
Email: edit\_pop\_quota  
Email: enable\_filter  
Email: enable\_mailbox\_autocreate  
Email: enable\_spam\_assassin  
Email: enable\_spam\_box  
Email: fetch\_charmaps  
Email: fts\_rescan\_mailbox  
Email: generate\_mailman\_otp  
Email: get\_auto\_responder  
Email: get\_chase

## ▼ cPanel Template Toolkit

```
<!-- Remove a domain's DKIM records. -->
[% data =
execute('EmailAuth',
'disable_dkim', {
'domain' =>
'example.com',
'domain' =>
'anotherexample.com'
} ) %]
[% FOREACH q =
data.resultname %]
    <p>
        [% q %]
    </p>
[% END %]
```

**Note:**

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Functions - DCV: ensure\_domains\_can\_pass\_dcw — This function indicates whether the account's domains can pass a Domain Control Validation (DCV) check.
- UAPI Modules - DNS — The DNS module checks DNS resolution issues.

ts

Email: get\_client\_settings

Email: get\_default\_email\_quota

Email: get\_default\_email\_quota\_mib

Email: get\_disk\_usage

Email: get\_filter

Email: get\_held\_message\_count

Email: get\_mailbox\_autocreate

Email: get\_mailman\_delegates

Email: get\_main\_account\_disk\_usage

Email: get\_main\_account\_disk\_usage\_bytes

Email: get\_max\_email\_quota

Email: get\_max\_email\_quota\_mib

Email: get\_pop\_quota

Email: get\_spam\_settings

Email: get\_webmail\_settings

Email: has\_delegated\_mailman\_lists

Email: has\_plaintext\_authentication

Email: hold\_outgoing

Email: is\_integer

Email: list\_autoresponders

Email: list\_default\_address

Email: list\_domain\_forwarders

Email: list\_filters

Email: list\_filters\_backups

Email: list\_forwarders

Email: list\_forward

## Command Line

```
uapi --user=username
EmailAuth
disable_dkim
domain=example.com
domain=anotherexample.com
```

### Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

## Output (JSON)

```
{
  "apiversion": 3,
  "module":
  "EmailAuth",
  "func":
  "disable_dkim",
  "result": {
    "data": [
      {
        "domain":
        "example.com",
        "msg":
        "[REMOVE:TXT@default._domainkey:v=DKIM1;k=rsa;p=AAAAAB3NzaC1yc2EAAAABiWAAAQEA5kSivOqhs0U9ZMN20nxFe27QZ3t01T2zbH70SXylKd1rjAjYXGnSXC9j2uaZ1emHlptBKVziMJC86ha7Hcj6dVOVrDQ6vF4q34bOCjtKLphQ0IjBzVIvq
```

- UAPI Functions - DNS: ensure domains reside on locally - This function indicates whether the account's domains resolve exclusively to this server.

ers\_backups  
Email: list\_lists  
Email: list\_mail\_omains  
Email: list\_mx  
Email: list\_pops  
Email: list\_pops\_with\_disk  
Email: list\_system\_filter\_info  
Email: passwd\_list  
Email: passwd\_pop  
Email: release\_outgoing  
Email: remove\_mailman\_delegates  
Email: reorder\_filters  
Email: set\_always\_accept  
Email: set\_default\_address  
Email: set\_list\_privacy\_options  
Email: stats\_db\_status  
Email: store\_filter  
Email: suspend\_incoming  
Email: suspend\_login  
Email: suspend\_outgoing  
Email: trace\_filter  
Email: unsuspend\_incoming  
Email: unsuspend\_login  
Email: unsuspend\_outgoing  
Email: verify\_password  
▼ EmailAuth  
EmailAuth: disable\_dkim  
EmailAuth: enable\_dkim  
EmailAuth: ensure\_dkim\_keys\_exist

```
ILH9eLJdRaOrS34CmgmPa
isrCk5wKVlakygvUfcj3H
zaTKS6THyZDGx5shdTpa9
lby8tpOD3JceV7ay4w8r0
DipoKPC00LpvS4EABEeMo
9sx8zQEaKv03XygyjNCCYt
Fvx1QQIRG1VoL7mPaHSaL
3anI05RpNbm/PS+9BhZg+
BqNjU4ofHBbfkXk5MiN6M
7ieR4Sk5BquccboGF13U5
slNgmCEekdt0amw; ]",
    "status":
1
    },
    {
      "domain":
"anotherexample.com",
      "msg":
"[REMOVE:TXT@default.
_domainkey:v=DKIM1;
k=rsa;
p=AAAAB3NzaC1yc2EAAA
BIwAAAE5kSivOqhs0U9
ZMN20nxFe27QZ3t01T2zb
H7OSXylKd1rjAjYXGnSXC
9j2uaZlemHlptBKVziMJC
86ha7Hcj6dVOVrDQ6vF4q
34bOCjtKLphQ0IjBzVIvq
ILH9eLJdRaOrS34CmgmPa
isrCk5wKVlakygvUfcj3H
zaTKS6THyZDGx5shdTpa9
lby8tpOD3JceV7ay4w8r0
DipoKPC00LpvS4EABEeMo
9sx8zQEaKv03XygyjNCCYt
Fvx1QQIRG1VoL7mPaHSaL
3anI05RpNbm/PS+9BhZg+
BqNjU4ofHBbfkXk5MiN6M
7ieR4Sk5BquccboGF13U5
slNgmCEekdt0amw; ]",
      "status": 1
    }
  ],
  "errors": null,
  "messages": null,
  "metadata": {
    "transformed":
1
    },
  "status": 1,
```

EmailAuth:: fetch\_  
dkim\_private\_keys

EmailAuth:: install  
\_dkim\_private\_key  
s

EmailAuth:: install  
\_spf\_records

EmailAuth:: validat  
e\_current\_dkims

EmailAuth:: validat  
e\_current\_ptrs

EmailAuth:: validat  
e\_current\_spfs

#### ExternalAuthenticat ion

ExternalAuthentic  
ation:: add\_authn\_li  
nk

ExternalAuthentic  
ation:: configured\_  
modules

ExternalAuthentic  
ation:: get\_authn\_lin  
ks

ExternalAuthentic  
ation:: has\_external  
\_auth\_modules\_co  
nfigured

ExternalAuthentic  
ation:: remove\_auth  
n\_link

#### Features

Features:: get\_feat  
ure\_metadata

Features:: has\_fea  
ture

Features:: list\_feat  
ures

#### Fileman

Fileman:: autocom  
pletedir

Fileman:: empty\_tr  
ash

Fileman:: get\_file\_  
content

Fileman:: get\_file\_i  
nformation

Fileman:: list\_files

Fileman:: save\_file  
\_content

Fileman:: transcod  
e

Fileman:: upload\_fi  
les

```
"warnings": null  
}  
}
```

#### Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

- Ftp:: add\_ftp
    - Ftp:: allows\_anonymous\_ftp
    - Ftp:: allows\_anonymous\_ftp\_incoming
    - Ftp:: delete\_ftp
    - Ftp:: ftp\_exists
    - Ftp:: get\_ftp\_daemon\_info
    - Ftp:: get\_port
    - Ftp:: get\_quota
    - Ftp:: get\_welcome\_message
    - Ftp:: kill\_session
    - Ftp:: list\_ftp
    - Ftp:: list\_ftp\_with\_disk
    - Ftp:: list\_sessions
    - Ftp:: passwd
    - Ftp:: server\_name
    - Ftp:: set\_anonymous\_ftp
    - Ftp:: set\_anonymous\_ftp\_incoming
    - Ftp:: set\_homedir
    - Ftp:: set\_quota
    - Ftp:: set\_welcome\_message
  - Integration
    - Integration:: fetch\_url
  - KnownHosts
    - KnownHosts:: create
    - KnownHosts:: delete
    - KnownHosts:: update
    - KnownHosts:: verify
  - LangPHP
    - LangPHP:: php\_get\_domain\_handler
    - LangPHP:: php\_get\_impacted\_domains
    - LangPHP:: php\_get\_installed\_version

domain	string	<p><b>Required</b></p> <p>The domain for which to remove DKIM records on the DNS server.</p> <div style="border: 1px solid orange; padding: 5px;"> <p><b>Note</b></p> <p>: To remove multiple domain DKIM records, duplicate the parameter name. For example, use the domain=example.com, domain=example.com, and domain=example.com parameters.</p> </div>	A valid domain.	example.com
--------	--------	---	-----------------	-------------

## Returns

Return	Type	Description	Possible values	Example
data	array of hashes	An array that contains information about the removal of a domain's DKIM record on the DNS server.	Each hash contains the domain, msg, and state returns.	



S

LangPHP:: php\_get\_system\_default\_version

LangPHP:: php\_get\_vhost\_versions

LangPHP:: php\_ini\_get\_user\_basic\_directives

LangPHP:: php\_ini\_get\_user\_content

LangPHP:: php\_ini\_get\_user\_paths

LangPHP:: php\_ini\_set\_user\_basic\_directives

LangPHP:: php\_ini\_set\_user\_content

LangPHP:: php\_set\_vhost\_versions

▼ LastLogin

LastLogin:: get\_last\_or\_current\_logged\_in\_ip

▼ Locale

Locale:: get\_attributes

▼ Mailboxes

Mailboxes:: expunge\_mailbox\_messages

Mailboxes:: expunge\_messages\_for\_mailbox\_guid

Mailboxes:: get\_mailbox\_status

Mailboxes:: has\_utf8\_mailbox\_names

Mailboxes:: set\_utf8\_mailbox\_names

▼ Market

Market:: cancel\_pending\_ssl\_certificate

Market:: create\_shopping\_cart

Market:: get\_all\_products

Market:: get\_certificate\_status\_details

Market:: get\_login\_url

Market:: get\_pending\_ssl\_certificates

domain	string	The domain for which the system removed the DKIM record.  This function returns this value in the data array.	A valid domain.	example.com
msg	string	Information about the removed DKIM record.  This function returns this value in the data array.	A valid string.	<p>▼ <a href="#">Click to view...</a></p> <pre>[REMOVE: TXT@default._domainkey: v=DKIM1; k=rsa; p=MIGfMA OGCSqGSI b3DQEBAQ UAA4GNAD CBiLMNOp QDw5nw4N P1RsWX1F miMzByDf OT16QCZO \xJtrPZ KskZF8\ sU0zWGTq KUOErlyJ foJzMDUv 3\zzjGs wc2nEmYq xxoQZaBk N4QaS6Mv JQxysAr+ sK8C248\ /r9zMper QdhJedUV ejtpFQHJ wgqpHy1t QMxY37L7 sQjdxmQ5 WnQ1acXi wIDAQAB\ \;]</pre>
status	Boolean	Whether the system removed the domain's DKIM record on the DNS server.  This function returns this value in the data array.	<ul style="list-style-type: none"> <li>1 — The system removed the domain's DKIM record.</li> <li>0 — The system did <b>not</b> remove the domain's DKIM record.</li> </ul>	1

Market:: get\_provider\_specific\_dcv\_constraints

Market:: get\_providers\_list

Market:: get\_ssl\_certificate\_if\_available

Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

#### ▼ Mime

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

#### ▼ ModSecurity

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

ModSecurity:: has  
\_modsecurity\_inst  
alled

ModSecurity:: list\_  
domains

▼ Mysql

Mysql:: add\_host

Mysql:: add\_host\_  
note

Mysql :: check\_dat  
abase

Mysql:: create\_dat  
abase

Mysql:: create\_use  
r

Mysql:: delete\_dat  
abase

Mysql:: delete\_hos  
t

Mysql:: delete\_use  
r

Mysql:: get\_host\_n  
otes

Mysql:: get\_privile  
ges\_on\_database

Mysql:: get\_restrict  
ions

Mysql:: get\_server  
\_information

Mysql:: locate\_ser  
ver

Mysql:: rename\_d  
atabase

Mysql:: rename\_us  
er

Mysql:: repair\_dat  
abase

Mysql:: revoke\_ac  
cess\_to\_database

Mysql:: set\_passw  
ord

Mysql:: set\_privile  
ges\_on\_database

▼ Notifications

Notifications:: get\_  
notifications\_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile\_rel  
ative\_uri

- ▼ PassengerApps
  - PassengerApps:: disable\_application
  - PassengerApps:: edit\_application
  - PassengerApps:: enable\_application
  - PassengerApps:: ensure\_deps
  - PassengerApps:: list\_applications
  - PassengerApps:: register\_application
  - PassengerApps:: unregister\_application
- ▼ PasswdStrength
  - PasswdStrength:: get\_required\_strength
- ▼ Personalization
  - Personalization::set
  - Personalization::get
- ▼ Postgresql
  - Postgresql:: create\_database
  - Postgresql:: create\_user
  - Postgresql:: delete\_database
  - Postgresql:: get\_restrictions
  - Postgresql:: grant\_all\_privileges
  - Postgresql:: rename\_database
  - Postgresql:: rename\_user
  - Postgresql:: rename\_user\_no\_password
  - Postgresql:: revoke\_all\_privileges
  - Postgresql:: set\_password
- ▼ Pushbullet
  - Pushbullet:: send\_test\_message
- ▼ Quota
  - Quota:: get\_quota\_info

- ▼ Resellers
  - Resellers:: list\_accounts
- ▼ ResourceUsage
  - ResourceUsage:: get\_usages
- ▼ Restore
  - Restore:: directory\_listing
  - Restore:: get\_users
  - Restore:: query\_file\_info
  - Restore:: restore\_file
- ▼ Session
  - Session:: create\_temp\_user
- ▼ SiteTemplates
  - SiteTemplates:: list\_site\_templates
  - SiteTemplates:: list\_user\_settings
  - SiteTemplates:: publish
- ▼ SpamAssassin
  - SpamAssassin :: clear\_spam\_box
  - SpamAssassin:: get\_symbolic\_test\_names
  - SpamAssassin:: get\_user\_preferences
  - SpamAssassin:: update\_user\_preference
- ▼ SSH
  - SSH:: get\_port
- ▼ SSL
  - SSL:: add\_autossl\_excluded\_domains
  - SSL:: check\_shared\_cert
  - SSL:: delete\_cert
  - SSL:: delete\_csr
  - SSL:: delete\_key
  - SSL:: delete\_ssl
  - SSL :: disable\_mail\_sni
  - SSL:: enable\_mail\_sni

SSL:: fetch\_best\_f  
or\_domain

SSL:: fetch\_cert\_in  
fo

SSL:: fetch\_certific  
ates\_for\_fqdns

SSL:: fetch\_key\_a  
nd\_cabundle\_for\_  
certificate

SSL:: find\_certifica  
tes\_for\_key

SSL:: find\_csrs\_for  
\_key

SSL:: generate\_ce  
rt

SSL:: generate\_cs  
r

SSL:: generate\_ke  
y

SSL:: get\_autossl\_  
excluded\_domains

SSL:: get\_autossl\_  
pending\_queue

SSL:: get\_autossl\_  
problems

SSL:: get\_cabundl  
e

SSL:: get\_cn\_nam  
e

SSL:: install\_ssl

SSL:: installed\_ho  
st

SSL:: installed\_ho  
sts

SSL:: is\_autossl\_c  
heck\_in\_progress

SSL:: is\_mail\_sni\_  
supported

SSL:: is\_sni\_supp  
orted

SSL:: list\_certs

SSL:: list\_csrs

SSL:: list\_keys

SSL:: list\_ssl\_item  
s

SSL:: mail\_sni\_sta  
tus

SSL:: rebuild\_mail  
\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_aut  
ossl\_excluded\_do  
mains

SSL:: set\_autossl\_  
excluded\_domains

SSL:: set\_cert\_frie  
ndly\_name

SSL:: set\_csr\_frien  
dly\_name

SSL:: set\_key\_frie  
ndly\_name

SSL:: set\_primary  
\_ssl

SSL:: set\_ssl\_shar  
e

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_  
\_check

SSL:: upload\_cert

SSL:: upload\_key

▼ StatsBar

StatsBar:: get\_stat  
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

▼ SubDomain

SubDomain:: adds  
ubdomain

▼ Themes

Themes:: get\_the  
me\_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create\_fu  
ll\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: g  
enerate\_user\_conf  
iguration

TwoFactorAuth:: g

et\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: set\_user\_configuration

#### ▼ UserManager

UserManager:: check\_account\_conflicts

UserManager:: create\_user

UserManager:: delete\_user

UserManager:: dismiss\_user

UserManager:: edit\_user

UserManager:: list\_users

UserManager:: lookup\_service\_account

UserManager:: lookup\_user

UserManager:: merge\_service\_account

UserManager:: unlink\_service\_account

#### ▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

#### ▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

#### ▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve



- WebDisk
  - WebDisk:: delete\_user
  - WebDisk:: set\_homedir
  - WebDisk:: set\_password
  - WebDisk:: set\_permissions

- WebmailApps
  - WebmailApps:: list\_webmailapps

- WebVhosts
  - WebVhost:: list\_domains
  - WebVhost:: list\_ssl\_capable\_domains

- WordPressBackup
  - WordPressBackup:: any\_running
  - WordPressBackup:: cancel
  - WordPressBackup:: cleanup
  - WordPressBackup:: get\_available\_backups
  - WordPressBackup:: is\_running
  - WordPressBackup:: start

- WordPressInstanceManager
  - WordPressInstanceManager:: cancel\_scan
  - WordPressInstanceManager:: cleanup\_scan
  - WordPressInstanceManager:: change\_admin\_password
  - WordPressInstanceManager:: configure\_autoupdate
  - WordPressInstanceManager:: get\_api\_version
  - WordPressInstanceManager:: get\_instance\_by\_id
  - WordPressInstanceManager:: get\_instances

WordPressInstanceManager:: **get\_latest\_wordpress\_version\_from\_wordpress\_org**

WordPressInstanceManager:: **get\_scan\_results**

WordPressInstanceManager:: **is\_installable\_addon\_available**

WordPressInstanceManager:: **start\_scan**

▼ **WordPressRestore**

WordPressRestore:: **any\_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**