

# WHM API 1 Functions - list\_hooks

## Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore\_modules\_summary
- restore\_queue\_activate
- restore\_queue\_add\_task
- restore\_queue\_clear\_all\_completed\_tasks
- restore\_queue\_clear\_all\_failed\_tasks
- restore\_queue\_clear\_all\_pending\_tasks
- restore\_queue\_clear\_all\_tasks
- restore\_queue\_clear\_completed\_task
- restore\_queue\_clear\_pending\_task
- restore\_queue\_is\_active
- restore\_queue\_list\_active
- restore\_queue\_list\_completed

## Description

This function lists the server's script hooks.

## Examples

### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/list_hooks?api.version=1
```

### XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/list_hooks?api.version=1
```

### Command Line

```
whmapil list_hooks
```

#### Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

### Output (JSON)

```
{  "data": {    "categories": [      {
```

## Function information

## About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

#### Notes:

- Scro
- us
- Yc
- mi
- us
- 20
- or
- 20
- )t

restore\_queue\_list\_pending  
restore\_queue\_state  
restoreaccount  
verify\_new\_username\_for\_restore

▼ Accounts

accountsummary  
applist  
createacct  
domainuser\_data  
editquota  
forcepasswordchange  
get\_disk\_usage  
get\_domain\_info  
getdomainowner  
has\_digest\_auth  
has\_mycnf\_for\_cpuser  
limitbw  
list\_users  
listaccts  
listlockedaccounts  
listsuspended  
modifyacct  
myprivs  
passwd  
quota\_enabled  
removeacct  
set\_digest\_auth  
showbw  
suspendacct  
unsuspendacct

```
        "events": [  
          {  
            "stage_order": [  
              "pre",  
              "post"  
            ],  
            "stages": [  
              {  
                "stage": "post",  
                "actions": [  
                  {  
                    "stage": "post",  
                    "blocking": 0,  
                    "description": null,  
                    "event":  
                    "MariaDB-server",  
                    "exectype": "script",  
                    "hook":  
                    "/scripts/postcourier-authlibup",  
                    "rollback": null,  
                    "check": null,  
                    "escalateprivs": 0,  
                    "weight": 100,  
                    "id":  
                    "KQVO65K_8MWe__3JMPETn43S",  
                    "category":  
                    "RPM::Versions",  
                    "enabled": 1  
                  }  
                ],  
                "attributes": {  
                  "escalateprivs": 0,  
                }  
              }  
            ]  
          }  
        ]
```

## Find a function

- WHM API 1 Functions - delete\_hook — This function removes a script hook .
- WHM API 1 Functions - edit\_hook — This function edits a script hook .

- untrack\_acct\_id
- verify\_new\_username
- ▼ Addon Domains
  - convert\_addon\_fetch\_conversion\_details
  - convert\_addon\_fetch\_domain\_details
  - convert\_addon\_get\_conversion\_status
  - convert\_addon\_initiate\_conversion
  - convert\_addon\_list\_domains
  - convert\_addon\_list\_conversions
- ▼ Authentication
  - api\_token\_create
  - api\_token\_list
  - api\_token\_revoke
  - api\_token\_update
  - disable\_authentication\_provider
  - disable\_failing\_authentication\_providers
  - enable\_authentication\_provider
  - get\_available\_authentication\_providers
  - get\_login\_url
  - get\_provider\_client\_configurations
  - get\_provider\_configuration\_fields
  - get\_provider

```

"blocking": 0
    },
    "description": ""
    },
    "event": "MariaDB-server"
    },
    "category": "RPM::Versions"
  ]
},
"metadata": {
  "version": 1,
  "reason": "OK",
  "result": 1,
  "command": ""
}
"list_hooks"
}

```

- WHM API 1 Functions - list\_hooks — This function lists the server's script hooks.
- WHM API 1 Functions - reorder\_hooks — This function changes the order of script hooks.

\_display\_co  
nfigurations

get\_users\_a  
uthn\_linked  
\_accounts

link\_user\_au  
thn\_provider

set\_provider  
\_client\_confi  
gurations

set\_provider  
\_display\_co  
nfigurations

twofactoraut  
h\_disable\_p  
olicy

twofactoraut  
h\_enable\_p  
olicy

twofactoraut  
h\_generate\_  
tfa\_config

twofactoraut  
h\_get\_issue  
r

twofactoraut  
h\_get\_user\_  
configs

twofactoraut  
h\_policy\_sta  
tus

twofactoraut  
h\_remove\_u  
ser\_config

twofactoraut  
h\_set\_issuer

twofactoraut  
h\_set\_tfa\_c  
onfig

unlink\_user\_  
authn\_provi  
der

validate\_logi  
n\_token

#### Backups

backup\_conf  
ig\_get

backup\_conf  
ig\_set

backup\_dat  
e\_list

backup\_dest  
ination\_add

backup\_dest  
ination\_dele  
te

```
}
```

#### Output (XML)

```
<result>
  <data>
    <categories>
      <events>

<stage_order>pre</st
age_order>

<stage_order>post</st
age_order>

<stages>

<stage>post</stage>

<actions>

<stage>post</stage>

<blocking>0</blocking
>

<description/>

<event>courier-authli
b</event>

<exectype>script</exe
ctype>

<hook>/scripts/postco
urier-authlibup</hook
>

<rollback/>

<check/>

<escalateprivs>0</esc
alateprivs>

<weight>100</weight>

<id>KQVO65K_8MWe__3JM
PEtn43S</id>
```

backup\_destination\_get  
backup\_destination\_list  
backup\_destination\_set  
backup\_destination\_validate  
backup\_get\_transport\_status  
backup\_list\_transported  
backup\_set\_list  
backup\_set\_list\_combined  
backup\_skip\_users\_all  
backup\_skip\_users\_all\_status  
backup\_user\_list  
convert\_and\_migrate\_from\_legacy\_config  
get\_users\_with\_backup\_metadata  
list\_cparchive\_files  
start\_background\_package  
toggle\_user\_backup\_status

▼ cPHulk

cphulk\_statuses  
create\_cphulk\_record  
delete\_cphulk\_record  
disable\_cphulk  
enable\_cphulk  
flush\_cphulk\_login\_history

```
<category>RPM::Versions</category>
<enabled>1</enabled>
</actions>
<attributes>
<escalateprivs>0</escalateprivs>
<blocking>0</blocking>
</attributes>
<description/>
</stages>
<event>courier-authlib</event>
</events>
<category>RPM::Versions</category>
</categories>
</data>
<metadata>
<version>1</version>
<reason>OK</reason>
<result>1</result>
<command>list_hooks</command>
```

flush\_cphulk\_login\_history\_for\_ips

get\_countries\_with\_known\_ip\_ranges

get\_cphulk\_brutes

get\_cphulk\_excessive\_brutes

get\_cphulk\_failed\_logins

get\_cphulk\_user\_brutes

load\_cphulk\_config

read\_cphulk\_records

save\_cphulk\_config

set\_cphulk\_config\_key

▼ Databases

background\_mysql\_upgrade\_status

current\_mysql\_version

installable\_mysql\_versions

latest\_available\_mysql\_version

list\_database\_users

list\_databases

list\_mysql\_databases\_and\_users

remote\_mysql\_create\_profile

remote\_mysql\_create\_profile\_via\_ssh

remote\_mysql\_delete\_profile

remote\_mysql\_initiate\_profile\_activation

```
</metadata>
</result>
```

**Note:**  
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

## Parameters

This function does not accept parameters.

## Returns

Parameter	Type	Description	Possible values	Example
categories	array	An array of hook categories.	This array includes the <code>events</code> hash and the <code>category</code> return.	
events	hash	A hash of events.  The function returns this hash in the <code>categories</code> hash.	This hash includes the <code>stage_order</code> , <code>attributes</code> , and <code>event</code> returns and the <code>stages</code> hash.	
stage_order	string	When the hook script is designed to execute.  The function returns this value in the <code>events</code> hash.	<ul style="list-style-type: none"> <li><code>pre</code> — The script runs before the function.</li> <li><code>post</code> — The script runs after the function.</li> </ul> <p><b>Note:</b> It is possible for a hook script to have both values.</p>	pre post

ion

remote\_mysql\_monitor\_profile\_activation

remote\_mysql\_read\_profile

remote\_mysql\_read\_profiles

remote\_mysql\_update\_profile

remote\_mysql\_validate\_profile

rename\_mysql\_database

rename\_mysql\_user

rename\_postgresql\_database

rename\_postgresql\_user

set\_local\_mysql\_root\_password

set\_mysql\_password

set\_postgresql\_password

start\_background\_mysql\_upgrade

▼ DNS

addns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get\_nameserver\_config

getzonerecord

has\_local\_authority

stages	hash	A hash of stage information.  The function returns this value in the events hash.	This hash includes the below.	
	string stage	When the hook script will execute.  The function returns this value in the stages hash.	<ul style="list-style-type: none"> <li>pre — The script runs before the function.</li> <li>post — The script runs after the function.</li> </ul>	post
	hash actions	A hash of hook script actions.  The function returns this value in the stages hash.	This hash includes the stage, blocking, description, event, exectype, hook, rollback, check, escalateprivs, weight, id, category, and enabled returns.	
	string stage	When the hook script will execute.  The function returns this value in the actions hash.	<ul style="list-style-type: none"> <li>pre — The script runs before the function.</li> <li>post — The script runs after the function.</li> </ul>	post
	Boolean blocking	Whether the script hook has a blocking contest.  The function returns this value in the actions hash.	<ul style="list-style-type: none"> <li>1 — Blocking contest.</li> <li>0 — No blocking contest.</li> </ul>	0
	string description	The hook script's description.  The function returns this value in the actions hash.	A valid string.	null
	string event	The event that triggers the script hook.  The function returns this value in the actions hash.	A valid string.	MariaDB-server
	string exectype	The type of function that the script hook launches.  The function returns this value in the actions hash.	A valid string.	script

killdns  
listmxs  
listzones  
lookupnsip  
lookupnsips  
removezone  
record  
resetzone  
resolvedomainname  
savemxs  
setresolvers  
update\_nameservers\_config

EasyApache

ea4\_get\_currently\_installed\_packages  
ea4\_get\_ea\_pkgs\_state  
ea4\_list\_profiles  
ea4\_maintain  
ea4\_migration  
ea4\_pre\_migrate\_check  
ea4\_recommendations  
ea4\_save\_profile  
ea4\_tomcat85\_add  
ea4\_tomcat85\_list  
ea4\_tomcat85\_remove

Greylisting

cpgreylist\_server\_network\_block\_trusted  
cpgreylist\_list\_entries\_for\_common\_mail\_provider  
cpgreylist\_load\_common\_mail\_provider

	<i>string</i>	hook	The hook script.  The function returns this value in the actions hash.	A valid absolute file path.	/scripts/postcourier-authlibup
	<i>string</i>	rollback	A script that can roll back the hook script.  The function returns this value in the actions hash.	A valid absolute file path.	null
	<i>string</i>	check	A script that runs after the hook script to check the results.  The function returns this value in the actions hash.	A valid absolute file path.	null
	<i>Boolean</i>	escalated	Whether the hook script will run with escalated root privileges.  The function returns this value in the actions hash.	<ul style="list-style-type: none"> <li>1 — Runs with escalated privileges.</li> <li>0 — Does not run with escalated privileges.</li> </ul>	0
	<i>integer</i>	weight	The priority of the script hook.  The function returns this value in the actions hash.	A valid positive integer, where lower values run before higher values.	100
	<i>string</i>	id	The script hook's ID.  The function returns this value in the actions hash.	A valid string.	KQVO65K_8MWe__3JMPETn43S
	<i>string</i>	category	The script hook's category.  The function returns this value in the actions hash.	A valid string.	RPM::Versions
	<i>Boolean</i>	enabled	Whether the hook script is enabled.  The function returns this value in the actions hash.	<ul style="list-style-type: none"> <li>1 — Enabled.</li> <li>0 — Disabled.</li> </ul>	1
	<i>hash</i>	attributes	A hash of hook script attributes.  The function returns this value in the stages hash.	This hash includes the escalatedprivs and blocking returns below.	



ers\_config  
 cpgreylist\_save\_common\_mail\_providers\_config  
 cpgreylist\_status  
 cpgreylist\_trusted\_entries\_for\_common\_mail\_provider  
 cpgreylist\_untrusted\_entries\_for\_common\_mail\_provider  
 create\_cpgreylist\_trusted\_host  
 delete\_cpgreylist\_trusted\_host  
 disable\_cpgreylist  
 enable\_cpgreylist  
 load\_cpgreylist\_config  
 read\_cpgreylist\_deferred\_entries  
 read\_cpgreylist\_trusted\_host  
 save\_cpgreylist\_config

	<i>Boolean</i> escalated	<p>Whether the hook script will run with escalated root privileges.</p> <p>The function returns this value in the attributes hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Runs with escalated privileges.</li> <li>• 0 — Does not run with escalated privileges.</li> </ul>	0
	<i>Boolean</i> blocking	<p>Whether the script hook contains a blocking context.</p> <p>The function returns this value in the attributes hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Blocking context.</li> <li>• 0 — No blocking context.</li> </ul>	0
	<i>string</i> description	<p>The hook script's description.</p> <p>The function returns this value in the stages hash.</p>	A valid string.	
<i>event</i>	<i>string</i>	<p>The event that triggers the script hook.</p> <p>The function returns this value in the events hash.</p>	A valid string.	MariaDB-server
<i>category</i>	<i>string</i>	<p>The script hook's category.</p> <p>The function returns this value in the categories hash.</p>	A valid string.	RPM::Versions

▼ Integration

batch  
 cpanel  
 create\_integration\_group  
 create\_integration\_link  
 get\_integration\_link\_user\_config  
 list\_integration\_groups  
 list\_integration\_links  
 remove\_integration\_group  
 remove\_inte

gration\_link

update\_inte  
gration\_link  
\_token

▼ IP Addresses

addips

delip

get\_public\_i  
p

get\_shared\_  
ip

ipv6\_disable  
\_account

ipv6\_enable  
\_account

ipv6\_range\_  
add

ipv6\_range\_  
edit

ipv6\_range\_  
list

ipv6\_range\_  
remove

ipv6\_range\_  
usage

listips

nat\_checkip

nat\_set\_pub  
lic\_ip

setsiteip

▼ Mail

disable\_dki  
m

disable\_mail  
\_sni

emailtrack\_s  
earch

emailtrack\_s  
tats

emailtrack\_u  
ser\_stats

enable\_dkim

enable\_mail  
\_sni

ensure\_dki  
m\_keys\_exi  
st

exim\_config  
uration\_che  
ck

expunge\_m

ailbox\_messages  
expunge\_messages\_for\_mailbox\_guid  
fetch\_dkim\_private\_keys  
fetch\_mail\_queue  
generate\_mobileconfig  
get\_mailbox\_status  
get\_mailbox\_status\_list  
get\_unique\_recipient\_count\_per\_sender\_for\_user  
get\_unique\_sender\_recipient\_count\_per\_user  
get\_user\_email\_forward\_destination  
hold\_outgoing\_email  
install\_dkim\_private\_keys  
install\_spf\_records  
is\_sni\_supported  
list\_pops\_for  
mail\_sni\_status  
rebuild\_mail\_sni\_config  
release\_outgoing\_email  
save\_spamd\_config  
set\_user\_email\_forward\_destination  
suspend\_outgoing\_email  
unsuspend\_outgoing\_email

validate\_currency\_installed\_exim\_configuration

validate\_currency\_dkims

validate\_currency\_ptrs

validate\_currency\_spfs

validate\_exim\_configuration\_syntax

▼ Market

disable\_market\_provider

enable\_market\_provider

get\_adjusted\_market\_providers\_products

get\_market\_providers\_commission\_config

get\_market\_providers\_list

get\_market\_providers\_product\_metadata

get\_market\_providers\_products

set\_market\_product\_attribute

set\_market\_provider\_commission\_id

▼ ModSecurity™

modsec\_add\_rule

modsec\_add\_vendor

modsec\_assemble\_config\_text

modsec\_batch\_settings

modsec\_check\_rule

modsec\_clone\_rule

modsec\_de  
ploy\_all\_rule  
\_changes

modsec\_de  
ploy\_rule\_ch  
anges

modsec\_de  
ploy\_setting  
s\_changes

modsec\_dis  
able\_rule

modsec\_dis  
able\_vendor

modsec\_dis  
able\_vendor  
\_configs

modsec\_dis  
able\_vendor  
\_updates

modsec\_dis  
card\_all\_rul  
e\_changes

modsec\_dis  
card\_rule\_c  
hanges

modsec\_edit  
\_rule

modsec\_en  
able\_vendor

modsec\_en  
able\_vendor  
\_configs

modsec\_en  
able\_vendor  
\_updates

modsec\_get  
\_config\_text

modsec\_get  
\_configs

modsec\_get  
\_configs\_wit  
h\_changes\_  
pending

modsec\_get  
\_log

modsec\_get  
\_rules

modsec\_get  
\_settings

modsec\_get  
\_vendors

modsec\_is\_i  
nstalled

modsec\_ma  
ke\_config\_a  
ctive

modsec\_make\_config\_inactive

modsec\_preview\_vendor

modsec\_remove\_rule

modsec\_remove\_setting

modsec\_remove\_vendor

modsec\_report\_rule

modsec\_set\_config\_text

modsec\_set\_setting

modsec\_disable\_rule

modsec\_update\_vendor

▼ Packages

\_getpkgextensionform

add\_override\_features\_for\_user

addpkg

addpkgext

changepackage

create\_feature\_relist

delete\_feature\_relist

delpkgext

editpkg

get\_available\_applications

get\_available\_featurelists

get\_feature\_metadata

get\_feature\_names

get\_featurelist\_data

get\_featureli

sts

get\_users\_f  
eatures\_sett  
ings

getfeaturelis  
t

getpkginfo

killpkg

listpkgs

manage\_fea  
tures

matchpkgs

read\_feature  
list

remove\_ove  
rride\_featu  
res\_for\_user

update\_feat  
urelist

verify\_user\_  
has\_feature

▼ PHP

convert\_all\_  
domains\_to  
\_fpm

get\_fpm\_co  
unt\_and\_util  
ization

is\_conversio  
n\_in\_progre  
ss

php\_get\_def  
ault\_accoun  
ts\_to\_fpm

php\_get\_ha  
ndlers

php\_get\_im  
pacted\_dom  
ains

php\_get\_ins  
talled\_versio  
ns

php\_get\_old  
\_fpm\_flag

php\_get\_sys  
tem\_default  
\_version

php\_get\_vh  
osts\_by\_ver  
sion

php\_get\_vh  
ost\_versions

php\_ini\_get  
\_content

php\_ini\_get  
\_directives

php\_ini\_set  
\_content

php\_ini\_set  
\_directives

php\_set\_def  
ault\_accoun  
ts\_to\_fpm

php\_set\_ha  
ndler

php\_set\_old  
\_fpm\_flag

php\_set\_ses  
sion\_save\_p  
ath

php\_set\_sys  
tem\_default  
\_version

php\_set\_vh  
ost\_versions

▼ Resellers

acctcounts

get\_public\_c  
ontact

getresellerip  
s

listacIs

listresellers

resellerstats

saveacllist

set\_public\_c  
ontact

setacIs

setresellerip  
s

setresellerli  
mits

setresellerm  
ainip

setresellern  
ameservers

setresellerp  
ackagelimit

setupreselle  
r

suspendres  
eller

terminateres  
eller

unsetuprese



ller

unsuspendr  
eseller

▼ RPM

delete\_rpm\_  
version

edit\_rpm\_ve  
rsion

get\_rpm\_ver  
sion\_data

install\_rpm\_  
plugin

list\_rpms

package\_m  
anager\_fixc  
ache

package\_m  
anager\_get\_  
build\_log

package\_m  
anager\_get\_  
package\_inf  
o

package\_m  
anager\_is\_p  
erforming\_a  
ctions

package\_m  
anager\_list\_  
packages

package\_m  
anager\_reso  
lve\_actions

package\_m  
anager\_sub  
mit\_actions

package\_m  
anager\_upgr  
ade

uninstall\_rp  
m\_plugin

▼ Script Hooks

delete\_hook

edit\_hook

list\_hooks

reorder\_hoo  
ks

▼ Security

accesshash

authorizessh  
key

check\_remo  
te\_ssh\_conn  
ection

convertopen  
sshtoputty

deletesshke  
y

fetch\_securi  
ty\_advice

generatessh  
keypair

importsshke  
y

listsshkeys

▼ Server

Administration

add\_configcl  
usterserver

configureba  
ckgroundpro  
cesskiller

configureser  
vice

cors\_proxy\_  
get

create\_user  
\_session

delete\_conf  
gclusterserv  
er

enable\_mon  
itor\_all\_ena  
bled\_service  
s

get\_all\_cont  
act\_importa  
nces

get\_appconf  
ig\_applicatio  
n\_list

get\_applicati  
on\_contact\_  
event\_import  
tance

get\_applicati  
on\_contact\_  
importance

get\_availabl  
e\_profiles

get\_current\_  
profile

get\_passwor  
d\_strength

get\_remote\_  
access\_has  
h

get\_service\_  
config

get\_service\_  
config\_key

get\_tcp4\_so  
ckets

get\_tcp6\_so  
ckets

get\_tweakse  
tting

get\_udp4\_s  
ockets

get\_udp6\_s  
ockets

get\_update\_  
availability

get\_users\_li  
nks

getdiskusag  
e

gethostname

is\_role\_ena  
bled

list\_configcl  
usterservers

loadavg

nvget

nvset

personalizati  
on\_get

personalizati  
on\_set

purchase\_a  
\_license

reboot

remove\_in\_  
progress\_ex  
im\_config\_e  
dit

restartservic  
e

restore\_conf  
ig\_from\_file

restore\_conf  
ig\_from\_upl  
oad

run\_cpkeyctl

send\_test\_p  
osturl

send\_test\_p  
ushbullet\_n  
ote

servicestatu

s

set\_applicati  
on\_contact\_  
event\_imp  
ortance

set\_applicati  
on\_contact\_  
importance

set\_primary  
\_servernam  
e

set\_service\_  
config\_key

set\_tweakse  
tting

sethostname

setminimum  
passwordstr  
engths

start\_profile  
\_activation

system\_nee  
ds\_reboot

systemloada  
vg

update\_conf  
igclusterserv  
er

update\_cont  
act\_email

verify\_aim\_a  
ccess

verify\_icq\_a  
ccess

verify\_oscar  
\_access

verify\_postu  
rl\_access

verify\_pushb  
ullet\_access

▼ SSL

disable\_aut  
ossl

fetch\_servic  
e\_ssl\_comp  
onents

fetch\_ssl\_ce  
rtificates\_for  
\_fqdns

fetch\_ssl\_vh  
osts

fetch\_vhost  
\_ssl\_compo  
nents

fetchcrtinfo  
fetchsslinfo  
generatessl  
get\_autossl  
\_check\_schedule  
get\_autossl  
\_log  
get\_autossl  
\_logs\_catalog  
get\_autossl  
\_metadata  
get\_autossl  
\_pending\_queue  
get\_autossl  
\_pending\_queue\_for\_domain  
get\_autossl  
\_pending\_queue\_for\_user  
get\_autossl  
\_problems\_for\_domain  
get\_autossl  
\_problems\_for\_user  
get\_autossl  
\_providers  
get\_best\_ssl  
domain\_for\_service  
install\_service\_ssl\_certificate  
installssl  
listcrts  
rebuildinstall  
edssldb  
rebuildusers  
sldb  
reset\_autossl\_provider  
reset\_service\_ssl\_certificate  
set\_autossl\_metadata  
set\_autossl\_metadata\_key

set\_autossl\_  
provider

start\_autossl\_  
check\_for\_  
all\_users

start\_autossl\_  
check\_for\_  
one\_user

▼ Styles and Themes

generate\_cp  
anel\_plugin

list\_styles

load\_style

remove\_log  
o

remove\_styl  
e

save\_style

set\_default

▼ Support Tickets

ticket\_creat  
e\_stub\_ticke  
t

ticket\_get\_s  
upport\_agre  
ement

ticket\_get\_s  
upport\_info

ticket\_grant

ticket\_list

ticket\_remov  
e\_closed

ticket\_revok  
e

ticket\_ssh\_t  
est

ticket\_ssh\_t  
est\_start

ticket\_updat  
e\_service\_a  
greement\_a  
pproval

ticket\_valida  
te\_oauth2\_c  
ode

ticket\_whitel  
ist\_check

ticket\_whitel  
ist\_setup

ticket\_whitel  
ist\_unsetup

▼ Transfers

abort\_transf  
er\_session

analyze\_tra  
nsfer\_sessio  
n\_remote

available\_tr  
ansfer\_mod  
ules

create\_remo  
te\_root\_tran  
sfer\_session

create\_remo  
te\_user\_tran  
sfer\_session

delete\_accou  
nt\_archives

enqueue\_tra  
nsfer\_item

fetch\_transf  
er\_session\_l  
og

get\_transfer  
\_session\_st  
ate

pause\_trans  
fer\_session

remote\_basi  
c\_credential  
\_check

retrieve\_tran  
sfer\_session  
\_remote\_an  
alysis

start\_transfe  
r\_session

transfer\_mo  
dule\_schem  
a

validate\_sys  
tem\_user

▼ Updates

accept\_eula

get\_availabl  
e\_tiers

get\_current\_  
lts\_expiratio  
n\_status

get\_lts\_wex  
pire

getlongterm  
support

installed\_ver  
sions

set\_cpanel\_  
updates

set\_tier

update\_upd  
ateconf

version