

WHM API 1 Functions - enqueue_transfer_item

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed

Description

This function adds a transfer session to a queue.

Note:

For more information about how this function works with other functions in the transfer and restore process, read our [Guide to Transfer and Restore API Functions](#) documentation.

Examples

JSON API

AccountLocal:

```
https://hostname.example.com:2087/cpsess#####/json-api/enqueue_transfer_item?api.version=1&transfer_session_id=vm5docscpanelcopya20140211211719FxjU&module=AccountLocal&user=username&size=123456789
```

AccountRemoteUser:

```
https://hostname.example.com:2087/cpsess#####/json-api/enqueue_transfer_item?api.version=1&user=transferme&transfer_session_id=remoteexamplecomnoroo20140501194105g7qG&module=AccountRemoteUser&localuser=transferme
```

AccountRemoteRoot:

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Source
- Yumius2020)tc

restore_queue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

▼ Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_my.cnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct

```
https://hostname.example.com:2087/cpsess#####/json-api/enqueue_transfer_item?api.version=1&transfer_session_id=remoteexamplecopya20140211211719FxfjU&module=AccountRemoteRoot&user=transferme&size=123456789&localuser=transferme&detected_remote_user=transferme&domain=transferme.com&replaceip=all&reseller=0&force=0&ip=0&skiphomedir=0&shared_mysql_server=0&skipres=1&skipacctdb=0&skipaccount=0&xferpoint=1
```

PackageRemoteRoot:

```
https://hostname.example.com:2087/cpsess#####/json-api/enqueue_transfer_item?api.version=1&transfer_session_id=remoteexamplecopya20140211211719FxfjU&module=PackageRemoteRoot&package=package1
```

▼ XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/enqueue_transfer_item?api.version=1&transfer_session_id=vm5docspanelcopya20140211211719FxfjU&module=AccountLocal&user=username&size=123456789
```

Find a function

- WHM API 1 Functions - abort_transfer_session — This function aborts an active transfer session.

untrack_acct_id

verify_new_username

▼ Addon Domains

convert_addon_fetch_conversion_details

convert_addon_fetch_domain_details

convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_addon_domains

convert_addon_list_conversions

▼ Authentication

api_token_create

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_failing_authentication_providers

enable_authentication_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider

▼ Command Line

```
whmapi1
enqueue_transfer_item
transfer_session_id=vm5docscpanelcopya20140211211719FxfjU
module=AccountLocal
user=username
size=123456789
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapi1 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi1` command:

```
/usr/local/cpanel/bin/whmapi1
```

▼ Output (JSON)

```
{
  "metadata": {
    "version": 1,
    "reason": "OK",
    "result": "1",
    "command": "enqueue_transfer_item"
  }
}
```

- WHM API 1 Functions - analyze_transfer_session_remote

This function checks the remote server's credentials, which a transfer session uses to connect.

- WHM API 1 Functions - available_transfer_modules
- This function lists all available transfer modules.

_display_co
nfigurations

get_users_a
uthn_linked
_accounts

link_user_au
thn_provider

set_provider
_client_confi
gurations

set_provider
_display_co
nfigurations

twofactoraut
h_disable_p
olicy

twofactoraut
h_enable_p
olicy

twofactoraut
h_generate_
tfa_config

twofactoraut
h_get_issu
er

twofactoraut
h_get_user_
configs

twofactoraut
h_policy_sta
tus

twofactoraut
h_remove_u
ser_config

twofactoraut
h_set_issu
er

twofactoraut
h_set_tfa_c
onfig

unlink_user_
authn_provi
der

validate_logi
n_token

Backups

backup_conf
ig_get

backup_conf
ig_set

backup_dat
e_list

backup_dest
ination_add

backup_dest
ination_dele
te

Output (XML)

```
<result>
  <metadata>

  <version>1</version>

  <reason>OK</reason>

  <result>1</result>

  <command>enqueue_tran  
sfer_item</command>
  </metadata>
</result>
```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

- WHM API 1 Functions - create_remote_root_transfer_session — This function creates a transfer session as the root user.

Parameters

Parameter	Type	Description	Possible values	Example
transfer_session_id	string	Required The transfer session's ID.	A valid string.	Click to view... vm5docs cpanelco pya20140 21121171 9FxjU
module	string	Required The transfer system module.		AccountRemoteRoot

backup_destination_get
backup_destination_list
backup_destination_set
backup_destination_validate
backup_get_transport_status
backup_list_transported
backup_set_list
backup_set_list_combined
backup_skip_users_all
backup_skip_users_all_status
backup_user_list
convert_and_migrate_from_legacy_config
get_users_with_backup_metadata
list_cparchive_files
start_background_package
toggle_user_backup_status
cPHulk
cphulk_statuses
create_cphulk_record
delete_cphulk_record
disable_cphulk
enable_cphulk
flush_cphulk_login_history

- LegacyAccountBackup — This module restores legacy-account backup files.
- FeatureListRemoteRoot — This module transfers the feature list from the remote server.
- PackageRemoteRoot — This module transfers the package settings.
- AccountLocal — This module restores backup files.
- AccountRemoteRoot — This module uses the root credentials to transfer account settings that are not a part of a package.
- AccountRemoteUser — This module uses the account's user credentials to transfer account settings that are not a part of a package.

Note
s:

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

get_cphulk_
brutes

get_cphulk_
excessive_b
rutes

get_cphulk_
failed_logins

get_cphulk_
user_brutes

load_cphulk
_config

read_cphulk
_records

save_cphulk
_config

set_cphulk_
config_key

▼ Databases

background
_mysql_upg
rade_status

current_mys
ql_version

installable_
mysql_versi
ons

latest_availa
ble_mysql_v
ersion

list_databas
e_users

list_databas
es

list_mysql_d
atabases_a
nd_users

remote_mys
ql_create_pr
ofile

remote_mys
ql_create_pr
ofile_via_ss
h

remote_mys
ql_delete_pr
ofile

remote_mys
ql_initiate_p
rofile_activat

• The module parameter determines which characters are added to the list of users with the function.

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

addns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

			<ul style="list-style-type: none"> • You must perform each module action as a separate step. 	
size	integer	<p>The size of the content to transfer.</p> <p>This parameter defaults to an empty string.</p>	<p>A valid positive integer that measures the size of the content, in bytes.</p>	123456789

Additional AccountLocal or AccountRemoteRoot parameters

▼ [Click to view...](#)

Parameter	Type	Description	Possible values	Example
user	string	<p>Required</p> <p>The account to transfer.</p>	A valid username.	user

- killdns
- listmxs
- listzones
- lookupnsip
- lookupnsips
- removezone
record
- resetzone
- resolvedom
ainname
- savemxs
- setresolvers
- update_nam
eservers_co
nfig
- ea4_get_cur
rently_install
ed_packages
 - ea4_get_ea
_pkgs_state
 - ea4_list_pro
files
 - ea4_metainf
o
 - ea4_migrati
on
 - ea4_pre_mi
grate_check
 - ea4_recom
mendations
 - ea4_save_p
rofile
 - ea4_tomcat
85_add
 - ea4_tomcat
85_list
 - ea4_tomcat
85_rem
 - cpgreylist_is
_server_net
block_truste
d
 - cpgreylist_li
st_entries_f
or_common
_mail_provid
er
 - cpgreylist_lo
ad_common
_mail_provid

localuser	<i>string</i>	Required The local account's username.	A valid username.	localuser
		Note: If the user and localuser parameter do not match, you can not use the skip packet or force parameter.		
detected_remote_user	<i>string</i>	The user account name that the remote server returns when you query the user account.	A valid username.	user
domain	<i>string</i>	The domain name.	A valid string.	example.com

gration_link
 update_inte
 gration_link
 _token

▼ IP Addresses

addips
 delip
 get_public_i
 p
 get_shared_
 ip
 ipv6_disable
 _account
 ipv6_enable
 _account
 ipv6_range_
 add
 ipv6_range_
 edit
 ipv6_range_
 list
 ipv6_range_
 remove
 ipv6_range_
 usage
 listips
 nat_checkip
 nat_set_pub
 lic_ip
 setsiteip

▼ Mail

disable_dki
 m
 disable_mail
 _sni
 emailtrack_s
 earch
 emailtrack_s
 tats
 emailtrack_u
 ser_stats
 enable_dkim
 enable_mail
 _sni
 ensure_dki
 m_keys_exi
 st
 exim_config
 uration_che
 ck
 expunge_m

replaceip	<i>string</i>	The lines in the domain's zonefile to replace with the new IP address.	<ul style="list-style-type: none"> • all — Replace all of the IP addresses in the zone file with the new IP address. • basic — Replace only the proxy, sub, mail, www, and main A records in the zone file with the new IP address. 	all
reseller	<i>Boolean</i>	Whether to make the account a reseller.	<ul style="list-style-type: none"> • 1 — Reseller account. • 0 — Not a reseller account. 	0

ailbox_messages
 expunge_messages_for_mailbox_guid
 fetch_dkim_private_keys
 fetch_mail_queue
 generate_mobileconfig
 get_mailbox_status
 get_mailbox_status_list
 get_unique_recipient_count_per_sender_for_user
 get_unique_sender_recipient_count_per_user
 get_user_email_forward_destination
 hold_outgoing_email
 install_dkim_private_keys
 install_spf_records
 is_sni_supported
 list_pops_for_mail_sni_status
 rebuild_mail_sni_config
 release_outgoing_email
 save_spamdb_config
 set_user_email_forward_destination
 suspend_outgoing_email
 unsuspend_outgoing_email

force	<i>Boolean</i>	<p>Whether to use the <code>--force</code> flag to create the account during the restore process. This flag skips username and database name validation, and it overwrites the target account.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: You can not use this parameter if the following conditions exist:</p> <ul style="list-style-type: none"> You called the WHM API 1 <code>create_remote_root_transfer_session</code> function with the <code>unrestricted_restore</code> parameter set to <code>1</code>. The <code>localuser</code> parameter does not match the <code>user</code> parameter. </div>	<ul style="list-style-type: none"> 1 — Use the <code>--force</code> flag. 0 — Do not use the <code>--force</code> flag. 	0
overwrite_samesowner_databases	<i>Boolean</i>	Whether to allow the system to overwrite the account's existing databases with the databases in the backup file.	<ul style="list-style-type: none"> 1 — Allow 0 — Do not allow. 	0
overwrite_samesowner_database_users	<i>Boolean</i>	Whether to allow the system to overwrite the account's existing database users with the database users in the backup file.	<ul style="list-style-type: none"> 1 — Allow 0 — Do not allow. 	0

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

skiphomedir	Boolean	Whether to skip the contents of the home directory.	<ul style="list-style-type: none">• 1 — Skip.• 0 — Restore.	0
shared_mysql_server	Boolean	Whether one of the following conditions is true: <ul style="list-style-type: none">• The target and remote servers share the same remote MySQL server.• The target server is the remote MySQL server for the remote server.• The remote server is the remote MySQL server for the target server.	<ul style="list-style-type: none">• 1 — One is true.• 0 — None are true.	0
skipres	Boolean	Whether to skip restoration of the account's reseller permissions.	<ul style="list-style-type: none">• 1 — Skip.• 0 — Restore.	1
skipacctdb	Boolean	Whether to skip the transfer of the account's databases.	<ul style="list-style-type: none">• 1 — Skip.• 0 — Restore.	0
skipbwdata	Boolean	Whether to skip the transfer of the account's bandwidth data.	<ul style="list-style-type: none">• 1 — Skip.• 0 — Restore.	0

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_close_rule

modsec_deploy_all_rule_changes
 modsec_deploy_rule_changes
 modsec_deploy_settings_changes
 modsec_disable_rule
 modsec_disable_vendor
 modsec_disable_vendor_configs
 modsec_disable_vendor_updates
 modsec_discard_all_rule_changes
 modsec_discard_rule_changes
 modsec_edit_rule
 modsec_enable_vendor
 modsec_enable_vendor_configs
 modsec_enable_vendor_updates
 modsec_get_config_text
 modsec_get_configs
 modsec_get_configs_with_changes_pending
 modsec_get_log
 modsec_get_rules
 modsec_get_settings
 modsec_get_vendors
 modsec_is_installed
 modsec_make_config_active

skipaccount	<i>Boolean</i>	Whether to skip the recreation of the account.	<ul style="list-style-type: none"> 1 — Skip. 0 — Restore. 	0
		<p>Note: This parameter is similar to the force parameter, but performs none of the account creation steps.</p>		
xferpoint	<i>Boolean</i>	Whether to use the <i>Express Transfer</i> feature.	<ul style="list-style-type: none"> 1 — Use. 0 — Do not use. 	0

Additional FeatureListRoot parameters

▼ [Click to view...](#)

Parameter	Type	Description	Possible values	Example
featurelist	<i>string</i>	Required The feature list's name.	A valid string.	user_features

Additional LegacyAccountBackup parameters

▼ [Click to view...](#)

Parameter	Type	Description	Possible values	Example
user	<i>string</i>	Required The account's username.	A valid string.	user

modsec_make_config_inactive
 modsec_preview_vendor
 modsec_remove_rule
 modsec_remove_setting
 modsec_remove_vendor
 modsec_report_rule
 modsec_set_config_text
 modsec_set_setting
 modsec_uninstall_rule
 modsec_update_vendor

▼ Packages

_getpkgextensionform
 add_override_features_for_user
 addpkg
 addpkgext
 changepackage
 create_featurelist
 delete_featurelist
 delpkgext
 editpkg
 get_available_applications
 get_available_featurelists
 get_feature_metadata
 get_feature_names
 get_featurelist_data
 get_featureli

restoretype	string	Required The backup type to restore.	<ul style="list-style-type: none"> monthly weekly daily 	daily
restoreall	Boolean	Whether to recreate the account on the target server.	<ul style="list-style-type: none"> 1 — Recreate. 0 — Do not recreate. 	0
restoreip	Boolean	Whether to assign the account's dedicated IP address that is stored in the backup file.	<ul style="list-style-type: none"> 1 — Assign. 0 — Do not assign. 	0
restoremail	Boolean	Whether to restore the account's mail data.	<ul style="list-style-type: none"> 1 — Restore. 0 — Do not restore. 	0
restoremysql	Boolean	Whether to restore MySQL database data	<ul style="list-style-type: none"> 1 — Restore. 0 — Do not restore. 	0
restorebandwidth	Boolean	Whether to restore bandwidth data.	<ul style="list-style-type: none"> 1 — Restore. 0 — Do not restore. 	0
restoresubs	Boolean	Whether to restore the account's subdomains.	<ul style="list-style-type: none"> 1 — Restore. 0 — Do not restore. 	0
unrestricted_restore	Boolean	Whether to bypass the <i>Restricted Restore</i> system.	<ul style="list-style-type: none"> 1 — Bypass. 0 — Do not bypass. 	0
overwrite_all_dbs	Boolean		<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	0

Note: We introduced this parameter in cPanel & WHM version 11.46.

Note: In cPanel & WHM version 11.46, you must set this value to 1.

In cPanel & WHM version 11.46, you must set this value to

sts
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm
get_fpm_count_and_utilization
is_conversion_in_progress
php_get_default_accounts_to_fpm
php_get_handlers
php_get_impacted_domains
php_get_installed_versions
php_get_old_fpm_flag
php_get_system_default_version
php_get_versions_by_version
php_get_versions
php_ini_get_content

Whether to allow the system to overwrite all of the account's databases with the databases in the backup file.

Note: You may use only **one** of the following parameters:

- `overwrite_all_dbs`
- `overwrite_sameowner_dbs`
- Both the `mysql_dbs_to_restore` and `pgsql_dbs_to_restore` parameters.

If you do not use any of the parameters, the system will restore all of the databases on the account, but will **not** overwrite any of the m.

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacfs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacfs

setresellerip
s

setresellerl
imits

setresellerm
ainip

setresellerm
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

Warning: The Restricted Restore feature does not allow an account to overwrite data that it does not own. If the transfer session's unrestricted_restore parameter has a value of 0, the overwrite_all_days parameter will automatically change to a value of 0 and the overwrite

- ller
- unsuspendr
- eseller
- delete_rpm_
 - version
 - edit_rpm_ve
 - rsion
 - get_rpm_ver
 - sion_data
 - install_rpm_
 - plugin
 - list_rpms
 - package_m
 - anager_fixc
 - ache
 - package_m
 - anager_get_
 - build_log
 - package_m
 - anager_get_
 - package_inf
 - o
 - package_m
 - anager_is_p
 - erforming_a
 - ctions
 - package_m
 - anager_list_
 - packages
 - package_m
 - anager_reso
 - lve_actions
 - package_m
 - anager_sub
 - mit_actions
 - package_m
 - anager_upgr
 - ade
 - uninstall_rp
 - m_plugin
- delete_hook
 - edit_hook
 - list_hooks
 - reorder_hoo
 - ks
- accesshash
 - authorizessh
 - key
 - check_remo
 - te_ssh_conn
 - ection

_sa
meo
wne
r_d
bs
par
am
eter
will
cha
nge
to a
valu
e of
1.
This
pre
ven
ts
the
rest
ore
syst
em
fro
m
ove
rwri
ting
dat
aba
ses
that
the
acc
oun
t
doe
s

- convertopensshputty
- deletesshkey
- fetch_security_advice
- generatesshkeypair
- importsshkey
- listsshkeys
- Server Administration
 - add_configuserserver
 - configurebackgroundprocesskiller
 - configureserver
 - cors_proxy_get
 - create_user_session
 - delete_configclusterserver
 - enable_monitor_all_enabled_services
 - get_all_contact_importances
 - get_appconfig_application_list
 - get_application_contact_event_importance
 - get_application_contact_importance
 - get_available_profiles
 - get_current_profile
 - get_password_strength
 - get_remote_access_has
 - get_service_config

		not own		
overwrite_s ameowner_db s	<i>Boolean</i>	Whether to allow the system to overwrite the account's existing databases with the databases in the backup file.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	0
overwrite_s ameowner_db users	<i>Boolean</i>	Whether to allow the system to overwrite the account's existing database users with the database users in the backup file.	<ul style="list-style-type: none"> • 1 — Allow • 0 — Do not allow. 	0
mysql_dbsto_restore	<i>string</i>	<p>The MySQL databases to restore, which will overwrite those databases on the account.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note: The default value is to select and overwrite all databases.</p> </div>	A database name or list of database names.	msdb1,msdb2,msdb3

get_service_
 config_key
 get_tcp4_so
 ckets
 get_tcp6_so
 ckets
 get_tweakse
 tting
 get_udp4_s
 ockets
 get_udp6_s
 ockets
 get_update_
 availability
 get_users_li
 nks
 getdiskusag
 e
 gethostname
 e
 is_role_ena
 bled
 list_configcl
 usterservers
 loadavg
 nvget
 nvset
 personalizati
 on_get
 personalizati
 on_set
 purchase_a
 _license
 reboot
 remove_in_
 progress_ex
 im_config_e
 dit
 restartservic
 e
 restore_conf
 ig_from_file
 restore_conf
 ig_from_upl
 oad
 run_cpkeyclt
 send_test_p
 osturl
 send_test_p
 ushbullet_n
 ote
 servicestatu

Warning:
 The *Restricted Restore* feature does not allow an account to overwrite data that it does not own. If the transfer session's unrestricted_restore parameter has a value of 0, this parameter is ignored.

pgsql_dbs_t
o_restore

string

The PostgreSQL®
 databases to
 restore, which
 will overwrite
 those
 databases on
 the account.

A database
 name or list of
 database
 names.

pgdb1 , pgdb2
, pgdb3

s

set_applicati
on_contact_
event_impor
tance

set_applicati
on_contact_
importance

set_primary_
_servername

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile_
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar_
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

If you do not use this parameter, the system selects and overwrites all databases.

Not e:
The default value is to select and overwrite all databases.

fetchcrtinfo
 fetchsslinfo
 generatessl
 get_autossl
 _check_sch
 edule
 get_autossl
 _log
 get_autossl
 _logs_catalo
 g
 get_autossl
 _metadata
 get_autossl
 _pending_q
 ueue
 get_autossl
 _pending_q
 ueue_for_do
 main
 get_autossl
 _pending_q
 ueue_for_us
 er
 get_autossl
 _problems_f
 or_domain
 get_autossl
 _problems_f
 or_user
 get_autossl
 _providers
 get_best_ssl
 domain_for_
 service
 install_servi
 ce_ssl_certif
 icate
 installssl
 listcrts
 rebuildinstall
 edssldb
 rebuildusers
 sldb
 reset_autos
 ssl_provider
 reset_servic
 e_ssl_certifi
 cate
 set_autossl_
 metadata
 set_autossl_
 metadata_k
 ey

Warning:
 The *Restricted Restore* feature does not allow an account to overwrite data that does not own. If the transfer session's unrestricted parameter has a value of 0, the system ignores this parameter.

Additional PackageRemoteRoot parameters

[Click to view...](#)

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

set_autoss_
provider

start_autoss
l_check_for_
all_users

start_autoss
l_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

package	string	Required The package's name	A valid string.	user_packag e
---------	--------	---------------------------------------	-----------------	------------------

Returns

This function only returns metadata.

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version