

UAPI - Sort Output

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup:: fullbacku
p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_pa
ssword

Backup:: list_back
ups

Bandwidth

Bandwidth:: get_e
nabled_protocols

Bandwidth:: get_re
tention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_app
lications

Branding:: get_app
lication_informatio
n

Branding:: get_ava
ilable_applications

Branding:: get_info

Introduction

You can use additional parameters to sort UAPI output.

Sort output

UAPI sorting uses four basic parameters:

parameter	Type	Description	Possible values
api.sort	Boolean	Whether to enable sorting.	<ul style="list-style-type: none">1 — Enable sorting.0 — Disable sorting.
api.sort_column	string	The return to sort by.	The name of one of the function's returns.
api.sort_method	string	The type of sorting to use. This parameter defaults to <code>lexicographic</code> .	<ul style="list-style-type: none">ipv4 — Sort output by the numeric value of each octet in an IPv4 address.numeric — Sort output in numeric order, with 0 as the lowest number.numeric_zero_as_max — Sort output in numeric order, with 0 as the highest number.lexicographic — Sort output in alphabetical order.
api.sort_reverse	Boolean	Whether to sort data in reverse order.	<ul style="list-style-type: none">1 — Sort in reverse order.0 — Do not sort in reverse order.

Warning: You **must** set this parameter whenever you sort numeric values, or the function will fail.

Examples

The following example function calls execute the `Email::list_lists` function and use the `numeric` method to sort the `diskused` parameter's values in reverse order.

cPanel or Webmail Session URLLiveAPI PHP ClassLiveAPI Perl Class
cPanel Template ToolkitCommand LineOutput (JSON)

```
/execute/Email/list_lists?api.sort=1&api.sort_column=diskused&api.sort_method=numeric&api.sort_reverse=0
```

UAPI Basics

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Notes:

- Th
Fe

int
• Ur
mu
us
20
or
20
)`
20
or
20
)

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkserverd

Chkserverd:: get_exim_ports

Chkserverd:: get_exim_ports_ssl

▼ Chrome

Chrome:: get_domain

▼ Contactus

Contactus:: is_enabled

▼ cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

▼ cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

▼ DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

```
$cpanel = new CPANEL(); // Connect to
cPanel - only do this once.

// List all of the mailing lists by the
amount of disk they use.
$list_by_disk = $cpanel->api2(
    'Email', 'list_lists',
    array(
        'api.sort'           => '1',
        'api.sort_column'   =>
'diskused',
        'api.sort_method'   =>
'numeric',
        'api.sort_reverse'  => '0',
    )
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

```
my $cpliveapi =
Cpanel::LiveAPI->new(); # Connect to
cPanel - only do this once.

# List all of the mailing lists by the
amount of disk they use.
my $list_by_disk = $cpliveapi->api2(
    'Email', 'list_lists',
    {
        'api.sort'           => '1',
        'api.sort_column'   =>
'diskused',
        'api.sort_method'   =>
'numeric',
        'api.sort_reverse'  => '0',
    }
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Related Documentation

- [Guide to cPanel API 1](#) — cPanel API 1 — access information from the cPanel interface.
- [Guide to cPanel API 2](#) — cPanel API 2 — access cPanel account information and modifies settings.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

```
<!-- List all of the mailing lists by the amount of disk they use. -->[% execute('Email', 'list_lists', { 'api.sort' => '1', 'api.sort_column' => 'diskused', 'api.sort_method' => 'numeric', 'api.sort_reverse' => '0', }) %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

```
uapi --user=username Email list_lists  
api.sort=1 api.sort_column=diskused  
api.sort_method=numeric  
api.sort_reverse=0
```

- [Guide to WHM API 0](#) — WHM API 0 accesses the WHM interface's features.
- [Guide to WHM API 1](#) — WHM API 1 accesses the WHM interface's features.
- [Guide to UAPI](#) — UAPI accesses the cPanel interface's features.

Email:: add_spam_filter
Email:: browse_mailbox
Email:: change_mx
Email:: check_fast_mail
Email:: check_pipe_forwarder
Email:: delete_auto_responder
Email:: delete_do_main_forwarder
Email:: delete_filter
Email:: delete_for_warder
Email:: delete_held_messages
Email:: delete_list
Email:: delete_mx
Email:: delete_pop
Email:: disable_filter
Email:: disable_mailbox_autocreate
Email:: disable_spam_assassin
Email:: disable_spam_autodelete
Email:: disable_spam_box
Email:: dispatch_client_settings
Email:: edit_pop_quota
Email:: enable_filter
Email:: enable_mailbox_autocreate
Email:: enable_spam_assassin
Email:: enable_spam_box
Email:: fetch_charmaps
Email:: fts_rescan_mailbox
Email:: generate_mailman_otp
Email:: get_auto_r

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "data": [
    {
      "listid": "list1_example.com",
      "accesstype": "public",
      "desthost":
"hostname.example.com",
      "diskused": "16040",
      "humandiskused": "16.04 KB",
      "listadmin": "user@example.com",
      "list": "list1@example.com",
      "advertised": "1",
      "archive_private": "1",
      "subscribe_policy": "1"
    }
    {
      "listid": "mylist_example.com",
      "accesstype": "public",
      "desthost":
"hostname.example.com",
      "diskused": "17647",
      "humandiskused": "17.23 KB",
      "listadmin": "admin@example.com",
      "list": "mylist@example.com",
      "advertised": "0",
      "archive_private": "1",
      "subscribe_policy": "1"
    }
    {
      "listid": "superlist_example.com",
      "accesstype": "public",
      "desthost":
"hostname.example.com",
      "diskused": "90120",
      "humandiskused": "90.12 KB",
      "listadmin": "charlie@example.com",
      "list": "superlist@example.com",
      "advertised": "1",
      "archive_private": "1",
      "subscribe_policy": "1"
    }
  ],
  "metadata": {
    "transformed": 1
  }
}
```

esponder

Email:: get_charse
ts

Email:: get_client_
settings

Email:: get_default_
_email_quota

Email:: get_default_
_email_quota_mib

Email:: get_disk_u
sage

Email:: get_filter

Email:: get_held_
message_count

Email:: get_mailbo
x_autocreate

Email:: get_mailm
an_delegates

Email:: get_main_
account_disk_usa
ge

Email:: get_main_
account_disk_usa
ge_bytes

Email:: get_max_e
mail_quota

Email:: get_max_e
mail_quota_mib

Email:: get_pop_q
uota

Email:: get_spam_
settings

Email:: get_webm
ail_settings

Email:: has_deleg
ated_mailman_list
s

Email:: has_plainte
xt_authentication

Email:: hold_outgo
ing

Email:: is_integer

Email:: list_auto_r
esponders

Email:: list_default_
_address

Email:: list_domain_
_forwarders

Email:: list_filters

Email:: list_filters_
backups

Email:: list_forward

Use multiple sorts

To use multiple sorts on a single UAPI call, append an underscore (_) and a number to the end of each sort parameter.

For example, use the following parameters to pass two sets of sorting information:

- Pass the first set of sorting information to the `api.sort_method_0`, `api.sort_column_0`, and `api.sort_reverse_0` parameters.
- Pass the second set of sorting information to the `api.sort_method_1`, `api.sort_column_1`, and `api.sort_reverse_1` parameters.

Note:

Do **not** include more than one `api.sort` boolean parameter.

For example, the following examples sort the `Email::list_lists` function's output by whether they appear on the Mailman directory page and then their list name in reverse alphabetical order.

cPanel or Webmail Session URLLiveAPI PHP ClassLiveAPI Perl Class
cPanel Template ToolkitCommand LineOutput (JSON)

```
/execute/Email/list_lists?api.sort=1&ap  
i.sort_column_0=advertised&api.sort_met  
hod=numeric&api.sort_reverse_0=0&api.so  
rt_column_1=list&api.sort_method_1=lexi  
cographic&api.sort_reverse_1=1
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

ers

Email: list_forward
ers_backups

Email: list_lists

Email: list_mail_d
omains

Email: list_mx

Email: list_pops

Email: list_pops_
with_disk

Email: list_system
_filter_info

Email: passwd_list

Email: passwd_po
p

Email: release_ou
tgoing

Email: remove_m
ailman_delegates

Email: reorder_filt
ers

Email: set_always
_accept

Email: set_default
_address

Email: set_list_pri
vacy_options

Email: stats_db_st
atus

Email: store_filter

Email: suspend_in
coming

Email: suspend_lo
gin

Email: suspend_o
utgoing

Email: trace_filter

Email: unsuspend
_incoming

Email: unsuspend
_login

Email: unsuspend
_outgoing

Email: verify_pass
word

▼ EmailAuth

EmailAuth: disabl
e_dkim

EmailAuth: enable
_dkim

```
$cpanel = new CPANEL(); // Connect to  
cPanel - only do this once.  
  
// List all of the mailing lists sorted  
by whether they are displayed  
// on the Mailman directory, and then by  
name in reverse alphabetical order  
$very_private_lists = $cpanel->uapi(  
    'Email', 'list_lists',  
    array(  
        'api.sort'           => '1',  
        'api.sort_column_0' =>  
'advertised',  
        'api.sort_method_0' =>  
'numeric',  
        'api.sort_type_0'   => '0',  
        'api.sort_column_1' => 'list',  
        'api.sort_method_1' =>  
'lexicographic',  
        'api.sort_type_1'   => '1',  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat ion

ExternalAuthenticat
ion:: add_authn_li
nk

ExternalAuthenticat
ion:: configured_
modules

ExternalAuthenticat
ion:: get_authn_lin
ks

ExternalAuthenticat
ion:: has_external
_auth_modules_co
nfigured

ExternalAuthenticat
ion:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file_
content

Fileman:: transcod
e

```
my $cpliveapi =  
Cpanel::LiveAPI->new(); # Connect to  
cPanel - only do this once.  
  
// List all of the mailing lists sorted  
by whether they are displayed  
// on the Mailman directory, and then by  
name in reverse alphabetical order  
my $very_private_lists =  
$cpliveapi->uapi(  
    'Email', 'list_lists',  
    {  
        'api.sort' => '1',  
        'api.sort_column_0' =>  
'advertised',  
        'api.sort_method_0' =>  
'numeric',  
        'api.sort_type_0' => '0',  
        'api.sort_column_1' => 'list',  
        'api.sort_method_1' =>  
'lexicographic',  
        'api.sort_type_1' => '1',  
    }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

```
<!-- List all of the mailing lists  
sorted by whether they are displayed on  
the Mailman directory, and then by name  
in reverse alphabetical order. -->  
[% execute('Email', 'list_lists', {  
'api.sort' => '1', 'api.sort_column_0'  
=> 'advertised', 'api.sort_method_0' =>  
'numeric', 'api.sort_reverse_0' =>  
'0', 'api.sort_column_1' => 'list',  
'api.sort_method_1' => 'lexicographic',  
'api.sort_reverse_1' => '1', }) %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

```

Fileman:: upload_files
  v Ftp
    Ftp:: add_ftp
    Ftp:: allows_anonymous_ftp
    Ftp:: allows_anonymous_ftp_incoming
    Ftp:: delete_ftp
    Ftp:: ftp_exists
    Ftp:: get_ftp_daemon_info
    Ftp:: get_port
    Ftp:: get_quota
    Ftp:: get_welcome_message
    Ftp:: kill_session
    Ftp:: list_ftp
    Ftp:: list_ftp_with_disk
    Ftp:: list_sessions
    Ftp:: passwd
    Ftp:: server_name
    Ftp:: set_anonymous_ftp
    Ftp:: set_anonymous_ftp_incoming
    Ftp:: set_homedir
    Ftp:: set_quota
    Ftp:: set_welcome_message
  v Integration
    Integration:: fetch_url
  v KnownHosts
    KnownHosts:: create
    KnownHosts:: delete
    KnownHosts:: update
    KnownHosts:: verify
  v LangPHP
    LangPHP:: php_get_domain_handler
    LangPHP:: php_get_impacted_domains

```

```

uapi --user=username Email list_lists
api.sort=1 api.sort_column_0=diskused
api.sort_method_0=numeric
api.sort_reverse_0=0
api.sort_column_1=list
api.sort_method_1=lexicographic
api.sort_reverse_1=1

```

```

{
  "data": [
    {
      "subscribe_policy": 3,
      "listadmin": "user@example.com",
      "humandiskused": "20.45 KB",
      "desthost": "example.com",
      "archive_private": 1,
      "accesstype": "private",
      "advertised": 0,
      "diskused": "20942",

      "list": "worldleaders@example.com",

      "listid": "worldleaders_example.com"
    },
    {
      "list": "talkshows@example.com",
      "diskused": "20920",
      "advertised": 0,

      "listid": "talkshows_example.com",
      "desthost": "example.com",
      "humandiskused": "20.43 KB",
      "subscribe_policy": 3,
      "listadmin": "user@example.com",
      "accesstype": "private",
      "archive_private": 1
    },
    {
      "listadmin": "user@example.com",
      "subscribe_policy": 3,
      "desthost": "example.com",
      "humandiskused": "20.46 KB",
      "archive_private": 1,
      "accesstype": "private",
      "advertised": 0,
      "diskused": "20956",

      "list": "campaigndonors@example.com",

      "listid": "campaigndonors_example.com"
    }
  ]
}

```



```

LangPHP:: php_ge
t_installed_version
s

LangPHP:: php_ge
t_system_default_
version

LangPHP:: php_ge
t_vhost_versions

LangPHP:: php_ini
_get_user_basic_d
irectives

LangPHP:: php_ini
_get_user_content

LangPHP:: php_ini
_get_user_paths

LangPHP:: php_ini
_set_user_basic_d
irectives

LangPHP:: php_ini
_set_user_content

LangPHP:: php_se
t_vhost_versions

▼ LastLogin
LastLogin:: get_las
t_or_current_logge
d_in_ip

▼ Locale
Locale:: get_attri
butes

▼ Mailboxes
Mailboxes:: expun
ge_mailbox_mess
ages

Mailboxes:: expun
ge_messages_for
_mailbox_guid

Mailboxes:: get_m
ailbox_status

Mailboxes:: has_ut
f8_mailbox_names

Mailboxes:: set_utf
8_mailbox_names

▼ Market
Market:: cancel_pe
nding_ssl_certifica
te

Market:: create_sh
opping_cart

Market:: get_all_pr
oducts

Market:: get_certifi
cate_status_detail
s

Market:: get_login
_url

```

```

    },
    {
        "archive_private":0,
        "accesstype":"public",
        "subscribe_policy":1,
        "listadmin":"user@example.com",
        "humandiskused":"20.52 KB",
        "desthost":"example.com",

"listid":"statedepartment_example.com",
        "advertised":1,
        "diskused":"21010",

"list":"statedepartment@example.com"
    },
    {
"listid":"foundationemployees_example.c
om",
        "advertised":1,
        "diskused":"20990",

"list":"foundationemployees@example.com
",
        "archive_private":0,
        "accesstype":"public",
        "listadmin":"user@example.com",
        "subscribe_policy":1,
        "humandiskused":"20.5 KB",
        "desthost":"example.com"
    }
],
"metadata":{
    "transformed":1
},
"messages":null,

```

Market:: get_pendi
ng_ssl_certificates

Market:: get_provi
der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

```
"errors":null,  
"status":1  
}
```

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql :: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relati
ative_uri

▼ PassengerApps

PassengerApps:: d
isable_application

PassengerApps:: e
dit_application

PassengerApps:: e
nable_application

PassengerApps:: e
nsure_deps

PassengerApps:: li
st_applications

PassengerApps:: r
egister_application

PassengerApps:: u
nregister_applicati
on

▼ PasswdStrength

PasswdStrength::
get_required_stren
gth

▼ Personalization

Personalization::se
t

Personalization ::g
et

▼ Postgresql

Postgresql:: create
_database

Postgresql:: create
_user

Postgresql:: delete
_database

Postgresql:: get_re
strictions

Postgresql:: grant_
all_privileges

Postgresql:: renam
e_database

Postgresql:: renam
e_user

Postgresql:: renam
e_user_no_passw
ord

Postgresql:: revok
e_all_privileges

Postgresql:: set_p
assword

▼ Pushbullet

Pushbullet:: send_
test_message

- ▼ Quota
 - Quota:: get_quota_info
- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key

SSL:: delete_ssl

SSL:: disable_mail_sni

SSL:: enable_mail_sni

SSL:: fetch_best_for_domain

SSL:: fetch_cert_info

SSL:: fetch_certificates_for_fqdns

SSL:: fetch_key_and_cabundle_for_certificate

SSL:: find_certificates_for_key

SSL:: find_csrs_for_key

SSL:: generate_certificate

SSL:: generate_csr

SSL:: generate_key

SSL:: get_autossl_excluded_domains

SSL:: get_autossl_pending_queue

SSL:: get_autossl_problems

SSL:: get_cabundle

SSL:: get_cn_name

SSL:: install_ssl

SSL:: installed_host

SSL:: installed_hosts

SSL:: is_autossl_check_in_progress

SSL:: is_mail_sni_supported

SSL:: is_sni_supported

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_items

SSL:: mail_sni_status

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
mains

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**