

WHM API 1 Functions - get_autossl_pending_queue_for_domain

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Account
Restoration
restore_modules_summary

restore_queue_activate

restore_queue_add_task

restore_queue_clear_all_completed_tasks

restore_queue_clear_all_failed_tasks

restore_queue_clear_all_pending_tasks

restore_queue_clear_all_tasks

restore_queue_clear_completed_task

restore_queue_clear_pending_task

restore_queue_is_active

restore_queue_list_active

restore_queue_list_com

Description

This function returns the most recent AutoSSL pending queue information for a specific domain.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/get_autossl_pending_queue_for_domain?api.version=1&domain=example.com
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/get_autossl_pending_queue_for_domain?api.version=1&domain=example.com
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-)t

Find a function

pleted
restore_queue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

▼ Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspenda

▼ Command Line

```
whmapil  
get_autossl_pending_queue_for_domain  
domain=example.com
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

- WHM API 1 Sections - Security — Security functions allow you to manage system security services.
- WHM API 1 Functions - `authorize_sshkey` — This function authorizes a key to access the server via SSH.

- cct
- untrack_acct_id
- verify_new_username
- ▼ Addon Domains
 - convert_addon_fetch_conversion_details
 - convert_addon_fetch_domain_details
 - convert_addon_get_conversion_status
 - convert_addon_initiate_conversion
 - convert_addon_list_domains
 - convert_addon_list_conversions
- ▼ Authentication
 - api_token_create
 - api_token_list
 - api_token_revoke
 - api_token_update
 - disable_authentication_provider
 - disable_failing_authentication_providers
 - enable_authentication_provider
 - get_available_authentication_providers
 - get_login_url
 - get_provider_client_configurations
 - get_provider_configuration_fields

▼ Output (JSON)

```

{
  "data" : {
    "queue_by_domain" : [
      {
        "last_poll_time" :
        "2017-08-19T13:27:03Z",
        "domains"
      : [
        "example.com",
        "www.example.com"
        ],
        "dcv_methods" : [
        "http",
        "dns"
        ],
        "request_time" :
        "2017-08-12T21:02:56Z",
        "vhost_name" :
        "example.com",
        "order_item_id" :
        "12345678"
      }
    ],
    "metadata" : {
      "version" : 1,
      "command" :
      "get_autossl_pending_queue_for_domain",
      "result" : 1,
      "reason" : "OK"
    }
  }
}

```

- WHM API 1 Functions - check_remote_ssh_connection — This function tests an SSH connection to another server.
- WHM API 1 Functions - convertopensslutility — This function converts an OpenSSH private key to a PuTTY key.

get_provider
_display_co
nfigurations

get_users_a
uthn_linked
_accounts

link_user_au
thn_provider

set_provider
_client_confi
gurations

set_provider
_display_co
nfigurations

twofactoraut
h_disable_p
olicy

twofactoraut
h_enable_p
olicy

twofactoraut
h_generate_
tfa_config

twofactoraut
h_get_issue
r

twofactoraut
h_get_user_
configs

twofactoraut
h_policy_sta
tus

twofactoraut
h_remove_u
ser_config

twofactoraut
h_set_issuer

twofactoraut
h_set_tfa_c
onfig

unlink_user_
authn_provi
der

validate_logi
n_token

Output (XML)

```
<data>
  <queue_by_domain>

  <dcv_methods>http</dcv
  v_methods>

  <dcv_methods>dns</dcv
  _methods>

  <domains>example.com<
  /domains>

  <domains>www.example.
  com</domains>

  <last_poll_time>2017-
  08-19T13:27:03Z</last
  _poll_time>

  <order_item_id>123456
  78</order_item_id>

  <request_time>2017-08
  -12T21:02:56Z</reques
  t_time>

  <vhost_name>example.c
  om</vhost_name>
  </queue_by_domain>
</data>
<metadata>

<command>get_autoss1_
pending_queue_for_dom
ain</command>
  <reason>OK</reason>
  <result>1</result>

<version>1</version>
</metadata>
```

Backups

backup_conf
ig_get

backup_conf
ig_set

backup_dat
e_list

backup_dest
ination_add

backup_dest

Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

ination_delete

backup_destination_get

backup_destination_list

backup_destination_set

backup_destination_validate

backup_get_transport_status

backup_list_transported

backup_set_list

backup_set_list_combined

backup_skip_users_all

backup_skip_users_all_status

backup_user_list

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

▼ cPHulk

cphulk_statuses

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk

Parameters

Parameter	Type	Description	Possible values	Example
domain	string	<p>Required</p> <p>The domain for which to check the AutoSSL pending queue.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : You can only enter one domain when you call this function. To check the most recent list of all AutoSSL queued domains that a user owns, read our get_autossl_pending_queue_for_user documentation.</p> </div>	A valid domain name that the account owns.	example.com

Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

[_login_history](#)
[flush_cphulk_login_history_for_ips](#)
[get_countries_with_known_ip_ranges](#)
[get_cphulk_brutes](#)
[get_cphulk_excessive_brutes](#)
[get_cphulk_failed_logins](#)
[get_cphulk_user_brutes](#)
[load_cphulk_config](#)
[read_cphulk_records](#)
[save_cphulk_config](#)
[set_cphulk_config_key](#)
 ▼ [Databases](#)
[background_mysql_upgrade_status](#)
[current_mysql_version](#)
[installable_mysql_versions](#)
[latest_available_mysql_version](#)
[list_database_users](#)
[list_databases](#)
[list_mysql_databases_and_users](#)
[remote_mysql_create_profile](#)
[remote_mysql_create_profile_via_ssh](#)
[remote_mysql_delete_profile](#)

queue_by_domain	<i>array of hashes</i>	An array of hashes that contain information about the AutoSSL pending queue for the specific domain.	This array of hashes includes the domains, last_poll_time, order_item_id, request_time, vhost_name, and dcvmethods returns.	
domains	<i>array of strings</i>	An array that contains information about the domains from the certificate's order_item_id parameter. The function returns this array in the queue_by_domain array of hashes.	A valid domain on the server.	www.example.com
last_poll_time	<i>string</i>	The time of the most recent poll of the provider for the DCV status. The function returns this value in the queue_by_domain array of hashes.	A time value, in ISO-8601 format.	2017-08-19T13:27:03Z
order_item_id	<i>string</i>	The provider's order item ID for the certificate. The function returns this value in the queue_by_domain array of hashes.	A valid order item ID.	12345678
request_time	<i>string</i>	When AutoSSL made the request to the provider. The function returns this value in the queue_by_domain array of hashes.	A time value, in ISO-8601 format.	2017-08-12T21:02:56Z
vhost_name	<i>string</i>	The virtual host that contains the domain. The function returns this value in the queue_by_domain array of hashes.	A valid virtual host name.	example.com

<p>remote_mysql_initiate_profile_activation</p> <p>remote_mysql_monitor_profile_activation</p> <p>remote_mysql_read_profile</p> <p>remote_mysql_read_profiles</p> <p>remote_mysql_update_profile</p> <p>remote_mysql_validate_profile</p> <p>rename_mysql_database</p> <p>rename_mysql_user</p> <p>rename_postgresql_database</p> <p>rename_postgresql_user</p> <p>set_local_mysql_root_password</p> <p>set_mysql_password</p> <p>set_postgresql_password</p> <p>start_background_mysql_upgrade</p>	<p>dcv_methods</p> <p><i>array of strings</i></p>	<p>The methods of Domain Control Validation (DCV) that the system requested the Certificate Authority (CA) to perform for the given domains.</p> <p>Note : We introduced this return in cPanel & WHM version 74.</p> <p>The function returns this value in the queue_by_domain array of hashes.</p>	<p>A comma-separated list that may contain http, dns, or both values.</p> <p>Note : This function returns the results from the domains parameter in the same order in which you called them.</p>	<p>http</p>
---	---	--	---	-------------

▼ DNS

- adddns
- addzonerecord
- addzonerecord (Reverse DNS)
- dumpzone
- editzonerecord
- get_nameserver_config
- getzonerecord

has_local_au
thority
killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages
ea4_get_ea
_pkgs_state
ea4_list_pro
files
ea4_metainf
o
ea4_migrati
on
ea4_pre_mi
grate_check
ea4_recom
mendations
ea4_save_p
rofile
ea4_tomcat
85_add
ea4_tomcat
85_list
ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d
cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid
ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgrey
list_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou

p

remove_inte
gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_i
p

get_shared_
ip

ipv6_disable
_account

ipv6_enable
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che

ck

expunge_mailbox_messages

expunge_messages_for_mailbox_guid

fetch_dkim_private_keys

fetch_mail_queue

generate_mobileconfig

get_mailbox_status

get_mailbox_status_list

get_unique_recipient_count_per_sender_for_user

get_unique_sender_recipient_count_per_user

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for

mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email

unsuspend_

outgoing_email

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule
modsec_deploy_all_rule_changes
modsec_deploy_rule_changes
modsec_deploy_settings_changes
modsec_disable_rule
modsec_disable_vendor
modsec_disable_vendor_configs
modsec_disable_vendor_updates
modsec_discard_all_rule_changes
modsec_discard_rule_changes
modsec_edit_rule
modsec_enable_vendor
modsec_enable_vendor_configs
modsec_enable_vendor_updates
modsec_get_config_text
modsec_get_configs
modsec_get_configs_with_changes_pending
modsec_get_log
modsec_get_rules
modsec_get_settings
modsec_get_vendors
modsec_is_installed

modsec_make_config_active

modsec_make_config_active

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_disable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_featurelist

delete_featurelist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featureli

st_data
get_featurelists
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm
get_fpm_count_and_utilization
is_conversion_in_progress
php_get_default_accounts_to_fpm
php_get_handlers
php_get_impacted_domains
php_get_installed_versions
php_get_old_fpm_flag
php_get_system_default_version
php_get_versions_by_version
php_get_versions

php_ini_get
_content

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres

eller

unsetuprese
ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remote_ssh_connection

convertopenssh_tputty

deletesshkey

fetch_security_advice

generatesshkeypair

importsshkey

listsshkeys

▼ Server

Administration

add_configclusterserver

configurebackgroundprocesskiller

configureSERVICE

cors_proxy_get

create_user_session

delete_configclusterserver

enable_monitor_all_enabled_services

get_all_contact_importances

get_application_list

get_application_contact_event_importance

get_application_contact_importance

get_available_profiles

get_current_profile

get_password_strength

get_remote_access_has

h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu
s

set_applicati
on_contact_
event_impor
tance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname
e

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh

osts
fetch_vhost
_ssl_compo
nents
fetchcrtinfo
fetchsslinfo
generatessl
get_autoss
_check_sch
edule
get_autoss
_log
get_autoss
_logs_catalo
g
get_autoss
_metadata
get_autoss
_pending_q
ueue
get_autoss
_pending_q
ueue_for_do
main
get_autoss
_pending_q
ueue_for_us
er
get_autoss
_problems_f
or_domain
get_autoss
_problems_f
or_user
get_autoss
_providers
get_best_ssl
domain_for_
service
install_servi
ce_ssl_certif
icate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autos
sl_provider
reset_servic
e_ssl_certifi
cate
set_autossl_

metadata

set_autossl_
metadata_
key

set_autossl_
provider

start_autoss
l_check_for_
all_users

start_autoss
l_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_acc
ount_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transf
er_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver

sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version