

WHM API 1 Functions - saveacllist

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Description

This function creates or modifies an [Access Control List \(ACL\)](#).

Warning:

We **strongly** recommend that WHM users create and edit ACLs and ACL privileges through WHM's *Edit Reseller Nameservers and Privileges* interface (*WHM >> Home >> Resellers >> Edit Reseller Nameservers and Privileges*).

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/saveacllist?api.version=1&acllist=my_acl_list&acl-all=1
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/saveacllist?api.version=1&acllist=my_acl_list&acl-all=1
```

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_or_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

Command Line

```
whmapil saveacllist  
acllist=my_acl_list  
acl-all=1
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Output (JSON)

```
{  
  "metadata": {  
    "version": 1,  
    "reason": "ACL  
List my_acl_list  
saved.",  
    "result": 1,  
    "command":  
    "saveacllist"  
  }  
}
```

Find a function

- WHM API 0 Functions - setresellernameuservers — This function assigns name servers to a reseller's account.

- _id
- verify_new_username
- convert_addon_fetch_conversion_details
 - convert_addon_fetch_main_details
 - convert_addon_get_conversion_status
 - convert_addon_initiate_conversion
 - convert_addon_list_addon_domains
 - convert_addon_list_conversions
- api_token_create
 - api_token_list
 - api_token_revoke
 - api_token_update
 - disable_authentication_provider
 - disable_failing_authentication_providers
 - enable_authentication_provider
 - get_available_authentication_providers
 - get_login_url
 - get_provider_client_configurations
 - get_provider_configuration_fields
 - get_provider_display_co

Output (XML)

```

<result>
  <metadata>

  <version>1</version>
  <reason>ACL
List my_acl_list
saved.</reason>

  <result>1</result>

  <command>saveacllist<
/command>
  </metadata>
</result>

```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
acclist	string	<p>Required</p> <p>The ACL to assign to the reseller.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : To modify an existing ACL, set this value to that ACL's name.</p> </div>	A valid ACL name.	my_acl_list

- WHM API 1 Sections - Resellers — Reseller functions allow you to manage your cPanel and WHM reseller accounts.
- WHM API 1 Functions - accounts — This function lists a reseller's total accounts, suspended accounts, and account creation limit.

nfigurations
 get_users_authn_linked_accounts
 link_user_authn_provider
 set_provider_client_configurations
 set_provider_display_configurations
 twofactorauth_disable_policy
 twofactorauth_enable_policy
 twofactorauth_generate_tfa_config
 twofactorauth_get_issuer
 twofactorauth_get_user_configs
 twofactorauth_policy_status
 twofactorauth_remove_user_config
 twofactorauth_set_issuer
 twofactorauth_set_tfa_config
 unlink_user_authn_provider
 validate_login_token

acl-edit-pkg	<i>Boolean</i>	Whether to allow the reseller to edit hosting plans (packages). This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
acl-add-pkg	<i>Boolean</i>	Whether to allow the reseller to add and remove hosting plans (packages). This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
acl-list-pkgs	<i>Boolean</i>	Whether to allow the reseller to view existing hosting plans (packages). This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
acl-mailcheck	<i>Boolean</i>	Whether to allow the reseller to troubleshoot mail delivery. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1

Note
: We added this parameter in cPanel & WHM version 68.

- WHM API 1 Functions - getresellerips — This function lists a reseller's available IP addresses.

▼ Backups

backup_config_get
 backup_config_set
 backup_data_list
 backup_destination_add
 backup_destination_delete

backup_dest_ination_get
 backup_dest_ination_list
 backup_dest_ination_set
 backup_dest_ination_validate
 backup_get_transport_status
 backup_list_transported
 backup_set_list
 backup_set_list_combined
 backup_skip_users_all
 backup_skip_users_all_status
 backup_user_list
 convert_and_migrate_from_legacy_config
 get_users_with_backup_metadata
 list_cparchive_files
 start_background_package
 toggle_user_backup_status
 cPHulk
 cphulk_statuses
 create_cphulk_record
 delete_cphulk_record
 disable_cphulk
 enable_cphulk
 flush_cphulk_login_history

acl-generate-email-config	<i>Boolean</i>	<p>Whether to allow the reseller to generate a mobile configuration profile for an email account.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-show-bandwidth	<i>Boolean</i>	<p>Whether to allow the reseller to view account bandwidth usage.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-list-accounts	<i>Boolean</i>	<p>Whether to allow the reseller to view the list of accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-acct-summary	<i>Boolean</i>	<p>Whether to allow the reseller to view an account summary.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brutes

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_user_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status

current_mysql_version

installable_mysql_versions

latest_available_mysql_version

list_database_users

list_databases

list_mysql_databases_and_users

remote_mysql_create_profile

remote_mysql_create_profile_via_ssh

remote_mysql_delete_profile

remote_mysql_initiate_profile_activation

acl-clustering	<i>Boolean</i>	Whether to allow the reseller to use DNS clusters. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-news	<i>Boolean</i>	Whether to allow the reseller to modify the server's news. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-thirdparty	<i>Boolean</i>	Whether to allow the reseller to manage third-party services. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-kill-dns	<i>Boolean</i>	Whether to allow the reseller to remove DNS zones. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-cpanel-api	<i>Boolean</i>	Whether to allow the reseller to execute cPanel API 1, cPanel API 2 and UAPI functions via WHM. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
		<div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note :</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div>		
acl-edit-dns	<i>Boolean</i>	Whether to allow the reseller to edit DNS zones. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

addns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

acl-park-dns	Boolean	Whether to allow the reseller to park DNS zones. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
acl-create-dns	Boolean	Whether to allow the reseller to add DNS zones. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
acl-manage-api-tokens	Boolean	Whether to allow the reseller to manage API tokens. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
<p>Note</p> <ul style="list-style-type: none"> This is a privileged operation. 				

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_package
s

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

i
o
n
s
t
h
a
t
y
o
u
s
e
t
o
n
t
h
e
A
P
I
t
o
k
e
n
.
F
o
r
m
o
r
e
i
n
f
o
r
m
a
t
i
o
n
,
r
e
a
d
o
u
r
M
a
n
a
g
e
A
P
I
T
o
k
e
n
s
d
o
c
u
m
e
n
t
a
t
i

ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyl
ist_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte

o

<p>gration_link</p> <p>update_inte gration_link _token</p> <p>▼ IP Addresses</p> <p>addips</p> <p>delip</p> <p>get_public_i p</p> <p>get_shared_ ip</p> <p>ipv6_disable _account</p> <p>ipv6_enable _account</p> <p>ipv6_range_ add</p> <p>ipv6_range_ edit</p> <p>ipv6_range_ list</p> <p>ipv6_range_ remove</p> <p>ipv6_range_ usage</p> <p>listips</p> <p>nat_checkip</p> <p>nat_set_pub lic_ip</p> <p>setsiteip</p>			<p>n .</p> <ul style="list-style-type: none"> • We added this parameter in cPanel & WHM version 68. 		
<p>▼ Mail</p> <p>disable_dki m</p> <p>disable_mail _sni</p> <p>emailtrack_s earch</p> <p>emailtrack_s tats</p> <p>emailtrack_u ser_stats</p> <p>enable_dkim</p> <p>enable_mail _sni</p> <p>ensure_dki m_keys_exi st</p> <p>exim_config uration_che ck</p> <p>expunge_m</p>	<p>acl-manage-o idc</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage external authentication for their accounts.</p> <p>This parameter defaults to 0.</p> <p>Note : We added this parameter in cPanel & WHM version 68.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>

<p>ailbox_messages</p> <p>expunge_messages_for_mailbox_guid</p> <p>fetch_dkim_private_keys</p> <p>fetch_mail_queue</p> <p>generate_mobileconfig</p> <p>get_mailbox_status</p> <p>get_mailbox_status_list</p> <p>get_unique_recipient_count_per_sender_for_user</p>	<p>acl-manage-dns-records</p> <p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage DNS records.</p> <p>This parameter defaults to 0.</p> <div data-bbox="732 338 870 747" style="border: 1px solid black; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>
<p>get_unique_sender_recipient_count_per_user</p> <p>get_user_email_forward_destination</p> <p>hold_outgoing_email</p> <p>install_dkim_private_keys</p> <p>install_spf_records</p> <p>is_sni_supported</p> <p>list_pops_for</p> <p>mail_sni_status</p> <p>rebuild_mail_sni_config</p> <p>release_outgoing_email</p> <p>save_spamd_config</p> <p>set_user_email_forward_destination</p> <p>suspend_outgoing_email</p> <p>unsuspend_outgoing_email</p>	<p>acl-manage-styles</p> <p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage their server's cPanel styles.</p> <p>This parameter defaults to 0.</p> <div data-bbox="732 1010 870 1419" style="border: 1px solid black; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>

<p>validate_current_installer_exim_config</p> <p>validate_current_dkims</p> <p>validate_current_ptrs</p> <p>validate_current_spfs</p> <p>validate_exim_configuration_syntax</p> <p>▼ Market</p> <p>disable_market_provider</p> <p>enable_market_provider</p> <p>get_adjusted_market_providers_products</p> <p>get_market_providers_commission_config</p> <p>get_market_providers_list</p> <p>get_market_providers_product_metadata</p> <p>get_market_providers_products</p> <p>set_market_product_attribute</p> <p>set_market_provider_commission_id</p> <p>▼ ModSecurity™</p> <p>modsec_added_rule</p> <p>modsec_added_vendor</p> <p>modsec_ensemble_config_text</p> <p>modsec_batch_settings</p> <p>modsec_check_rule</p> <p>modsec_clone_rule</p>	<p>acl-nameserver-config</p> <p><i>Boolean</i></p> <p>Whether to allow the reseller to manage nameservers.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>
<p>get_market_providers_list</p>	<p>acl-ssl</p> <p><i>Boolean</i></p> <p>Whether to allow the reseller to perform SSL site management.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>
<p>get_market_providers_list</p> <p>get_market_providers_product_metadata</p> <p>get_market_providers_products</p> <p>set_market_product_attribute</p> <p>set_market_provider_commission_id</p>	<p>acl-ssl-info</p> <p><i>Boolean</i></p> <p>Whether to allow the reseller to view their server's SSL information.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>

<p>modsec_deploy_all_rule_changes</p> <p>modsec_deploy_rule_changes</p> <p>modsec_deploy_settings_changes</p> <p>modsec_disable_rule</p> <p>modsec_disable_vendor</p> <p>modsec_disable_vendor_configs</p> <p>modsec_disable_vendor_updates</p> <p>modsec_discard_all_rule_changes</p>	acl-mysql-info	Boolean	<p>Whether to allow the reseller to retrieve MySQL® database and user data.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
<p>modsec_discard_rule_changes</p> <p>modsec_edit_rule</p>	acl-create-acct	Boolean	<p>Whether to allow the reseller to create accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
<p>modsec_enable_vendor</p> <p>modsec_enable_vendor_configs</p> <p>modsec_enable_vendor_updates</p>	acl-suspend-acct	Boolean	<p>Whether to allow the reseller to suspend or unsuspend accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
<p>modsec_get_config_text</p> <p>modsec_get_configs</p> <p>modsec_get_configs_with_changes_pending</p> <p>modsec_get_log</p> <p>modsec_get_rules</p> <p>modsec_get_settings</p> <p>modsec_get_vendors</p> <p>modsec_is_installed</p> <p>modsec_make_config_active</p>	acl-basic-system-info	Boolean	<p>Whether to allow the reseller to retrieve basic system information.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

<p>modsec_make_config_active</p> <p>modsec_preview_vendor</p> <p>modsec_remove_rule</p> <p>modsec_remove_setting</p> <p>modsec_remove_vendor</p> <p>modsec_report_rule</p> <p>modsec_set_config_text</p> <p>modsec_set_setting</p>	<p>acl-basic-whm-functions</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to access basic cPanel & WHM options.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>
<p>modsec_undo_rule</p> <p>modsec_update_vendor</p> <p>▼ Packages</p> <p>_getpkgextensionform</p> <p>add_override_features_for_user</p> <p>addpkg</p> <p>addpkgext</p> <p>changepackage</p> <p>create_featurelist</p> <p>delete_featurelist</p> <p>delpkgext</p> <p>editpkg</p> <p>get_available_applications</p> <p>get_available_featurelists</p> <p>get_feature_metadata</p> <p>get_feature_names</p> <p>get_featurelist_data</p> <p>get_featureli</p>	<p>acl-res-cart</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to reset the Interchange shopping cart.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p>Important:</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>

sts
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm
get_fpm_count_and_utilization
is_conversion_in_progress
php_get_default_accounts_to_fpm
php_get_handlers
php_get_impacted_domains
php_get_installed_versions
php_get_old_fpm_flag
php_get_system_default_version
php_get_whoists_by_version
php_get_whoist_versions
php_ini_get_content

• W
e
r
e
r
e
m
o
v
e
d
t
h
i
s
r
e
t
u
r
n
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.4
6
.

php_ini_get
_directives
php_ini_set
_content
php_ini_set
_directives
php_set_def
ault_accoun
ts_to_fpm
php_set_ha
ndler
php_set_old
_fpm_flag
php_set_ses
sion_save_p
ath
php_set_sys
tem_default
_version
php_set_vh
ost_versions

▼ Resellers

acctcounts
get_public_c
ontact
getresellerip
s
listacfs
listresellers
resellerstats
saveacllist
set_public_c
ontact
setacfs
setresellerip
s
setreselleri
mits
setresellerm
ainip
setresellerm
ameservers
setresellerp
ackagelimit
setupreselle
r
suspendres
eller
terminateres
eller
unsetuprese

• D
o
n
o
t
u
s
e
t
h
i
s
p
r
i
v
i
l
e
g
e
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.3
8
o
r
l
a
t
e
r
.

<ul style="list-style-type: none"> llers unsuspendreseller ▼ RPM <ul style="list-style-type: none"> delete_rpm_version edit_rpm_version get_rpm_version_data install_rpm_plugin list_rpms package_manager_fixache package_manager_get_build_log package_manager_get_package_info package_manager_is_performing_actions package_manager_list_packages package_manager_resolve_actions package_manager_submit_actions package_manager_upgrade ▼ Script Hooks <ul style="list-style-type: none"> uninstall_rpm_plugin delete_hook edit_hook list_hooks reorder_hooks ▼ Security <ul style="list-style-type: none"> accesshash authorizesshkey check_remote_ssh_connection 	<p>acl-passwd</p> <p><i>Boolean</i></p> <p>Whether to allow the reseller to change passwords.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : This privilege allows an API token user to change account passwords and login with a new password. For more information, read our Manage API Tokens documentation.</p> </div> <p>1</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
<p>acl-ssl-buy</p> <p><i>Boolean</i></p> <p>Whether to allow the reseller to purchase SSL certificates.</p> <p>This parameter defaults to 0.</p>	<p>1</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

[convertopensshputty](#)
[deletesshkey](#)
[fetch_security_advice](#)
[generatesshkeypair](#)
[importsshkey](#)
[listsshkeys](#)

Server Administration

[add_configuserserver](#)
[configurebackgroundprocesskiller](#)
[configureservice](#)
[cors_proxy_get](#)
[create_user_session](#)
[delete_configclusterserver](#)
[enable_monitor_all_enabled_services](#)
[get_all_contact_importances](#)
[get_appconfig_application_list](#)
[get_application_contact_event_importance](#)
[get_application_contact_importance](#)
[get_available_profiles](#)
[get_current_profile](#)
[get_password_strength](#)
[get_remote_access_has_h](#)
[get_service_config](#)

acl-cpanel-integration	<i>Boolean</i>	<p>Whether to allow the reseller to manage how their server and its services connect to other servers and services.</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 430 870 840" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-frontpage	<i>Boolean</i>	<p>Whether to allow the reseller to manage Microsoft® FrontPage® Extensions.</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 1165 870 1965" style="border: 1px solid orange; padding: 5px;"> <p>Notes:</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

• W
e
r
e
r
e
m
o
v
e
d
t
h
i
s
p
a
r
a
m
e
t
e
r
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
6
8
.
• c
P
a
n
e
l
&
W
H
M
w
i
l
l
i
g
n
o
r
e
a
l
l
M
i
c
r
o
s
o
f
t
®
F
r

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servername

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

o
n
t
P
a
g
e
s
e
t
t
i
n
g
s
a
n
d
p
a
r
a
m
e
t
e
r
s
i
f
e
i
t
h
e
r
o
f
t
h
e
f
o
l
l
o
w
i
n
g
s
t
a
t
e
m
e
n
t
s
a
r
e
t
r
u

fetchcrtinfo			<p>e :</p> <ul style="list-style-type: none"> Your server runs cPanel & WHM version 11.44 and FrontPage extensic Your server runs cPanel & WHM version 11.46 or later. 		
fetchsslinfo					
generatessl					
get_autossl_check_schedule	acl-cors-proxy-get	Boolean	<p>Whether to allow the reseller to perform Cross-Origin Resource Sharing (CORS) HTTP requests.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
get_autossl_log					
get_autossl_logs_catalog					
get_autossl_metadata					
get_autossl_pending_queue					
get_autossl_pending_queue_for_domain					
get_autossl_pending_queue_for_user					
get_autossl_problems_for_domain	acl-upgrade-account	Boolean	<p>Whether to allow the reseller to upgrade or downgrade accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
get_autossl_problems_for_user					
get_autossl_providers					
get_best_ssl_domain_for_service	acl-ssl-generate	Boolean	<p>Whether to allow the reseller to generate SSL certificates.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
install_service_ssl_certificate					
installssl					
listcrts	acl-create-user-session	Boolean	<p>Whether to allow the reseller to create a temporary user session for a specified service.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. 	1
rebuildinstallssl					
rebuildssl					
rebuilduserssl					
reset_autossl_provider					
reset_service_ssl_certificate					
set_autossl_metadata					
set_autossl_metadata_key					
			<p>Note</p> <ul style="list-style-type: none"> This is a private key 		

set_autossl_provider

start_autossl_check_for_all_users

start_autossl_check_for_one_user

▼ Styles and Themes

generate_cpanel_plugin

list_styles

load_style

remove_log_o

remove_style

save_style

set_default

▼ Support Tickets

ticket_create_stub_ticket

ticket_get_support_agreement

ticket_get_support_info

ticket_grant

ticket_list

ticket_remove_closed

ticket_revoke

ticket_ssh_test

ticket_ssh_test_start

ticket_update_service_agreement_approval

ticket_validate_oauth2_code

ticket_whitelist_check

ticket_whitelist_setup

ticket_whitelist_unsetup

▼ Transfers

l
e
g
a
l
l
o
w
s
a
n
A
P
I
t
o
k
e
n
u
s
e
r
t
o
b
y
p
a
s
s
a
n
y
r
e
s
t
r
i
c
t
i
o
n
s
t
h
a
t
y
o
u
s
e
t
o
n
t
h
e
A
P
I
t
o
k
e
n
.
F
o
r
m
o
r
e
i
n

abort_transfer_session
analyze_transfer_session_remote
available_transfer_modules
create_remote_root_transfer_session
create_remote_user_transfer_session
delete_account_archives
enqueue_transfer_item
fetch_transfer_session_log
get_transfer_session_state
pause_transfer_session
remote_basic_credential_check
retrieve_transfer_session_remote_analysis
start_transfer_session
transfer_module_schema
validate_system_user

▼ Updates

accept_eula
get_available_tiers
get_current_lts_expiration_status
get_lts_wexpire
getlongterm_support
installed_versions
set_cpanel_updates

f
o
r
m
a
t
i
o
n
,
r
e
a
d
o
u
r
M
a
n
a
g
e
A
P
I
T
o
k
e
n
s
d
o
c
u
m
e
n
t
a
t
i
o

set_tier
 update_upd
 ateconf
 version

n .
 • W e a d d e d t h i s p a r a m e t e r i n c P a n e l & W H M v e r s i o n 6 8 .

acl-edit-mx	<i>Boolean</i>	Whether to allow the reseller to edit MX entries. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
-------------	----------------	--	---	---

acl-digest-auth	<i>Boolean</i>	<p>Whether to allow the reseller to manage Digest Authentication support.</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 361 868 768" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-kill-account	<i>Boolean</i>	<p>Whether to allow the reseller to terminate accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-viewglobalpackages	<i>Boolean</i>	<p>Whether to allow the reseller to use all global packages. For more information, read our reseller packages documentation.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

acl-allow-shell	<i>Boolean</i>	<p>Whether to allow the reseller to create accounts with shell access.</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 361 873 768" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-add-pkg-shell	<i>Boolean</i>	<p>Whether to allow the reseller to create packages with shell access.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-allow-addoncreate	<i>Boolean</i>	<p>Whether to allow the reseller to create packages with addon domains.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-disallow-shell	<i>Boolean</i>	<p>Whether to allow the reseller to create accounts that possess shell access.</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 1478 873 1885" style="border: 1px solid orange; padding: 5px;"> <p>Note : We removed this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Do not allow. • 0 — Allow. 	1

acl-allow-parkedcreate	<i>Boolean</i>	Whether to allow the reseller to create packages with parked domains (aliases). This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-allow-unlimited-disk-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited disk space. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-allow-unlimited-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited features. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-allow-unlimited-bw-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited bandwidth. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-add-pkg-ip	<i>Boolean</i>	Whether to allow the reseller to create packages with a dedicated IP address. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-locale-edit	<i>Boolean</i>	Whether to allow the reseller to create and modify locales on the server. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-resftp	<i>Boolean</i>	Whether to allow the reseller to resync FTP passwords. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-restart	<i>Boolean</i>	Whether to allow the reseller to restart services. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

acl-status	<i>Boolean</i>	Whether to allow the reseller to view the server's status. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-stats	<i>Boolean</i>	Whether to allow the reseller to view server information. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-quota	<i>Boolean</i>	Whether to allow the reseller to modify quotas. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
		<p>Warning : If you do not use resource limits, this privilege allows resellers to circumvent package limits for disk space.</p>		
acl-demo-setup	<i>Boolean</i>	Whether to allow the reseller to enable demo mode for accounts. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-edit-account	<i>Boolean</i>	Whether to allow the reseller to edit accounts. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

<p>acl-limit-bandwidth</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to modify bandwidth limits (quotas).</p> <p>This parameter defaults to 0.</p> <div data-bbox="734 405 872 1110" style="border: 1px solid red; padding: 5px; margin: 10px 0;"> <p>Warning : If you do not use resource limits, a value of 1 allows resellers to circumvent package limits for disk space.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>
<p>acl-rearrange-accts</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to rearrange accounts.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	<p>1</p>

acl-track-email	<i>Boolean</i>	<p>Whether to allow the reseller to view reports about email message delivery attempts from their account.</p> <p>This parameter defaults to 0.</p> <div data-bbox="732 407 872 814" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1
acl-all	<i>Boolean</i>	<p>Whether to grant the reseller all privileges.</p> <p>This parameter defaults to 0.</p> <div data-bbox="732 1031 872 1465" style="border: 1px solid red; padding: 5px;"> <p>Warning : A value of 1 grants root-level privileges to the reseller.</p> </div>	<ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. 	1

Returns

This function only returns metadata.