

WHM API 0 Functions - acctcounts

Guide to WHM API 0

Return Data

accounts
summary

applist

createacct

domainuser
data

editquota

limitbw

listaccts

listsuspended

modifyacct

myprivs

passwd

removeacct

showbw

suspendacct

unsuspendacct

▼ DNS

addns

addzonerecord

dumpzone

editzonerecord

getzonerecord

killdns

listzones

lookupnsip

lookupnsips

removezone
record

resetzone

setresolvers

▼ IP Addresses

addip

Description

This function lists a reseller's total accounts, suspended accounts, and account creation limit.

Examples

Accounts

▼ JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/acctcounts?user=username
```

▼ XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/acctcounts?user=username
```

▼ Command Line

```
whmapi0 acctcounts  
user=username
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local  
/cpanel/bin/whmapi0
```

Function information

About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

Warning:
WHM API 0 is deprecated.
We strongly recommend using WHM API 1.

- delip
- listips
- setsiteip
- deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_dockey
 - purge_mail_queue
 - remove_in_progress_exim_configuration_dit
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_config
 - validate_exim_configuration_syntax
 - addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
 - acctcounts
 - getresellerips
 - listacls
 - listresellers
 - resellerstats
 - saveacllist
 - setaccls

Output (JSON)

```
{
  "reseller": {
    "account": "root",
    "suspended": 0,
    "active": 9,
    "limit": ""
  },
  "result": [
    {
      "statusmsg": "Obtained reseller account counts.",
      "status": 1
    }
  ]
}
```

Output (XML)

```
<acctcounts>
  <reseller>

  <account>root</account>

  <active>9</active>
  <limit/>

  <suspended>0</suspended>
  </reseller>
  <result>

  <status>1</status>

  <statusmsg>Obtained reseller account counts.</statusmsg>
  </result>
</acctcounts>
```

Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

Notes:

- Scro
- Yomius 20 or 20)tc

Find a function

- WHM API 0 Functions - acctcounts — This function lists a reseller's total account counts, suspended accounts, and account creation limit.

setresellerips
 setresellerlimits
 setresellermainip
 setresellernameservers
 setresellerpackagelimit
 setupreseller

suspendreseller
 terminatereseller
 unsetupreseller
 unsuspendreseller

Server Administration
 configureSERVICE

gethostname
 getlanglist
 loadavg
 nvget
 nvset
 reboot
 restartSERVICE
 servicestatus
 sethostname

SSL
 fetchsslinfo
 generatessl
 installssl
 listcerts

Updates
 get_available_tiers
 set_cpanel_updates
 set_tier
 version

user	string	A reseller's username, to query only that reseller. If you do not specify a value, the function lists information for the authenticated account.	A valid WHM username on the server.	username
------	--------	---	-------------------------------------	----------

Returns

Return	Type	Description	Possible values	Example
reseller	hash	A hash of information for an account.	This hash includes the account, suspended, active, and limit returns.	
account	string	The account username. The function returns this value in the reseller hash.	<ul style="list-style-type: none"> root A valid WHM username. 	root
suspended	integer	The number of suspended accounts that the user owns. The function returns this value in the reseller hash.	A positive integer that represents a number of currently-suspended accounts.	5
active	integer	The number of active accounts that the user owns. The function returns this value in the reseller hash.	A positive integer that represents a number of currently-active accounts.	9
limit	integer	The maximum number of accounts that the user may create, if a maximum exists. The function returns this value in the reseller hash.	<ul style="list-style-type: none"> A positive integer that represents the user's account creation limit. A null value, if the user does not possess an account creation limit. 	25
result	array of hashes	An array of hashes of function information.	This hash includes the status and statmsg returns.	username

- WHM API 0 Functions - getresellerips — This function lists a reseller's available IP addresses.
- WHM API 0 Functions - listaccounts — This function lists the reseller's Access Control Lists (ACLs) and each list's privileges.

status	<i>Boolean</i>	Whether the function succeeded. The function returns this value in the <code>result</code> hash.	<ul style="list-style-type: none"> 1 — Success. 0 — Failure. 	1
status msg	<i>string</i>	A message of success or a reason for failure. The function returns this value in the <code>result</code> hash.	<ul style="list-style-type: none"> Ok An error message. 	Ok

- WHM API 0 Functions - listresellers — This function lists the reseller accounts on the server.