

UAPI Modules - Mysql

Guide to UAPI

[Return Data](#)
[Filter Output](#)
[Sort Output](#)
[Paginate Output](#)
[Output Columns](#)
[Calls from the WHM API](#)
[Custom UAPI Modules](#)

[Backup](#)
[Backup::fullbackup](#)

[p_to_ftp](#)

[Backup::fullbackup_p_to_homedir](#)

[Backup::fullbackup_p_to_scp_with_key](#)

[Backup::fullbackup_p_to_scp_with_password](#)

[Backup::list_backups](#)

Bandwidth

[Bandwidth::get_enabled_protocols](#)

[Bandwidth::get_retention_periods](#)

[Bandwidth::query](#)

Batch

[Batch::strict](#)

Brand

[Brand::read](#)

Branding

[Branding::file](#)

[Branding::get_applications](#)

[Branding::get_application_information](#)

[Branding::get_available_applications](#)

[Branding::get_information_for_applications](#)

Introduction

The `Mysql` module manages MySQL® users, databases, and services.

Important:

In cPanel & WHM version 76, we introduced server profiles and roles. When you enable a non-*Standard Node* server profile, the system **disables** API calls associated with that profile's disabled roles.

Available functions

- [UAPI Functions - Mysql::add_host](#) — This function authorizes a remote MySQL® host to access the account's databases.
- [UAPI Functions - Mysql::add_host_note](#) — This function adds a note about a remote MySQL® server.
- [UAPI Functions - Mysql::check_database](#) — This function checks for errors in all of the tables in a MySQL® database.
- [UAPI Functions - Mysql::create_database](#) — This function creates a MySQL® database.
- [UAPI Functions - Mysql::create_user](#) — This function creates a MySQL® database user.
- [UAPI Functions - Mysql::delete_database](#) — This function deletes a MySQL® database.
- [UAPI Functions - Mysql::delete_host](#) — This function removes a remote MySQL® host's access to the account's databases.
- [UAPI Functions - Mysql::delete_user](#) — This function deletes a MySQL® user.
- [UAPI Functions - Mysql::get_host_notes](#) — This function returns the notes associated with the account's remote MySQL® hosts.
- [UAPI Functions - Mysql::get_privileges_on_database](#) — This function lists a MySQL® database user's privileges.
- [UAPI Functions - Mysql::get_restrictions](#) — This function lists a MySQL® database's name, username length restrictions, and database prefix.
- [UAPI Functions - Mysql::get_server_information](#) — This function returns information about the account's MySQL® host.
- [UAPI Functions - Mysql::locate_server](#) — This function returns information about the account's MySQL® host.
- [UAPI Functions - Mysql::rename_database](#) — This function renames a MySQL® database.
- [UAPI Functions - Mysql::rename_user](#) — This function renames a MySQL® database user.
- [UAPI Functions - Mysql::repair_database](#) — This function repairs all of the tables in a MySQL® database.
- [UAPI Functions - Mysql::revoke_access_to_database](#) — This function revokes a MySQL® database user's privileges.
- [UAPI Functions - Mysql::set_password](#) — This function sets a MySQL® database user's password.
- [UAPI Functions - Mysql::set_privileges_on_database](#) — This function sets a MySQL® database user's privileges.

UAPI Basics

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Notes:

- `Th`
`Fe`

`int`
• `Ur`
`mi`
`us`
`20`
`or`
`20`
`).`
`'`
`20`
`or`
`20`
`).`

Branding:: image
Branding:: include
Branding:: spritelist

▼ CacheBuster
CacheBuster:: read
CacheBuster:: update

▼ Chkservd
Chkservd:: get_exim_ports
Chkservd:: get_exim_ports_ssl

▼ Chrome
Chrome:: get_dom

▼ Contactus
Contactus:: is_enabled

▼ cPAddons
cPAddons:: get_available_addons
cPAddons:: get_instance_settings
cPAddons:: list_addon_instances

▼ cPGreyList
cPGreyList:: disable_all_domains
cPGreyList:: disable_domains
cPGreyList:: enable_all_domains
cPGreyList:: enable_domains
cPGreyList:: has_greylisting_enabled
cPGreyList:: list_domains

▼ DAV
DAV:: disable_shared_global_addressbook
DAV:: enable_shared_global_addressbook
DAV:: get_calendar_contacts_config
DAV:: has_shared_global_addressbook
DAV:: is_dav_service_enabled

Related Documentation

- [Guide to cPanel API 1](#) — cPanel API 1 accesses information from the cPanel interface.
- [Guide to cPanel API 2](#) — cPanel API 2 accesses cPanel account information and modifies settings.

- DAV:: is_horde_enabled
- DCV:: check_domains_via_dns
 - DCV:: check_domains_via_http
 - DCV:: ensure_domains_can_pass_dcv
- DomainInfo:: domains_data
 - DomainInfo:: list_domains
 - DomainInfo:: main_domain_builtin_subdomain_aliases
 - DomainInfo:: single_domain_data
- DNS:: ensure_domains_reside_only_locally
 - DNS:: has_local_authority
- DNSSEC:: disable_dnssec
 - DNSSEC:: enable_dnssec
 - DNSSEC:: fetch_dns_records
 - DNSSEC:: set_nsec3
 - DNSSEC:: unset_nsec3
- Email:: account_name
 - Email:: add_auto_responder
 - Email:: add_domain_forwarder
 - Email:: add_forwarder
 - Email:: add_list
 - Email:: add_mailman_delegates
 - Email:: add_mx
 - Email:: add_pop
 - Email:: add_spam_filter

- [Guide to WHM API 0](#) — WHM API 0 accesses the WHM interface's features.
- [Guide to WHM API 1](#) — WHM API 1 accesses the WHM interface's features.
- [Guide to UAPI](#) — UAPI accesses the cPanel interface's features.

Email:: browse_mailbox

Email:: change_mx

Email:: check_fastmail

Email:: check_pipe_forwarder

Email:: delete_auto_responder

Email:: delete_domain_forwarder

Email:: delete_filter

Email:: delete_forwarder

Email:: delete_held_messages

Email:: delete_list

Email:: delete_mx

Email:: delete_pop

Email:: disable_filter

Email:: disable_mailbox_autocreate

Email:: disable_spam_assassin

Email:: disable_spam_autodelete

Email:: disable_spam_box

Email:: dispatch_client_settings

Email:: edit_pop_quota

Email:: enable_filter

Email:: enable_mailbox_autocreate

Email:: enable_spam_assassin

Email:: enable_spam_box

Email:: fetch_charmaps

Email:: fts_rescan_mailbox

Email:: generate_mailman_opt

Email:: get_auto_responder

Email:: get_chase

ts

Email:: get_client_
settings

Email:: get_default_
_email_quota

Email:: get_default_
_email_quota_mib

Email:: get_disk_u
sage

Email:: get_filter

Email:: get_held_
message_count

Email:: get_mailbo
x_autocreate

Email:: get_mailm
an_delegates

Email:: get_main_
account_disk_usa
ge

Email:: get_main_
account_disk_usa
ge_bytes

Email:: get_max_e
mail_quota

Email:: get_max_e
mail_quota_mib

Email:: get_pop_q
uota

Email:: get_spam_
settings

Email:: get_webm
ail_settings

Email:: has_deleg
ated_mailman_list
s

Email:: has_plainte
xt_authentication

Email:: hold_outgo
ing

Email:: is_integer

Email:: list_auto_r
esponders

Email:: list_default_
_address

Email:: list_domain_
_forwarders

Email:: list_filters

Email:: list_filters_
backups

Email:: list_forward
ers

Email:: list_forward

ers_backups

Email:: list_lists

Email:: list_mail_d
omains

Email:: list_mxs

Email:: list_pops

Email:: list_pops_
with_disk

Email:: list_system
_filter_info

Email:: passwd_list

Email:: passwd_po
p

Email:: release_ou
tgoing

Email:: remove_m
ailman_delegates

Email:: reorder_filt
ers

Email:: set_always
_accept

Email:: set_default
_address

Email:: set_list_pri
vacy_options

Email:: stats_db_st
atus

Email:: store_filter

Email:: suspend_in
coming

Email:: suspend_lo
gin

Email:: suspend_o
utgoing

Email:: trace_filter

Email:: unsuspend
_incoming

Email:: unsuspend
_login

Email:: unsuspend
_outgoing

Email:: verify_pass
word

▼ EmailAuth

EmailAuth:: disabl
e_dkim

EmailAuth:: enable
_dkim

EmailAuth:: ensure
_dkim_keys_exist

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthentic
ation:: add_auth_li
nk

ExternalAuthentic
ation:: configured_
modules

ExternalAuthentic
ation:: get_auth_lin
ks

ExternalAuthentic
ation:: has_external
_auth_modules_co
nfigured

ExternalAuthentic
ation:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

▼ Ftp

Ftp:: add_ftp

Ftp:: allows_anonymous_ftp

Ftp:: allows_anonymous_ftp_incoming

Ftp:: delete_ftp

Ftp:: ftp_exists

Ftp:: get_ftp_daemon_info

Ftp:: get_port

Ftp:: get_quota

Ftp:: get_welcome_message

Ftp:: kill_session

Ftp:: list_ftp

Ftp:: list_ftp_with_disk

Ftp:: list_sessions

Ftp:: passwd

Ftp:: server_name

Ftp:: set_anonymous_ftp

Ftp:: set_anonymous_ftp_incoming

Ftp:: set_homedir

Ftp:: set_quota

Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create

KnownHosts:: delete

KnownHosts:: update

KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler

LangPHP:: php_get_impacted_domains

LangPHP:: php_get_installed_version

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provi
der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server_
information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start