

cPanel API 2 Functions - CustInfo::contactemails

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddomain

omain

AddonDomain:: deladdondomain

AddonDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagelist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Branding:: gensprites

Description

This function retrieves the account's primary and secondary email addresses.

Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Note:

You can **only** execute this function if your hosting provider enables the following features in WHM's [Feature Manager](#) interface (*WHM >> Home >> Features >> Feature Manager*).

- The *Contact Information* feature.
- The *Update Notification Preferences* feature.

[AddonDomain](#)

Examples

WHM API (JSON)

```
https://hostname.example.com:2083/cpsess#####/json-api/cpanel?cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=CustInfo&cpanel_jsonapi_func=contactemails&username=example1%40example.com
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The `CustInfo` module manages the account's notifications and contact information.

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpackages

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Retrieve the  
primary and secondary  
email contacts.  
$save_contact =  
$cpanel->api2(  
    'CustInfo',  
    'contactemails',  
    array(  
        username =>  
        'example1@example.com'  
    ),  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- Thursday, February 20, 2014, 2:00 PM

Find a function

- Contactus:: isenab
led
 - Contactus:: sendc
ontact
 - Cron
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo
 - CustInfo:: contacte
mails
 - CustInfo:: contactp
refs
 - CustInfo:: displayc
ontactinfo
 - CustInfo:: savecon
tactinfo
 - DBmap
 - DBmap:: status
 - DBmap:: version
 - DKIMUI
 - DKIMUI:: available
 - DKIMUI:: getrecor
ds
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - Denylp
 - Denylp:: listdenyip
s
 - DiskCounter
 - DiskCounter:: disk
_counter
 - DiskUsage
 - DiskUsage:: buildc
ache
 - DiskUsage:: clearc
ache
 - DiskUsage:: fetch_
raw_disk_usage
 - DiskUsage:: fetchd
iskusage
 - DiskUsage:: fetchd
iskusagewithextras

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Retrieve the
primary and secondary
email contacts.
my $save_contact =
$cpliveapi->api2(
  'CustInfo',
  'contactemails',
  {
    username =>
'example1@example.com
',
  }
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat ed**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Dep recated cPanel Tag Usage](#) docume ntation.

- cPan
el
API
2
Mod
ules
-
Cont
actus
— T
he C
onta
ctus
mod
ule
man
ages
supp
ort
requ
ests
to
the
host.

- cPan
el
API
2
Func
tions
-
Cont
actus
::isen
able
d —
This
funct
ion
chec
ks
whet
her
the
acco
unt's
cont
act
optio
n is
enab
led.

▼ DnsLookup

DnsLookup:: name2ip

▼ DomainLookup

DomainLookup:: countbaseddomains

DomainLookup:: getbaseddomains

DomainLookup:: getdocroot

DomainLookup:: getdocroots

DomainLookup:: getmaindomain

▼ Email

Email:: accountname

Email:: adddomainforward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browseboxes

Email:: changemx

Email:: checkmaindiscard

Email:: clearpopcache

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautosponder

Email:: fetchcharmaps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archiving_configuration

Email:: get_archiving_default_configuration

▼ Command Line

```
cpapi2
--user=username
CustInfo
contactemails
username=example1@example.com
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local
/cpanel/bin/cpapi2
```

▼ Output (JSON)

- cPanel API 2 Functions - Contactus::sendcontact — This function sends a support request to the site's host.
- cPanel API 2 Modules - CustInfo — The CustInfo module manages the account's notifications and contact information.

ration

Email: get_archiving_types

Email: get_default_email_quota

Email: get_email_signing

Email: get_max_email_quota

Email: getabsbrowserdir

Email: getalwaysaccept

Email: getdiskusage

Email: getmxcheck

Email: has_delegated_mailman_lists

Email: list_system_filter_info

Email: listaliasesbackups

Email: listautoresponders

Email: listdefaultaddresses

Email: listdomainforwards

Email: listfilterbackups

Email: listfilters

Email: listforwards

Email: listlists

Email: listmaildomains

Email: listmx

Email: listmxs

Email: listpops

Email: listpopssingle

Email: listpopswithdisk

Email: listpopswithimage

Email: loadfilter

Email: passwdpop

Email: reorderfilters

```
{
  "cpanelresult": {
    "func":
    "contactemails",
    "apiversion": 2,
    "data": [{
      "descp": "The
system sends account
notifications and
password reset
confirmations to this
email address. Do not
use an email address
owned by your cPanel
account.",
      "value":
      "bob@example2.com",
      "enabled": 1,
      "name": "email",
      "type": "string"
    }, {
      "enabled": 1,
      "descp": "Enter a
second email address
to receive account
notifications and
password reset
confirmations.",
      "value": "",
      "type": "string",
      "name":
      "second_email"
    }, {
      "type": "string",
      "name":
      "pushbullet_access_to
ken",
      "enabled": 1,
      "descp": "An
access token for
Pushbullet.",
      "value":
      "a1b2c3d4e5f6g7h8i9j0"
    }
  ],
  "module":
  "CustInfo",
  "event": {
    "result": 1
  }
}
```

- cPanel API 2 Functions - CustInfo: contactemails - This function retrieves the account's primary and secondary email addresses.

Email:: set_archiving_configuration

Email:: set_archiving_default_configuration

Email:: set_email_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get_encodings

Encoding:: guess_file

Encoding:: guess_file_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: geteditty

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
username	string	The Subaccount in which to load the contact information. Note: <ul style="list-style-type: none">W e a d d e d t h i s p a r a m e t e r i n c P a n e l & W H M v e r s i o n 5 6 .l f y o u s e	A valid Subaccount the that authenticated cPanel account user owns.	example1@example.com

Fileman:: search
Fileman:: statfiles
Fileman:: uploadfiles
Fileman:: viewfile
▼ ForcePassword
ForcePassword:: get_force_password_flags
ForcePassword:: update_force_password_flags
▼ Frontpage
Frontpage:: fpenabled
Frontpage:: list
▼ Ftp
Ftp:: addftp
Ftp:: delftp
Ftp:: listftp
Ftp:: listftpessions
Ftp:: listftpwithdisk
Ftp:: passwd
Ftp:: setquota
▼ Gpg
Gpg:: listgpgkeys
Gpg:: listsecretgpgkeys
Gpg:: number_of_private_keys
Gpg:: number_of_public_keys
▼ Htaccess
Htaccess:: listuser
Htaccess:: listusers
▼ HttpUtils
HttpUtils:: getdirindices
▼ ImageManager
ImageManager:: thumbnail
▼ LVEInfo
LVEInfo:: getUsage
▼ LangMods
LangMods:: getarchname
LangMods:: getkey

t
t
h
e
u
s
e
r
n
a
m
e
p
a
r
a
m
e
t
e
r
,
t
h
e
f
u
n
c
t
i
o
n
o
n
l
y
r
e
t
u
r
n
s
t
h
e
S
u
b
a
c
c
o
u
n
t
,
s
c
o
n
t
a
c
t
i
n
f
o
r
m
a
t
i
o

LangMods:: getpre
fix

LangMods:: install

LangMods:: languis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
locale

Locale:: get_user_
locale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

		n		
--	--	---	--	--

Returns

Return	Type	Description	Possible values	Example
enabled	<i>Boolean</i>	Whether the notification setting is enabled.	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	1
value	<i>string</i>	The notification setting's value.	A valid email address.	user@example.com
type	<i>string</i>	The notification setting's data type.	<ul style="list-style-type: none"> string Boolean 	string
descp	<i>string</i>	The notification setting's description.	A valid string.	<p>▼ Click to view...</p> <p>This is an email address at which the system can contact you. This should be an email address that is not on your account.</p>
name	<i>string</i>	The notification setting's name.	<ul style="list-style-type: none"> email second_email pushbullet_access_token 	email
reason	<i>string</i>	A reason for failure.	A string that describes the error.	This is an error message.
result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> 1 — Success. 0 — Failure. 	1

Note : This function only returns a reason value if it failed.

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change
dbuserpassword

MysqlFE:: created
b

MysqlFE:: created
buser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deleted
b

MysqlFE:: deleted
buser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdatabasesprivileges

MysqlFE:: getdatabases

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdatabasesbackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers
indb

MysqlIFE:: revoked
buserprivileges

MysqlIFE:: setdbus
erprivileges

MysqlIFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
mdir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

