

WHM API 1 Functions - setacIs

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function creates or modifies an Access Control List (ACL).

Warning:

We **strongly** recommend that WHM users create and edit ACLs and privileges in WHM's *Edit Reseller Nameservers and Privileges* interface (*WHM >> Home >> Resellers >> Edit Reseller Nameservers and Privileges*).

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/setacIs?api.version=1&reseller=username&acl-kill-dns=1&acl-edit-dns=1&acl-edit-mx=1&acl-add-pkg=1&acl-suspend-acct=1&acl-ssl=1&manage-api-tokens=1&cpanel-integration=1
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/setacIs?api.version=1&reseller=username&acl-kill-dns=1&acl-edit-dns=1&acl-edit-mx=1&acl-add-pkg=1&acl-suspend-acct=1&acl-ssl=1&manage-api-tokens=1&cpanel-integration=1
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
-) t

ue_list_pending

restore_queue_state

restoreaccount

verify_new_username_or_restore

Accounts

accountsummary

applist

createacct

domainuserdata

editquota

forcepasswordchange

get_disk_usage

get_domain_info

getdomainowner

has_digest_auth

has_mycnf_for_cpuser

limitbw

list_users

listaccts

listlockedaccounts

listsuspended

modifyacct

myprivs

passwd

quota_enabled

removeacct

set_digest_auth

showbw

suspendacct

unsuspendacct

untrack_acct

Command Line

```
whmapil setaccls  
reseller=username  
acl-kill-dns=1  
acl-edit-dns=1  
acl-edit-mx=1  
acl-add-pkg=1  
acl-suspend-acct=1  
acl-ssl=1  
manage-api-tokens=1  
cpanel-integration=1
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Find a function

- WHM API 0 Functions - setresellername - This function assigns nameservers to a reseller's account.

_id

verify_new_username

▼ Addon Domains

convert_addon_fetch_conversion_details

convert_addon_fetch_domain_details

convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_domains

convert_addon_list_conversions

▼ Authentication

api_token_create

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_failing_authentication_providers

enable_authentication_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider_display_co

▼ Output (JSON)

```
{
  "data": {
    "acl": [
      "kill-dns",
      "ssl",
      "edit-mx",
      "suspend-acct",
      "edit-dns",
      "add-pkg-1"
    ],
    "manage-api-tokens": "cpanel-integration"
  },
  "metadata": {
    "version": 1,
    "reason": "OK",
    "result": 1
  },
  "command": "setacls"
}
```

- WHM API 1 Sections - Resellers — Reseller functions allow you to manage your cPanel and WHM reseller accounts.
- WHM API 1 Functions - acctouts — This function lists a reseller's total accounts, suspended accounts, and account creation limit.

nfigurations

get_users_authn_linked_accounts

link_user_authn_provider

set_provider_client_configurations

set_provider_display_configurations

twofactorauth_disable_policy

twofactorauth_enable_policy

twofactorauth_generate_tfa_config

twofactorauth_get_issuer

twofactorauth_get_user_configs

twofactorauth_policy_status

twofactorauth_remove_user_config

twofactorauth_set_issuer

twofactorauth_set_tfa_config

unlink_user_authn_provider

validate_login_token

Backups

backup_config_get

backup_config_set

backup_data_list

backup_destination_add

backup_destination_delete

Output (XML)

```

<result>
  <data>

  <acl>kill-dns</acl>

  <acl>ssl</acl>

  <acl>edit-mx</acl>

  <acl>suspend-acct</acl>

  <acl>edit-dns</acl>

  <acl>add-pkg-1</acl>

  <acl>manage-api-tokens</acl>

  <acl>cpanel-integration</acl>

  </data>
  <metadata>

  <version>1</version>

  <reason>OK</reason>

  <result>1</result>

  <command>setacls</command>

  </metadata>
</result>

```

Note:
 Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

- WHM API 1 Functions - getresellerips - This function lists a reseller's available IP addresses.

Parameters

Note:
 This function's Boolean parameters do not perform like most other cPanel & WHM API parameters. The function interprets any value of a parameter as a true value, and it interprets the lack of a parameter as a false value.

backup_destination_get
 backup_destination_list
 backup_destination_set
 backup_destination_validate
 backup_get_transport_status
 backup_list_transported
 backup_set_list
 backup_set_list_combined
 backup_skip_users_all
 backup_skip_users_all_status
 backup_user_list
 convert_and_migrate_from_legacy_config
 get_users_with_backup_metadata
 list_cparchive_files
 start_background_package
 toggle_user_backup_status
 v cPHulk
 cphulk_statuses
 create_cphulk_record
 delete_cphulk_record
 disable_cphulk
 enable_cphulk
 flush_cphulk_login_history

Parameter	Type	Description	Possible values	Example
reseller	string	Required The reseller's username.	A valid username on the server.	username
aclist	string	The ACL to assign to the reseller. <div style="border: 1px solid red; padding: 5px;"> <p>Warning : Functions should either use this parameter, or a combination of the acl-* parameters below. Do not include both in a single function.</p> </div>	An ACL on the server.	my_acl_list
acl-edit-pkg	Boolean	Whether to allow the reseller to edit hosting plans (packages). This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-add-pkg	Boolean	Whether to allow the reseller to add and remove hosting plans (packages). This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brutes

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_user_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status

current_mysql_version

installable_mysql_versions

latest_available_mysql_version

list_database_users

list_databases

list_mysql_databases_and_users

remote_mysql_create_profile

remote_mysql_create_profile_via_ssh

remote_mysql_delete_profile

remote_mysql_initiate_profile_activation

acl-list-pkgs	<i>Boolean</i>	<p>Whether to allow the reseller to view existing hosting plans (packages).</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-mailcheck	<i>Boolean</i>	<p>Whether to allow the reseller to troubleshoot mail delivery.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-generate-email-config	<i>Boolean</i>	<p>Whether to allow the reseller to generate a mobile configuration profile for an email account.</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

addns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

acl-show-bandwidth	<i>Boolean</i>	Whether to allow the reseller to view account bandwidth usage. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-list-accounts	<i>Boolean</i>	Whether to allow the reseller to view the list of accounts. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-acct-summary	<i>Boolean</i>	Whether to allow the reseller to view an account summary. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	1
acl-clustering	<i>Boolean</i>	Whether to allow the reseller to use DNS clusters. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-news	<i>Boolean</i>	Whether to allow the reseller to modify the server's news. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-thirdparty	<i>Boolean</i>	Whether to allow the reseller to manage third-party services. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

killdns	acl-kill-dns	Boolean	Whether to allow the reseller to remove DNS zones. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
listmxs					
listzones					
lookupnsip					
lookupnsips					
removezone record	acl-edit-dns	Boolean	Whether to allow the reseller to edit DNS zones. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
resetzone					
resolvedomainname					
savemxs					
setresolvers	acl-cpanel-api	Boolean	Whether to allow the reseller to execute cPanel API 1, cPanel API 2 and UAPI functions via WHM. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
update_nameservers_config					
EasyApache <ul style="list-style-type: none"> ea4_get_currently_installed_packages ea4_get_ea_pkgs_state ea4_list_profiles ea4_metainfo ea4_migration ea4_pre_migrate_check ea4_recommendations 			<div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note :</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div>		
ea4_save_profile	acl-park-dns	Boolean	Whether to allow the reseller to park DNS zones. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
ea4_tomcat85_add					
ea4_tomcat85_list					
ea4_tomcat85_remove	acl-create-dns	Boolean	Whether to allow the reseller to add DNS zones. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
Greylisting <ul style="list-style-type: none"> cpgreylist_server_network_block_trusted cpgreylist_list_entries_for_common_mail_provider cpgreylist_load_common_mail_provider 	acl-manage-api-tokens	Boolean	Whether to allow the reseller to manage API tokens. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

ers_config
cpgreylist_s
ave_commo
n_mail_provi
ders_config
cpgreylist_st
atus
cpgreylist_tr
ust_entries_
for_common
_mail_provid
er
cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider
create_cpgr
eylist_truste
d_host
delete_cpgr
eylist_truste
d_host
disable_cpgr
eylist
enable_cpgr
eylist
load_cpgreyl
ist_config
read_cpgrey
list_deferred
_entries
read_cpgrey
list_trusted_
host
save_cpgrey
list_config

▼ Integration

batch
cpanel
create_integ
ration_group
create_integ
ration_link
get_integrati
on_link_user
_config
list_integrati
on_groups
list_integrati
on_links
remove_inte
gration_grou
p
remove_inte

**Note
s:**

- This is a private illegal geolocation and an API token user is required to bypass this restriction.

- gration_link
- update_inte
- gration_link
- _token
- IP Addresses
 - addips
 - delip
 - get_public_i
 - p
 - get_shared_
 - ip
 - ipv6_disable
 - _account
 - ipv6_enable
 - _account
 - ipv6_range_
 - add
 - ipv6_range_
 - edit
 - ipv6_range_
 - list
 - ipv6_range_
 - remove
 - ipv6_range_
 - usage
 - listips
 - nat_checkip
 - nat_set_pub
 - lic_ip
 - setsiteip
 - Mail
 - disable_dki
 - m
 - disable_mail
 - _sni
 - emailtrack_s
 - earch
 - emailtrack_s
 - tats
 - emailtrack_u
 - ser_stats
 - enable_dkim
 - enable_mail
 - _sni
 - ensure_dki
 - m_keys_exi
 - st
 - exim_config
 - uration_che
 - ck
 - expunge_m

n . F o r m o r e i n f o r m a t i o n ; r e a d o u r M a n a g e A P I T o k e n s 7 2 D o c s u m e n t a t i o

mailbox_messages
 expunge_messages_for_mailbox_guid
 fetch_dkim_private_keys
 fetch_mail_queue
 generate_mobileconfig
 get_mailbox_status
 get_mailbox_status_list
 get_unique_recipient_count_per_sender_for_user
 get_unique_sender_recipient_count_per_user
 get_user_email_forward_destination
 hold_outgoing_email
 install_dkim_private_keys
 install_spf_records
 is_sni_supported
 list_pops_for
 mail_sni_status
 rebuild_mail_sni_config
 release_outgoing_email
 save_spamd_config
 set_user_email_forward_destination
 suspend_outgoing_email
 unsuspend_outgoing_email

			<p> . We added this parameter in cPanel & WHM version 68. </p>	
<p> acl-manage-oidc is_sni_supported list_pops_for mail_sni_status rebuild_mail_sni_config release_outgoing_email save_spamd_config set_user_email_forward_destination suspend_outgoing_email unsuspend_outgoing_email </p>	<p> <i>Boolean</i> </p>	<p> Whether to allow the reseller to manage external authentication for their accounts. This parameter defaults to <code>undef</code>. </p> <p> Note : We added this parameter in cPanel & WHM version 68. </p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	<p>1</p>

<p>validate_current_installed_exim_config</p> <p>validate_current_dkims</p> <p>validate_current_ptrs</p> <p>validate_current_spfs</p> <p>validate_exim_configuration_syntax</p> <p>▼ Market</p> <p>disable_market_provider</p> <p>enable_market_provider</p> <p>get_adjusted_market_providers_products</p>	<p>acl-manage-dns-records</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage DNS records. This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note :</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	<p>1</p>
<p>get_market_providers_commission_config</p> <p>get_market_providers_list</p> <p>get_market_providers_product_metadata</p> <p>get_market_providers_products</p> <p>set_market_product_attribute</p> <p>set_market_provider_commission_id</p>	<p>acl-manage-styles</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage their server's cPanel styles. This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note :</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	<p>1</p>
<p>▼ ModSecurity™</p> <p>modsec_added_rule</p> <p>modsec_added_vendor</p> <p>modsec_ensemble_config_text</p> <p>modsec_batch_settings</p> <p>modsec_check_rule</p> <p>modsec_close_rule</p>					

<p>modsec_deploy_all_rule_changes</p> <p>modsec_deploy_rule_changes</p> <p>modsec_deploy_settings_changes</p> <p>modsec_disable_rule</p> <p>modsec_disable_vendor</p> <p>modsec_disable_vendor_configs</p> <p>modsec_disable_vendor_updates</p> <p>modsec_discard_all_rule_changes</p>	<p>acl-nameserver-config</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage nameservers.</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>
<p>modsec_discard_rule_changes</p> <p>modsec_edit_rule</p> <p>modsec_enable_vendor</p>	<p>acl-ssl</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to perform SSL site management.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>
<p>modsec_enable_vendor_configs</p> <p>modsec_enable_vendor_updates</p> <p>modsec_get_config_text</p> <p>modsec_get_configs</p> <p>modsec_get_configs_with_changes_pending</p> <p>modsec_get_log</p> <p>modsec_get_rules</p> <p>modsec_get_settings</p> <p>modsec_get_vendors</p> <p>modsec_is_installed</p> <p>modsec_make_config_active</p>	<p>acl-ssl-info</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to view their server's SSL information.</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>

- modsec_make_config_active
- modsec_preview_vendor
- modsec_remove_rule
- modsec_remove_setting
- modsec_remove_vendor
- modsec_report_rule
- modsec_set_config_text
- modsec_set_setting
- modsec_uninstall_rule
- modsec_update_vendor
- ▼ Packages
- _getpkgextensionform
- add_override_features_for_user
- addpkg
- addpkgext
- changepackage
- create_feature_relist
- delete_feature_relist
- delpkgext
- editpkg
- get_available_applications
- get_available_featurelists
- get_feature_metadata
- get_feature_names
- get_featurelist_data
- get_featureli

acl-mysql-info	<i>Boolean</i>	<p>Whether to allow the reseller to retrieve MySQL® database and user data.</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	1
acl-create-acct	<i>Boolean</i>	<p>Whether to allow the reseller to create accounts.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	1
acl-suspend-acct	<i>Boolean</i>	<p>Whether to allow the reseller to suspend or unsuspend accounts.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	1

<p>sts</p> <p>get_users_features_settings</p> <p>getfeaturelist</p> <p>getpkginfo</p> <p>killpkg</p> <p>listpkgs</p> <p>manage_features</p> <p>matchpkgs</p> <p>read_featurelist</p> <p>remove_override_features_for_user</p> <p>update_featurelist</p>	<p>acl-basic-system-info</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to retrieve basic system information. This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>
<p>verify_user_has_feature</p> <p>▼ PHP</p> <p>convert_all_domains_to_fpm</p> <p>get_fpm_count_and_utilization</p> <p>is_conversion_in_progress</p> <p>php_get_default_accounts_to_fpm</p> <p>php_get_handlers</p> <p>php_get_impacted_domains</p>	<p>acl-basic-whm-functions</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to access basic cPanel & WHM options. This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>
<p>php_get_installed_versions</p> <p>php_get_old_fpm_flag</p> <p>php_get_system_default_version</p> <p>php_get_versions_by_version</p> <p>php_get_versions</p> <p>php_ini_get_content</p>	<p>acl-res-cart</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to reset the Interchange shopping cart. This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid red; padding: 5px; margin-top: 10px;"> <p>Important:</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setreselleri
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

• W
e
r
e
r
e
m
o
v
e
d
t
h
i
s
r
e
t
u
r
n
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.4
6
.

llers

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

• D
o
n
o
t
u
s
e
t
h
i
s
p
r
i
v
i
l
e
g
e
i
n
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.3
8
o
r
l
a
t
e
r
.

convertopen
 ssttoputty

 deletesshke
 y

 fetch_securi
 ty_advice

 generatessh
 keypair

 importsshke
 y

 listsshkeys

Server

Administration

add_configcl
 usterserver

 configureba
 ckgroundpro
 cesskiller

 configureser
 vice

 cors_proxy_
 get

 create_user
 _session

 delete_conf
 gclusterserv
 er

 enable_mon
 itor_all_ena
 bled_service
 s

 get_all_cont
 act_importa
 nces

 get_appconf
 ig_applicatio
 n_list

 get_applicati
 on_contact_
 event_import
 tance

 get_applicati
 on_contact_
 importance

 get_availabl
 e_profiles

 get_current_
 profile

 get_passwor
 d_strength

 get_remote_
 access_has
 h

 get_service_
 config

<p>acl-passwd</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to change passwords.</p> <p>This parameter defaults to <code>undefined</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : This privilege allows an API token user to change account passwords and log in with a new password. For more information, read our Manage API Tokens 7.2 Documentation.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undefined</code> — Do not allow. 	<p>1</p>
<p>acl-ssl-buy</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to purchase SSL certificates.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undefined</code> — Do not allow. 	<p>1</p>

<p>get_service_config_key</p> <p>get_tcp4_sockets</p> <p>get_tcp6_sockets</p> <p>get_tweaksetting</p> <p>get_udp4_sockets</p> <p>get_udp6_sockets</p> <p>get_update_availability</p> <p>get_users_links</p> <p>getdiskusage</p> <p>gethostname</p> <p>is_role_enabled</p>	<p>acl-cpanel-integration</p> <p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage how their server and its services connect to other servers and services.</p> <p>This parameter defaults to <code>undef</code>.</p> <div data-bbox="734 453 873 863" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>
<p>list_configlusterservers</p> <p>loadavg</p> <p>nvget</p> <p>nvset</p> <p>personalization_get</p> <p>personalization_set</p> <p>purchase_a_license</p> <p>reboot</p> <p>remove_in_progress_exim_configedit</p> <p>restartservice</p> <p>restore_config_from_file</p> <p>restore_config_from_upload</p> <p>run_cpkeyctl</p> <p>send_test_posturl</p> <p>send_test_pushbullet_note</p> <p>servicestatus</p>	<p>acl-frontpage</p> <p><i>Boolean</i></p>	<p>Whether to allow the reseller to manage Microsoft® FrontPage® Extensions.</p> <p>This parameter defaults to <code>undef</code>.</p> <div data-bbox="734 1171 873 1967" style="border: 1px solid orange; padding: 5px;"> <p>Note : cPanel & WHM will ignore all Microsoft FrontPage settings and parameters if either of the following statements are true:</p> <ul style="list-style-type: none"> • <code>Y</code> <code>o</code> <code>u</code> <code>r</code> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undef</code> — Do not allow. 	<p>1</p>

s
set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

s
e
r
v
e
r
r
u
n
s
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.4
4
a
n
d
F
r
o
n
t
P
a
g
e
e
x
t
e
n
s
i
o
n
s
a
r
e
n
o
t
i
n
s
t
a
l
l
e
d
o
n
y
o
u
r
s
e
r
v
e

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_sch
edule
get_autossl
_log
get_autossl
_logs_catalo
g
get_autossl
_metadata
get_autossl
_pending_q
ueue
get_autossl
_pending_q
ueue_for_do
main
get_autossl
_pending_q
ueue_for_us
er
get_autossl
_problems_f
or_domain
get_autossl
_problems_f
or_user
get_autossl
_providers
get_best_ssl
domain_for_
service
install_servi
ce_ssl_certif
icate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autos
ssl_provider
reset_servic
e_ssl_certifi
cate
set_autossl_
metadata
set_autossl_
metadata_k
ey

r
• Y
o
u
r
s
e
r
v
e
r
r
u
n
s
c
P
a
n
e
l
&
W
H
M
v
e
r
s
i
o
n
1
1
.4
6
o
r
l
a
t
e
r
.

- set_autoss_provider
- start_autossil_check_for_all_users
- start_autossil_check_for_one_user
- generate_cpanel_plugin
 - list_styles
 - load_style
 - remove_log
 - remove_style
 - save_style
 - set_default
- ticket_create_stub_ticket
 - ticket_get_support_agreement
 - ticket_get_support_info
 - ticket_grant
 - ticket_list
 - ticket_remove_closed
 - ticket_revoke
 - ticket_ssh_test
 - ticket_ssh_test_start
 - ticket_update_service_agreement_approval
 - ticket_validate_oauth2_code
 - ticket_whitelist_check
 - ticket_whitelist_setup
 - ticket_whitelist_unsetup
- Transfers

ac1-cors-proxy-get	Boolean	<p>Whether to allow the reseller to perform Cross-Origin Resource Sharing (CORS) HTTP requests.</p> <p>This parameter defaults to <code>undefined</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1
ac1-upgrade-account	Boolean	<p>Whether to allow the reseller to upgrade or downgrade accounts.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1
ac1-ssl-generate	Boolean	<p>Whether to allow the reseller to generate SSL certificates.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1
ac1-create-user-session	Boolean	<p>Whether to allow the reseller to create a temporary session user for a specified service.</p> <p>This parameter defaults to <code>undefined</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Notes:</p> <ul style="list-style-type: none"> • This is a privileged file </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1

abort_transfer_session
analyze_transfer_session_remote
available_transfer_modules
create_remote_root_transfer_session
create_remote_user_transfer_session
delete_account_archives
enqueue_transfer_item
fetch_transfer_session_log
get_transfer_session_state
pause_transfer_session
remote_basic_credential_check
retrieve_transfer_session_remote_analysis
start_transfer_session
transfer_module_schema
validate_system_user

▼ Updates

accept_eula
get_available_tiers
get_current_lts_expiration_status
get_lts_wexpire
getlongterm_support
installed_versions
set_cpanel_updates

g
e
a
l
l
o
w
s
a
n
A
P
I
t
o
k
e
n
u
s
e
r
t
o
b
y
p
a
s
s
a
n
y
r
e
s
t
r
i
c
t
i
o
n
s
t
h
a
t
y
o
u
s
e
t
o
n
t
h
e
A
P
I
t
o
k
e
n
.
F
o
r
m
o
r
e
i
n
f
o

set_tier
update_upd
ateconf
version

r
m
a
t
i
o
n
,
r
e
a
d
o
u
r
M
a
n
a
g
e
A
P
I
T
o
k
e
n
s
7
2
D
o
c
s
u
m
e
n
t
a
t
i
o

n . W e a d d e d t h i s p a r a m e t e r i n c P a n e l & W H M v e r s i o n 6 8 .

acl-edit-mx	<i>Boolean</i>	Whether to allow the reseller to edit MX entries. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none">Any value — Allow.<code>undef</code> — Do not allow.	1

acl-digest-auth	<i>Boolean</i>	<p>Whether to allow the reseller to manage Digest Authentication support.</p> <p>This parameter defaults to <code>undef</code>.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-kill-account	<i>Boolean</i>	<p>Whether to allow the reseller to terminate accounts.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-viewglobalpackages	<i>Boolean</i>	<p>Whether to allow the reseller to use all global packages. For more information, read our reseller packages documentation.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-disallow-shell	<i>Boolean</i>	<p>Whether to allow the reseller to create accounts with shell access.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-add-pkg-shell	<i>Boolean</i>	<p>Whether to allow the reseller to create packages with shell access.</p> <p>This parameter defaults to <code>undef</code>.</p>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

acl-allow-addoncreate	<i>Boolean</i>	Whether to allow the reseller to create packages with addon domains. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-allow-parkedcreate	<i>Boolean</i>	Whether to allow the reseller to create packages with parked domains (aliases). This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-allow-unlimited-disk-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited disk space. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-allow-unlimited-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited features. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-allow-unlimited-bw-pkgs	<i>Boolean</i>	Whether to allow the reseller to create packages with unlimited bandwidth. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-add-pkg-ip	<i>Boolean</i>	Whether to allow the reseller to create packages with a dedicated IP address. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

acl-locale-edit	<i>Boolean</i>	Whether to allow the reseller to create and modify locales on the server. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-resftp	<i>Boolean</i>	Whether to allow the reseller to resync FTP passwords. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-restart	<i>Boolean</i>	Whether to allow the reseller to restart services. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-status	<i>Boolean</i>	Whether to allow the reseller to view the server's status. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-stats	<i>Boolean</i>	Whether to allow the reseller to view server information. This parameter defaults to <code>undef</code> .	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

acl-quota	<i>Boolean</i>	<p>Whether to allow the reseller to modify quotas.</p> <p>This parameter defaults to <code>undefined</code>.</p> <div style="border: 1px solid red; padding: 5px; margin: 10px 0;"> <p>Warning : If you do not use resource limits, this ACL allows resellers to circumvent package limits for disk space.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1
acl-demo-setup	<i>Boolean</i>	<p>Whether to allow the reseller to enable demo mode for accounts.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1
acl-edit-account	<i>Boolean</i>	<p>Whether to allow the reseller to edit accounts.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	1

<p>acl-limit-bandwidth</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to modify bandwidth limits (quotas).</p> <p>This parameter defaults to <code>undefined</code>.</p> <div style="border: 1px solid red; padding: 5px; margin: 10px 0;"> <p>Warning : If you do not use resource limits, a value of 1 allows resellers to circumvent package limits for disk space.</p> </div>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	<p>1</p>
<p>acl-rearrange-accts</p>	<p><i>Boolean</i></p>	<p>Whether to allow the reseller to rearrange accounts.</p> <p>This parameter defaults to <code>undefined</code>.</p>	<ul style="list-style-type: none"> • Any value — Allow. • <code>undefined</code> — Do not allow. 	<p>1</p>

acl-track-email	<i>Boolean</i>	<p>Whether to allow the reseller to view reports about email message delivery attempts from their account.</p> <p>This parameter defaults to <code>undef</code>.</p> <div data-bbox="734 432 870 842" style="border: 1px solid orange; padding: 5px;"> <p>Note : We added this parameter in cPanel & WHM version 68.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1
acl-all	<i>Boolean</i>	<p>Whether to grant the reseller all ACL privileges.</p> <p>This parameter defaults to <code>undef</code>.</p> <div data-bbox="734 1081 870 1518" style="border: 1px solid red; padding: 5px;"> <p>Warning : A value of <code>1</code> grants root-level privileges to the reseller.</p> </div>	<ul style="list-style-type: none"> Any value — Allow. <code>undef</code> — Do not allow. 	1

Returns

Return	Type	Description	Possible values	Example
acl	<i>array</i>	An array of the reseller's privileges.	An array that contains the names of one or more privileges.	all