

UAPI Functions - SSL::generate_csr

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbackup

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_pa
ssword

Backup:: list_back
ups

Bandwidth

Bandwidth:: get_e
nabled_protocols

Bandwidth:: get_re
tention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_app
lications

Branding:: get_app
lication_informati
on

Branding:: get_ava
ilable_applications

Branding:: get_info
rmation_for_applic
ations

Description

This function generates a certificate signing request (CSR).

Note:

This function requires a valid key in the account's `ssl` directory. You can generate a key with UAPI's `SSL::generate_key` function.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/SSL/generate_csr?domains=example.com&pass=12345luggage&countryName=US&stateOrProvinceName=Texas&localityName=Houston&organizationName=Organization&organizationalUnitName=Department&emailAddress=user%40example.com&key_id=example_com_a74f7_9dddf_1446659822_eae1ff43c4ec1991e195877c55755eff&friendly_name=TestCSR
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI documentation](#).

▼ LiveAPI PHP Class

Function information

About this module

The `SSL` module manages certificates, certificate requests, and keys on your server.

Branding:: image

Branding:: include

Branding:: spritelist

▼ CacheBuster

CacheBuster:: read

CacheBuster:: update

▼ Chkserverd

Chkserverd:: get_exim_ports

Chkserverd:: get_exim_ports_ssl

▼ Chrome

Chrome:: get_dom

▼ Contactus

Contactus:: is_enabled

▼ cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

▼ cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

▼ DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

DAV:: is_dav_service_enabled

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Generate a
certificate signing
request for the
example.com site.
$SSL_generate_csr =
$cpanel->uapi(
    'SSL',
    'generate_csr',
    array(
        'key_id'
=>
'example_com_a74f7_9d
ddf_1446659822_eae1ff
43c4ec1991e195877c557
55eff',
        'pass'
=> '12345luggage',
        'domains'
=> 'example.com',

        'countryName'
=> 'US',

        'stateOrProvinceName'
=> 'Texas',

        'localityName'
=> 'Houston',

        'organizationName'
=> 'Organization',

        'organizationalUnitName' => 'Department',

        'emailAddress'
=>
'user@example.com',

        'friendly_name'
=> 'TestCert',
    )
);

```

About UAPI

UAPI accesses and modifies data for cPanel accounts.

Notes:

- The
- Ur
- int
- mi
- us
- 20
- or
- 20
-).
- 20
- or
- 20
-).

Find a function

SSL:
:ins
tall
_ssl
functi
on.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

- UAPI Modules -

Market — The Market module manages connections to cPanel Market providers.

- UAPI Functions -

Market::cancel_pending_ssl_certificate —

This function cancels an order and removes the polling for a pending certificate.

Email: browse_mailbox
Email: change_mx
Email: check_fastmail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_domain_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_held_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_opt
Email: get_auto_responder
Email: get_chase

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# Generate a  
certificate signing  
request for the  
example.com site.  
my $SSL_generate_csr  
= $cpliveapi->uapi(  
    'SSL',  
    'generate_csr', {  
        'key_id'  
=>  
    'example_com_a74f7_9d  
ddf_1446659822_eae1ff  
43c4ec1991e195877c557  
55eff',  
        'pass'  
=> '12345luggage',  
        'domains'  
=> 'example.com',  
  
    'countryName'  
=> 'US',  
  
    'stateOrProvinceName'  
=> 'Texas',  
  
    'localityName'  
=> 'Houston',  
  
    'organizationName'  
=> 'Organization',  
  
    'organizationalUnitName'  
=> 'Department',  
  
    'emailAddress'  
=>  
    'user@example.com',  
  
    'friendly_name'  
=> 'TestCert',  
    }  
);
```

- UAPI Functions - Market:create_shopping_cart — This function creates a shopping cart with which the system sends an order to the cPanel Store.
- UAPI Functions - Market:get_all_products — This function lists all products available through all enabled cPanel Market providers.

ts

Email: [get_client_settings](#)

Email: [get_default_email_quota](#)

Email: [get_default_email_quota_mib](#)

Email: [get_disk_usage](#)

Email: [get_filter](#)

Email: [get_held_message_count](#)

Email: [get_mailbox_autocreate](#)

Email: [get_mailman_delegates](#)

Email: [get_main_account_disk_usage](#)

Email: [get_main_account_disk_usage_bytes](#)

Email: [get_max_email_quota](#)

Email: [get_max_email_quota_mib](#)

Email: [get_pop_quota](#)

Email: [get_spam_settings](#)

Email: [get_webmail_settings](#)

Email: [has_delegated_mailman_lists](#)

Email: [has_plaintext_authentication](#)

Email: [hold_outgoing](#)

Email: [is_integer](#)

Email: [list_autoresponders](#)

Email: [list_default_address](#)

Email: [list_domain_forwarders](#)

Email: [list_filters](#)

Email: [list_filters_backups](#)

Email: [list_forwarders](#)

Email: [list_forward](#)

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ [cPanel Template Toolkit](#)

```
<!-- Generate a certificate signing request for the example.com site.-->
[% data = execute(
  'SSL',
  'generate_csr', {
    pass =>
      '12345luggage',
    friendly_name =>
      'TestCSR', domains =>
      'example.com',
    countryName => 'US',
    stateOrProvinceName => 'Texas',
    localityName =>
      'Houston',
    organizationName =>
      'Organization',
    organizationalUnitName => 'Department',
    emailAddress =>
      'user@example.com',
    key_id =>
      'example_com_a74f7_9d
      ddf_1446659822_eae1ff
      43c4ec1991e195877c557
      55eff', friendly_name
      => 'TestCert', } ); %]
[% FOREACH q = data
  %]
    <p>
      [% q %]
    </p>
[% END %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

ers_backups

Email: list_lists

Email: list_mail_domains

Email: list_mx

Email: list_pops

Email: list_pops_with_disk

Email: list_system_filter_info

Email: passwd_list

Email: passwd_pop

Email: release_outgoing

Email: remove_mailman_delegates

Email: reorder_filters

Email: set_always_accept

Email: set_default_address

Email: set_list_privacy_options

Email: stats_db_status

Email: store_filter

Email: suspend_incoming

Email: suspend_login

Email: suspend_outgoing

Email: trace_filter

Email: unsuspend_incoming

Email: unsuspend_login

Email: unsuspend_outgoing

Email: verify_password

▼ EmailAuth

EmailAuth: disable_dkim

EmailAuth: enable_dkim

EmailAuth: ensure_dkim_keys_exist

▼ Command Line

```
uapi --user=username
SSL generate_csr
domains=example.com
pass=12345luggage
countryName=US
stateOrProvinceName=Texas
localityName=Houston
organizationName=Organization
organizationalUnitName=Department
emailAddress=user%40example.com
key_id=example_com_a74f7_9dddf_1446659822_eae1ff43c4ec1991e195877c55755eff
friendly_name=TestCSR
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

▼ Output (JSON)

```
{
  "data": {
    "commonName":
    "example.com",
    "created":
    "1366386445",
    "domains": [
      "example.com"
    ],
  },
}
```

EmailAuth:: fetch_dkim_private_keys

EmailAuth:: install_dkim_private_keys

EmailAuth:: install_spf_records

EmailAuth:: validate_current_dkims

EmailAuth:: validate_current_ptrs

EmailAuth:: validate_current_spfs

ExternalAuthentication

ExternalAuthentication:: add_authn_link

ExternalAuthentication:: configured_modules

ExternalAuthentication:: get_authn_links

ExternalAuthentication:: has_external_auth_modules_configured

ExternalAuthentication:: remove_authn_link

Features

Features:: get_feature_metadata

Features:: has_feature

Features:: list_features

Fileman

Fileman:: autocompletedir

Fileman:: empty_trash

Fileman:: get_file_content

Fileman:: get_file_information

Fileman:: list_files

Fileman:: save_file_content

Fileman:: transcode

Fileman:: upload_files

```
"friendly_name" :
"example.com" ,
  "id" :
"example_com_bbe7e_16
e2d_a626d1b34b62cefb1
3076a25b6831ca5" ,
  "modulus" : "THE
MODULUS" ,
  "text" :
"-----BEGIN
CERTIFICATE
REQUEST-----
MIIC3TCCAcUCAQAwgZcxF
DASBgNVBAMMC2V4YW1wbG
UuY29tMRYwFAYDVQQLEDA1
E
b2N1bWVudGF0aW9uMQswC
QYDVQQGEwJVUzEiMCAGCS
qGSIB3DQEJARYTbGF1cmV
u
Y2VAY3BhbmVsLm5ldDEUM
BIGA1UECgwLY1BhbmVsIE
luYy4xDjAMBgNVBAGMBVR
l
eGFzMRAwDgYDVQQHDAdIb
3VzdG9uMIIBIjANBgkqhK
iG9w0BAQEFAAOCAQ8AMI
B
CgKCAQEAp092NvpqyT7mg
2qDqZW1XetQGeo217o9r7
AONaTrNsMgbL/d31rQzP
C
D65SPxJ/NSpovMi48tbue
3A5W6+r2CN62oFk/d34N2
swN1w11NTLzOfTPQgGnBe
0
CRdqNonx6818Cwj+auRMG
akqxtaESOfx0T87Ngr/1C
IqUbTzU0LembWh+1VI5Dj
Y
2CRmRWKkSAAu7X/OJN7cf
cPh7ReZc9Ha6VmzNxbutB
DRcnCJVOAGMsv2Cg4mQZh
g
yMC8KF1r/ktHneDdGJdyp
drmdr0qkqzMwTaYIb6M/9
3Yp+bswGH4oyqa4GYeTpR
u
20OCeydxONOnYRZWfL0Sn
L2Gnvnd3wIDAQABoAAwDQ
YJKoZIhvcNAQEFBQADggE
B
AF1olzJbcviWcdZUv+PJ7
```

▼ Ftp

- Ftp:: add_ftp
- Ftp:: allows_anonymous_ftp
- Ftp:: allows_anonymous_ftp_incoming
- Ftp:: delete_ftp
- Ftp:: ftp_exists
- Ftp:: get_ftp_daemon_info
- Ftp:: get_port
- Ftp:: get_quota
- Ftp:: get_welcome_message
- Ftp:: kill_session
- Ftp:: list_ftp
- Ftp:: list_ftp_with_disk
- Ftp:: list_sessions
- Ftp:: passwd
- Ftp:: server_name
- Ftp:: set_anonymous_ftp
- Ftp:: set_anonymous_ftp_incoming
- Ftp:: set_homedir
- Ftp:: set_quota
- Ftp:: set_welcome_message

▼ Integration

- Integration:: fetch_url

▼ KnownHosts

- KnownHosts:: create
- KnownHosts:: delete
- KnownHosts:: update
- KnownHosts:: verify

▼ LangPHP

- LangPHP:: php_get_domain_handler
- LangPHP:: php_get_impacted_domains
- LangPHP:: php_get_installed_version

```
G8cAqFAxa8a3W2a0Y1U0B
aMrpDfu0HpQgOt062rr+i
+
hkrIReuk7Isyl6GoZkXl7
KhQ1Vo9aW8a8Ur7+0RGDb
xRlK9jJWnvSFn6cMMqRSf
A
DXpptxhqBFZJIZMc3pPX9
Jqycuu8bxelVUKeSMe3Jx
c1lZXEXX47FeRZxvd+WXF
9
4Xu4KZXHdzb5tB6jPhzIa
N0/3d92N/KhvCcnw3YC2f
EGDkpOlZaoa7072+aq5K3
b
MlhtFv9deAHqIHefV4liO
rxUCIKIhdPIjvAm774lDH
LzPpJVrshO/NpA74LEkny
5
FMwKKx+6Jgx1HSWucn5kW
ek=
-----END CERTIFICATE
REQUEST-----\n"
},
"errors": null,
"messages": [
    "Certificate
    Signing Request
    generated!"
```


s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_get_user_basic_directives

LangPHP:: php_get_user_content

LangPHP:: php_get_user_paths

LangPHP:: php_set_user_basic_directives

LangPHP:: php_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

```
],
  "status": 1
}
```

Note:
Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
domains	string	Required The domain(s) for which to generate the certificate.	A valid string. Note : If there is more than one domain, this parameter must be a comma-separated list.	example.com
countryName	string	Required The two-letter country code.	A valid two-letter ISO-3166 country code.	US
stateOrProvinceName	string	Required The state's or locality's full name.	A valid string.	Texas
localityName	string	Required The certificate's city name.	A valid string.	Houston
organizationName	string	Required The certificate's organization.	A valid string.	Organization

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info


▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains


ModSecurity:: enable_domains

organizationUnitName	string	The certificate's organizational unit or department name. This parameter defaults to an empty string.	A valid string.	Department
emailAddress	string	A valid email address to associate with the certificate. This parameter defaults to an empty string.	A valid email address.	user@example.com
key_id	string	Required The key's ID.	A valid string.	▼ Click to view... 
friendly_name	string	A friendly name for the new certificate. This parameter defaults to the domain name for which you generated the certificate.	A valid string.	TestCert

Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

- ModSecurity:: has_modsecurity_installed
- ModSecurity:: list_domains
- ▼ Mysql
 - Mysql:: add_host
 - Mysql:: add_host_note
 - Mysql:: check_database
 - Mysql:: create_database
 - Mysql:: create_user
 - Mysql:: delete_database
 - Mysql:: delete_host
 - Mysql:: delete_user
 - Mysql:: get_host_notes
 - Mysql:: get_privileges_on_database
 - Mysql:: get_restrictions
 - Mysql:: get_server_information
 - Mysql:: locate_server
 - Mysql:: rename_database
 - Mysql:: rename_user
 - Mysql:: repair_database
 - Mysql:: revoke_access_to_database
 - Mysql:: set_password
 - Mysql:: set_privileges_on_database
- ▼ Notifications
 - Notifications:: get_notifications_count
- ▼ NVData
 - NVData:: get
 - NVData:: set
- ▼ Parser
 - Parser:: firstfile_relative_uri

modulus	string	The CSR's modulus.	A valid string.	Click to view... a74f7636fa 6ac93ee683 6a83a995b5 5deb5019ea 36d7ba3daf b00e38d693 acdb0c81b2 ff777d6b43 3a420fae52 3f127f352a 68bcc8b8f2 d6ee7b7039 5bafabd823 7ada8164fd ddf8376b30 375c35d4d4 cbcce7d33d 08069c17b4 09176a3689 f1ebc97c0b 08fe6ae44c 19a92ac6d6 8448e7f1d1 3f3b360aff d4222a51b4 f35342de99 b5a1fb5548 e438f2d824 664562a448 002eed7fce 24dedc7dc3 e1ed179973 d1dae959b3 3716eeb410 d172708954 e00632cbf6 0a0e264198 60c8c0bc28 5d6bfe4b47 9de0dd1897 72a5dae676 bd2a92accc c1369821be 8cffddd8a7 e6ecc061f8 a32a9ae066 1e4e946ed8 e3827b2771 38d3a76116 567cbd129c bd869ef9ddf df
created	string	When the CSR was created.	A valid date in Unix time format.	1366386445
domains	string	The domains that the CSR covers.	A valid domain or domains.	example.com
commonName	string	The name that issued the CSR.	Usually, a valid domain.	example.com
friendly_name	string	The CSR's friendly name.	A valid string.	TestCSR
id	string	The CSR's ID.	A valid string.	Click to view... 
text	string	The CSR's text.	A valid CSR.	Click to view... -----BEGIN CERTIFICATE REQUEST----- -- MIIC3TCCAc UCAQAwwZcx FDASBgNVBA MMC2V4YW1w bGUuY29tMR YwFAYDVQQL DAIE b2N1bWVudG F0aW9uMQsw

- PassengerApps:: isable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- PasswdStrength:: get_required_strength
- Personalization::set
 - Personalization::get
- Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- Pushbullet:: send_test_message
- Quota:: get_quota_info

CQYDVQQGEw
 JVUzEiMCAg
 CSqGSIb3DQ
 EJARYTbGF1
 cmVu
 Y2VAY3Bhbm
 VsLm5ldDEU
 MBIGAlUECg
 wLY1BhbmVs
 IEluYy4xDj
 AMBgNVBAgM
 BVRL
 eGFzMRAwDg
 YDVQOHdAdI
 b3VzdG9uMI
 IBIjANBgkq
 hkiG9w0BAQ
 EFAAOCAQ8A
 MIIB
 CgKCAQEAp0
 92NvpqyT7m
 g2qdqZWLXe
 tQGeo217o9
 r7A0ONaTrN
 sMgbL/d31r
 Qzpc
 D65SPxJ/NS
 povMi48tbu
 e3A5W6+r2C
 N62oFk/d34
 N2swN1w1LN
 TLzOfTPQgG
 nBe0
 CRdqNonx68
 l8Cwj+auRM
 GakqxtaESO
 fx0T87Ngr/
 lCIqUbTzU0
 LembWh+1VI
 5Djy
 2CRmRWKkSA
 Au7X/QJN7c
 fcPh7ReZc9
 Ha6VmzNxbu
 tBDRcnCJVO
 AGMsv2Cg4m
 QZhg
 yMC8KF1r/k
 tHneDdGJdy
 pdrmdr0qkq
 zMwTaYIb6M
 /93Yp+bswG
 H4oyqa4GYe
 TpRu
 200CeydxON
 OnYRZWfL0S
 nL2Gnvnd3w
 IDAQABoAAw
 DQYJKoZIhv
 cNAQEFBQAD
 ggEB
 AF1o1zJbcv
 iWcdZUv+PJ
 7G8cAqFAxa
 8a3W2a0Y1U
 0BaMrpDfu0
 HpQgOtO62r
 r+i+
 hkrIReuk7I
 sy16GoZkXl
 7KhQ1Vo9aW
 8a8Ur7+0RG
 DbxR1K9jJW
 nvSFn6cMMq
 RSfA
 DXpptxhqBF
 ZJIZMc3pPX
 9Jqycuu8bx
 eIvUKeSMe3
 Jxc11ZXEXX
 47FeRZxvd+
 WXF9
 4Xu4KZXhdz
 b5tB6jPhzI
 aN0/3d92N/
 KhvCcnw3YC
 2fEGDkp0LZ
 aoa7072+aq
 5K3b
 M1htFv9deA

- Resellers:: list_accounts
- ResourceUsage:: get_usages
- Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- Session:: create_temp_user
- SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- SpamAssassin:: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- SSH:: get_port
- SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL:: disable_mail_sni

```

HqIHeFV41i
OrxUCIKIhd
PIjvAm7741
DHLzPpJVrs
hO/NpA74LE
kny5
FMwKKx+6Jg
x1HSWucn5k
Wek=
-----END
CERTIFICAT

```

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

				E REQUEST--- --
--	--	--	--	-----------------------

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start