

WHM API 1 Functions - listaccts

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function lists the accounts on the server.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/listaccts?api.version=1&search=username&searchtype=user
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/listaccts?api.version=1&search=username&searchtype=user
```

Command Line

```
whmapil listaccts search=username searchtype=user
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

Output (JSON)

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Yc
- mi
- us
- 20
- or
- 20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

```
{
  "data": {
    "acct": [
      {
        "mailbox_format": "mailbox",
        "inodesused": "1",
        "inodeslimit": "unlimited",
        "maxaddons": "1",
        "ip": "192.168.0.20",
        "ipv6": ["0101:ca75:0101:ca75:0101:ca75:0101:ca77"],
        "outgoing_mail_suspended": 0,
        "outgoing_mail_hold": 0,
        "min_defer_fail_to_trigger_protection": 5,
        "legacy_backup": 0,
        "diskused": "0M",
        "maxftp": "2",
        "startdate": "13 Jul 08 14:33",
        "max_defer_fail_percentage": "10",
        "disklimit": "100M",
        "is_locked": "0",
        "suspendtime": null,
        "email": "",
        "domain": "example.com",
        "unix_startdate": 1373312011,
        "user":
```

Find a function

- WHM API 0 Functions - setresellernameservers - This function assigns nameservers to a reseller's account.

_id
 verify_new_username
 Addon Domains
 convert_addon_fetch_conversion_details
 convert_addon_fetch_domain_details
 convert_addon_get_conversion_status
 convert_addon_initiate_conversion
 convert_addon_list_addon_domains
 convert_addon_list_conversions
 Authentication
 api_token_create
 api_token_list
 api_token_revoke
 api_token_update
 disable_authentication_provider
 disable_failing_authentication_providers
 enable_authentication_provider
 get_available_authentication_providers
 get_login_url
 get_provider_client_configurations
 get_provider_configuration_fields
 get_provider_display_co

```

"example",
  "plan":
    "plan9",
      "shell":
        "\/bin\/bash",
          "maxpop":
            "20",

            "max_emailacct_quota"
              : "unlimited",
                "backup": 0,
                  "temporary":
                    0,
                      "theme":
                        "paper_lantern",
                          "owner":
                            "root",

                            "max_email_per_hour":
                              "100",

                              "suspendreason": "not
suspended",
                                "maxlst":
                                  "5",
                                    "suspended":
                                      0,
                                        "maxsql":
                                          "1",
                                            "maxparked":
                                              "1",
                                                "partition":
                                                  "home",
                                                    "maxsub": "5"
                                                    },
                                                ],
                                                },
                                                "metadata": {
                                                  "version": 1,
                                                  "reason": "OK",
                                                  "result": 1,
                                                  "command":
  
```

- WHM API 1 Sections - Accounts — Account functions allow you to manage cPanel accounts, WHM accounts, and their settings.
- WHM API 1 Functions - accounts summary — This function retrieves a summary of a user's account.

```

nfigurations
get_users_authn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer
twofactorauth_get_user_configs
twofactorauth_policy_status
twofactorauth_remove_user_config
twofactorauth_set_issuer
twofactorauth_set_tfa_config
unlink_user_authn_provider
validate_login_token

```

▼ Backups

```

backup_config_get
backup_config_set
backup_date_list
backup_destination_add
backup_destination_delete

```

```

"listaccts"
}
}

```

▼ Output (XML)

```

<result>
  <data>
    <acct>

    <mailbox_format>mdbox
</mailbox_format>

    <inodesused>1</inodes
used>

    <inodeslimit>unlimite
d</inodeslimit>

    <maxaddons>1</maxaddo
ns>

    <ip>192.168.0.20</ip>

    <ipv6>0101:ca75:0101:
ca75:0101:ca75:0101:c
a75</ipv6>

    <outgoing_mail_suspen
ded>0</outgoing_mail_
suspended>

    <outgoing_mail_hold>0
</outgoing_mail_hold>
    <min_defer_fail_to_tr
igger_protection>5</m
in_defer_fail_to_trig
ger_protection>

    <legacy_backup>0</leg
acy_backup>

    <diskused>0M</diskuse
d>

    <maxftp>2</maxftp>

    <startdate>13 Jul 08
14:33</startdate>

    <max_defer_fail_perce

```

- WHM API 1 Functions - domain data - This function retrieves domain data.

backup_destination_get	<max_defer_fail_percentage>10</max_defer_fail_percentage>
backup_destination_list	<disklimit>100M</disklimit>
backup_destination_set	<is_locked>0</is_locked>
backup_destination_validate	<suspendtime/> <email/>
backup_get_transport_status	<domain>example.com</domain>
backup_list_transported	<unix_startdate>1373312011</unix_startdate>
backup_set_list	<user>example</user>
backup_set_list_combined	<plan>plan9</plan>
backup_skip_users_all	<shell>/bin/bash</shell>
backup_skip_users_all_status	<maxpop>20</maxpop>
backup_user_list	<max_emailacct_quota>unlimited</max_emailacct_quota>
convert_and_migrate_from_legacy_config	<backup>0</backup>
get_users_with_backup_metadata	<theme>paper_lantern</theme>
list_cparchive_files	<owner>root</owner>
start_background_package	<max_email_per_hour>100</max_email_per_hour>
toggle_user_backup_state	<suspendreason>not_suspended</suspendreason>
▼ cPHulk	<maxlst>5</maxlst>
cphulk_statuses	<suspended>0</suspended>
create_cphulk_record	<temporary>0</temporary>
delete_cphulk_record	
disable_cphulk	
enable_cphulk	
flush_cphulk_login_history	

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

get_cphulk_
brutes

get_cphulk_
excessive_b
rutes

get_cphulk_
failed_logins

get_cphulk_
user_brutes

load_cphulk
_config

read_cphulk
_records

save_cphulk
_config

set_cphulk_
config_key

▼ Databases

background
_mysql_upg
rade_status

current_mys
ql_version

installable_
mysql_versi
ons

latest_availa
ble_mysql_v
ersion

list_databas
e_users

list_databas
es

list_mysql_d
atabases_a
nd_users

remote_mys
ql_create_pr
ofile

remote_mys
ql_create_pr
ofile_via_ss
h

remote_mys
ql_delete_pr
ofile

remote_mys
ql_initiate_p
rofile_activat

```
ry>  
  
<maxsql>1</maxsql>  
  
<maxparked>1</maxpark  
ed>  
  
<partition>home</part  
ition>  
  
<maxsub>5</maxsub>  
  </acct>  
  </data>  
  <metadata>  
  
<version>1</version>  
  
<reason>OK</reason>  
  
<result>1</result>  
  
<command>listaccts</c
```

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

```
ommand>
  </metadata>
</result>
```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
searchtype	string	The account information to query. If you do not specify a value for both the searchtype and search parameters, the function returns all of the server's accounts.	<ul style="list-style-type: none"> domain — Match domains against the search regular expression . owner — Match the WHM user who owns the account against the search regular expression . user — Match usernames against the search regular expression . ip — Match IP addresses against the search regular expression . package — Match hosting plans (packages) against the search regular expression . 	domain

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

search	string	A Perl Compatible Regular Expression (PCRE) that filters the results. The system matches the PCRE against the searchtype parameter's specified type. If you do not specify a value for both the searchtype and search parameters, the function returns all of the server's accounts.	A valid PCRE.	username
searchmethod	string	The function's search method.	<ul style="list-style-type: none"> exact — The matched value and the search value must be identical. regex — The matched value must contain the search value. 	exact
want	string	The returns to include in the output for each account. If you do not specify a value, the function's output includes all of its returns.	A comma-separated list of one or more of the function's returns.	domain, diskused

Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

ers_config
 cpgreylist_save_common_mail_providers_config
 cpgreylist_status
 cpgreylist_trust_entries_for_common_mail_provider
 cpgreylist_untrust_entries_for_common_mail_provider
 create_cpgreylist_trusted_host
 delete_cpgreylist_trusted_host
 disable_cpgreylist
 enable_cpgreylist
 load_cpgreylist_config
 read_cpgreylist_deferred_entries
 read_cpgreylist_trusted_host
 save_cpgreylist_config
 Integration
 batch
 cpanel
 create_integration_group
 create_integration_link
 get_integration_link_user_config
 list_integration_groups
 list_integration_links
 remove_integration_group
 remove_inte

acct	<i>array of hashes</i>	An array of hashes of account data.	Each hash includes the backup, disklimit, diskused, domain, email, ip, is_locked, legacy_backup, max_defer_fail_percentage, max_emailacct_quota, max_email_per_hour, max_addons, maxftp, maxlst, maxparked, maxpop, maxsql, maxsub, min_defer_fail_to_trigger_protection, outgoing_mail_suspended, outgoing_mail_hold, owner, partition, plan, shell, startdate, suspended, suspendreason, suspendtime, theme, unix_startdate, and user returns.	
backup	<i>Boolean</i>	Whether backups are enabled. The function returns this value in the acct array.	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	0
disklimit	<i>string</i>	The account's disk space quota. The function returns this value in the acct array.	<ul style="list-style-type: none"> unlimited A maximum amount of disk space, in Megabytes (MB). 	unlimited
diskused	<i>string</i>	The account's current disk space usage. The function returns this value in the acct array.	<p>An integer that represents an amount of disk space, in Megabytes (MB).</p> <p>For example, 14M represents 14 MB of disk space.</p>	14M
domain	<i>string</i>	The account's main domain. The function returns this value in the acct array.	A valid domainname on the account.	example.com

gration_link
 update_inte
 gration_link
 _token

▼ IP Addresses

addips

delip

get_public_i
 p

get_shared_
 ip

ipv6_disable
 _account

ipv6_enable
 _account

ipv6_range_
 add

ipv6_range_
 edit

ipv6_range_
 list

ipv6_range_
 remove

ipv6_range_
 usage

listips

nat_checkip

nat_set_pub
 lic_ip

setsiteip

▼ Mail

disable_dki
 m

disable_mail
 _sni

emailtrack_s
 earch

emailtrack_s
 tats

emailtrack_u
 ser_stats

enable_dkim

enable_mail
 _sni

ensure_dki
 m_keys_exi
 st

exim_config
 uration_che
 ck

expunge_m

email	string	The account's contact email address. The function returns this value in the acc t array.	A valid email address.	username@example.com
inodes used	integer	The number of files that the account owns. Note : We introduced this return in cPanel & WHM version 64. The function returns this value in the acc t array.	<ul style="list-style-type: none"> A positive integer. 	1
inodes limit	integer	The limit on the number of files that the account owns. Note : We introduced this return in cPanel & WHM version 64. This function returns this value in the acc t array.	<ul style="list-style-type: none"> unlimited A positive integer. 	unlimited
ip	string	The account's main domain's IP address. The function returns this value in the acc t array.	A valid IP address.	192.168.0.128

ailbox_messages
 expunge_messages_for_mailbox_guid
 fetch_dkim_private_keys
 fetch_mail_queue
 generate_mobileconfig
 get_mailbox_status
 get_mailbox_status_list
 get_unique_recipient_count_per_sender_for_user
 get_unique_sender_recipient_count_per_user
 get_user_email_forward_destination
 hold_outgoing_email
 install_dkim_private_keys
 install_spf_records
 is_sni_supported
 list_pops_for
 mail_sni_status
 rebuild_mail_sni_config
 release_outgoing_email
 save_spamd_config
 set_user_email_forward_destination
 suspend_outgoing_email
 unsuspend_outgoing_email

ipv6	array	<p>The account's main domain's IPv6 address</p> <p>The function returns this value in the <code>acct</code> array.</p>	<p>A valid IPv6 address.</p>	<p>0101:ca75:0101:ca75:0101:ca75:0101:ca77</p>
is_locked	Boolean	<p>Whether the account is currently locked.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> 1 — The account is locked. 0 — The account is not locked. 	0
legacy_backup	Boolean	<p>Whether legacy backups are enabled.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> 1 — Enabled. 0 — Disabled. 	0
mailbox_format	string	<p>The type of mailbox the account uses.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> mdbox maildir 	mdbox
max_deferred_email_percentage	string	<p>The percentage of failed or deferred email messages that the account can send per hour before outgoing mail is rate-limited.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 11.32.</p> </div> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> unlimited An integer that represents a percentage of messages. 	unlimited

<p>validate_current_installeg validate_current_dkims validate_current_ptrs validate_current_spfs validate_exim_configuration_syntax</p> <p>▼ Market</p> <p>disable_market_provider enable_market_provider get_adjusted_market_providers_products</p>	<p>max_email_quota</p>	<p>integer</p>	<p>The maximum size that the account can define when it creates an email account.</p> <div data-bbox="734 296 873 703" style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 70.</p> </div> <p>The function returns this value in the acct array.</p>	<ul style="list-style-type: none"> • unlimited • A positive integer that represents the allowable maximum size of an email account, in Megabytes (MB). 	<p>unlimited</p>
<p>get_market_providers_commission_config get_market_providers_list get_market_providers_product_metadata get_market_providers_products set_market_product_attribute set_market_provider_commission_id</p> <p>▼ ModSecurity™</p> <p>modsec_add_rule modsec_add_vendor modsec_assemble_config_text modsec_batch_settings modsec_check_rule modsec_clone_rule</p>	<p>max_email_per_hour</p>	<p>string</p>	<p>The maximum number of emails that the account can send in one hour.</p> <div data-bbox="734 995 873 1423" style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 11.32.</p> </div> <p>The function returns this value in the acct array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of sent emails. 	<p>unlimited</p>
	<p>maxaddons</p>	<p>string</p>	<p>The account's maximum number of addon domains.</p> <p>The function returns this value in the acct array.</p>	<ul style="list-style-type: none"> • unlimited • *unknown* — The account cannot use addon domains. • An integer that represents a number of addon domains. 	<p>unlimited</p>

modsec_deploy_all_rule_changes
 modsec_deploy_rule_changes
 modsec_deploy_settings_changes
 modsec_disable_rule
 modsec_disable_vendor
 modsec_disable_vendor_configs
 modsec_disable_vendor_updates
 modsec_discard_all_rule_changes
 modsec_discard_rule_changes
 modsec_edit_rule
 modsec_enable_vendor
 modsec_enable_vendor_configs
 modsec_enable_vendor_updates
 modsec_get_config_text
 modsec_get_configs
 modsec_get_configs_with_changes_pending
 modsec_get_log
 modsec_get_rules
 modsec_get_settings
 modsec_get_vendors
 modsec_is_installed
 modsec_make_config_active

maxftp	string	<p>The account's maximum number of FTP accounts.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of FTP accounts. 	unlimited
maxlst	string	<p>The account's maximum number of mailing lists.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of mailing lists. 	unlimited
maxparked	string	<p>The account's maximum number of parked domains (aliases).</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • *unknown* — The account cannot use parked domains. • An integer that represents a number of parked domains. 	unlimited
maxpop	string	<p>The account's maximum number of email addresses.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of email accounts. 	unlimited
maxsql	string	<p>The account's maximum number of each available type of SQL database.</p> <p>For example, if you set this value to 5 and the system administrator allows MySQL® and PostgreSQL® databases, users can create up to five MySQL databases and up to five PostgreSQL databases.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of SQL databases. 	unlimited

- modsec_make_config_active
- modsec_preview_vendor
- modsec_remove_rule
- modsec_remove_setting
- modsec_remove_vendor
- modsec_report_rule
- modsec_set_config_text
- modsec_set_setting
- modsec_uninstall_rule
- modsec_update_vendor
- ▼ Packages
- _getpkgextensionform
- add_override_features_for_user
- addpkg
- addpkgext
- changepackage
- create_featurelist
- delete_featurelist
- delpkgext
- editpkg
- get_available_applications
- get_available_featurelists
- get_feature_metadata
- get_feature_names
- get_featurelist_data
- get_featureli

	maxsub <i>string</i>	<p>The account's maximum number of subdomains.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • *unknown* — The account cannot use subdomains. • An integer that represents a number of subdomains. 	unlimited
	min_defer_fail_to_trigger_protection <i>string</i>	<p>The minimum number of failed or deferred messages that the account can send before outgoing mail is subject to rate-limiting.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 11.32.</p> </div> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • unlimited • An integer that represents a number of failed or deferred messages. 	5

<p>sts</p> <p>get_users_features_settings</p> <p>getfeaturelist</p> <p>getpkginfo</p> <p>killpkg</p> <p>listpkgs</p> <p>manage_features</p> <p>matchpkgs</p> <p>read_featurelist</p> <p>remove_override_features_for_user</p> <p>update_featurelist</p> <p>verify_user_has_feature</p> <p>▼ PHP</p> <p>convert_all_domains_to_fpm</p> <p>get_fpm_count_and_utilization</p> <p>is_conversion_in_progress</p> <p>php_get_default_accounts_to_fpm</p> <p>php_get_handlers</p> <p>php_get_impacted_domains</p> <p>php_get_installed_versions</p> <p>php_get_old_fpm_flag</p> <p>php_get_system_default_version</p> <p>php_get_versions_by_version</p> <p>php_get_versions</p> <p>php_ini_get_content</p>	<p>outgoing_mail_suspended</p>	<p><i>Boolean</i></p>	<p>Whether to suspend outgoing email from the account's users and force failure of any of their mail currently in the mail queue.</p> <p>Note : If mail for a cPanel user's account is suspended, the system will reject their email before the system puts it in the mail server queue.</p> <p>The function returns this value in the <code>acct</code> array.</p> <p>Note : We introduced this return in cPanel & WHM version 56.</p>	<ul style="list-style-type: none"> • 1 — Suspend and forcefailure of outgoing email. • 0 — Do not suspend and forcefailure of outgoing email. 	<p>0</p>
--	--------------------------------	-----------------------	---	---	----------

[php_ini_get_directives](#)
[php_ini_set_content](#)
[php_ini_set_directives](#)
[php_set_default_accounts_to_fpm](#)
[php_set_handler](#)
[php_set_old_fpm_flag](#)
[php_set_session_save_path](#)
[php_set_system_default_version](#)
[php_set_vhost_versions](#)

▼ Resellers

[acctcounts](#)
[get_public_contact](#)
[getresellers](#)
[listacks](#)
[listresellers](#)
[resellerstats](#)
[saveacllist](#)
[set_public_contact](#)
[setacks](#)
[setresellers](#)
[setresellerslimits](#)
[setresellersmainip](#)
[setresellersnameservers](#)
[setresellerspackagelimit](#)
[setupreseller](#)
[suspendreseller](#)
[terminatereseller](#)
[unsetupreseller](#)

	outgoing_mail_hold	<i>Boolean</i>	<p>Whether to retain outgoing mail in the mail queue for the account's users.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 56.</p> </div> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> 1 — Hold outgoing email in the mail queue. 0 — Do not hold outgoing mail in the mail queue. 	
	owner	<i>string</i>	<p>The account's owner.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> root A reseller account's username. 	root
	partition	<i>string</i>	<p>The partition that contains the account's home directory.</p> <p>The function returns this value in the <code>acct</code> array.</p>	The name of a partition on the server.	home
	plan	<i>string</i>	<p>The account's hosting package.</p> <p>The function returns this value in the <code>acct</code> array.</p>	The name of a package on the server.	packagename
	shell	<i>string</i>	<p>The account's shell.</p> <p>The function returns this value in the <code>acct</code> array.</p>	The absolute path to a shell location on the server.	/bin/bash

ller
 unsuspendreseller
 RPM
 delete_rpm_version
 edit_rpm_version
 get_rpm_version_data
 install_rpm_plugin
 list_rpms
 package_manager_fixcache
 package_manager_get_build_log
 package_manager_get_package_info
 package_manager_is_performing_actions
 package_manager_list_packages
 package_manager_resolve_actions
 package_manager_submit_actions
 package_manager_upgrade
 uninstall_rpm_plugin
 Script Hooks
 delete_hook
 edit_hook
 list_hooks
 reorder_hooks
 Security
 accesshash
 authorizesshkey
 check_remote_ssh_connection

startdate	string	<p>The account creation date.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<p>The date in YY-Mon-DD HH-mm human-readable format, where:</p> <ul style="list-style-type: none"> YY represents the year. Mon represents the month. DD represents the date. HH represents the hour. mm represents the minute. 	13 May 22 16:03
suspended	Boolean	<p>Whether the account is currently suspended.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> 1 — Suspended. 0 — Not suspended. 	0
suspensionreason	string	<p>The reason for account suspension, if one was provided.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> null — The account is not currently suspended. A blank value, if the suspender did not provide a reason. A message that explains the suspension. 	not suspended
suspensiontime	string	<p>The time of suspension.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> null — The account is not currently suspended. The time at which the account became suspended. 	null
theme	string	<p>The account's cPanel interface theme.</p> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> paper_lantern Another valid theme on the server. 	paper_lantern

convertopensshputty
 deletesshkey
 fetch_security_advice
 generatesshkeypair
 importsshkey
 listsshkeys
 Server
 Administration
 add_configclusterserver
 configurebackgroundprocesskiller
 configurereverse
 cors_proxy_get
 create_user_session
 delete_configclusterserver
 enable_monitor_all_enabled_services
 get_all_contact_importances
 get_appconfig_application_list
 get_application_contact_event_importance
 get_application_contact_importance
 get_available_profiles
 get_current_profile
 get_password_strength
 get_remote_access_has
 get_service_config

temporary	<i>Boolean</i>	<p>Whether the Customer Support Ticket process created this user for temporary access to the system.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : We introduced this return in cPanel & WHM version 64.</p> </div> <p>The function returns this value in the <code>acct</code> array.</p>	<ul style="list-style-type: none"> • 1 — Temporary user. • 0 — Regular user. 	0
unix_startdate	<i>string</i>	<p>The account creation date.</p> <p>The function returns this value in the <code>acct</code> array.</p>	The account creation date and time, in Unix time format.	1369256589
user	<i>string</i>	<p>The account username.</p> <p>The function returns this value in the <code>acct</code> array.</p>	A cPanel account or reseller username on the server.	username

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyctl

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_implemen
tation

set_applicati
on_contact_
importance

set_primary_
servername

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile_
activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar_
access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version