

# WHM API 1 Functions - convert\_addon\_get\_conversion\_status

## Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

## Description

This function returns the status of the convert addon domain to account process for specified conversion jobs. For more detailed information about the conversion status of all jobs, use the `convert_addon_fetch_conversion_details` function.

### Important:

In cPanel & WHM version 76 and later, when you disable the `WebServerRole`, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/convert_addon_get_conversion_status?api.version=1&job_id=1
```

### XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/convert_addon_get_conversion_status?api.version=1&job_id=1
```

- Account Restoration
- restore\_modules\_summary
- restore\_queue\_activate
- restore\_queue\_add\_task
- restore\_queue\_clear\_all\_completed\_tasks
- restore\_queue\_clear\_all\_failed\_tasks
- restore\_queue\_clear\_all\_pending\_tasks
- restore\_queue\_clear\_all\_tasks
- restore\_queue\_clear\_completed\_task
- restore\_queue\_clear\_pending\_task
- restore\_queue\_is\_active
- restore\_queue\_list\_active
- restore\_queue\_list\_completed
- restore\_queue

## Function Information

## About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

### Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
- )tc

ue\_list\_pending  
restore\_queue\_state  
restoreaccount  
verify\_new\_username\_for\_restore

Accounts

accountsummary  
applist  
createacct  
domainuserdata  
editquota  
forcepasswordchange  
get\_disk\_usage  
get\_domain\_info  
getdomainowner  
has\_digest\_auth  
has\_mycnf\_for\_cpuser  
limitbw  
list\_users  
listaccts  
listlockedaccounts  
listsuspended  
modifyacct  
myprivs  
passwd  
quota\_enabled  
removeacct  
set\_digest\_auth  
showbw  
suspendacct  
unsuspendacct  
untrack\_acct

Command Line

```
whmapi1  
convert_addon_get_con  
version_status  
job_id=1
```

**Notes:**

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

Find a function

- WHM API 1 Functions - convert\_addon\_fetch\_conversion\_details — This function returns the details of the convert\_addon\_domain to account process.

\_id

verify\_new\_username

▼ Addon Domains

convert\_addon\_fetch\_conversion\_details

convert\_addon\_fetch\_domain\_details

convert\_addon\_get\_conversion\_status

convert\_addon\_initiate\_conversion

convert\_addon\_list\_addon\_domains

convert\_addon\_list\_conversions

▼ Authentication

api\_token\_create

api\_token\_list

api\_token\_revoke

api\_token\_update

disable\_authentication\_provider

disable\_failing\_authentication\_providers

enable\_authentication\_provider

get\_available\_authentication\_providers

get\_login\_url

get\_provider\_client\_configurations

get\_provider\_configuration\_fields

get\_provider\_display\_co

▼ Output (JSON)

```
{
  "data" : {
    "1" : {
      "source_acct" :
        "user1",
      "job_end_time" :
        1462383658,
      "job_status" :
        "DONE",
      "job_id" :
        "1"
    },
    "metadata" : {
      "reason" :
        "OK",
      "version" : 1,
      "result" : 1,
      "command" :
        "convert_addon_get_conversion_status"
    }
  }
}
```

- WHM API 1 Functions - convert\_addon\_fetch\_domain\_details - This function retrieves domain data for an addon domain.

configurations

get\_users\_authn\_linked\_accounts

link\_user\_authn\_provider

set\_provider\_client\_configurations

set\_provider\_display\_configurations

twofactorauth\_disable\_policy

twofactorauth\_enable\_policy

twofactorauth\_generate\_tfa\_config

twofactorauth\_get\_issuer

twofactorauth\_get\_user\_configs

twofactorauth\_policy\_status

twofactorauth\_remove\_user\_config

twofactorauth\_set\_issuer

twofactorauth\_set\_tfa\_config

unlink\_user\_authn\_provider

validate\_login\_token

### Output (XML)

```

<result>
  <metadata>

  <version>1</version>

  <result>1</result>

  <command>convert_addon_get_conversion_status</command>

  <reason>OK</reason>
  </metadata>
  <data>
    <1>

    <source_acct>user1</source_acct>

    <job_end_time>1462383658</job_end_time>

    <job_status>DONE</job_status>

    <job_id>1</job_id>
    </1>
  </data>
</result>

```

**Note:**  
 Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

- WHM API 1 Functions - convert\_addon\_get\_conversion\_status - This function returns the status of the convert\_addon domain to account process for specified conversion jobs.

### Backups

backup\_config\_get

backup\_config\_set

backup\_date\_list

backup\_destination\_add

backup\_destination\_delete

### Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

backup_dest_ination_get	job_id	integer	<b>Required.</b> The conversion's job identification number.	A valid positive integer.	1
backup_dest_ination_list					
backup_dest_ination_set					
backup_dest_ination_validate					
backup_get_transport_status					
backup_list_transported					
backup_set_list					
backup_set_list_combined					
backup_skip_users_all					
backup_skip_users_all_status					
backup_user_list					
convert_and_migrate_from_legacy_config					
get_users_with_backup_metadata					
list_cparchive_files					
start_background_pkgact					
toggle_user_backup_status					

**Note :**  
To list entries for multiple conversion jobs, increment the parameter name. For example: job\_b\_id-0, job\_b\_id-1, and job\_id-2.

- WHM API 1 Functions - convert\_addon\_initiate\_conversion — This function initiates the conversion process for an add-on domain.

## Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

### ▼ cPHulk

- cphulk\_status
- create\_cphulk\_record
- delete\_cphulk\_record
- disable\_cphulk
- enable\_cphulk
- flush\_cphulk\_login\_history

flush\_cphulk\_login\_history\_for\_ips

get\_countries\_with\_known\_ip\_ranges

get\_cphulk\_brutes

get\_cphulk\_excessive\_brutes

get\_cphulk\_failed\_logins

get\_cphulk\_user\_brutes

load\_cphulk\_config

read\_cphulk\_records

save\_cphulk\_config

set\_cphulk\_config\_key

▼ Databases

background\_mysql\_upgrade\_status

current\_mysql\_version

installable\_mysql\_versions

latest\_available\_mysql\_version

list\_databases\_users

list\_databases

list\_mysql\_databases\_and\_users

remote\_mysql\_create\_profile

remote\_mysql\_create\_profile\_via\_ssh

remote\_mysql\_delete\_profile

remote\_mysql\_initiate\_profile\_activation

job_id*	hash or hash of hashes	A hash of the status information of the requested job.	This hash includes details of the conversion job's status. Each hash includes the source_acct, job_end_time, job_status, and job_id returns.	
	<p><b>Note</b> :</p> <p>If you specify more than one job_id parameter, this return value displays as a hash of hashes.</p>	<p><b>Note</b> :</p> <p>The value's name is the identification number of the requested job.</p>		
source_acct	string	The addon domain that you converted into an account.	A valid addon domain.	user1
job_end_time	integer	The time when the convert addon domain to account process ended.	A date in Unix time format.	1462383658
job_status	string	The status of the conversion process.	<ul style="list-style-type: none"> <li>• DONE</li> <li>• IN PROGRESS</li> <li>• FAILED</li> </ul>	DONE

ion	job_id	string	The conversion's job identification number.  The function returns this value in the job_id hash.	A valid positive integer.	1
remote_mysql_monitor_profile_activation					
remote_mysql_read_profile					
remote_mysql_read_profiles					
remote_mysql_update_profile					
remote_mysql_validate_profile					
rename_mysql_database					
rename_mysql_user					
rename_postgresql_database					
rename_postgresql_user					
set_local_mysql_root_password					
set_mysql_password					
set_postgresql_password					
start_background_mysql_upgrade					

**Note**  
:  
The system stores this numeric value as a *string*.

▼ DNS

- adddns
- addzonerecord
- addzonerecord (Reverse DNS)
- dumpzone
- editzonerecord
- get\_nameserver\_config
- getzonerecord
- has\_local\_authority

killdns  
listmxs  
listzones  
lookupnsip  
lookupnsips  
removezone  
record  
resetzone  
resolvedom  
ainname  
savemxs  
setresolvers  
update\_nam  
eservers\_co  
nfig

▼ EasyApache

ea4\_get\_cur  
rently\_install  
ed\_packages  
  
ea4\_get\_ea  
\_pkgs\_state  
  
ea4\_list\_pro  
files  
  
ea4\_metainf  
o  
  
ea4\_migrati  
on  
  
ea4\_pre\_mi  
grate\_check  
  
ea4\_recom  
mendations  
  
ea4\_save\_p  
rofile  
  
ea4\_tomcat  
85\_add  
  
ea4\_tomcat  
85\_list  
  
ea4\_tomcat  
85\_rem

▼ Greylisting

cpgreylist\_is  
\_server\_net  
block\_truste  
d  
  
cpgreylist\_li  
st\_entries\_f  
or\_common  
\_mail\_provid  
er  
  
cpgreylist\_lo  
ad\_common  
\_mail\_provid



ers\_config

cpgreylist\_s  
ave\_commo  
n\_mail\_provi  
ders\_config

cpgreylist\_st  
atus

cpgreylist\_tr  
ust\_entries\_  
for\_common  
\_mail\_provid  
er

cpgreylist\_u  
ntrust\_entrie  
s\_for\_comm  
on\_mail\_pro  
vider

create\_cpgr  
eylist\_truste  
d\_host

delete\_cpgr  
eylist\_truste  
d\_host

disable\_cpgr  
eylist

enable\_cpgr  
eylist

load\_cpgreyl  
ist\_config

read\_cpgrey  
list\_deferred  
\_entries

read\_cpgrey  
list\_trusted\_  
host

save\_cpgrey  
list\_config

▼ Integration

batch

cpanel

create\_integ  
ration\_group

create\_integ  
ration\_link

get\_integrati  
on\_link\_user  
\_config

list\_integrati  
on\_groups

list\_integrati  
on\_links

remove\_inte  
gration\_grou  
p

remove\_inte

gration\_link

update\_inte  
gration\_link  
\_token

▼ IP Addresses

addips

delip

get\_public\_i  
p

get\_shared\_  
ip

ipv6\_disable  
\_account

ipv6\_enable  
\_account

ipv6\_range\_  
add

ipv6\_range\_  
edit

ipv6\_range\_  
list

ipv6\_range\_  
remove

ipv6\_range\_  
usage

listips

nat\_checkip

nat\_set\_pub  
lic\_ip

setsiteip

▼ Mail

disable\_dki  
m

disable\_mail  
\_sni

emailtrack\_s  
earch

emailtrack\_s  
tats

emailtrack\_u  
ser\_stats

enable\_dkim

enable\_mail  
\_sni

ensure\_dki  
m\_keys\_exi  
st

exim\_config  
uration\_che  
ck

expunge\_m

ailbox\_messages  
expunge\_messages\_for\_mailbox\_guid  
fetch\_dkim\_private\_keys  
fetch\_mail\_queue  
generate\_mobileconfig  
get\_mailbox\_status  
get\_mailbox\_status\_list  
get\_unique\_recipient\_count\_per\_sender\_for\_user  
get\_unique\_sender\_recipient\_count\_per\_user  
get\_user\_email\_forward\_destination  
hold\_outgoing\_email  
install\_dkim\_private\_keys  
install\_spf\_records  
is\_sni\_supported  
list\_pops\_for  
mail\_sni\_status  
rebuild\_mail\_sni\_config  
release\_outgoing\_email  
save\_spamd\_config  
set\_user\_email\_forward\_destination  
suspend\_outgoing\_email  
unsuspend\_outgoing\_email

validate\_currency\_installed\_exim\_configuration

validate\_currency\_dkims

validate\_currency\_ptrs

validate\_currency\_spfs

validate\_exim\_configuration\_syntax

▼ Market

disable\_market\_provider

enable\_market\_provider

get\_adjusted\_market\_providers\_products

get\_market\_providers\_commission\_config

get\_market\_providers\_list

get\_market\_providers\_product\_metadata

get\_market\_providers\_products

set\_market\_product\_attribute

set\_market\_provider\_commission\_id

▼ ModSecurity™

modsec\_add\_rule

modsec\_add\_vendor

modsec\_assemble\_config\_text

modsec\_batch\_settings

modsec\_check\_rule

modsec\_clone\_rule

modsec\_de  
ploy\_all\_rule  
\_changes

modsec\_de  
ploy\_rule\_ch  
anges

modsec\_de  
ploy\_setting  
s\_changes

modsec\_dis  
able\_rule

modsec\_dis  
able\_vendor

modsec\_dis  
able\_vendor  
\_configs

modsec\_dis  
able\_vendor  
\_updates

modsec\_dis  
card\_all\_rul  
e\_changes

modsec\_dis  
card\_rule\_c  
hanges

modsec\_edit  
\_rule

modsec\_en  
able\_vendor

modsec\_en  
able\_vendor  
\_configs

modsec\_en  
able\_vendor  
\_updates

modsec\_get  
\_config\_text

modsec\_get  
\_configs

modsec\_get  
\_configs\_wit  
h\_changes\_  
pending

modsec\_get  
\_log

modsec\_get  
\_rules

modsec\_get  
\_settings

modsec\_get  
\_vendors

modsec\_is\_i  
nstalled

modsec\_ma  
ke\_config\_a  
ctive

modsec\_make\_config\_inactive

modsec\_preview\_vendor

modsec\_remove\_rule

modsec\_remove\_setting

modsec\_remove\_vendor

modsec\_report\_rule

modsec\_set\_config\_text

modsec\_set\_setting

modsec\_disable\_rule

modsec\_update\_vendor

▼ Packages

\_getpkgextensionform

add\_override\_features\_for\_user

addpkg

addpkgext

changepackage

create\_feature\_relist

delete\_feature\_relist

delpkgext

editpkg

get\_available\_applications

get\_available\_featurelists

get\_feature\_metadata

get\_feature\_names

get\_featurelist\_data

get\_featureli

sts

get\_users\_f  
eatures\_sett  
ings

getfeaturelis  
t

getpkginfo

killpkg

listpkgs

manage\_fea  
tures

matchpkgs

read\_feature  
list

remove\_ove  
rride\_featu  
res\_for\_user

update\_feat  
urelist

verify\_user\_  
has\_feature

▼ PHP

convert\_all\_  
domains\_to  
\_fpm

get\_fpm\_co  
unt\_and\_util  
ization

is\_conversio  
n\_in\_progre  
ss

php\_get\_def  
ault\_accoun  
ts\_to\_fpm

php\_get\_ha  
ndlers

php\_get\_im  
pacted\_dom  
ains

php\_get\_ins  
talled\_versio  
ns

php\_get\_old  
\_fpm\_flag

php\_get\_sys  
tem\_default  
\_version

php\_get\_vh  
osts\_by\_ver  
sion

php\_get\_vh  
ost\_versions

php\_ini\_get  
\_content

php\_ini\_get  
\_directives

php\_ini\_set  
\_content

php\_ini\_set  
\_directives

php\_set\_def  
ault\_accoun  
ts\_to\_fpm

php\_set\_ha  
ndler

php\_set\_old  
\_fpm\_flag

php\_set\_ses  
sion\_save\_p  
ath

php\_set\_sys  
tem\_default  
\_version

php\_set\_vh  
ost\_versions

▼ Resellers

acctcounts

get\_public\_c  
ontact

getresellerip  
s

listacIs

listresellers

resellerstats

saveacllist

set\_public\_c  
ontact

setacIs

setresellerip  
s

setresellerli  
mits

setresellerm  
ainip

setresellern  
ameservers

setresellerp  
ackagelimit

setupreselle  
r

suspendres  
eller

terminateres  
eller

unsetuprese



ller

unsuspendr  
eseller

▼ RPM

delete\_rpm\_  
version

edit\_rpm\_ve  
rsion

get\_rpm\_ver  
sion\_data

install\_rpm\_  
plugin

list\_rpms

package\_m  
anager\_fixc  
ache

package\_m  
anager\_get\_  
build\_log

package\_m  
anager\_get\_  
package\_inf  
o

package\_m  
anager\_is\_p  
erforming\_a  
ctions

package\_m  
anager\_list\_  
packages

package\_m  
anager\_reso  
lve\_actions

package\_m  
anager\_sub  
mit\_actions

package\_m  
anager\_upgr  
ade

uninstall\_rp  
m\_plugin

▼ Script Hooks

delete\_hook

edit\_hook

list\_hooks

reorder\_hoo  
ks

▼ Security

accesshash

authorizessh  
key

check\_remo  
te\_ssh\_conn  
ection

convertopen  
sshtoputty

deletesshke  
y

fetch\_securi  
ty\_advice

generatessh  
keypair

importsshke  
y

listsshkeys

▼ Server

Administration

add\_configcl  
usterserver

configureba  
ckgroundpro  
cesskiller

configureser  
vice

cors\_proxy\_  
get

create\_user  
\_session

delete\_confi  
gclusterserv  
er

enable\_mon  
itor\_all\_ena  
bled\_service  
s

get\_all\_cont  
act\_importa  
nces

get\_appconf  
ig\_applicatio  
n\_list

get\_applicati  
on\_contact\_  
event\_import  
tance

get\_applicati  
on\_contact\_  
importance

get\_availabl  
e\_profiles

get\_current\_  
profile

get\_passwor  
d\_strength

get\_remote\_  
access\_has  
h

get\_service\_  
config

get\_service\_  
config\_key

get\_tcp4\_so  
ckets

get\_tcp6\_so  
ckets

get\_tweakse  
tting

get\_udp4\_s  
ockets

get\_udp6\_s  
ockets

get\_update\_  
availability

get\_users\_li  
nks

getdiskusag  
e

gethostname

is\_role\_ena  
bled

list\_configcl  
usterservers

loadavg

nvget

nvset

personalizati  
on\_get

personalizati  
on\_set

purchase\_a  
\_license

reboot

remove\_in\_  
progress\_ex  
im\_config\_e  
dit

restartservic  
e

restore\_conf  
ig\_from\_file

restore\_conf  
ig\_from\_upl  
oad

run\_cpkeyclt

send\_test\_p  
osturl

send\_test\_p  
ushbullet\_n  
ote

servicestatu

s

set\_applicati  
on\_contact\_  
event\_imp  
ortance

set\_applicati  
on\_contact\_  
importance

set\_primary  
\_servernam  
e

set\_service\_  
config\_key

set\_tweakse  
tting

sethostname

setminimum  
passwordstr  
engths

start\_profile  
\_activation

system\_nee  
ds\_reboot

systemloada  
vg

update\_conf  
igclusterserv  
er

update\_cont  
act\_email

verify\_aim\_a  
ccess

verify\_icq\_a  
ccess

verify\_oscar  
\_access

verify\_postu  
rl\_access

verify\_pushb  
ullet\_access

▼ SSL

disable\_aut  
ossl

fetch\_servic  
e\_ssl\_comp  
onents

fetch\_ssl\_ce  
rtificates\_for  
\_fqdns

fetch\_ssl\_vh  
osts

fetch\_vhost  
\_ssl\_compo  
nents

fetchcrtinfo  
fetchsslinfo  
generatessl  
get\_autossl  
\_check\_schedule  
get\_autossl  
\_log  
get\_autossl  
\_logs\_catalog  
get\_autossl  
\_metadata  
get\_autossl  
\_pending\_queue  
get\_autossl  
\_pending\_queue\_for\_domain  
get\_autossl  
\_pending\_queue\_for\_user  
get\_autossl  
\_problems\_for\_domain  
get\_autossl  
\_problems\_for\_user  
get\_autossl  
\_providers  
get\_best\_ssl  
domain\_for\_service  
install\_service\_ssl\_certificate  
installssl  
listcrts  
rebuildinstall  
edssldb  
rebuildusers  
sldb  
reset\_autossl\_provider  
reset\_service\_ssl\_certificate  
set\_autossl\_metadata  
set\_autossl\_metadata\_key

set\_autossl\_  
provider

start\_autossl\_  
check\_for\_  
all\_users

start\_autossl\_  
check\_for\_  
one\_user

▼ Styles and Themes

generate\_cp  
anel\_plugin

list\_styles

load\_style

remove\_log  
o

remove\_styl  
e

save\_style

set\_default

▼ Support Tickets

ticket\_creat  
e\_stub\_ticke  
t

ticket\_get\_s  
upport\_agre  
ement

ticket\_get\_s  
upport\_info

ticket\_grant

ticket\_list

ticket\_remov  
e\_closed

ticket\_revok  
e

ticket\_ssh\_t  
est

ticket\_ssh\_t  
est\_start

ticket\_updat  
e\_service\_a  
greement\_a  
pproval

ticket\_valida  
te\_oauth2\_c  
ode

ticket\_whitel  
ist\_check

ticket\_whitel  
ist\_setup

ticket\_whitel  
ist\_unsetup

▼ Transfers

abort\_transfer\_session

analyze\_transfer\_session\_remote

available\_transfer\_modules

create\_remote\_root\_transfer\_session

create\_remote\_user\_transfer\_session

delete\_account\_archives

enqueue\_transfer\_item

fetch\_transfer\_session\_log

get\_transfer\_session\_state

pause\_transfer\_session

remote\_basic\_credential\_check

retrieve\_transfer\_session\_remote\_analysis

start\_transfer\_session

transfer\_module\_schema

validate\_system\_user

▼ Updates

accept\_eula

get\_available\_tiers

get\_current\_lts\_expiration\_status

get\_lts\_expire

getlongterm support

installed\_versions

set\_cpanel\_updates

set\_tier

update\_upd  
ateconf

version