

# WHM API 1 Functions - listpkgs

## Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore\_modules\_summary
- restore\_queue\_activate
- restore\_queue\_add\_task
- restore\_queue\_clear\_all\_completed\_tasks
- restore\_queue\_clear\_all\_failed\_tasks
- restore\_queue\_clear\_all\_pending\_tasks
- restore\_queue\_clear\_all\_tasks
- restore\_queue\_clear\_completed\_task
- restore\_queue\_clear\_pending\_task
- restore\_queue\_is\_active
- restore\_queue\_list\_active
- restore\_queue\_list\_completed
- restore\_queue

## Description

This function lists the authenticated user's available hosting plans (packages).

### Important:

This function **only** returns packages that a user with `root`-level privileges or a reseller can use when they create an account.

## Examples

### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/listpkgs?api.version=1
```

### XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/listpkgs?api.version=1
```

### Command Line

```
whmapil listpkgs
```

### Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

### Output (JSON)

```
{
```

## Function information

## About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

### Notes:

- Scro
- Ycmt
- 20
- or
- 20
- )tc

ue\_list\_pending  
restore\_queue\_state  
restoreaccount  
verify\_new\_username\_for\_restore

▼ Accounts

accountsummary  
applist  
createacct  
domainuserdata  
editquota  
forcepasswordchange  
get\_disk\_usage  
get\_domain\_info  
getdomainowner  
has\_digest\_auth  
has\_mycnf\_for\_cpuser  
limitbw  
list\_users  
listaccts  
listlockedaccounts  
listsuspended  
modifyacct  
myprivs  
passwd  
quota\_enabled  
removeacct  
set\_digest\_auth  
showbw  
suspendacct  
unsuspendacct  
untrack\_acct

```
"data":{  
  "pkg":[  
    {  
      "FRONTPAGE":"n",  
      "CPMOD":"paper_lantern",  
      "FEATURELIST":"default",  
      "BWLIMIT":"unlimited",  
      "IP":"n",  
      "CGI":"y",  
      "MAXSUB":"unlimited",  
      "name":"standard",  
      "MAXSQL":"unlimited",  
      "MAXFTP":"unlimited",  
      "QUOTA":"unlimited",  
      "MAXPARK":"2",  
      "HASSHELL":"y",  
      "MAXADDON":"2",  
      "MAXPOP":"unlimited",  
      "MAXLST":"unlimited",  
      "MAX_EMAILACCT_QUOTA": "unlimited",  
      "LANG":"english"  
    },  
    {  
      "FRONTPAGE":"n",  
      "CPMOD":"paper_lantern",  
      "FEATURELIST":"Default",  
      "BWLIMIT":"9999",
```

## Find a function

- WHM API 1 Functions - change package — This function changes a cPanel account's hosting plan (package).

\_id  
 verify\_new\_username

▼ Addon Domains

convert\_addon\_fetch\_conversion\_details  
 convert\_addon\_fetch\_domain\_details  
 convert\_addon\_get\_conversion\_status  
 convert\_addon\_initiate\_conversion  
 convert\_addon\_list\_addon\_domains  
 convert\_addon\_list\_conversions

▼ Authentication

api\_token\_create  
 api\_token\_list  
 api\_token\_revoke  
 api\_token\_update  
 disable\_authentication\_provider  
 disable\_failing\_authentication\_providers  
 enable\_authentication\_provider  
 get\_available\_authentication\_providers  
 get\_login\_url  
 get\_provider\_client\_configurations  
 get\_provider\_configuration\_fields  
 get\_provider\_display\_co

```

    "IP": "y",
    "CGI": "y",

    "MAXSUB": "888",

    "name": "bronze",

    "MAXSQL": "99",

    "MAXFTP": "9",

    "QUOTA": "unlimited",

    "MAXPARK": "88",

    "HASSHELL": "y",

    "MAXADDON": "888",

    "MAXPOP": "999",

    "MAXLST": "999",

    "MAX_EMAILACCT_QUOTA":
      : "unlimited",

    "LANG": "english"
      },
      {

    "FRONTPAGE": "n",

    "CPMOD": "paper_lantern",

    "FEATURELIST": "default",

    "BWLIMIT": "unlimited"
  ,
    "IP": "n",
    "CGI": "y",

    "MAXSUB": "unlimited",

    "name": "silver",

    "MAXSQL": "unlimited",

    "MAXFTP": "unlimited",

    "QUOTA": "unlimited",
  
```

- WHM API 1 Functions - listpkgs — This function lists the authenticated user's available hosting plans (packages).
- WHM API 1 Functions - killpkg — This function deletes a hosting plan (package).

nfigurations  
get\_users\_authn\_linked\_accounts  
link\_user\_authn\_provider  
set\_provider\_client\_configurations  
set\_provider\_display\_configurations  
twofactorauth\_disable\_policy  
twofactorauth\_enable\_policy  
twofactorauth\_generate\_tfa\_config  
twofactorauth\_get\_issuer  
twofactorauth\_get\_user\_configs  
twofactorauth\_policy\_status  
twofactorauth\_remove\_user\_config  
twofactorauth\_set\_issuer  
twofactorauth\_set\_tfa\_config  
unlink\_user\_authn\_provider  
validate\_login\_token

▼ Backups

backup\_config\_get  
backup\_config\_set  
backup\_data\_list  
backup\_destination\_add  
backup\_destination\_delete

```
"MAXPARK": "0",  
"HASSHELL": "y",  
"MAXADDON": "0",  
"MAXPOP": "unlimited",  
"MAXLST": "unlimited",  
"MAX_EMAILACCT_QUOTA":  
"unlimited",  
"LANG": "english",  
    },  
    {  
"FRONTPAGE": "n",  
"CPMOD": "paper_lantern",  
"FEATURELIST": "default",  
"BWLIMIT": "unlimited",  
,  
"MAXSUB": "unlimited",  
    "CGI": "y",  
    "IP": "n",  
"name": "gold",  
"MAXSQL": "unlimited",  
"MAXPARK": "2",  
"QUOTA": "unlimited",  
"MAXFTP": "unlimited",  
"HASSHELL": "y",  
"MAXADDON": "2",  
"LANG": "english",  
"MAXLST": "unlimited",  
"MAXPOP": "unlimited",  
"MAX_EMAILACCT_QUOTA"
```

- WHM API 1 Functions - \_get\_pkg\_extensions - This function retrieves a hosting plan's package extension templates.

backup\_dest  
ination\_get

backup\_dest  
ination\_list

backup\_dest  
ination\_set

backup\_dest  
ination\_valid  
ate

backup\_get  
\_transport\_s  
tatus

backup\_list\_  
transported

backup\_set\_  
list

backup\_set\_  
list\_combine  
d

backup\_skip  
\_users\_all

backup\_skip  
\_users\_all\_s  
tatus

backup\_use  
r\_list

convert\_and  
\_migrate\_fro  
m\_legacy\_c  
onfig

get\_users\_w  
ith\_backup\_  
metadata

list\_cparchiv  
e\_files

start\_backgr  
ound\_pkgac  
t

toggle\_user  
\_backup\_sta  
te

▼ cPHulk

cphulk\_statu  
s

create\_cphu  
lk\_record

delete\_cphu  
lk\_record

disable\_cph  
ulk

enable\_cph  
ulk

flush\_cphulk  
\_login\_histo  
ry

```
: "unlimited"  
  }  
  ]  
},  
  "metadata": {  
    "command":  
      "listpkgs",  
    "reason": "OK",  
    "result": 1,  
    "version": 1  
  }  
}
```

▼ Output (XML)

```
<data>  
  <pkg>  
  
    <name>gold</name>  
  
    <BWLIMIT>unlimited</B  
WLIMIT>  
  
    <CGI>y</CGI>  
  
    <CPMOD>paper_lantern<  
/CPMOD>  
  
    <FEATURELIST>default<  
/FEATURELIST>  
  
    <FRONTPAGE>n</FRONT  
PAGE>  
  
    <HASSHELL>y</HASSHELL  
>  
  
    <IP>n</IP>  
  
    <LANG>english</LANG>  
  
    <MAXADDON>2</MAXADDON  
>  
  
    <MAX_EMAILACCT_QUOTA>  
unlimited</MAX_EMAILA  
CCT_QUOTA>  
  
    <MAXFTP>unlimited</MA  
XFTP>
```

flush\_cphulk\_login\_history\_for\_ips  
get\_countries\_with\_known\_ip\_ranges  
get\_cphulk\_brutes  
get\_cphulk\_excessive\_brutes  
get\_cphulk\_failed\_logins  
get\_cphulk\_user\_brutes  
load\_cphulk\_config  
read\_cphulk\_records  
save\_cphulk\_config  
set\_cphulk\_config\_key

▼ Databases

background\_mysql\_upgrade\_status  
current\_mysql\_version  
installable\_mysql\_versions  
latest\_available\_mysql\_version  
list\_database\_users  
list\_databases  
list\_mysql\_databases\_and\_users  
remote\_mysql\_create\_profile  
remote\_mysql\_create\_profile\_via\_ssh  
remote\_mysql\_delete\_profile  
remote\_mysql\_initiate\_profile\_activation

```
<MAXLST>unlimited</MAXLST>  
  
<MAXPARK>2</MAXPARK>  
  
<MAXPOP>unlimited</MAXPOP>  
  
<MAXSQL>unlimited</MAXSQL>  
  
<MAXSUB>unlimited</MAXSUB>  
  
<QUOTA>unlimited</QUOTA>  
  </pkg>  
</data>  
<metadata>  
  
<command>listpkgs</command>  
  <reason>OK</reason>  
  <result>1</result>
```

ion

remote\_mysql\_monitor\_profile\_activation

remote\_mysql\_read\_profile

remote\_mysql\_read\_profiles

remote\_mysql\_update\_profile

remote\_mysql\_validate\_profile

rename\_mysql\_database

rename\_mysql\_user

rename\_postgresql\_database

rename\_postgresql\_user

set\_local\_mysql\_root\_password

set\_mysql\_password

set\_postgresql\_password

start\_background\_mysql\_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get\_nameserver\_config

getzonerecord

has\_local\_authority

```
<version>1</version>
</metadata>
```

**Note:**  
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
want	string	The permissions of packages that you wish to list.  This parameter defaults to all.	<ul style="list-style-type: none"> <li>all — All packages on the system.</li> <li>creatable — Packages that the authenticated user can use for accounts.</li> <li>editable — Packages that the authenticated user can edit.</li> <li>viewable — Packages that the authenticated user can view.</li> </ul>	all

## Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

killdns  
listmxs  
listzones  
lookupnsip  
lookupnsips  
removezone  
record  
resetzone  
resolvedom  
ainname  
savemxs  
setresolvers  
update\_nam  
eservers\_co  
nfig

▼ EasyApache

ea4\_get\_cur  
rently\_install  
ed\_packages  
  
ea4\_get\_ea  
\_pkgs\_state  
  
ea4\_list\_pro  
files  
  
ea4\_metainf  
o  
  
ea4\_migrati  
on  
  
ea4\_pre\_mi  
grate\_check  
  
ea4\_recom  
mendations  
  
ea4\_save\_p  
rofile  
  
ea4\_tomcat  
85\_add  
  
ea4\_tomcat  
85\_list  
  
ea4\_tomcat  
85\_rem

▼ Greylisting

cpgreylist\_is  
\_server\_net  
block\_truste  
d  
  
cpgreylist\_li  
st\_entries\_f  
or\_common  
\_mail\_provid  
er  
  
cpgreylist\_lo  
ad\_common  
\_mail\_provid

	<i>pkg</i>	<i>hash</i>	A hash of hosting plan settings.	This function contains one or more of the following <b>returns:</b> name, MAXSUB, MAXADDON, MAX_DEFER_FAIL_PERCENTAGE, _PACKAGE_EXTENSIONS, CPMOD, MAX_EMAIL_PER_HOUR, MAX_EMAIL_ACCOUNT_QUOTA, LANG, MAXLST, MAXPARK, MAXSQL, FEATURELIST, CGI, MAXFTP, BWLIMIT, QUOTA, DIGESTAUTH, IP. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p><b>Note</b>  :  If the account or its hosting plan usage extensions, the pkg hash also includes the extension's variables.</p> </div>	
	name	<i>string</i>	The hosting plan name.  The function returns this value in the <i>pkg</i> hash.	A valid hosting plan name.	package1
	MAXSUB	<i>string</i>	The hosting plan's maximum number of subdomains.  The function returns this value in the <i>pkg</i> hash.	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a number of subdomains.</li> </ul>	unlimited



ers\_config  
 cpgreylis\_t  
 ave\_commo  
 n\_mail\_provi  
 ders\_config  
 cpgreylis\_st  
 atus  
 cpgreylis\_tr  
 ust\_entries\_  
 for\_common  
 \_mail\_provid  
 er  
 cpgreylis\_u  
 ntrust\_entrie  
 s\_for\_comm  
 on\_mail\_pro  
 vider  
 create\_cpgr  
 eylist\_truste  
 d\_host  
 delete\_cpgr  
 eylist\_truste  
 d\_host  
 disable\_cpgr  
 eylist  
 enable\_cpgr  
 eylist  
 load\_cpgrey  
 list\_config  
 read\_cpgrey  
 list\_deferred  
 \_entries  
 read\_cpgrey  
 list\_trusted\_  
 host  
 save\_cpgrey  
 list\_config

MAXADD ON	<i>string</i>	<p>The hosting plan's maximum number of addon domains.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a number of addon domains.</li> </ul>	unlimited
MAX_DE FER_FA IL_PER CENTAG E	<i>string</i>	<p>The percentage of failed or deferred email messages that the hosting plan can send per hour before the system rate-limits outgoing mail.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a percentage of messages.</li> </ul>	unlimited
_PACKA GE_EXT ENSION S	<i>string</i>	<p>The hosting plan's package extensions.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	A space-separated list of one or more package extension names.	ext1 ext2 ext3
CPMOD	<i>string</i>	<p>The hosting plan's cPanel interface theme.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• paper_lantern</li> <li>• Another valid theme on the server.</li> </ul>	paper_lantern
MAX_EM AIL_PE R_HOUR	<i>string</i>	<p>The maximum number of emails that the hosting plan can send in one hour.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a number of sent emails.</li> </ul>	unlimited

▼ Integration

batch  
 cpanel  
 create\_integ  
 ration\_group  
 create\_integ  
 ration\_link  
 get\_integrati  
 on\_link\_user  
 \_config  
 list\_integrati  
 on\_groups  
 list\_integrati  
 on\_links  
 remove\_inte  
 gration\_grou  
 p  
 remove\_inte

gration\_link  
 update\_inte  
 gration\_link  
 \_token

▼ IP Addresses

addips  
 delip  
 get\_public\_i  
 p  
 get\_shared\_  
 ip  
 ipv6\_disable  
 \_account  
 ipv6\_enable  
 \_account  
 ipv6\_range\_  
 add  
 ipv6\_range\_  
 edit  
 ipv6\_range\_  
 list  
 ipv6\_range\_  
 remove  
 ipv6\_range\_  
 usage  
 listips  
 nat\_checkip  
 nat\_set\_pub  
 lic\_ip  
 setsiteip

▼ Mail

disable\_dki  
 m  
 disable\_mail  
 \_sni  
 emailtrack\_s  
 earch  
 emailtrack\_s  
 tats  
 emailtrack\_u  
 ser\_stats  
 enable\_dkim  
 enable\_mail  
 \_sni  
 ensure\_dki  
 m\_keys\_exi  
 st  
 exim\_config  
 uration\_che  
 ck  
 expunge\_m

	MAX_EM ALLACC T_QUOT A	string	The hosting plan's maximum email account quota size, in Megabytes (MB).  <div style="border: 1px solid orange; padding: 5px; width: fit-content; margin: 10px auto;"> <p><b>Note</b> : We introduce this return in cPanel &amp; WHM version 70.</p> </div> <p>This function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>unlimited</li> <li>A positive integer that represents the maximum email quota, in Megabytes (MB).</li> </ul>	unlimited
	LANG	string	The hosting plan's locale.  The function returns this value in the <code>pkg</code> hash.	The ISO code for any locale on the server.	en
	MAXLST	string	The hosting plan's maximum number of mailing lists.  The function returns this value in the <code>pkg</code> hash.	<ul style="list-style-type: none"> <li>unlimited</li> <li>An integer that represents a number of mailing lists.</li> </ul>	unlimited
	MAXPAR K	string	The hosting plan's maximum number of parked domains (aliases).  The function returns this value in the <code>pkg</code> hash.	<ul style="list-style-type: none"> <li>unlimited</li> <li>An integer that represents a number of parked domains.</li> </ul>	unlimited

ailbox\_messages  
 expunge\_messages\_for\_mailbox\_guid  
 fetch\_dkim\_private\_keys  
 fetch\_mail\_queue  
 generate\_mobileconfig  
 get\_mailbox\_status  
 get\_mailbox\_status\_list  
 get\_unique\_recipient\_count\_per\_sender\_for\_user  
 get\_unique\_sender\_recipient\_count\_per\_user  
 get\_user\_email\_forward\_destination  
 hold\_outgoing\_email  
 install\_dkim\_private\_keys  
 install\_spf\_records  
 is\_sni\_supported  
 list\_pops\_for  
 mail\_sni\_status  
 rebuild\_mail\_sni\_config  
 release\_outgoing\_email  
 save\_spam\_config  
 set\_user\_email\_forward\_destination  
 suspend\_outgoing\_email  
 unsuspend\_outgoing\_email

MAXSQL	string	<p>The hosting plan's maximum number of each available type of SQL database.</p> <p>For example, if you set this value to 5 and the system administrator allows MySQL® and PostgreSQL® databases, users can create up to five MySQL databases and up to five PostgreSQL databases.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a number of SQL databases.</li> </ul>	unlimited
FEATURELIST	string	<p>The hosting plan's featurelist.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	A valid feature list name.	default
CGI	Boolean	<p>Whether CGI is enabled for the hosting plan.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Enabled.</li> <li>• 0 — Disabled.</li> </ul>	1
MAXFTP	string	<p>The hosting plan's maximum number of FTP accounts.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• An integer that represents a number of FTP accounts.</li> </ul>	unlimited
BWLIMIT	string	<p>The hosting plan's bandwidth limit.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• A maximum amount of bandwidth, in Megabytes (MB).</li> </ul>	unlimited
QUOTA	string	<p>The hosting plan's disk space limit.</p> <p>The function returns this value in the <code>pkg</code> hash.</p>	<ul style="list-style-type: none"> <li>• unlimited</li> <li>• A maximum amount of disk space, in Megabytes (MB).</li> </ul>	unlimited

validate\_current\_installeg  
d\_exim\_config

validate\_current\_dkims

validate\_current\_ptrs

validate\_current\_spfs

validate\_exim\_configuration\_syntax

DIGEST AUTH	string	Whether the hosting plan enables Digest Authentication.  The function returns this value in the pkg hash.	<ul style="list-style-type: none"><li>• y — Enable.</li><li>• n — Disable.</li></ul>	n
IP	string	Whether the hosting plan grants accounts a dedicated IP address.  The function returns this value in the pkg hash.	<ul style="list-style-type: none"><li>• y — Dedicated IP address.</li><li>• n — Shared IP address.</li></ul>	n

▼ Market

disable\_market\_provider

enable\_market\_provider

get\_adjusted\_market\_providers\_products

get\_market\_providers\_commission\_config

get\_market\_providers\_list

get\_market\_providers\_product\_metadata

get\_market\_providers\_products

set\_market\_product\_attribute

set\_market\_provider\_commission\_id

▼ ModSecurity™

modsec\_added\_rule

modsec\_added\_vendor

modsec\_assemble\_config\_text

modsec\_batch\_settings

modsec\_check\_rule

modsec\_close\_rule

modsec\_de  
ploy\_all\_rule  
\_changes

modsec\_de  
ploy\_rule\_ch  
anges

modsec\_de  
ploy\_setting  
s\_changes

modsec\_dis  
able\_rule

modsec\_dis  
able\_vendor

modsec\_dis  
able\_vendor  
\_configs

modsec\_dis  
able\_vendor  
\_updates

modsec\_dis  
card\_all\_rul  
e\_changes

modsec\_dis  
card\_rule\_c  
hanges

modsec\_edit  
\_rule

modsec\_en  
able\_vendor

modsec\_en  
able\_vendor  
\_configs

modsec\_en  
able\_vendor  
\_updates

modsec\_get  
\_config\_text

modsec\_get  
\_configs

modsec\_get  
\_configs\_wit  
h\_changes\_  
pending

modsec\_get  
\_log

modsec\_get  
\_rules

modsec\_get  
\_settings

modsec\_get  
\_vendors

modsec\_is\_i  
nstalled

modsec\_ma  
ke\_config\_a  
ctive

modsec\_make\_config\_inactive

modsec\_preview\_vendor

modsec\_remove\_rule

modsec\_remove\_setting

modsec\_remove\_vendor

modsec\_report\_rule

modsec\_set\_config\_text

modsec\_set\_setting

modsec\_disable\_rule

modsec\_update\_vendor

▼ Packages

\_getpkgextensionform

add\_override\_features\_for\_user

addpkg

addpkgext

changepackage

create\_feature\_relist

delete\_feature\_relist

delpkgext

editpkg

get\_available\_applications

get\_available\_featurelists

get\_feature\_metadata

get\_feature\_names

get\_featurelist\_data

get\_featureli

sts

get\_users\_f  
eatures\_sett  
ings

getfeaturelis  
t

getpkginfo

killpkg

listpkgs

manage\_fea  
tures

matchpkgs

read\_feature  
list

remove\_ove  
rride\_featu  
res\_for\_user

update\_feat  
urelist

verify\_user\_  
has\_feature

▼ PHP

convert\_all\_  
domains\_to  
\_fpm

get\_fpm\_co  
unt\_and\_util  
ization

is\_conversio  
n\_in\_progre  
ss

php\_get\_def  
ault\_accoun  
ts\_to\_fpm

php\_get\_ha  
ndlers

php\_get\_im  
pacted\_dom  
ains

php\_get\_ins  
talled\_versio  
ns

php\_get\_old  
\_fpm\_flag

php\_get\_sys  
tem\_default  
\_version

php\_get\_vh  
osts\_by\_ver  
sion

php\_get\_vh  
ost\_versions

php\_ini\_get  
\_content

php\_ini\_get  
\_directives

php\_ini\_set  
\_content

php\_ini\_set  
\_directives

php\_set\_def  
ault\_accoun  
ts\_to\_fpm

php\_set\_ha  
ndler

php\_set\_old  
\_fpm\_flag

php\_set\_ses  
sion\_save\_p  
ath

php\_set\_sys  
tem\_default  
\_version

php\_set\_vh  
ost\_versions

▼ Resellers

acctcounts

get\_public\_c  
ontact

getresellerip  
s

listacIs

listresellers

resellerstats

saveacllist

set\_public\_c  
ontact

setacIs

setresellerip  
s

setresellerli  
mits

setresellerm  
ainip

setresellern  
ameservers

setresellerp  
ackagelimit

setupreselle  
r

suspendres  
eller

terminateres  
eller

unsetuprese



ller

unsuspendr  
eseller

▼ RPM

delete\_rpm\_  
version

edit\_rpm\_ve  
rsion

get\_rpm\_ver  
sion\_data

install\_rpm\_  
plugin

list\_rpms

package\_m  
anager\_fixc  
ache

package\_m  
anager\_get\_  
build\_log

package\_m  
anager\_get\_  
package\_inf  
o

package\_m  
anager\_is\_p  
erforming\_a  
ctions

package\_m  
anager\_list\_  
packages

package\_m  
anager\_reso  
lve\_actions

package\_m  
anager\_sub  
mit\_actions

package\_m  
anager\_upgr  
ade

uninstall\_rp  
m\_plugin

▼ Script Hooks

delete\_hook

edit\_hook

list\_hooks

reorder\_hoo  
ks

▼ Security

accesshash

authorizessh  
key

check\_remo  
te\_ssh\_conn  
ection

convertopen  
sshtoputty

deletesshke  
y

fetch\_securi  
ty\_advice

generatessh  
keypair

importsshke  
y

listsshkeys

▼ Server

Administration

add\_configcl  
usterserver

configureba  
ckgroundpro  
cesskiller

configureser  
vice

cors\_proxy\_  
get

create\_user  
\_session

delete\_conf  
gclusterserv  
er

enable\_mon  
itor\_all\_ena  
bled\_service  
s

get\_all\_cont  
act\_importa  
nces

get\_appconf  
ig\_applicatio  
n\_list

get\_applicati  
on\_contact\_  
event\_import  
tance

get\_applicati  
on\_contact\_  
importance

get\_availabl  
e\_profiles

get\_current\_  
profile

get\_passwor  
d\_strength

get\_remote\_  
access\_has  
h

get\_service\_  
config

get\_service\_  
config\_key

get\_tcp4\_so  
ckets

get\_tcp6\_so  
ckets

get\_tweakse  
tting

get\_udp4\_s  
ockets

get\_udp6\_s  
ockets

get\_update\_  
availability

get\_users\_li  
nks

getdiskusag  
e

gethostname

is\_role\_ena  
bled

list\_configcl  
usterservers

loadavg

nvget

nvset

personalizati  
on\_get

personalizati  
on\_set

purchase\_a  
\_license

reboot

remove\_in\_  
progress\_ex  
im\_config\_e  
dit

restartservic  
e

restore\_conf  
ig\_from\_file

restore\_conf  
ig\_from\_upl  
oad

run\_cpkeyclt

send\_test\_p  
osturl

send\_test\_p  
ushbullet\_n  
ote

servicestatu

s

set\_applicati  
on\_contact\_  
event\_imp  
ortance

set\_applicati  
on\_contact\_  
importance

set\_primary  
\_servernam  
e

set\_service\_  
config\_key

set\_tweakse  
tting

sethostname

setminimum  
passwordstr  
engths

start\_profile  
\_activation

system\_nee  
ds\_reboot

systemloada  
vg

update\_conf  
igclusterserv  
er

update\_cont  
act\_email

verify\_aim\_a  
ccess

verify\_icq\_a  
ccess

verify\_oscar  
\_access

verify\_postu  
rl\_access

verify\_pushb  
ullet\_access

▼ SSL

disable\_aut  
ossl

fetch\_servic  
e\_ssl\_comp  
onents

fetch\_ssl\_ce  
rtificates\_for  
\_fqdns

fetch\_ssl\_vh  
osts

fetch\_vhost  
\_ssl\_compo  
nents

fetchcrtinfo  
fetchsslinfo  
generatessl  
get\_autossl  
\_check\_schedule  
get\_autossl  
\_log  
get\_autossl  
\_logs\_catalog  
get\_autossl  
\_metadata  
get\_autossl  
\_pending\_queue  
get\_autossl  
\_pending\_queue\_for\_domain  
get\_autossl  
\_pending\_queue\_for\_user  
get\_autossl  
\_problems\_for\_domain  
get\_autossl  
\_problems\_for\_user  
get\_autossl  
\_providers  
get\_best\_ssl  
domain\_for\_service  
install\_service\_ssl\_certificate  
installssl  
listcrts  
rebuildinstall  
edssldb  
rebuildusers  
sldb  
reset\_autossl\_provider  
reset\_service\_ssl\_certificate  
set\_autossl\_metadata  
set\_autossl\_metadata\_key

set\_autossl\_  
provider

start\_autossl\_  
check\_for\_  
all\_users

start\_autossl\_  
check\_for\_  
one\_user

▼ Styles and Themes

generate\_cp  
anel\_plugin

list\_styles

load\_style

remove\_log  
o

remove\_styl  
e

save\_style

set\_default

▼ Support Tickets

ticket\_creat  
e\_stub\_ticke  
t

ticket\_get\_s  
upport\_agre  
ement

ticket\_get\_s  
upport\_info

ticket\_grant

ticket\_list

ticket\_remov  
e\_closed

ticket\_revok  
e

ticket\_ssh\_t  
est

ticket\_ssh\_t  
est\_start

ticket\_updat  
e\_service\_a  
greement\_a  
pproval

ticket\_valida  
te\_oauth2\_c  
ode

ticket\_whitel  
ist\_check

ticket\_whitel  
ist\_setup

ticket\_whitel  
ist\_unsetup

▼ Transfers

abort\_transf  
er\_session

analyze\_tra  
nsfer\_sessio  
n\_remote

available\_tr  
ansfer\_mod  
ules

create\_remo  
te\_root\_tran  
sfer\_session

create\_remo  
te\_user\_tran  
sfer\_session

delete\_accou  
nt\_archives

enqueue\_tra  
nsfer\_item

fetch\_transf  
er\_session\_l  
og

get\_transfer  
\_session\_st  
ate

pause\_trans  
fer\_session

remote\_basi  
c\_credential  
\_check

retrieve\_tran  
sfer\_session  
\_remote\_an  
alysis

start\_transfe  
r\_session

transfer\_mo  
dule\_schem  
a

validate\_sys  
tem\_user

▼ Updates

accept\_eula

get\_availabl  
e\_tiers

get\_current\_  
lts\_expiratio  
n\_status

get\_lts\_wex  
pire

getlongterm  
support

installed\_ver  
sions

set\_cpanel\_  
updates

set\_tier

update\_upd  
ateconf

version