

# WHM API 1 Functions - cors\_proxy\_get

## Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

### Account Restoration

restore\_modules\_summary

restore\_queue\_activate

restore\_queue\_add\_task

restore\_queue\_clear\_all\_completed\_tasks

restore\_queue\_clear\_all\_failed\_tasks

restore\_queue\_clear\_all\_pending\_tasks

restore\_queue\_clear\_all\_tasks

restore\_queue\_clear\_completed\_task

restore\_queue\_clear\_pending\_task

restore\_queue\_is\_active

restore\_queue\_list\_active

restore\_queue\_list\_completed

restore\_queue

## Description

This function allows your system to perform Cross-Origin Resource Sharing (CORS) HTTP requests.

## Examples

### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/cors_proxy_get?api.version=1&url=http%3A%2F%2Fwww.example.com
```

### Command Line

```
whmapil cors_proxy_get url=http%3A%2F%2Fwww.example.com
```

#### Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

### Output (JSON)

```
{  "metadata": {    "result": 1,    "reason": "OK",    "version": 1,
```

## Function information

## About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

#### Notes:

- Scro
- Yomius 20 or 20)tc

## Find a function

ue\_list\_pending  
 restore\_queue\_state  
 restoreaccount  
 verify\_new\_username\_for\_restore

▼ Accounts

accountsummary  
 applist  
 createacct  
 domainuserdata  
 editquota  
 forcepasswordchange  
 get\_disk\_usage  
 get\_domain\_info  
 getdomainowner  
 has\_digest\_auth  
 has\_myconf\_or\_cpuser  
 limitbw  
 list\_users  
 listaccts  
 listlockedaccounts  
 listsuspended  
 modifyacct  
 myprivs  
 passwd  
 quota\_enabled  
 removeacct  
 set\_digest\_auth  
 showbw  
 suspendacct  
 unsuspendacct  
 untrack\_acct

```
"command": "cors_proxy_get",
  },
  "data": {
    "content": "<!doctype html>\n<html>\n<head>\n  <title>Example Domain</title>\n\n  <meta charset=\"utf-8\" />\n  <meta http-equiv=\"Content-type\" content=\"text/html; charset=utf-8\" />\n  <meta name=\"viewport\" content=\"width=device-width, initial-scale=1\" />\n  <style type=\"text/css\">\n  body {\n    background-color: #f0f0f2;\n    margin: 0;\n    padding: 0;\n    font-family: \"Open Sans\", \"Helvetica Neue\", Helvetica, Arial, sans-serif;\n  }\n  div {\n    width: 600px;\n    margin: 5em auto;\n    padding: 50px;\n    background-color: #fff;\n    border-radius: 1em;\n  }\n  a:link,\n  a:visited {\n    color: #38488f;\n    text-decoration: none;\n  }\n  @media (max-width: 700px) {\n    body {\n      background-color: #fff;\n    }\n    div {\n      width: auto;\n      margin: 0 auto;\n      border-radius: 0;\n
```

- WHM API 1 Functions - configure background processes killer. — This function configures the server's background process killer.

```

_id
verify_new_
username
  Addon Domains
convert_add
on_fetch_co
nversion_de
tails
convert_add
on_fetch_do
main_details
convert_add
on_get_con
version_stat
us
convert_add
on_initiate_c
onversion
convert_add
on_list_add
on_domains
convert_add
on_list_conv
ersions
  Authentication
api_token_c
reate
api_token_li
st
api_token_r
evoke
api_token_u
pdate
disable_aut
hentication_
provider
disable_fail
ing_authenti
cation_provi
ders
enable_auth
entication_p
rovider
get_availabl
e_authentic
ation_provid
ers
get_login_ur
l
get_provider
_client_conf
igurations
get_provider
_configurati
on_fields
get_provider
_display_co

```

```

padding: 1em;\n
}\n  }\n
</style>
\n</head>\n\n<body>\n
<div>\n
<h1>Example
Domain</h1>\n
<p>This domain is
established to be
used for illustrative
examples in
documents. You may
use this\n  domain
in examples without
prior coordination or
asking for
permission.</p>\n
<p><a
href="\http://www.ian
a.org/domains/example
\n">More
information...</a></p>
>\n</div>\n</body>\n<
/html>\n",
  "_cp_redirects":null,
    "reason":"OK",
  "url":"http://www.exa
mple.com",
    "headers":{
  "expires":"Thu, 06
Jul 2017 17:50:19
GMT",
  "content-type":"text/
html",
  "server":"ECS
(den/1D9E)",
  "content-length":"127
0",
  "vary":"Accept-Encodi
ng",
  "etag":"\"359670651+g
zip+ident\"",
  "last-modified":"Fri,
09 Aug 2013 23:54:35

```

- WHM API 1 Functions - get\_all\_content\_importances - This function lists the importance of all applications even in WHM's Contact Manager interface (Home >> Server Contacts >> Contact Manager).

nfigurations

get\_users\_authn\_linked\_accounts

link\_user\_authn\_provider

set\_provider\_client\_configurations

set\_provider\_display\_configurations

twofactorauth\_disable\_policy

twofactorauth\_enable\_policy

twofactorauth\_generate\_tfa\_config

twofactorauth\_get\_issuer

twofactorauth\_get\_user\_configs

twofactorauth\_policy\_status

twofactorauth\_remove\_user\_config

twofactorauth\_set\_issuer

twofactorauth\_set\_tfa\_config

unlink\_user\_authn\_provider

validate\_login\_token

▼ Backups

backup\_config\_get

backup\_config\_set

backup\_data\_list

backup\_destination\_add

backup\_destination\_delete

GMT",

"x-cache": "HIT",

"cache-control": "max-age=604800",

"date": "Thu, 29 Jun 2017 17:50:19 GMT"

},

"protocol": "HTTP/1.1"

,

"success": "1",

- WHM API 1 Functions - get\_appconfig\_application\_list — This function lists registered App Config applications.

backup\_destination\_get  
 backup\_destination\_list  
 backup\_destination\_set  
 backup\_destination\_validate  
 backup\_get\_transport\_status  
 backup\_list\_transported  
 backup\_set\_list  
 backup\_set\_list\_combined  
 backup\_skip\_users\_all  
 backup\_skip\_users\_all\_status  
 backup\_user\_list  
 convert\_and\_migrate\_from\_legacy\_config  
 get\_users\_with\_backup\_metadata  
 list\_cparchive\_files  
 start\_background\_package  
 toggle\_user\_backup\_status  
 cPHulk  
 cphulk\_statuses  
 create\_cphulk\_record  
 delete\_cphulk\_record  
 disable\_cphulk  
 enable\_cphulk  
 flush\_cphulk\_login\_history

```

    "status": "200"
  }
}

```

**Note:**  
Use WHM's *API Shell* interface (WHM >> Home >> Development >> API Shell) to directly test WHM API calls.

## Parameters

| Parameter | Type   | Description   | Possible values | Example                |
|-----------|--------|---|-----------------|------------------------|
| url       | string | <b>Required</b><br>The website that you wish to access. | A valid URL.    | http://www.example.com |

## Returns

| Return  | Type   | Description                            | Possible values | Example                          |
|---------|--------|--|-----------------|----------------------------------|
| content | string | The URL's content.<br><br><b>Note:</b> | A valid string. | <a href="#">Click to view...</a> |

• WHM API 1 Functions - get\_application\_contact\_event\_importance — This function retrieves the importance level of an application event for WHM's *Contact Manager* interface (Home >> Server Controls >> Contact Manager).

flush\_cphulk  
\_login\_histo  
ry\_for\_ips  
  
get\_countrie  
s\_with\_kno  
wn\_ip\_rang  
es  
  
get\_cphulk\_  
brutes  
  
get\_cphulk\_  
excessive\_b  
rutes  
  
get\_cphulk\_  
failed\_logins  
  
get\_cphulk\_  
user\_brutes  
  
load\_cphulk  
\_config  
  
read\_cphulk  
\_records  
  
save\_cphulk  
\_config  
  
set\_cphulk\_  
config\_key

▼ Databases

background  
\_mysql\_upg  
rade\_status  
  
current\_mys  
ql\_version  
  
installable\_  
mysql\_versi  
ons  
  
latest\_availa  
ble\_mysql\_v  
ersion  
  
list\_databas  
e\_users  
  
list\_databas  
es  
  
list\_mysql\_d  
atabases\_a  
nd\_users  
  
remote\_mys  
ql\_create\_pr  
ofile  
  
remote\_mys  
ql\_create\_pr  
ofile\_via\_ss  
h  
  
remote\_mys  
ql\_delete\_pr  
ofile  
  
remote\_mys  
ql\_initiate\_p  
rofile\_activat

• W  
e  
s  
t  
r  
o  
n  
g  
l  
y  
r  
e  
c  
o  
m  
m  
e  
n  
d  
t  
h  
a  
t  
y  
o  
u  
c  
o  
n  
f  
i  
r  
m  
t  
h  
e  
c  
o  
n  
t  
e  
n  
t  
,  
s  
t  
y  
p  
e  
b  
e  
f  
o  
r  
e  
y  
o  
u  
u  
s  
e  
t  
h  
e  
r  
e  
t  
u  
r  
n  
v  
a  
l  
u  
e  
.

ion  
remote\_mysql\_monitor\_profile\_activation  
remote\_mysql\_read\_profile  
remote\_mysql\_read\_profiles  
remote\_mysql\_update\_profile  
remote\_mysql\_validate\_profile  
rename\_mysql\_database  
rename\_mysql\_user  
rename\_postgresql\_database  
rename\_postgresql\_user  
set\_local\_mysql\_root\_password  
set\_mysql\_password  
set\_postgresql\_password  
start\_background\_mysql\_upgrade

▼ DNS

addns  
addzonerecord  
addzonerecord (Reverse DNS)  
dumpzone  
editzonerecord  
get\_nameserver\_config  
getzonerecord  
has\_local\_authority

• The function may also return this value in the \_c\_p\_r\_e\_d\_i\_r\_e\_c\_t\_s\_a\_r\_r\_a\_y\_o\_f\_h\_a\_s\_h\_e\_s.

|  |  |  |   |
|--|--|--|---|
| killdns<br>listmxs<br>listzones<br>lookupnsip<br>lookupnsips<br>removezone<br>record<br>resetzone<br>resolvedom<br>ainname<br>savemxs<br>setresolvers<br>update_nam<br>eservers_co<br>nfig<br><br>▼ EasyApache<br>ea4_get_cur<br>rently_install<br>ed_package<br>s<br><br>ea4_get_ea<br>_pkgs_state<br><br>ea4_list_pro<br>files<br><br>ea4_metainf<br>o<br><br>ea4_migrati<br>on<br><br>ea4_pre_mi<br>grate_check<br><br>ea4_recom<br>mendations<br><br>ea4_save_p<br>rofile<br><br>ea4_tomcat<br>85_add<br><br>ea4_tomcat<br>85_list<br><br>ea4_tomcat<br>85_rem<br><br>▼ Greylisting<br>cpgreylist_is<br>_server_net<br>block_truste<br>d<br><br>cpgreylist_li<br>st_entries_f<br>or_common<br>_mail_provid<br>er<br><br>cpgreylist_lo<br>ad_common<br>_mail_provid | _cp_redirect<br>s<br><br>array of hashes | An array<br>redirects that<br>the website<br>performs, if any<br>exist.<br><br><div style="border: 1px solid black; padding: 5px;"> <p><b>Note</b></p> <ul style="list-style-type: none"> <li>This<br/> returns<br/> the<br/> count<br/> of<br/> redirects.</li> <li>This<br/> returns<br/> a<br/> list<br/> of<br/> domains<br/> for<br/> which<br/> only<br/> one<br/> redirect<br/> exists.</li> </ul> </div> | <ul style="list-style-type: none"> <li>If redirects<br/> exist, an ar<br/> ray of<br/> hashes<br/> that<br/> contains<br/> the conte<br/> nt, prot<br/> ocol, re<br/> ason, st<br/> atus, su<br/> ccess,<br/> and url re<br/> turns and<br/> the head<br/> ers hash.</li> <li>null —<br/> Redirects<br/> do not<br/> exist.</li> </ul><br><div style="border: 1px solid black; padding: 5px;"> <p><b>Note</b></p> <p>The<br/> JSON<br/> exam<br/> ple<br/> out<br/> put<br/> abo<br/> ve<br/> dis<br/> play<br/> s<br/> th<br/> is<br/> con<br/> di<br/> tion.</p> </div> |
|--|--|--|---|



ers\_config  
 cpgreylist\_s  
 ave\_commo  
 n\_mail\_provi  
 ders\_config  
 cpgreylist\_st  
 atus  
 cpgreylist\_tr  
 ust\_entries\_  
 for\_common  
 \_mail\_provid  
 er  
 cpgreylist\_u  
 ntrust\_entrie  
 s\_for\_comm  
 on\_mail\_pro  
 vider  
 create\_cpgr  
 eylist\_truste  
 d\_host  
 delete\_cpgr  
 eylist\_truste  
 d\_host  
 disable\_cpgr  
 eylist  
 enable\_cpgr  
 eylist  
 load\_cpgreyl  
 ist\_config  
 read\_cpgrey  
 list\_deferred  
 \_entries  
 read\_cpgrey  
 list\_trusted\_  
 host  
 save\_cpgrey  
 list\_config  
  
 Integration  
 batch  
 cpanel  
 create\_integ  
 ration\_group  
 create\_integ  
 ration\_link  
 get\_integrati  
 on\_link\_user  
 \_config  
 list\_integrati  
 on\_groups  
 list\_integrati  
 on\_links  
 remove\_inte  
 gration\_grou  
 p  
 remove\_inte

|  |          |         |  |   |                        |
|--|----------|---------|--|---|------------------------|
|  | reason   | string  | <p>The response that the server returned.</p> <p>If redirects exist, the function returns this value in the <code>_cp_redirects</code> array of hashes.</p>                | A valid string.   | OK                     |
|  | url      | string  | <p>The URL that provided the response.</p> <p>If redirects exist, the function returns this value in the <code>_cp_redirects</code> array of hashes.</p>                   | A valid URL.  | http://www.example.com |
|  | headers  | hash    | <p>A hash of the header fields that the request returned.</p> <p>If redirects exist, the function returns this hash in the <code>_cp_redirects</code> array of hashes.</p> | <p>A hash of valid header fields.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p><b>Note</b><br/>: This hash's returns vary based on the URL's headers.</p> </div> |                        |
|  | protocol | string  | <p>The URL's HTTP protocol.</p> <p>If redirects exist, the function returns this value in the <code>_cp_redirects</code> array of hashes.</p>                              | A valid HTTP protocol.  | HTTP/1                 |
|  | success  | Boolean | <p>Whether the function returned a 2XX HTTP status code.</p> <p>If redirects exist, the function returns this value in the <code>_cp_redirects</code> array of hashes.</p> | <ul style="list-style-type: none"> <li>• 1 — Success.</li> <li>• 0 — Failure.</li> </ul>  | 1                      |
|  | status   | string  | <p>The response's HTTP status code.</p> <p>If redirects exist, the function returns this value in the <code>_cp_redirects</code> array of hashes.</p>                      | A valid HTTP status code.   | 200                    |

gration\_link

update\_inte  
gration\_link  
\_token

▼ IP Addresses

addips

delip

get\_public\_i  
p

get\_shared\_  
ip

ipv6\_disable  
\_account

ipv6\_enable  
\_account

ipv6\_range\_  
add

ipv6\_range\_  
edit

ipv6\_range\_  
list

ipv6\_range\_  
remove

ipv6\_range\_  
usage

listips

nat\_checkip

nat\_set\_pub  
lic\_ip

setsiteip

▼ Mail

disable\_dki  
m

disable\_mail  
\_sni

emailtrack\_s  
earch

emailtrack\_s  
tats

emailtrack\_u  
ser\_stats

enable\_dkim

enable\_mail  
\_sni

ensure\_dki  
m\_keys\_exi  
st

exim\_config  
uration\_che  
ck

expunge\_m

ailbox\_messages  
expunge\_messages\_for\_mailbox\_guid  
fetch\_dkim\_private\_keys  
fetch\_mail\_queue  
generate\_mobileconfig  
get\_mailbox\_status  
get\_mailbox\_status\_list  
get\_unique\_recipient\_count\_per\_sender\_for\_user  
get\_unique\_sender\_recipient\_count\_per\_user  
get\_user\_email\_forward\_destination  
hold\_outgoing\_email  
install\_dkim\_private\_keys  
install\_spf\_records  
is\_sni\_supported  
list\_pops\_for  
mail\_sni\_status  
rebuild\_mail\_sni\_config  
release\_outgoing\_email  
save\_spamd\_config  
set\_user\_email\_forward\_destination  
suspend\_outgoing\_email  
unsuspend\_outgoing\_email

validate\_currency\_installed\_exim\_configuration

validate\_currency\_dkims

validate\_currency\_ptrs

validate\_currency\_spfs

validate\_exim\_configuration\_syntax

▼ Market

disable\_market\_provider

enable\_market\_provider

get\_adjusted\_market\_providers\_products

get\_market\_providers\_commission\_config

get\_market\_providers\_list

get\_market\_providers\_product\_metadata

get\_market\_providers\_products

set\_market\_product\_attribute

set\_market\_provider\_commission\_id

▼ ModSecurity™

modsec\_add\_rule

modsec\_add\_vendor

modsec\_assemble\_config\_text

modsec\_batch\_settings

modsec\_check\_rule

modsec\_clone\_rule

modsec\_de  
ploy\_all\_rule  
\_changes

modsec\_de  
ploy\_rule\_ch  
anges

modsec\_de  
ploy\_setting  
s\_changes

modsec\_dis  
able\_rule

modsec\_dis  
able\_vendor

modsec\_dis  
able\_vendor  
\_configs

modsec\_dis  
able\_vendor  
\_updates

modsec\_dis  
card\_all\_rul  
e\_changes

modsec\_dis  
card\_rule\_c  
hanges

modsec\_edit  
\_rule

modsec\_en  
able\_vendor

modsec\_en  
able\_vendor  
\_configs

modsec\_en  
able\_vendor  
\_updates

modsec\_get  
\_config\_text

modsec\_get  
\_configs

modsec\_get  
\_configs\_wit  
h\_changes\_  
pending

modsec\_get  
\_log

modsec\_get  
\_rules

modsec\_get  
\_settings

modsec\_get  
\_vendors

modsec\_is\_i  
nstalled

modsec\_ma  
ke\_config\_a  
ctive

modsec\_make\_config\_inactive

modsec\_preview\_vendor

modsec\_remove\_rule

modsec\_remove\_setting

modsec\_remove\_vendor

modsec\_report\_rule

modsec\_set\_config\_text

modsec\_set\_setting

modsec\_disable\_rule

modsec\_update\_vendor

▼ Packages

\_getpkgextensionform

add\_override\_features\_for\_user

addpkg

addpkgext

changepackage

create\_feature\_relist

delete\_feature\_relist

delpkgext

editpkg

get\_available\_applications

get\_available\_featurelists

get\_feature\_metadata

get\_feature\_names

get\_featurelist\_data

get\_featureli

sts

get\_users\_f  
eatures\_sett  
ings

getfeaturelis  
t

getpkginfo

killpkg

listpkgs

manage\_fea  
tures

matchpkgs

read\_feature  
list

remove\_ove  
rride\_feature  
s\_for\_user

update\_feat  
urelist

verify\_user\_  
has\_feature

▼ PHP

convert\_all\_  
domains\_to  
\_fpm

get\_fpm\_co  
unt\_and\_util  
ization

is\_conversio  
n\_in\_progre  
ss

php\_get\_def  
ault\_accoun  
ts\_to\_fpm

php\_get\_ha  
ndlers

php\_get\_im  
pacted\_dom  
ains

php\_get\_ins  
talled\_versio  
ns

php\_get\_old  
\_fpm\_flag

php\_get\_sys  
tem\_default  
\_version

php\_get\_vh  
osts\_by\_ver  
sion

php\_get\_vh  
ost\_versions

php\_ini\_get  
\_content

php\_ini\_get  
\_directives

php\_ini\_set  
\_content

php\_ini\_set  
\_directives

php\_set\_def  
ault\_accoun  
ts\_to\_fpm

php\_set\_ha  
ndler

php\_set\_old  
\_fpm\_flag

php\_set\_ses  
sion\_save\_p  
ath

php\_set\_sys  
tem\_default  
\_version

php\_set\_vh  
ost\_versions

▼ Resellers

acctcounts

get\_public\_c  
ontact

getresellerip  
s

listacIs

listresellers

resellerstats

saveacllist

set\_public\_c  
ontact

setacIs

setresellerip  
s

setresellerli  
mits

setresellerm  
ainip

setresellern  
ameservers

setresellerp  
ackagelimit

setupreselle  
r

suspendres  
eller

terminateres  
eller

unsetuprese



ller

unsuspendr  
eseller

▼ RPM

delete\_rpm\_  
version

edit\_rpm\_ve  
rsion

get\_rpm\_ver  
sion\_data

install\_rpm\_  
plugin

list\_rpms

package\_m  
anager\_fixc  
ache

package\_m  
anager\_get\_  
build\_log

package\_m  
anager\_get\_  
package\_inf  
o

package\_m  
anager\_is\_p  
erforming\_a  
ctions

package\_m  
anager\_list\_  
packages

package\_m  
anager\_reso  
lve\_actions

package\_m  
anager\_sub  
mit\_actions

package\_m  
anager\_upgr  
ade

uninstall\_rp  
m\_plugin

▼ Script Hooks

delete\_hook

edit\_hook

list\_hooks

reorder\_hoo  
ks

▼ Security

accesshash

authorizessh  
key

check\_remo  
te\_ssh\_conn  
ection

convertopen  
sshtoputty

deletesshke  
y

fetch\_securi  
ty\_advice

generatessh  
keypair

importsshke  
y

listsshkeys

▼ Server

Administration

add\_configcl  
usterserver

configureba  
ckgroundpro  
cesskiller

configureser  
vice

cors\_proxy\_  
get

create\_user  
\_session

delete\_confi  
gclusterserv  
er

enable\_mon  
itor\_all\_ena  
bled\_service  
s

get\_all\_cont  
act\_importa  
nces

get\_appconf  
ig\_applicatio  
n\_list

get\_applicati  
on\_contact\_  
event\_import  
tance

get\_applicati  
on\_contact\_  
importance

get\_availabl  
e\_profiles

get\_current\_  
profile

get\_passwor  
d\_strength

get\_remote\_  
access\_has  
h

get\_service\_  
config

get\_service\_  
config\_key

get\_tcp4\_so  
ckets

get\_tcp6\_so  
ckets

get\_tweakse  
tting

get\_udp4\_s  
ockets

get\_udp6\_s  
ockets

get\_update\_  
availability

get\_users\_li  
nks

getdiskusag  
e

gethostname

is\_role\_ena  
bled

list\_configcl  
usterservers

loadavg

nvget

nvset

personalizati  
on\_get

personalizati  
on\_set

purchase\_a  
\_license

reboot

remove\_in\_  
progress\_ex  
im\_config\_e  
dit

restartservic  
e

restore\_conf  
ig\_from\_file

restore\_conf  
ig\_from\_upl  
oad

run\_cpkeyclt

send\_test\_p  
osturl

send\_test\_p  
ushbullet\_n  
ote

servicestatu

s

set\_applicati  
on\_contact\_  
event\_imp  
ortance

set\_applicati  
on\_contact\_  
importance

set\_primary  
\_servernam  
e

set\_service\_  
config\_key

set\_tweakse  
tting

sethostname

setminimum  
passwordstr  
engths

start\_profile  
\_activation

system\_nee  
ds\_reboot

systemloada  
vg

update\_conf  
igclusterserv  
er

update\_cont  
act\_email

verify\_aim\_a  
ccess

verify\_icq\_a  
ccess

verify\_oscar  
\_access

verify\_postu  
rl\_access

verify\_pushb  
ullet\_access

▼ SSL

disable\_aut  
ossl

fetch\_servic  
e\_ssl\_comp  
onents

fetch\_ssl\_ce  
rtificates\_for  
\_fqdns

fetch\_ssl\_vh  
osts

fetch\_vhost  
\_ssl\_compo  
nents

fetchcrtinfo  
fetchsslinfo  
generatessl  
get\_autossl  
\_check\_schedule  
get\_autossl  
\_log  
get\_autossl  
\_logs\_catalog  
get\_autossl  
\_metadata  
get\_autossl  
\_pending\_queue  
get\_autossl  
\_pending\_queue\_for\_domain  
get\_autossl  
\_pending\_queue\_for\_user  
get\_autossl  
\_problems\_for\_domain  
get\_autossl  
\_problems\_for\_user  
get\_autossl  
\_providers  
get\_best\_ssl  
domain\_for\_service  
install\_service\_ssl\_certificate  
installssl  
listcrts  
rebuildinstall  
edssldb  
rebuildusers  
sldb  
reset\_autossl\_provider  
reset\_service\_ssl\_certificate  
set\_autossl\_metadata  
set\_autossl\_metadata\_key

set\_autossl\_  
provider

start\_autossl\_  
check\_for\_  
all\_users

start\_autossl\_  
check\_for\_  
one\_user

▼ Styles and Themes

generate\_cp  
anel\_plugin

list\_styles

load\_style

remove\_log  
o

remove\_styl  
e

save\_style

set\_default

▼ Support Tickets

ticket\_creat  
e\_stub\_ticke  
t

ticket\_get\_s  
upport\_agre  
ement

ticket\_get\_s  
upport\_info

ticket\_grant

ticket\_list

ticket\_remov  
e\_closed

ticket\_revok  
e

ticket\_ssh\_t  
est

ticket\_ssh\_t  
est\_start

ticket\_updat  
e\_service\_a  
greement\_a  
pproval

ticket\_valida  
te\_oauth2\_c  
ode

ticket\_whitel  
ist\_check

ticket\_whitel  
ist\_setup

ticket\_whitel  
ist\_unsetup

▼ Transfers

abort\_transf  
er\_session

analyze\_tra  
nsfer\_sessio  
n\_remote

available\_tr  
ansfer\_mod  
ules

create\_remo  
te\_root\_tran  
sfer\_session

create\_remo  
te\_user\_tran  
sfer\_session

delete\_accou  
nt\_archives

enqueue\_tra  
nsfer\_item

fetch\_transf  
er\_session\_l  
og

get\_transfer  
\_session\_st  
ate

pause\_trans  
fer\_session

remote\_basi  
c\_credential  
\_check

retrieve\_tran  
sfer\_session  
\_remote\_an  
alysis

start\_transfe  
r\_session

transfer\_mo  
dule\_schem  
a

validate\_sys  
tem\_user

▼ Updates

accept\_eula

get\_availabl  
e\_tiers

get\_current\_  
lts\_expiratio  
n\_status

get\_lts\_wex  
pire

getlongterm  
support

installed\_ver  
sions

set\_cpanel\_  
updates

set\_tier

update\_upd  
ateconf

version