

UAPI Functions - Brand::read

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup:
Backup::fullbacku
p_to_ftp

Backup::fullbacku
p_to_homedir

Backup::fullbacku
p_to_scp_with_key

Backup::fullbacku
p_to_scp_with_pa
ssword

Backup::list_back
ups

Bandwidth

Bandwidth::get_e
nabled_protocols

Bandwidth::get_re
tention_periods

Bandwidth::query

Batch

Batch::strict

Brand

Brand::read

Branding

Branding::file

Branding::get_app
lications

Branding::get_app
lication_informati
on

Branding::get_ava
ilable_applications

Branding::get_info
rmation_for_applic
ations

Description

This function retrieves the cPanel account's branding information. For more information, read our [Customization](#) documentation.

Note:

cPanel accounts that do not use the Paper Lantern theme, or that use Paper Lantern without configured branding information, return blank values.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.exam  
ple.com:2083/cpsess##  
#####/execute/Brand/  
read
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Get Paper Lantern  
branding settings.  
$pl_branding =  
$cpanel->uapi(  
    'Brand', 'read'  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

Function information

About this module

The Brand module accesses branding data.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

▼ cPanel Template Toolkit

```
<!-- Get a hash of all the data, then display the company_name value. -->
[% data = execute('Brand', 'read'); %]
[% FOREACH q = data.company_name %]
    <p>
        [% q %]
    </p>
[% END %]

<!-- Get only the company name. -->
[% execute('Brand', 'read').data.company_name %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

- UAPI Functions -

- Brand:read — This function retrieves the cPanel account's branding information.

- UAPI Modules -

- Branding — The Branding module accesses cPanel's theming system.

- UAPI Functions - Branding:file

- This function retrieves a branding file's path.

Email: browse_mailbox
Email: change_mx
Email: check_fastmail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_domain_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_hidden_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_opt
Email: get_auto_responder
Email: get_chase

Command Line

```
uapi --user=username  
Brand read
```

Notes:

- You **must** [URI-encode](#) values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin/uapi
```

- UAPI Functions - Branding: :get_application_information - This function retrieves an application's information from the dynamic interface file.

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaintext_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {

  },
  "data": {
    "company_name":
    "Hosting Company,
    Inc.",
    "display_company_name": 1,
    "webmail_display_company_name": 1,
    "documentation_url":
    "http://www.hostingcompany.com/docs",
    "help_url":
    "http://www.hostingcompany.com/support",
    "cpanel_logo":
    "logo.svg",
    "cpanel_logo_small":
    "logo_small.svg",
    "webmail_logo":
    "webmail.svg"
  }
}
```

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

This function does not accept parameters.

Returns

ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

EmailAuth:: ensure_dkim_keys_exist

Return	Type	Description	Possible values	Example
company_name	string	The company name. This name appears in the top left corner of the branded cPanel interface.	<ul style="list-style-type: none">A string value.An empty string.	Hosting Company, Inc.
display_company_name	Boolean	Whether the cPanel interface displays the company_name value or a logo in the branded cPanel interface.	<ul style="list-style-type: none">1 — Display the company_name value.0 — Display the company's logo.	1
webmail_display_company_name	Boolean	Whether the Webmail interface displays the company_name value or a logo in the branded Webmail interface. Note : We added this return in cPanel & WHM version 60.	<ul style="list-style-type: none">1 — Display the company_name value.0 — Display the company's logo.	1
documentation_url	string	The company's documentation URL. The <i>Documentation</i> link uses this URL in branded cPanel interfaces.	<ul style="list-style-type: none">A valid URL.An empty string.	http://www.hostingcompany.com/docs

<p>EmailAuth:: fetch_dkim_private_keys</p> <p>EmailAuth:: install_dkim_private_keys</p> <p>EmailAuth:: install_spf_records</p> <p>EmailAuth:: validate_current_dkims</p> <p>EmailAuth:: validate_current_ptrs</p> <p>EmailAuth:: validate_current_spfs</p> <p>ExternalAuthentication</p> <p>ExternalAuthentication:: add_auth_link</p> <p>ExternalAuthentication:: configured_modules</p> <p>ExternalAuthentication:: get_auth_links</p> <p>ExternalAuthentication:: has_external_auth_modules_configured</p>	<p>help_url</p> <p>string</p>	<p>The company's support URL.</p> <p>In cPanel & WHM version 11.48 and earlier, the <i>Help</i> link uses this URL in branded cPanel interfaces.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note :</p> <p>In cPanel & WHM version 11.50 and later, we removed the <i>Help</i> link from the cPanel interface.</p> </div>	<ul style="list-style-type: none"> • A valid URL. • An empty string. 	<p>http://www.hostingcompany.com/support</p>
<p>ExternalAuthentication:: remove_authn_link</p> <p>Features</p> <p>Features:: get_feature_metadata</p> <p>Features:: has_feature</p> <p>Features:: list_features</p> <p>Fileman</p> <p>Fileman:: autocompletedir</p> <p>Fileman:: empty_trash</p> <p>Fileman:: get_file_content</p> <p>Fileman:: get_file_information</p> <p>Fileman:: list_files</p> <p>Fileman:: save_file_content</p> <p>Fileman:: transcode</p> <p>Fileman:: upload_files</p>	<p>cpanel_logo</p> <p>string</p>	<p>The filename of the logo file that displays in the cPanel interface.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note :</p> <p>We added this return in cPanel & WHM version 60.</p> </div>	<ul style="list-style-type: none"> • logo.svg • logo.png 	<p>logo.svg</p>

▼ Ftp

- Ftp:: add_ftp
- Ftp:: allows_anonymous_ftp
- Ftp:: allows_anonymous_ftp_incoming
- Ftp:: delete_ftp
- Ftp:: ftp_exists
- Ftp:: get_ftp_daemon_info
- Ftp:: get_port
- Ftp:: get_quota
- Ftp:: get_welcome_message
- Ftp:: kill_session
- Ftp:: list_ftp
- Ftp:: list_ftp_with_disk
- Ftp:: list_sessions
- Ftp:: passwd
- Ftp:: server_name
- Ftp:: set_anonymous_ftp
- Ftp:: set_anonymous_ftp_incoming
- Ftp:: set_homedir
- Ftp:: set_quota
- Ftp:: set_welcome_message

<p>cpanel_logo_small</p>	<p><i>string</i></p>	<p>The filename of the small logo file that displays in the cPanel interface.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this return in cPanel & WHM version 60.</p> </div>	<ul style="list-style-type: none"> • logo_small.svg • logo_small.png 	<p>logo_small.svg</p>
<p>webmail_logo</p>	<p><i>string</i></p>	<p>The filename of the logo file that displays in the Webmail interface.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : We added this return in cPanel & WHM version 60.</p> </div>	<ul style="list-style-type: none"> • webmail.svg • webmail.png 	<p>webmail.svg</p>

▼ Integration

- Integration:: fetch_url

▼ KnownHosts

- KnownHosts:: create
- KnownHosts:: delete
- KnownHosts:: update
- KnownHosts:: verify

▼ LangPHP

- LangPHP:: php_get_domain_handler
- LangPHP:: php_get_impacted_domains
- LangPHP:: php_get_installed_version

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

Market:: get_provi
der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

ModSecurity:: has
_modsecurity_inst
alled

ModSecurity:: list_
domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_
note

Mysql :: check_dat
abase

Mysql:: create_dat
abase

Mysql:: create_use
r

Mysql:: delete_dat
abase

Mysql:: delete_hos
t

Mysql:: delete_use
r

Mysql:: get_host_n
otes

Mysql:: get_privile
ges_on_database

Mysql:: get_restrict
ions

Mysql:: get_server_
information

Mysql:: locate_ser
ver

Mysql:: rename_d
atabase

Mysql:: rename_us
er

Mysql:: repair_dat
abase

Mysql:: revoke_ac
cess_to_database

Mysql:: set_passw
ord

Mysql:: set_privile
ges_on_database

▼ Notifications

Notifications:: get_
notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_rel
ative_uri

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start