

WHM API 0 Functions - setupreseller

Guide to WHM API 0

Return Data

accounts
summary

applist

createacct

domainuser
data

editquota

limitbw

listaccts

listsuspend
ed

modifyacct

myprivs

passwd

removeacct

showbw

suspendacct

unsuspenda
acct

▼ DNS

adddns

addzonerec
ord

dumpzone

editzonerec
ord

getzonereco
rd

killdns

listzones

lookupnsip

lookupnsips

removezone
record

resetzone

setresolvers

▼ IP Addresses

addip

Description

This function grants reseller status to an account.

Note:

This function grants reseller status to an **existing** account. You **cannot** create a new account with this function.

Examples

▼ JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/setupreseller?user=username&makeowner=0
```

▼ XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/setupreseller?user=username&makeowner=0
```

Function information

About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

Warning: WHM API 0 is deprecated. We strongly recommend using WHM API 1.

- delip
- listips
- setsiteip
- deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_dockey
 - purge_mail_queue
 - remove_in_progress_exim_configuration_dit
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_config
 - validate_exim_configuration_syntax
 - addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
 - acccounts
 - getresellers
 - listaccls
 - listresellers
 - resellerstats
 - saveacclist
 - setaccls

Command Line

```
whmapi0 setupreseller
user=username
makeowner=0
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local
/cpanel/bin/whmapi0
```

Output (JSON)

```
{
  "result": [
    {
      "status": 1,
      "statusmsg": null
    }
  ]
}
```

Output (XML)

```
<setupreseller>
  <result>

  <status>1</status>

  <statusmsg/>
</result>
</setupreseller>
```

Parameters

Notes:

- Scro
- Yomius
- 20
- or
- 20
-)tc

Find a function

- WHM API 0 Functions - acctcounts — This function lists a reseller's total accounts, suspended accounts, and account creation limit.

setresellerips
 setresellerlimits
 setresellermainip
 setresellernameservers
 setresellerpackagelimit
 setupreseller

suspendreseller
 terminatereseller
 unsetupreseller
 unsuspendreseller

Server

Administration

configureserver
 gethostname
 getlanglist
 loadavg
 nvget
 nvset
 reboot
 restartservice
 servicestatus
 sethostname

SSL

fetchsslinfo
 generatessl
 installssl
 listcerts

Updates

get_available_tiers
 set_cpanel_updates
 set_tier
 version

Parameter	Type	Description	Possible values	Example
user	string	Required The account's username.	A valid username on the server.	username
makeowner	Boolean	Whether to set the account to own itself. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Make the account own itself. 0 — Keep the account's current owner. 	0

Returns

Return	Type	Description	Possible values	Example
result	array of hashes	An array of hashes of function output.	This hash includes the status and statusmsg returns.	
status	Boolean	Whether the function succeeded. The function returns this value in the result hash.	<ul style="list-style-type: none"> 1 — Success. 0 — Failure. 	1
statusmsg	string	A message of success or a reason for failure. The function returns this value in the result hash.	<ul style="list-style-type: none"> null An error message. 	null

- WHM API 0 Functions - getresellerips — This function lists a reseller's available IP addresses.
- WHM API 0 Functions - listaccls — This function lists the reseller's Access Control Lists (ACLs) and each list's privileges.

- WHM API 0 Functions - listresellers — This function lists the reseller accounts on the server.