

# WHM API 0 Functions - getlanglist

## Guide to WHM API 0

Return Data

## Description

This function lists your server's available languages.

## Examples

### Accounts

#### JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/getlanglist
```

#### XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/getlanglist
```

#### Command Line

```
whmapi0 getlanglist
```

#### Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local  
/cpanel/bin/whmapi0
```

#### Output (JSON)

```
{  
  "lang": [  
    "arabic",  
  
    "brazilian-portuguese
```

## Function information

## About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

**Warning:**  
WHM API 0 is deprecated.  
We strongly recommend using WHM API 1.

- accounts summary
- applist
- createacct
- domainuserdata
- editquota
- limitbw
- listaccts
- listsuspended
- modifyacct
- myprivs
- passwd
- removeacct
- showbw
- suspendacct
- unsuspendacct
- ▼ DNS
  - adddns
  - addzonerecord
  - dumpzone
  - editzonerecord
  - getzonerecord
  - killdns
  - listzones
  - lookupnsip
  - lookupnsips
  - removezone record
  - resetzone
  - setresolvers
- ▼ IP Addresses
  - addip

- delip
- listips
- setsiteip
- ▼ Mail
  - deliver\_mail\_queue
  - deliver\_messages\_mail\_queue
  - exim\_configuration\_check
  - fetch\_dockey
  - purge\_mail\_queue
  - remove\_in\_progress\_exim\_configuration\_dit
  - remove\_messages\_mail\_queue
  - unfreeze\_messages\_mail\_queue
  - validate\_current\_installed\_exim\_config
  - validate\_exim\_configuration\_syntax
- ▼ Packages
  - addpkg
  - changepackage
  - editpkg
  - getfeaturelist
  - killpkg
  - listpkgs
- ▼ Resellers
  - acctcounts
  - getresellers
  - listacls
  - listresellers
  - resellerstats
  - saveacllist
  - setacls

```

-utf8",
  "chinese",
  "dutch-utf8",
  "english",
  "english-utf8",
  "french",
  "french-utf8",
  "german",
  "german-utf8",

  "iberian_spanish",
  "japanese",
  "portuguese",

  "portuguese-utf8",
  "russian",
  "spanish",
  "spanish-utf8",

  "spanish_latinamerica"
],
  "themes":{

  "paper_lantern":{

  "french-utf8":1,

  "english-utf8":1,

  "japanese":1,
    "german":1,

  "german-utf8":1,
    "chinese":1,
    "french":1,

  "portuguese-utf8":1,

  "spanish-utf8":1,
    "russian":1,
    "english":1,
    "spanish":1,

  "dutch-utf8":1,
    "arabic":1,

  "iberian_spanish":1,

  "brazilian-portuguese-utf8":1,

  "portuguese":1

```

**Notes:**

- Scro
- Yomius
- 20 or 20 )tc

**Find a function**

- WHM API 0 Functions - getlanglist - This function lists your server's available languages.

- setresellerips
- setresellerlimits
- setresellermainip
- setreselleramazonipservers
- setresellerpackagelimit
- setupreseller
- suspendreseller
- terminatereseller
- unsetupreseller
- unsuspendreseller
- Server Administration
    - configureserver
    - gethostname
    - getlanglist
    - loadavg
    - nvget
    - nvset
    - reboot
    - restartservice
    - servicestatus
    - sethostname
  - SSL
  - fetchsslinfo
    - generatessl
    - installssl
    - listcerts
  - Updates
  - get\_available\_tiers
    - set\_cpanel\_updates
    - set\_tier
    - version

```

    },
    "/" : {
        "portuguese" : 1,
        "brazilian-portuguese-utf8" : 1,
        "spanish_latinamerica" : 1,
        "dutch-utf8" : 1,
            "arabic" : 1,
        "iberian_spanish" : 1,
            "english" : 1,
            "spanish" : 1,
        "spanish-utf8" : 1,
            "russian" : 1,
        "german-utf8" : 1,
            "chinese" : 1,
            "french" : 1,
        "portuguese-utf8" : 1,
            "german" : 1,
        "french-utf8" : 1,
        "english-utf8" : 1,
            "japanese" : 1
    }

```

- WHM API 0 Functions - loadavg — This function retrieves the server's load average.
- WHM API 0 Functions - reboot — This function reboots the server.
- WHM API 0 Functions - sethostname — This function changes the server's hostname.

```
}  
  }  
}
```

#### ▼ Output (XML)

```
<getlanglist>  
  
<lang>arabic</lang>  
  
<lang>brazilian-portu  
guese-utf8</lang>  
  
<lang>chinese</lang>  
  
<lang>dutch-utf8</lan  
g>  
  
<lang>english</lang>  
  
<lang>english-utf8</l  
ang>  
  
<lang>french</lang>  
  
<lang>french-utf8</la  
ng>  
  
<lang>german</lang>  
  
<lang>german-utf8</la  
ng>  
  
<lang>iberian_spanish  
</lang>  
  
<lang>japanese</lang>  
  
<lang>portuguese</lan  
g>  
  
<lang>portuguese-utf8  
</lang>  
  
<lang>russian</lang>  
  
<lang>spanish</lang>  
  
<lang>spanish-utf8</l  
ang>
```

```
<lang>spanish_latinam
erica</lang>
  <themes>

<name>/</name>

<arabic>1</arabic>

<brazilian-portuguese
-utf8>1</brazilian-po
rtuguese-utf8>

<chinese>1</chinese>

<dutch-utf8>1</dutch-
utf8>

<english>1</english>

<english-utf8>1</engl
ish-utf8>

<french>1</french>

<french-utf8>1</frenc
h-utf8>

<german>1</german>

<german-utf8>1</germa
n-utf8>

<iberian_spanish>1</i
berian_spanish>

<japanese>1</japanese
>

<portuguese>1</portug
uese>

<portuguese-utf8>1</p
ortuguese-utf8>

<russian>1</russian>

<spanish>1</spanish>

<spanish-utf8>1</span
ish-utf8>

<spanish_latinamerica
>1</spanish_latinamer
```

```
ica>
  </themes>
  <themes>

  <name>paper_lantern</
name>

  <arabic>1</arabic>

  <brazilian-portuguese
-utf8>1</brazilian-po
rtuguese-utf8>

  <chinese>1</chinese>

  <dutch-utf8>1</dutch-
utf8>

  <english>1</english>

  <english-utf8>1</engl
ish-utf8>

  <french>1</french>

  <french-utf8>1</frenc
h-utf8>

  <german>1</german>

  <german-utf8>1</germa
n-utf8>

  <iberian_spanish>1</i
berian_spanish>

  <japanese>1</japanese
>

  <portuguese>1</portug
uese>

  <portuguese-utf8>1</p
ortuguese-utf8>

  <russian>1</russian>

  <spanish>1</spanish>

  <spanish-utf8>1</span
```

```
ish-utf8>
  </themes>
</getlanglist>
```

## Parameters

This function does not accept parameters.

## Returns

Return	Type	Description	Possible values	Example
<code>getlanglist</code>	<i>hash</i>	A hash of the server's languages.	This hash includes the <code>lang</code> array and the <code>themes hash</code> .	
<code>lang</code>	<i>array</i>	A list of available languages.  The function returns this array in the <code>getlanglist hash</code> .	A valid language name.	<code>english</code>
<code>themes</code>	<i>hash</i>	A hash of the server's themes.  The function returns this hash in the <code>getlanglist hash</code> .	This hash includes the <code>theme name hash</code> .	

<p>theme name</p>	<p><i>hash</i></p>	<p>A theme's name (paper_lantern or the name of another theme on the server).</p> <div data-bbox="732 296 870 638" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p><b>Note</b> : The theme's name is the parameter name.</p> </div> <p>The function returns this hash in the theme hash.</p>	<p>This hash includes the character name return.</p>	
	<p><del>Boolean</del> set name</p>	<p>Whether the theme possesses a character set.</p> <div data-bbox="732 884 870 1247" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p><b>Note</b> : The character set's name is the parameter name.</p> </div> <p>The function returns this value in the name hash.</p>	<ul style="list-style-type: none"> <li>• 1 — Available.</li> </ul>	<p>1</p>