

WHM API 0 Functions - reboot

Guide to WHM API 0

Return Data

Description

This function reboots the server.

Examples

Accounts

accounts
ummary

applist

createacct

domainuser
data

editquota

limitbw

listaccts

listsuspende
d

modifyacct

myprivs

passwd

removeacct

showbw

suspendacct

unsuspenda
acct

▼ DNS

adddns

addzonerec
ord

dumpzone

editzonerec
ord

getzonereco
rd

killdns

listzones

lookupnsip

lookupnsips

removezone
record

resetzone

setresolvers

▼ IP Addresses

addip

Func tion infor mati on

About t WHM API 0

WHM
API 0
performs
functions
and
accesses
data in
WHM.

Warning:
WHM API 0
deprecat
. We strong

- delip
- listips
- setsiteip
- deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_doc_key
 - purge_mail_queue
 - remove_in_progress_exim_configuration_dit
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_config
 - validate_exim_configuration_syntax
- addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
- acccounts
 - getresellerrips
 - listacts
 - listresellers
 - resellerstats
 - saveacllist
 - setacts

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/reboot?force=0
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/reboot?force=0
```

Command Line

```
whmapi0 reboot force=0
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local/cpanel/bin/whmapi0
```

Output (JSON)

```
{
  "reboot": "normal"
}
```

Output (XML)

```
<reboot>
<reboot>normal</reboot>
```

Notes:

- Scro
- You must use 20 or 20) t

Find a function

- WHM API 0 Functions - getlanglist - This function lists your server's available languages.

setresellerips

setresellerlimits

setresellermainip

setresellernameservers

setresellerpackagelimit

setupreseller

suspendreseller

terminatereseller

unsetupreseller

unsuspendreseller

Server Administration

Administration

configureSERVICE

gethostname

getlanglist

loadavg

nvget

nvset

reboot

restartSERVICE

SERVICESTATUS

sethostname

SSL

fetchsslinfo

generatessl

installssl

listcerts

Updates

get_available_tiers

set_cpanel_updates

set_tier

version

Parameters

Parameter	Type	Description	Possible values	Example
force	Boolean	Whether to use a forceful reboot. Warning: A forceful reboot may result in data loss if there are active processes.	<ul style="list-style-type: none"> 1 — Use a forceful reboot. 0 — Do not use a forceful reboot. 	0

Returns

Return	Type	Description	Possible values	Example
reboot	string	The server's hostname.	normal	normal

- WHM API 0 Functions - loadavg — This function retrieves the server's load average.
- WHM API 0 Functions - reboot — This function reboots the server.
- WHM API 0 Functions - sethostname — This function changes the server's hostname.

