

WHM API 0 Functions - listsuspended

Guide to WHM API 0

Return Data

Description

This function lists suspended accounts on the server.

Examples

Accounts

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/listsuspended
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/listsuspended
```

Command Line

```
whmapi0 listsuspended
```

Notes:

- You **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 0](#) documentation or run the `whmapi0 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapi0` command:

```
/usr/local  
/cpanel/bin/whmapi0
```

Function information

About WHM API 0

WHM API 0 performs functions and accesses data in WHM.

Warning:
WHM API 0 is deprecated.
We strongly recommend using WHM API 1.

- accounts summary
- applist
- createacct
- domainuser data
- editquota
- limitbw
- listaccts
- listsuspended
- modifyacct
- myprivs
- passwd
- removeacct
- showbw
- suspendacct
- unsuspendacct
- ▼ DNS
 - adddns
 - addzonerecord
 - dumpzone
 - editzonerecord
 - getzonerecord
 - killdns
 - listzones
 - lookupnsip
 - lookupnsips
 - removezone record
 - resetzone
 - setresolvers
- ▼ IP Addresses
 - addip


- delip
- listips
- setsiteip
- deliver_mail_queue
 - deliver_messages_mail_queue
 - exim_configuration_check
 - fetch_doc_key
 - purge_mail_queue
 - remove_in_progress_exim_configuration_dit
 - remove_messages_mail_queue
 - unfreeze_messages_mail_queue
 - validate_current_installed_exim_configuration
 - validate_exim_configuration_syntax
 - addpkg
 - changepackage
 - editpkg
 - getfeaturelist
 - killpkg
 - listpkgs
 - acccounts
 - getresellers
 - listacls
 - listresellers
 - resellerstats
 - saveacllist
 - setacls

Output (JSON)

```
{
  "status":1,
  "statusmsg":"Ok",
  "accts":[
    {
      "reason":"Unknown",
      "unixtime":1242056074,
      "owner":"user123",
      "user":"user123",
      "is_locked":"0",
      "time":"Mon May 11 10:34:34 2009"
    }
  ]
}
```

Output (XML)

```
<listsuspended>
  <accts>
    <owner>user123</owner>
    <reason>Late Payment</reason>
    <time>Wed May 20 14:51:02 2009</time>
    <is_locked>0</is_locked>
    <unixtime>1242849062</unixtime>
    <user>user123</user>
  </accts>
  <status>1</status>
  <statusmsg>Ok</statusmsg>
</listsuspended>
```



Notes:

- Scro
- Yomius
- 20 or 20)tc

Find a function

- WHM API 0 Functions - account summary - This function retrieves a user's account summary.

setresellerips

setresellerlimits

setresellermainip

setreselleramazonserver

setresellerpackagelimit

setupreseller

suspendreseller

terminatereseller

unsetupreseller

unsuspendreseller

Server

Administration

configureSERVICE

gethostname

getlanglist

loadavg

nvget

nvset

reboot

restartSERVICE

SERVICESTATUS

sethostname

SSL

fetchsslinfo

generatessl

installssl

listcerts

Updates

get_available_tiers

set_cpanel_updates

set_tier

version

Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
accts	array of hashes	A hash of suspended account data.	This hash includes the owner, reason, time, unixtime, user, and is_locked returns.	
owner	string	The account's owner. The function returns this value in the accts hash.	<ul style="list-style-type: none"> root A reseller's username. The account's username. 	owner_username
reason	string	The reason why the account is suspended, if one exists. The function returns this value in the accts hash.	A valid string.	Suspended for nonpayment.
time	string	The current date and time. The function returns this value in the accts hash.	<p>The date in YYYY-MM-DD HH-mm-SS human-readable format, where:</p> <ul style="list-style-type: none"> YYYY represents the year. MM represents the month. DD represents the date. HH represents the hour. mm represents the minute. SS represents the second. 	Thu Nov 18 10:34:34 2014
unixtime	integer	The current date and time. The function returns this value in the accts hash.	A date in Unix time format.	1416306874

- WHM API 0 Functions - domainuserdata — This function retrieves domain data.
- WHM API 0 Functions - editquota — This function modifies a user's disk quota.
- WHM API 0 Functions - limitbandwidth — This function modifies a cPanel account's bandwidth quota.

user	<i>string</i>	<p>The account's username.</p> <p>The function returns this value in the <code>accounts</code> hash.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note : This return only appears in cPanel & WHM version 11.40+.</p> </div>	A valid cPanel username.	username
is_locked	<i>Boolean</i>	<p>Whether the account is locked.</p> <p>The function returns this value in the <code>accounts</code> hash.</p>	<ul style="list-style-type: none"> • 1 — Locked. • 0 — Not locked. 	0
status	<i>Boolean</i>	<p>Whether the system successfully called the function.</p>	<ul style="list-style-type: none"> • 1 — Success. • 0 — Failure. 	1
statusmsg	<i>string</i>	<p>A message of success or a reason for failure.</p>	<ul style="list-style-type: none"> • Ok • An error message. 	Ok