

WHM API 1 Functions - modsec_report_rule

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Description

This function submits ModSecurity™ rule error reports to a remote receiver. The third party rule vendors use these error reports to identify problems with their rule sets.

Important:

In cPanel & WHM version 76 and later, when you disable the `WebServerRole`, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/modsec_report_rule?api.version=1&send=1&email=john.doe%40example.com&type=false%20positive&message=Hi.%20We%27re%20having%20some%20trouble%20with%20this%20rule.%20It%20seems%20to%20be%20blocking%20all%20requests.&row_ids=794828
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/modsec_report_rule?api.version=1&send=1&email=john.doe%40example.com&type=false%20positive&message=Hi.%20We%27re%20having%20some%20trouble%20with%20this%20rule.%20It%20seems%20to%20be%20blocking%20all%20requests.&row_ids=794828
```

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_my.cnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

Command Line

```
whmapil  
modsec_report_rule  
send=1  
email=john.doe%40example.com type=false  
positive  
message=\"Hi. We're  
having some trouble  
with this rule. It  
seems to be blocking  
all requests.  
row_ids=794828\"
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Output (JSON)

```
{  
  "data": {  
    "report": {  
      "email":  
"john.doe@example.com",  
      "hits": [  
        {  
          "meta_id":  
"12345694",  
          "ip":  
"10.215.215.236",  
          "http_version":  
"HTTP/1.1",
```

Notes:

- Scro
- Yc

Find a function

- WHM API 1 Functions - modsec_add_rule - This function adds a new rule to a Mod Security™ configuration staging file.

```

_id
verify_new_
username
  Addon Domains
convert_add
on_fetch_co
nversion_de
tails
convert_add
on_fetch_do
main_details
convert_add
on_get_con
version_stat
us
convert_add
on_initiate_c
onversion
convert_add
on_list_add
on_domains
convert_add
on_list_conv
ersions
  Authentication
api_token_c
reate
api_token_li
st
api_token_r
evoke
api_token_u
pdate
disable_aut
hentication_
provider
disable_faili
ng_authenti
cation_provi
ders
enable_auth
entication_p
rovider
get_availabl
e_authentic
ation_provid
ers
get_login_ur
l
get_provider
_client_confi
gurations
get_provider
_configurati
on_fields
get_provider
_display_co

```

```

"meta_line": "1",
"timestamp":
"2014-12-04
17:34:35",
"meta_uri": null,
"id": "794828",
"http_method": "GET",
"http_status": "406",
"timezone": "-360",
"meta_file":
"/usr/local/apache/co
nf/modsec_vendor_conf
igs/MyVendor/one.conf
",
"action_desc":
"Access denied with
code 406 (phase 2).",
"meta_logdata": null,
"path": "/something",
"host": "xtext1.tld",
"handler": null,
"meta_offset": "0",
"meta_rev": null,
"justification":
"Unconditional match
in SecAction.",
"meta_severity":
null,
"meta_msg": null
    }
  ],
"rule_text":
"SecAction
\"deny,auditlog,id:'1
2345694'\n",

```

- WHM API 1 Functions - modsec_add_vendor — This function adds a new ModSecurity™ vendor rule set to the server.
- WHM API 1 Functions - modsec_batch_settings — This function adds, updates, and removes global ModSecurity™ configuration directives.

nfigurations
get_users_authn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer
twofactorauth_get_user_configs
twofactorauth_policy_status
twofactorauth_remove_user_config
twofactorauth_set_issuer
twofactorauth_set_tfa_config
unlink_user_authn_provider
validate_login_token

▼ Backups

backup_config_get
backup_config_set
backup_data_list
backup_destination_add
backup_destination_delete

```
      "type":  
      "false positive",  
  
      "message": "Hi. We're  
      having some trouble  
      with this rule. It  
      seems to be blocking  
      all requests."  
    }  
  },  
  "metadata": {  
    "version": 1,  
    "reason":  
    "OK",  
    "result": 1,  
    "command":
```

- WHM API 1 Functions - modsec_clone_rule - This function copies a Mod Security™ rule with a new rule ID.

backup_destination_get
backup_destination_list
backup_destination_set
backup_destination_validate
backup_get_transport_status
backup_list_transported
backup_set_list
backup_set_list_combined
backup_skip_users_all
backup_skip_users_all_status
backup_user_list
convert_and_migrate_from_legacy_config
get_users_with_backup_metadata
list_cparchive_files
start_background_package
toggle_user_backup_status
cPHulk
cphulk_statuses
create_cphulk_record
delete_cphulk_record
disable_cphulk
enable_cphulk
flush_cphulk_login_history

```
"modsec_report_rule"  
  }  
}
```

Output (XML)

```
<result>  
  <data>  
    <report>  
  
    <email>john.doe@example.com</email>  
      <hits>  
  
    <meta_id>12345694</meta_id>  
  
    <ip>10.215.215.236</ip>  
  
    <http_version>HTTP/1.1</http_version>  
  
    <meta_line>1</meta_line>  
  
    <timestamp>2014-12-04 17:34:35</timestamp>  
  
    <meta_uri/>  
  
    <id>794828</id>  
  
    <http_method>GET</http_method>  
  
    <http_status>406</http_status>  
  
    <timezone>-360</timezone>  
  
    <meta_file>  
    /usr/local/apache/conf/modsec_vendor_configs/MyVendor/one.conf  
    </meta_file>  
  
    <action_desc>Access denied with code 406 (phase
```

flush_cphulk_login_history_for_ips
get_countries_with_known_ip_ranges
get_cphulk_brutes
get_cphulk_excessive_brutes
get_cphulk_failed_logins
get_cphulk_user_brutes
load_cphulk_config
read_cphulk_records
save_cphulk_config
set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status
current_mysql_version
installable_mysql_versions
latest_available_mysql_version
list_database_users
list_databases
list_mysql_databases_and_users
remote_mysql_create_profile
remote_mysql_create_profile_via_ssh
remote_mysql_delete_profile
remote_mysql_initiate_profile_activation

```
2).</action_desc>
<meta_logdata/>
<path>/something</path>
<host>xtext1.tld</host>
<handler/>
<meta_offset>0</meta_offset>
<meta_rev/>
<justification>Unconditional match in SecAction.</justification>
<meta_severity/>
<meta_msg/>
    </hits>
<rule_text>SecAction "deny,auditlog,id:'12345694'"</rule_text>
<type>>false positive</type>
    <message>
Hi. We're having some trouble with this rule. It seems to be blocking all requests.
    </message>
    </report>
    </data>
    <metadata>
<version>1</version>
<reason>OK</reason>
<result>1</result>
<command>modsec_repor
```

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

```
t_rule</command>
</metadata>
</result>
```

Note:
 Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameters	Type	Description	Possible values	Example
row_ids	integer	Required The MySQL® row IDs from the <code>hits</code> table in the <code>modsec_d</code> database for the audit log event to report.	A comma-separated list of positive integers. Note : If you specify more than one row ID:	794828

▼ DNS

adddns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

• Y
o
u
m
u
s
t
c
o
m
m
a
-
s
e
p
a
r
a
t
e
t
h
e
r
u
l
e
f
i
e
l
d
s
.

ers_config
 cpgreylis
 ave_commo
 n_mail_provi
 ders_config
 cpgreylis_st
 atus
 cpgreylis_tr
 ust_entries_
 for_common
 _mail_provid
 er
 cpgreylis_u
 ntrust_entrie
 s_for_comm
 on_mail_pro
 vider
 create_cpgr
 eylist_truste
 d_host
 delete_cpgr
 eylist_truste
 d_host
 disable_cpgr
 eylist
 enable_cpgr
 eylist
 load_cpgrey
 list_config
 read_cpgrey
 list_deferred
 _entries
 read_cpgrey
 list_trusted_
 host
 save_cpgrey
 list_config

Integration

batch
 cpanel
 create_integ
 ration_group
 create_integ
 ration_link
 get_integrati
 on_link_user
 _config
 list_integrati
 on_groups
 list_integrati
 on_links
 remove_integ
 ration_grou
 p
 remove_inte

			<ul style="list-style-type: none"> The ID must allow correspondence to the same ModSecurity rule ID. 	
message	string	Required A short message that explains the reason for the report.	A valid string. <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> Note : You should write this message. </div>	Click to view... "Hi. We're having some trouble with this rule. It seems to be blocking all requests".

gration_link
 update_inte
 gration_link
 _token

▼ IP Addresses

addips
 delip
 get_public_i
 p
 get_shared_
 ip
 ipv6_disable
 _account
 ipv6_enable
 _account
 ipv6_range_
 add
 ipv6_range_
 edit
 ipv6_range_
 list
 ipv6_range_
 remove
 ipv6_range_
 usage
 listips
 nat_checkip
 nat_set_pub
 lic_ip
 setsiteip

email	<i>string</i>	Required The contact email address to send with the error report, to allow the rule's vendor to reply to the user directly.	A valid email address.	john.doe@example.com
type	<i>string</i>	Required The report's type.	A valid string. <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;">Note : This value does not use a specified format. Treat the value as freeform text.</div>	false positive
send	<i>Boolean</i>	Required Whether the function sends the report to the rule's vendor.	<ul style="list-style-type: none"> • 1 — Send the report. • 0 — Do not send the report. 	1

▼ Mail

disable_dkim
 disable_mail_sni
 emailtrack_search
 emailtrack_stats
 emailtrack_user_stats
 enable_dkim
 enable_mail_sni
 ensure_dkim_keys_exist
 exim_configuration_check
 expunge_m

Returns

Return	Type	Description	Possible values	Example
report	<i>array of hashes</i>	An array of hashes of information for the report that the function sends, or would send if you set the send value to 1.	Each hash includes the email, rule_text, type, and message returns and the hits array.	
email	<i>string</i>	The contact email address to send with the error report, to allow the rule's vendor to reply to the report directly. The function returns this value in the report array.	A valid email address.	john.doe@example.com

ailbox_messages
 expunge_messages_for_mailbox_guid
 fetch_dkim_private_keys
 fetch_mail_queue
 generate_mobileconfig
 get_mailbox_status
 get_mailbox_status_list
 get_unique_recipient_count_per_sender_for_user
 get_unique_sender_recipient_count_per_user
 get_user_email_forwarded_destination
 hold_outgoing_email
 install_dkim_private_keys
 install_spf_records
 is_sni_supported
 list_pops_for_mail_sni_status
 rebuild_mail_sni_config
 release_outgoing_email
 save_spamd_config
 set_user_email_forwarded_destination
 suspend_outgoing_email
 unsuspend_outgoing_email

hits	array	<p>An array that contains information about the hit.</p> <p>The function returns this array in the report array.</p>	<p>This array includes the meta_id, id, ip, http_version, meta_line, timestamp, meta_uri, http_method, http_status, timezone, meta_file, action_desc, meta_logdata, path, host, handler, meta_offset, meta_rev, justification, meta_severity, and meta_msg returns.</p>	
meta_id	integer	<p>The ID of the ModSecurity rule that triggered the log entry.</p> <p>The function returns this value in the hits array.</p>	<p>A valid ModSecurity ID.</p>	12345694
id	integer	<p>The modsec database line number.</p> <p>The function returns this value in the hits array.</p>	<p>A positive integer.</p>	794828
ip	integer	<p>The client's IP address.</p> <p>The function returns this value in the hits array.</p>	<p>A valid IP address.</p>	10.215.215.236
http_version	string	<p>The HTTP version number.</p> <p>The function returns this value in the hits array.</p>	<p>A valid string.</p>	HTTP/1.1
meta_line	integer	<p>The line number of the ModSecurity rule that triggered the log entry.</p> <p>The function returns this value in the hits array.</p>	<p>A positive integer.</p>	1

<p>validate_current_installeg</p> <p>validate_current_dkims</p> <p>validate_current_ptrs</p> <p>validate_current_spfs</p> <p>validate_exim_configuration_syntax</p> <p>▼ Market</p> <p>disable_market_provider</p> <p>enable_market_provider</p> <p>get_adjusted_market_providers_products</p> <p>get_market_providers_commission_config</p> <p>get_market_providers_list</p> <p>get_market_providers_product_metadata</p> <p>get_market_providers_products</p> <p>set_market_product_attribute</p> <p>set_market_provider_commission_id</p> <p>▼ ModSecurity™</p> <p>modsec_added_rule</p> <p>modsec_added_vendor</p> <p>modsec_ensemble_config_text</p> <p>modsec_batch_settings</p> <p>modsec_check_rule</p> <p>modsec_close_rule</p>	<p>t i m e s t a m p</p> <p>m e t a - u r i</p> <p>h t t p - m e t h o d</p>	<p>string</p> <p>string</p> <p>string</p>	<p>The time at which the log entry was made.</p> <p>The function returns this value in the hits array.</p> <p>The client-requested URI.</p> <p>The function returns this value in the hits array.</p> <p>The HTTP method that the client used to generate the hit.</p> <p>The function returns this parameter in the hits array.</p>	<p>A valid date in YYYY-MM-DD HH:mm:ss format:</p> <ul style="list-style-type: none"> • YYYY represents the year • MM represents the month • DD represents the day • HH represents the hour • mm represents the minute • DD represents the day. <p>Note : This parameter uses the server's configured time zone.</p> <p>A valid URI.</p> <p>Note : This data is not always available.</p> <p>A valid HTTP method.</p>	<p>2014-10-13 07:58:04</p> <p>null</p> <p>GET</p>
--	--	---	--	---	---

[modsec_deploy_all_rule_changes](#)
[modsec_deploy_rule_changes](#)
[modsec_deploy_settings_changes](#)
[modsec_disable_rule](#)
[modsec_disable_vendor](#)
[modsec_disable_vendor_configs](#)
[modsec_disable_vendor_updates](#)
[modsec_discard_all_rules_changes](#)
[modsec_discard_rule_changes](#)
[modsec_edit_rule](#)
[modsec_enable_vendor](#)
[modsec_enable_vendor_configs](#)
[modsec_enable_vendor_updates](#)
[modsec_get_config_text](#)
[modsec_get_configs](#)
[modsec_get_configs_with_changes_pending](#)
[modsec_get_log](#)
[modsec_get_rules](#)
[modsec_get_settings](#)
[modsec_get_vendors](#)
[modsec_is_installed](#)
[modsec_make_config_active](#)

modsec_deploy_all_rule_changes modsec_deploy_rule_changes modsec_deploy_settings_changes	h t t p - s t a t u s	<i>integer</i>	<p>The HTTP status code that the web server returned.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid HTTP status code.	406
modsec_disable_rule modsec_disable_vendor modsec_disable_vendor_configs	t i m e z o n e	<i>integer</i>	<p>The server's configured timezone.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid timezone bias, in minutes difference from UTC/GMT.	-300
modsec_disable_vendor_updates modsec_discard_all_rules_changes modsec_discard_rule_changes	m e t a - f i l e	<i>string</i>	<p>The ModSecurity configuration file that contains the rule that triggered the log entry.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid file path and name.	Click to view... <code>/usr/local/apache/conf/modsec_vendor_configs/MyVendor/one.conf</code>
modsec_edit_rule modsec_enable_vendor modsec_enable_vendor_configs	a c t i o n - d e s c	<i>string</i>	<p>The web server's response to the client.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid string.	Click to view... Access denied with code 406 (phase 2).
modsec_enable_vendor_updates modsec_get_config_text modsec_get_configs modsec_get_configs_with_changes_pending	m e t a - l o g d a t a	<i>string</i>	<p>The transaction data fragment from the ModSecurity rule's logdata action.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid string.	null
modsec_get_log modsec_get_rules	p a t h	<i>string</i>	<p>The accessed file's path.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid file path and name, relative to the document root.	/something
modsec_get_settings modsec_get_vendors	h o s t	<i>string</i>	<p>The virtual host's domain name.</p> <p>The function returns this value in the <code>hits</code> array.</p>	A valid hostname.	xtest1.tld

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_featurelist

delete_featurelist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featureli

h a n d l e r	string	This parameter only returns null. The function returns this value in the hits array.	null	null
m e t a - o f f s e t	integer	The byte offset at which a match occurred within the target data. The function returns this value in the hits array.	A valid integer. Note : This data is not always available.	0
m e t a - r e v	integer	The revision number from the ModSecurity rule's revision. The function returns this value in the hits array.	A positive integer.	1
j u s t i f i c a t i o n	string	The specific criteria from the ModSecurity rule that generated the hit. The function returns this value in the hits array.	A valid string.	▼ Click to view... Unconditional match in SecAction.
m e t a - s e v e r i t y	string	The hit severity level from the ModSecurity rule's severity action. The function returns this value in the hits array.	A valid string.	CRITICAL
m e t a - m s g	string	The human-readable message from the ModSecurity rule's msg action. The function returns this value in the hits array.	A valid string.	▼ Click to view... Method is not allowed by policy

sts
 get_users_features_settings
 getfeaturelist
 getpkginfo
 killpkg
 listpkgs
 manage_features
 matchpkgs
 read_featurelist
 remove_override_features_for_user
 update_featurelist
 verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm
 get_fpm_count_and_utilization
 is_conversion_in_progress
 php_get_default_accounts_to_fpm
 php_get_handlers
 php_get_implicit_domains
 php_get_installed_versions
 php_get_old_fpm_flag
 php_get_system_default_version
 php_get_versions_by_version
 php_get_versions
 php_ini_get_content

rule_text	string	The rule text from the configuration file. The function returns this value in the report array.	A valid string.	deny,auditlog,id:'12345694'\n\n
type	string	The report's type. The function returns this value in the report array.	A valid string. Note : This value does not use a specified format. Treat the value as freeform text.	false positive
message	string	A short message that explains the reason for the report. The function returns this value in the report array.	A valid string.	▼ Click to view... Hi. We're having some trouble with this rule. It seems to be blocking all requests.

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autoss_
provider

start_autoss
l_check_for_
all_users

start_autoss
l_check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version