

WHM API 1 Functions - generate_mobileconfig

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

- Account Restoration
- restore_modules_summary
- restore_queue_activate
- restore_queue_add_task
- restore_queue_clear_all_completed_tasks
- restore_queue_clear_all_failed_tasks
- restore_queue_clear_all_pending_tasks
- restore_queue_clear_all_tasks
- restore_queue_clear_completed_task
- restore_queue_clear_pending_task
- restore_queue_is_active
- restore_queue_list_active
- restore_queue_list_completed
- restore_queue

Description

This function generates a mobile configuration profile for an email account.

Important:

In cPanel & WHM version 76 and later, when you disable the MailReceive role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/generate_mobileconfig?api.version=1&account=username%40example.com&use_ssl=1
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/generate_mobileconfig?api.version=1&account=username@example.com&use_ssl=1
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Sc
- ro
- us
- Yc
- mi
- us
- 20
- or
- 20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnfor_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

Command Line

```
whmapil  
generate_mobileconfig  
account=username%40example.com use_ssl=1
```

Notes:

- Unless otherwise noted, you **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Output (JSON)

```
{  
  "data": {  
  
    "payload": "0\u00119\u0006\t*H\r\u0001\u0007\u0002\u0011*0\u0011&\u0002\u0001\u0001\u000b0\t\u0006\u0005+\u000e\u0003\u0002\u0001a\u0005\u0000\u000bB\u0006\t*H\r\u0001\u0007\u0001\u000b3\u0004\u000b/<?xml  
version=\"1.0\"  
encoding=\"UTF-8\"?>\r\n<!DOCTYPE plist  
PUBLIC  
\"-//Apple//DTD PLIST  
1.0//EN\"  
\"http://www.apple.com/DTDs/PropertyList-1.0.dtd\">\r\n<plist  
version=\"1.0\">\r\n<dict>\r\n<key>PayloadContent</  
key>\r\n  <array>\r\n
```

Find a function

- WHM API 1 Functions - email tracking - This function retrieves email delivery records.
- WHM API 1 Functions - email tracking status - This function retrieves email tracking statistics.

_id

verify_new_username

▼ Addon Domains

convert_addon_fetch_conversion_details

convert_addon_fetch_domain_details

convert_addon_get_conversion_status

convert_addon_initiate_conversion

convert_addon_list_addon_domains

convert_addon_list_conversions

▼ Authentication

api_token_create

api_token_list

api_token_revoke

api_token_update

disable_authentication_provider

disable_failing_authentication_providers

enable_authentication_provider

get_available_authentication_providers

get_login_url

get_provider_client_configurations

get_provider_configuration_fields

get_provider_display_co

```
<dict>\r\n
<key>EmailAccountDescription</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>EmailAccountName</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>EmailAccountType</key>\r\n
<string>EmailTypeIMAP</string>\r\n
<key>EmailAddress</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>IncomingMailServerAuthentication</key>\r\n
<string>EmailAuthPassword</string>\r\n
<key>IncomingMailServerHostName</key>\r\n
<string>laurence.dev.cpanel.net</string>\r\n
<key>IncomingMailServerPortNumber</key>\r\n
<integer>993</integer>\r\n
<key>IncomingMailServerUseSSL</key>\r\n
<true/>\r\n
<key>IncomingMailServerUsername</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>OutgoingMailServerAuthentication</key>\r\n
<string>EmailAuthPassword</string>\r\n
<key>OutgoingMailServerHostName</key>\r\n
<string>laurence.dev.cpanel.net</string>\r\n
\r\n
```

- WHM API 1 Functions - email_tracking_stats — This function retrieves email tracking statistics for each user.
- WHM API 1 Functions - expunge_messages_for_mailbox_guid — This function removes mail messages from a cPanel account.

nfigurations
get_users_authn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer
twofactorauth_get_user_configs
twofactorauth_policy_status
twofactorauth_remove_user_config
twofactorauth_set_issuer
twofactorauth_set_tfa_config
unlink_user_authn_provider
validate_login_token

▼ Backups

backup_config_get
backup_config_set
backup_date_list
backup_destination_add
backup_destination_delete

```
<key>OutgoingMailServerPortNumber</key>\r\n
<integer>465</integer>\r\n
<key>OutgoingMailServerUseSSL</key>\r\n
<true/>\r\n
<key>OutgoingMailServerUsername</key>\r\n
<string>mister.bad@example.com</string>\r\n
<key>OutgoingPasswordSameAsIncomingPassword</key>\r\n
<true/>\r\n
<key>PayloadDescription</key>\r\n
<string>username@example.com Secure Email Setup</string>\r\n
<key>PayloadDisplayName</key>\r\n
<string>username@example.com Secure Email Setup</string>\r\n
<key>PayloadIdentifier</key>\r\n
<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
<key>PayloadOrganization</key>\r\n
<string>example.com</string>\r\n
<key>PayloadType</key>\r\n
<string>com.apple.mail.managed</string>\r\n
<key>PayloadUUID</key>\r\n
<string>6de23f78-a548-8c49-b060-4c4dd39c5db0</string>\r\n
<key>PayloadVersion</key>\r\n
<integer>1</integer>\r\n
<key>PreventAppSheet</key>\r\n
<false/>\r\n
```

backup_destination_get
backup_destination_list
backup_destination_set
backup_destination_validate
backup_get_transport_status
backup_list_transported
backup_set_list
backup_set_list_combined
backup_skip_users_all
backup_skip_users_all_status
backup_user_list
convert_and_migrate_from_legacy_config
get_users_with_backup_metadata
list_cparchive_files
start_background_package
toggle_user_backup_status
▼ cPHulk
cphulk_statuses
create_cphulk_record
delete_cphulk_record
disable_cphulk
enable_cphulk
flush_cphulk_login_history

```
<key>PreventMove</key>
>\r\n
<false/>\r\n
<key>SMIMEEnabled</key>
>\r\n
<false/>\r\n
</dict>\r\n
</array>\r\n
<key>PayloadDescription</key>\r\n
<string>mister.bad@example.com Secure
Email
Setup</string>\r\n
<key>PayloadDisplayName</key>\r\n
<string>mister.bad@example.com Secure
Email
Setup</string>\r\n
<key>PayloadIdentifier</key>\r\n
<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
<key>PayloadOrganization</key>\r\n
<string>cpanel.mail.org.mister.bad.example.com</string>\r\n
<key>PayloadRemovalDisallowed</key>\r\n
<false/>\r\n
<key>PayloadType</key>
>\r\n
<string>Configuration</string>\r\n
<key>PayloadUUID</key>
>\r\n
<string>3e259e6f-8edf-0041-7554-c6f0a4585f87</string>\r\n
<key>PayloadVersion</key>\r\n
<integer>1</integer>\r\n
</dict>\r\n</plist>
>\r\n\u0003o0\u0003k0\u0002S\u0003\u0002\u0001\u0002\u0002\u0005\u00022;`0\r\u0006\t*H\r\u0001\u0001\u0005\u0005\u0000N10\u001e\u0006\u0003U\
```

flush_cphulk
_login_histo
ry_for_ips

get_countrie
s_with_kno
wn_ip_rang
es

get_cphulk_
brutes

get_cphulk_
excessive_b
rutes

get_cphulk_
failed_logins

get_cphulk_
user_brutes

load_cphulk
_config

read_cphulk
_records

save_cphulk
_config

set_cphulk_
config_key

▼ Databases

background
_mysql_upg
rade_status

current_mys
ql_version

installable_
mysql_versi
ons

latest_availa
ble_mysql_v
ersion

list_databas
e_users

list_databas
es

list_mysql_d
atabases_a
nd_users

remote_mys
ql_create_pr
ofile

remote_mys
ql_create_pr
ofile_via_ss
h

remote_mys
ql_delete_pr
ofile

remote_mys
ql_initiate_p
rofile_activat

u0004\u0003\xf\u0017la
urence.dev.cpanel.net
1*0(\u0006\t*H\r\u000
1\t\u0001\u0016\u001b
ssl@laurence.dev.cpan
el.net0\u001e\u0017\r
140811190945Z\u0017\r
150811190945Z0N1
0\u001e\u0006\u0003U\
u0004\u0003\xf\u0017la
urence.dev.cpanel.net
1*0(\u0006\t*H\r\u000
1\t\u0001\u0016\u001b
ssl@laurence.dev.cpan
el.net0\u0001\"0\r\u0
006\t*H\r\u0001\u0001
\u0001\u0005\u0000\u0
003\u0001\u000f\u0000
0\u0001\n\u0002\u0001
\u0001\u0000UzVy#%\u0
010A)\u0004%i\$}`/\u00
04a\u0003_\u0017CvGoc
\bH##!(*lhfn0*.VR-8\u
001d\u0019\";\rG\u000
5:\u0007qH[>!Ã^\u0015
qi\u0006\u0014/\u001a
{\u0001YJ0';k|'GWx\u0
01c\u0005sRP/\u0018;K
w'\u001d|7zCy^Q|;\u00
0e\fp^\u000bQ)\fHg)0\
u001ak\u0018M}\u0013\
u0002\u0003\u0001\u00
00\u0001P0N0\u001d\u0
006\u0003U\u001d\u000
e\u0004\u0016\u0004\u
0014V\u0003_\u001eX&v
wk0\u001f\u0006\u0003
U\u001d#\u0004\u00180
\u0016\u0014V\u0003_
u001eX&vwk0\f\u0006\u
0003U\u001d\u0013\u00
04\u00050\u0003\u0001
\u00010\r\u0006\t*H\r
\u0001\u0001\u0005\u0
005\u0000\u0003\u0001
\u0001\u00004.,\b8\u0
007`0+RRH\u0016a\u000
4H[S2{-Y=^\\"u0018A1\
u0010\u0014e\u0004{`E
D|\u000f\u000e%b]AY];
J\u000b\u0000D)n\u001
4\u0000fV23\u001d\u000
b\u0016xIGW%A\u0000j\
\"

ion
remote_mysql_monitor_profile_activation
remote_mysql_read_profile
remote_mysql_read_profiles
remote_mysql_update_profile
remote_mysql_validate_profile
rename_mysql_database
rename_mysql_user
rename_postgresql_database
rename_postgresql_user
set_local_mysql_root_password
set_mysql_password
set_postgresql_password
start_background_mysql_upgrade

▼ DNS

addns
addzonerecord
addzonerecord (Reverse DNS)
dumpzone
editzonerecord
get_nameserver_config
getzonerecord
has_local_authority

u0015Vx\u0012#Qe\fvn\u0013\u0003?&FPk\u0013n\u0000SU51#0
:P~f\u001f-m\u001a5E<H\u0016ZO\nlD\u0019\u001by\u0014\u0005iAca gVfLd1\u0002Y0\u0002U\u0002\u0001\u00010W0N1
0\u001e\u0006\u0003U\u0004\u0003\f\u0017laurence.dev.cpanel.net
1*0(\u0006\t*H\r\u0001\t\u0001\u0016\u001bssl@laurence.dev.cpanel.net\u0002\u0005\u0022;\`0\t\u0006\u0005+\u000e\u0003\u0002\u001a\u0005\u0000\u0018\u0006\t*H\r\u0001\t\u00031\u000b\u0006\t*H\r\u0001\u0007\u0010\u001c\u0006\t*H\r\u0001\t\u00051\u000f\u0017\r150602150437Z0#\u0006\t*H\r\u0001\t\u00041\u0016\u0004\u0014n&\u0010mN\u0002nrA{o\u001e0y\u0006\t*H\r\u0001\t\u000f110j0\u000b\u0006\t`H\u0001e\u0003\u0004\u0001*0\u000b\u0006\t`H\u0001e\u0003\u0004\u0001\u00160\u000b\u0006\t`H\u0001e\u0003\u0004\u0006\u001b*H\r\u0003\u0006\u0001\u0001\u00020\n\u0006\b*H\r\u0003\u0007\u000e\u0006\b*H\r\u0003\u0002\u0002\u0002\u0000\r\u0006\b*H\r\u0003\u0002\u0002\u0001@0\u0007\u0006\u0005+\u000e\u0003\u0002\u00070\r\u0006\b*H\r\u0003\u0002\u0002\u0001(0\r\u0006\t*H\r\u0001\u0001\u0001\u0005\u0000\u0004\u0001\u0000,ju\u001ccCV@OS\r\r\u0004)x#{vD\u0014x>[o\u00188\u0000\b)*\u001f(hIO-^\u001a\$\r\u

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_package
s

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

```
001fn>&$RA\u001eJ+\u0
013DC\u000f\u0004\u00
1a\u0007L@_J|\u0017f\
u0002\u000121'bp6\"#i
8uX\u0019
\u001c\b!]}&\u0003G`\
u000bd[\" \u0015$_u1N\
u0000D\u0018UD\r}*|5$
x/\u001f\f\u0006P}\u0
011XN}w\u0011z[z|,lg*
WM\u001eU!1"
},
"metadata":{
  "version":1,
  "reason":"OK",
  "result":1,
"command":"generate_m
```


ers_config
cpgreylis_t
ave_commo
n_mail_prov
iders_config

cpgreylis_st
atus

cpgreylis_tr
ust_entries_
for_common
_mail_provid
er

cpgreylis_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgrey
list_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte

```
obileconfig"  
  }  
}
```

Output (XML)

```
<result>  
  <data>  
  
    <payload>0\u00119\u00  
06\t*H\r\u0001\u0007\  
u0002\u0011*0\u0011&\  
u0002\u0001\u00011\u0  
00b0\t\u0006\u0005+\u  
000e\u0003\u0002\u001  
a\u0005\u0000\u000bB  
\u0006\t*H\r\u0001\u0  
007\u0001\u000b3\u000  
4\u000b/<?xml  
version=\"1.0\  
encoding=\"UTF-8\"?>\r\n<!DOCTYPE plist  
PUBLIC  
\"-//Apple//DTD PLIST  
1.0//EN\  
\"http://www.apple.co  
m/DTDs/PropertyList-1  
.0.dtd\">\r\n<plist  
version=\"1.0\  
dict>\r\n  <key>PayloadContent</  
key>\r\n  <array>\r\n  <dict>\r\n  <key>EmailAccountDesc  
ription</key>\r\n  <string>mister.bad@ex  
ample.com</string>\r\  
n  
  <key>EmailAccountName  
</key>\r\n  <string>mister.bad@ex  
ample.com</string>\r\  
n  
  <key>EmailAccountType  
</key>\r\n  <string>EmailTypeIMAP  
</string>\r\n  <key>EmailAddress</ke  
y>\r\n  <string>mister.bad@ex  
ample.com</string>\r\  
n
```

gration_link	n
update_inte gration_link _token	<key>IncomingMailServ erAuthentication</key >\r\n
▼ IP Addresses	<string>EmailAuthPass word</string>\r\n
addips	<key>IncomingMailServ erHostName</key>\r\n
delip	<string>laurence.dev. cpanel.net</string>\r \n
get_public_i p	<key>IncomingMailServ erPortNumber</key>\r\ \n
get_shared_ ip	<integer>993</integer >\r\n
ipv6_disable _account	<key>IncomingMailServ erUseSSL</key>\r\n
ipv6_enable _account	<true/>\r\n
ipv6_range_ add	<key>IncomingMailServ erUsername</key>\r\n
ipv6_range_ edit	<string>mister.bad@ex ample.com</string>\r\ \n
ipv6_range_ list	<key>OutgoingMailServ erAuthentication</key >\r\n
ipv6_range_ remove	<string>EmailAuthPass word</string>\r\n
ipv6_range_ usage	<key>OutgoingMailServ erHostName</key>\r\n
listips	<string>laurence.dev. cpanel.net</string>\r \n
nat_checkip	<key>OutgoingMailServ erPortNumber</key>\r\ \n
nat_set_pub lic_ip	<integer>465</integer >\r\n
setsiteip	<key>OutgoingMailServ erUseSSL</key>\r\n
▼ Mail	<true/>\r\n
disable_dki m	<key>OutgoingMailServ erUsername</key>\r\n
disable_mail _sni	<string>mister.bad@ex ample.com</string>\r\ \n
emailtrack_s earch	<key>OutgoingPassword SameAsIncomingPasswor d</key>\r\n
emailtrack_s tats	<true/>\r\n
emailtrack_u ser_stats	<key>PayloadDescripti on</key>\r\n
enable_dkim	
enable_mail _sni	
ensure_dki m_keys_exi st	
exim_config uration_che ck	
expunge_m	

modsec_deploy_all_rule_changes
modsec_deploy_rule_changes
modsec_deploy_setting_s_changes
modsec_disable_rule
modsec_disable_vendor
modsec_disable_vendor_configs
modsec_disable_vendor_updates
modsec_discard_all_rule_e_changes
modsec_discard_rule_changes
modsec_edit_rule
modsec_enable_vendor
modsec_enable_vendor_configs
modsec_enable_vendor_updates
modsec_get_config_text
modsec_get_configs
modsec_get_configs_with_changes_pending
modsec_get_log
modsec_get_rules
modsec_get_settings
modsec_get_vendors
modsec_is_installed
modsec_make_config_active

003\u0001\u000f\u0000
0\u0001\n\u0002\u0001
\u0001\u0000UzVy#%\u0
010A)\u0004%i\$}`/\u00
04a\u0003_\u0017CvGoc
\bH##!(*lhfn0*.VR-8\u
001d\u0019\";\rG\u000
5:\u0007qH[>!Ã^\u0015
qi\u0006\u0014/\u001a
{\u0001YJ0';k|'GWx\u0
01c\u0005sRP/\u0018;K
w'\u001d|7zCy^Q|;\u00
0e\fp^\u000bQ)\fHg)0\
u001ak\u0018M}\u0013\
u0002\u0003\u0001\u00
00\u0001P0N0\u001d\u00
006\u0003U\u001d\u000
e\u0004\u0016\u0004\u0
0014V\u0003_\u001eX&v
wk0\u001f\u0006\u0003
U\u001d#\u0004\u00180
\u0016\u0014V\u0003_\
u001eX&vwk0\f\u0006\u
0003U\u001d\u0013\u00
04\u00050\u0003\u0001
\u00010\r\u0006\t*H\r
\u0001\u0001\u0005\u00
005\u0000\u0003\u0001
\u0001\u00004. ,\b8\u0
007`0+RRH\u0016a\u000
4H[S2{-Y=^\" \u0018A1\
u0010\u0014e\u0004{`E
D|\u000f\u000e%b]AY};
l\u000b\u0000D)n\u001
4\u000fv23\u001d\u000
b\u0016xIGW%A\u0000j\
u0015Vx\u0012#Qe\fvn\
u0013\u0003?&FPk\u001
3n\u0000SU51#0
:P~f\u001f-m\u001a5E<
H\u0016ZO\nlD\u0019\u
001bY\u0014\u0005iAca
gVfLd1\u0002Y0\u0002U
\u0002\u0001\u00010W0
N1
0\u001e\u0006\u0003U\
u0004\u0003\f\u0017la
urence.dev.cpanel.net
1*0(\u0006\t*H\r\u000
1\t\u0001\u0016\u001b
ssl@laurence.dev.cpan
el.net\u0002\u0005\u00
0022;`0\t\u0006\u0005

modsec_ma
ke_config_in
active

modsec_pre
view_vendor

modsec_re
move_rule

modsec_re
move_settin
g

modsec_re
move_vend
or

modsec_rep
ort_rule

modsec_set
_config_text

modsec_set
_setting

modsec_un
disable_rule

modsec_up
date_vendor

▼ Packages

_getpkgexte
nsionform

add_overrid
e_features_
or_user

addpkg

addpkgext

changepack
age

create_featu
relist

delete_featu
relist

delpkgext

editpkg

get_availabl
e_applicatio
ns

get_availabl
e_featurelist
s

get_feature_
metadata

get_feature_
names

get_featureli
st_data

get_featureli

```
+\\u000e\\u0003\\u0002\\u  
001a\\u0005\\u00000\\u00  
18\\u0006\\t*H\\r\\u0001\\  
t\\u00031\\u000b\\u0006\\  
t*H\\r\\u0001\\u0007\\u00  
010\\u001c\\u0006\\t*H\\r  
\\u0001\\t\\u00051\\u000f  
\\u0017\\r150602150437Z  
0#\\u0006\\t*H\\r\\u0001\\  
t\\u00041\\u0016\\u0004\\  
u0014n&\\u0010mN\\u0002  
nrA{o\\u001e0y\\u0006\\t  
*H\\r\\u0001\\t\\u000f110  
j0\\u000b\\u0006\\t`H\\u0  
001e\\u0003\\u0004\\u000  
1*0\\u000b\\u0006\\t`H\\u  
0001e\\u0003\\u0004\\u00  
01\\u00160\\u000b\\u0006  
\\t`H\\u0001e\\u0003\\u00  
04\\u0001\\u00020\\n\\u00  
06\\b*H\\r\\u0003\\u00070  
\\u000e\\u0006\\b*H\\r\\u0  
003\\u0002\\u0002\\u0002  
\\u00000\\r\\u0006\\b*H\\r  
\\u0003\\u0002\\u0002\\u0  
001@0\\u0007\\u0006\\u00  
05+\\u000e\\u0003\\u0002  
\\u00070\\r\\u0006\\b*H\\r  
\\u0003\\u0002\\u0002\\u0  
001(0\\r\\u0006\\t*H\\r\\u  
0001\\u0001\\u0001\\u000  
5\\u0000\\u0004\\u0001\\u  
0000, ]u\\u001cCV@OS\\r\\  
r\\u0004)x#{vD\\u0014x>  
[o\\u00188\\u0000\\b)*\\u  
001f(hIO-^\\u001a$\\r\\u  
001fn>&$RA\\u001eJ+\\u0  
013DC\\u000f\\u0004\\u00  
1a\\u0007L@_J|\\u0017f\\  
u0002\\u000121'bp6\"#i  
8uX\\u0019  
\\u001c\\b! ]}&\\u0003G`\\  
u000bd[\"\\u0015$_u1N\\  
u0000D\\u0018UD\\r}*|5$  
x/\\u001f\\f\\u0006P}\\u0  
011XN}w\\u0011z[z|,lg*  
WM\\u001eU!1</payload>  
    <metadata>  
  
    <version>1</version>  
  
    <reason>OK</reason>
```

sts
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature

▼ PHP

convert_all_domains_to_fpm
get_fpm_count_and_utilization
is_conversion_in_progress
php_get_default_accounts_to_fpm
php_get_handlers
php_get_impacted_domains
php_get_installed_versions
php_get_old_fpm_flag
php_get_system_default_version
php_get_versions_by_version
php_get_versions
php_ini_get_content

<result>1</result>

<command>generate_mob

php_ini_get
 _directives
 php_ini_set
 _content
 php_ini_set
 _directives
 php_set_def
 ault_accoun
 ts_to_fpm
 php_set_ha
 ndler
 php_set_old
 _fpm_flag
 php_set_ses
 sion_save_p
 ath
 php_set_sys
 tem_default
 _version
 php_set_vh
 ost_versions

▼ Resellers

acctcounts
 get_public_c
 ontact
 getresellerip
 s
 listacks
 listresellers
 resellerstats
 saveacllist
 set_public_c
 ontact
 setacks
 setresellerip
 s
 setresellerli
 mits
 setresellerm
 ainip
 setresellerm
 ameservers
 setresellerp
 ackagelimit
 setupreselle
 r
 suspendres
 eller
 terminateres
 eller
 unsetuprese

```


    ileconfig</command>
      </metadata>
    </result>
  
```

Note:
 Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
account	string	Required The email account.	A valid email account.	username@example.com
use_ssl	Boolean	Required Whether to use an SSL-encrypted connection.	<ul style="list-style-type: none"> 1 — Use an SSL-encrypted connection 0 — Do not use an SSL-encrypted connection 	1

Returns

Return	Type	Description	Possible values	Example
payload	binary	The function's raw output.	A valid binary of an Apple® mobile configuration file that contains a series of sub-tags and keys. For more information, read Apple's key reference.	Click to view... 

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transfer_session

analyze_transfer_session_remote

available_transfer_modules

create_remote_root_transfer_session

create_remote_user_transfer_session

delete_account_archives

enqueue_transfer_item

fetch_transfer_session_log

get_transfer_session_state

pause_transfer_session

remote_basic_credential_check

retrieve_transfer_session_remote_analysis

start_transfer_session

transfer_module_schema

validate_system_user

▼ Updates

accept_eula

get_available_tiers

get_current_lts_expiration_status

get_lts_expire

getlongterm support

installed_versions

set_cpanel_updates

set_tier

update_upd
ateconf

version