

WHM API 1 Functions - get_service_config

Guide to WHM API 1

Return Data
Filter Output
Sort Output
Paginate Output
Output Columns
Call cPanel API 2 and UAPI

Account Restoration

restore_modules_summary

restore_queue_activate

restore_queue_add_task

restore_queue_clear_all_completed_tasks

restore_queue_clear_all_failed_tasks

restore_queue_clear_all_pending_tasks

restore_queue_clear_all_tasks

restore_queue_clear_completed_task

restore_queue_clear_pending_task

restore_queue_is_active

restore_queue_list_active

restore_queue_list_completed

Description

This function returns a service's configuration settings.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/get_service_config?api.version=1&service=dovecot
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/get_service_config?api.version=1&service=dovecot
```

Command Line

```
whmapil  
get_service_config  
service=dovecot
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local  
/cpanel/bin/whmapil
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Ycmtus20 or 20)t

restore_queue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

▼ Accounts

accountsummary
applist
createacct
domainuser_data
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct

▼ Output (JSON)

```
{  
  "data": {  
  
    "login_max_processes_count": "50",  
  
    "auth_cache_ttl": "3600",  
  
    "mdbox_rotate_size": "2M",  
  
    "auth_cache_negative_ttl": "3600",  
  
    "ssl_protocols": "!SSLv2 !SSLv3",  
  
    "login_processes_count": "2",  
  
    "mailbox_idle_check_interval": "30",  
  
    "mdbox_rotate_interval": "12w",  
    "ipv6": "on",  
  
    "protocols": "imap pop3",  
  
    "login_process_per_connection": "no",  
  
    "expire_trash_ttl": "30",  
  
    "disable_plaintext_auth": "no",  
  
    "mail_process_size": "256",  
  
    "ssl_cipher_list": "ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE-RSA-AES256-GCM-SHA384:ECDHE-ECDSA-AES256-GCM-SHA384:DHE-RSA-AES128-GCM-SHA256:DHE-DSS
```

Find a function

- WHM API 1 Sections - Server Administration — Server administration functions allow you to manage your server's services and functions.

```

untrack_acct_id
verify_new_username
  v Addon Domains
    convert_addon_fetch_conversion_details
    convert_addon_fetch_domain_details
    convert_addon_get_conversion_status
    convert_addon_initiate_conversion
    convert_addon_list_addon_domains
    convert_addon_list_conversions
  v Authentication
    api_token_create
    api_token_list
    api_token_revoke
    api_token_update
    disable_authentication_provider
    disable_failing_authentication_providers
    enable_authentication_provider
    get_available_authentication_providers
    get_login_url
    get_provider_client_configurations
    get_provider_configuration_fields
    get_provider

```

```

-AES128-GCM-SHA256:kEDH+AESGCM:ECDHE-RSA-AES128-SHA256:ECDHE-ECDSA-AES128-SHA256:ECDHE-RSA-AES128-SHA:ECDHE-ECDSA-AES128-SHA:ECDHE-RSA-AES256-SHA384:ECDHE-ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA:ECDHE-ECDSA-AES256-SHA:DHE-RSA-AES128-SHA256:DHE-RSA-AES128-SHA:DHE-DSS-AES128-SHA256:DHE-RSA-AES256-SHA256:DHE-RSA-AES256-SHA:AES128-GCM-SHA256:AES256-GCM-SHA384:AES128-SHA256:AES256-SHA256:AES128-SHA:AES256-SHA:AES:CAMELLIA:DES-CBC3-SHA:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!PSK:!aECDH:!EDH-DSS-DES-CBC3-SHA:!EDH-RSA-DES-CBC3-SHA:!KRB5-DES-CBC3-SHA",
"max_mail_processes": "512",
"expire_trash": "1",
"protocol_pop3": {
"mail_max_userip_connections": "3"
},
"login_process_size": "64",
"auth_cache_size": "8192",
"protocol_imap": {
"mail_max_userip_connections": "20",
"imap_idle_notify_interval": "24"
}

```

- WHM API 1 Functions - configure background processes killer — This function configures the server's background process killer.

_display_co
nfigurations

get_users_a
uthn_linked
_accounts

link_user_au
thn_provider

set_provider
_client_confi
gurations

set_provider
_display_co
nfigurations

twofactoraut
h_disable_p
olicy

twofactoraut
h_enable_p
olicy

twofactoraut
h_generate_
tfa_config

twofactoraut
h_get_issue
r

twofactoraut
h_get_user_
configs

twofactoraut
h_policy_sta
tus

twofactoraut
h_remove_u
ser_config

twofactoraut
h_set_issuer

twofactoraut
h_set_tfa_c
onfig

unlink_user_
authn_provi
der

validate_logi
n_token

▼ Backups

backup_conf
ig_get

backup_conf
ig_set

backup_dat
e_list

backup_dest
ination_add

backup_dest
ination_dele
te

```
},  
  "metadata": {  
    "result": 1,  
  
    "command": "get_servic  
e_config",  
    "reason": "OK",  
  }  
}
```

- WH
M
API
1
Func
tions
-
get_
all_c
onta
ct_im
porta
nces
—
This
functi
on
lists
the
impo
rtanc
e of
all
appli
catio
n
even
ts in
WH
M's
*Cont
act
Man
ager*
interf
ace (
*Hom
e >>
Serv
er
Cont
acts
>>
Cont
act
Man
ager*)
.

backup_destination_get

backup_destination_list

backup_destination_set

backup_destination_validate

backup_get_transport_status

backup_list_transported

backup_set_list

backup_set_list_combined

backup_skip_users_all

backup_skip_users_all_status

backup_user_list

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgact

toggle_user_backup_status

▼ cPHulk

cphulk_statuses

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk_login_history

```
    "version":1
  }
}
```

▼ Output (XML)

```
<result>
  <metadata>
    <version>1</version>
  </metadata>
  <result>1</result>
  <reason>OK</reason>
  <command>get_service_config</command>
  <data>
    <auth_cache_ttl>3600</auth_cache_ttl>
    <ipv6>on</ipv6>
    <auth_cache_size>8192</auth_cache_size>
    <max_mail_processes>512</max_mail_processes>
    <mail_process_size>256</mail_process_size>
    <expire_trash_ttl>30</expire_trash_ttl>
    <login_processes_count>2</login_processes_count>
    <protocol_imap>
      <imap_idle_notify_interval>24</imap_idle_notify_interval>
    </protocol_imap>
    <mail_max_userip_connections>20</mail_max_userip_connections>
  </data>
</result>
```

- WHM API 1 Functions - get_appconfig_application_list — This function lists registered Applications.

flush_cphulk_login_history_for_ips
get_countries_with_known_ip_ranges
get_cphulk_brutes
get_cphulk_excessive_brutes
get_cphulk_failed_logins
get_cphulk_user_brutes
load_cphulk_config
read_cphulk_records
save_cphulk_config
set_cphulk_config_key

▼ Databases

background_mysql_upgrade_status
current_mysql_version
installable_mysql_versions
latest_available_mysql_version
list_database_users
list_databases
list_mysql_databases_and_users
remote_mysql_create_profile
remote_mysql_create_profile_via_ssh
remote_mysql_delete_profile
remote_mysql_initiate_profile_activation

```
</protocol_imap>  
  
<expire_trash>1</expire_trash>  
  
<ssl_protocols>!SSLv2!  
!SSLv3</ssl_protocols>  
>  
  
<disable_plaintext_auth>no</disable_plaintext_auth>  
  
<login_process_per_connection>no</login_process_per_connection>  
  
<protocol_pop3>  
  
<mail_max_userip_connections>3</mail_max_userip_connections>  
  
</protocol_pop3>  
  
<mdbox_rotate_size>2M</mdbox_rotate_size>  
  
<mailbox_idle_check_interval>30</mailbox_idle_check_interval>  
  
<auth_cache_negative_ttl>3600</auth_cache_negative_ttl>  
  
<login_max_processes_count>50</login_max_processes_count>  
  
<login_process_size>64</login_process_size>  
>  
  
<protocols>imap  
pop3</protocols>  
  
<ssl_cipher_list>  
  
ECDHE-RSA-AES128-GCM-SHA256:ECDHE-ECDSA-AES128-GCM-SHA256:ECDHE
```

ion
remote_mysql_monitor_profile_activation
remote_mysql_read_profile
remote_mysql_read_profiles
remote_mysql_update_profile
remote_mysql_validate_profile
rename_mysql_database
rename_mysql_user
rename_postgresql_database
rename_postgresql_user
set_local_mysql_root_password
set_mysql_password
set_postgresql_password
start_background_mysql_upgrade

▼ DNS


addns
addzonerecord
addzonerecord (Reverse DNS)
dumpzone
editzonerecord
get_nameserver_config
getzonerecord
has_local_authority

```
-RSA-AES256-GCM-SHA384:ECDHE-ECDSA-AES256-GCM-SHA384:DHE-RSA-AES128-GCM-SHA256:DHE-DSS-AES128-GCM-SHA256:kEDH+AESGCM:ECDHE-RSA-AES128-SHA256:ECDHE-ECDSA-AES128-SHA256:ECDSA-AES128-SHA256:CDHE-RSA-AES128-SHA256:CDHE-ECDSA-AES128-SHA256:ECDHE-RSA-AES256-SHA384:ECDHE-ECDSA-AES256-SHA384:ECDHE-RSA-AES256-SHA:ECDHE-ECDSA-AES256-SHA:DHE-RSA-AES128-SHA:DHE-DSS-AES128-SHA256:DHE-RSA-AES256-SHA256:DHE-DSS-AES256-SHA:AES128-GCM-SHA384:AES256-GCM-SHA384:AES128-SHA256:AES256-SHA:AES:CAMELLIA:DES-CBC3-SHA:!aNULL:!eNULL:!EXPORT:!DES:!RC4:!MD5:!PSK:!aECDH:!EDH-DSS-DES-CBC3-SHA:!EDH-RSA-DES-CBC3-SHA:!KRB5-DES-CBC3-SHA
```

</ssl_cipher_list>

<mdbox_rotate_interval>12w</mdbox_rotate_i

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig



EasyApache

ea4_get_cur
rently_install
ed_packages
ea4_get_ea
_pkgs_state
ea4_list_pro
files
ea4_metainf
o
ea4_migrati
on
ea4_pre_mi
grate_check
ea4_recom
mendations
ea4_save_p
rofile
ea4_tomcat
85_add
ea4_tomcat
85_list
ea4_tomcat
85_rem

Parameters

Parameter	Type	Description	Possible values	Example
service	string	Required The service's name.	A valid cPanel & WHM service name. Warning: As of cPanel & WHM version 58, only the dovecot service is compatible with this function.	dovecot

Greylisting

cpgreylist_is
_server_net
block_truste
d
cpgreylist_li
st_entries_f
or_common
_mail_provid
er
cpgreylist_lo
ad_common
_mail_provid

Returns

Note:
Each service outputs a different set of returns and values.

ers_config
 cpgreylist_s
 ave_commo
 n_mail_prov
 iders_config

 cpgreylist_st
 atus

 cpgreylist_tr
 ust_entries_
 for_common
 _mail_provid
 er

 cpgreylist_u
 ntrust_entri
 es_for_comm
 on_mail_pro
 vider

 create_cpgr
 eylist_truste
 d_host

 delete_cpgr
 eylist_truste
 d_host

 disable_cpgr
 eylist

 enable_cpgr
 eylist

 load_cpgreyl
 ist_config

 read_cpgrey
 list_deferred
 _entries

 read_cpgrey
 list_trusted_
 host

 save_cpgrey
 list_config

Return	Type	Description	Possible values	Example
key name	<i>varies</i>	A configuration key's setting. <div style="border: 1px solid black; padding: 5px; width: fit-content; margin: 10px auto;"> <p>Note : The key name is the return's name.</p> </div>	Varies, depending on the service and key.	This is what it sounds like when the doves cry.

▼ Integration

batch

 cpanel

 create_integ
 ration_group

 create_integ
 ration_link

 get_integrati
 on_link_user
 _config

 list_integrati
 on_groups

 list_integrati
 on_links

 remove_inte
 gration_grou
 p

 remove_inte

gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_i
p

get_shared_
ip

ipv6_disable
_account

ipv6_enable
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m

ailbox_messages
expunge_messages_for_mailbox_guid
fetch_dkim_private_keys
fetch_mail_queue
generate_mobileconfig
get_mailbox_status
get_mailbox_status_list
get_unique_recipient_count_per_sender_for_user
get_unique_sender_recipient_count_per_user
get_user_email_forward_destination
hold_outgoing_email
install_dkim_private_keys
install_spf_records
is_sni_supported
list_pops_for
mail_sni_status
rebuild_mail_sni_config
release_outgoing_email
save_spamd_config
set_user_email_forward_destination
suspend_outgoing_email
unsuspend_outgoing_email

validate_currency_installed_exim_config

validate_currency_dkims

validate_currency_ptrs

validate_currency_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_add_rule

modsec_add_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_de
ploy_all_rule
_changes

modsec_de
ploy_rule_ch
anges

modsec_de
ploy_setting
s_changes

modsec_dis
able_rule

modsec_dis
able_vendor

modsec_dis
able_vendor
_configs

modsec_dis
able_vendor
_updates

modsec_dis
card_all_rul
e_changes

modsec_dis
card_rule_c
hanges

modsec_edit
_rule

modsec_en
able_vendor

modsec_en
able_vendor
_configs

modsec_en
able_vendor
_updates

modsec_get
_config_text

modsec_get
_configs

modsec_get
_configs_wit
h_changes_
pending

modsec_get
_log

modsec_get
_rules

modsec_get
_settings

modsec_get
_vendors

modsec_is_i
nstalled

modsec_ma
ke_config_a
ctive

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_disable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_feature_relist

delete_feature_relist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featureli

sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_ove
rride_feature
s_for_user

update_feat
urelist

verify_user_
has_feature

▼ PHP

convert_all_
domains_to
_fpm

get_fpm_co
unt_and_util
ization

is_conversio
n_in_progre
ss

php_get_def
ault_accoun
ts_to_fpm

php_get_ha
ndlers

php_get_im
pacted_dom
ains

php_get_ins
talled_versio
ns

php_get_old
_fpm_flag

php_get_sys
tem_default
_version

php_get_vh
osts_by_ver
sion

php_get_vh
ost_versions

php_ini_get
_content

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version