

How to Run a Manual Backup

[Overview](#)

[Run a manual backup](#)

[Options](#)

[Create a cpmove archive for an account](#)

[Additional documentation](#)

Overview

Use the `/usr/local/cpanel/bin/backup` script to run a backup in WHM via the command line.

Run a manual backup

To run a backup manually, log in to the command line via SSH as the `root` user and run the following command:

```
/usr/local/cpanel/bin/backup
```

Options

The `/usr/local/cpanel/bin/backup` script accepts the following options:

Option	Description	Example
<code>--force</code>	Performs an additional backup, even if the system already contains up-to-date backup files.	<code>/usr/local/cpanel/bin/backup --force</code>
<code>--debug</code>	Runs the backup in the foreground and prints its progress on the command line.	<code>/usr/local/cpanel/bin/backup --debug</code>
<code>--help</code>	Displays additional information.	<code>/usr/local/cpanel/bin/backup --help</code>

Create a cpmove archive for an account

You can use the `/usr/local/cpanel/scripts/pkgacct` script to create a `cpmove` archive for an account. For more information, read [The pkgacct Script](#) documentation.

To use a custom packaging script, perform the following steps:

1. Copy the `/usr/local/cpanel/scripts/pkgacct` file and modify it.
2. Store the modified `pkgacct` file in the `/var/cpanel/lib/Whostmgr/Pkgacct/pkgacct` directory.
3. Run the `/usr/local/cpanel/bin/backup` command with the `--allow-override` flag.

Additional documentation

[Suggested documentation](#) [For cPanel users](#) [For WHM users](#) [For developers](#)

- [How to Create a Custom Transport Script for Backups](#)
- [How to Run a Manual Backup](#)
- [How to Run Backups on Locally-Mounted Remote Filesystems](#)

- [How to Manage Metadata Settings](#)
- [How to Resolve CIFS-mounted Backup Drive Permissions Errors](#)

- [Backup for cPanel](#)
- [Backup Wizard](#)
- [File and Directory Restoration for cPanel](#)

- [The backup_restore_manager Script](#)
- [The backups_create_metadata Script](#)
- [Backup Tarball Contents](#)
- [The backups_list_user_files Script](#)
- [The restorepkg Script](#)

- [WHM API 1 Functions - backup_destination_list](#)
- [WHM API 1 Functions - backup_destination_add](#)
- [WHM API 1 Functions - backup_destination_get](#)
- [WHM API 1 Functions - backup_destination_set](#)
- [WHM API 1 Functions - backup_set_list](#)