

WHM API 1 Functions - read_cphulk_records

Guide to WHM API 1

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Call cPanel API 2 and UAPI

Account Restoration

restore_modules_summary

restore_queue_activate

restore_queue_add_task

restore_queue_clear_all_completed_tasks

restore_queue_clear_all_failed_tasks

restore_queue_clear_all_pending_tasks

restore_queue_clear_all_tasks

restore_queue_clear_completed_task

restore_queue_clear_pending_task

restore_queue_is_active

restore_queue_list_active

restore_queue_list_completed

restore_queue

Description

This function displays a cPHulk list's records.

Examples

JSON API

```
https://hostname.example.com:2087/cpsess#####/json-api/read_cphulk_records?api.version=1&list_name=white
```

XML API

```
https://hostname.example.com:2087/cpsess#####/xml-api/read_cphulk_records?api.version=1&list_name=white
```

Command Line

```
whmapil read_cphulk_records list_name=white
```

Notes:

- Unless otherwise noted, you **must** URI-encode values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

Function information

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.

Notes:

- Scro
- Ycmt
- us20
- or20
-)tc

ue_list_pending
restore_queue_state
restoreaccount
verify_new_username_for_restore

Accounts

accountsummary
applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_mycnf_for_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct

Output (JSON)

```
{  
  "data": {  
    "list_name":  
    "white",  
    "requester_ip":  
    "10.1.4.228",  
  
    "requester_ip_is_whitelisted": 0,  
    "ips_in_list": {  
      "10.10.0.0":  
      null,  
      "10.10.10.11":  
      null  
    }  
  },  
  "metadata": {  
    "version": 1,  
    "reason": "OK",  
    "result": 1,  
    "command":  
    "read_cphulk_records"  
  }  
}
```

Find a function

- WHM API 1 Functions - cphulk_status
— This function returns the status of the cphulk service.

- _id
- verify_new_username
- convert_addon_fetch_conversion_details
 - convert_addon_fetch_domain_details
 - convert_addon_get_conversion_status
 - convert_addon_initiate_conversion
 - convert_addon_list_addon_domains
 - convert_addon_list_conversions
 - api_token_create
 - api_token_list
 - api_token_revoke
 - api_token_update
 - disable_authentication_provider
 - disable_failing_authentication_providers
 - enable_authentication_provider
 - get_available_authentication_providers
 - get_login_url
 - get_provider_client_configurations
 - get_provider_configuration_fields
 - get_provider_display_co

Output (XML)

```

<result>
  <data>

  <list_name>white</list_name>

  <requester_ip>10.1.4.228</requester_ip>

  <requester_ip_is_whitelisted>0</requester_ip_is_whitelisted>

  <ips_in_list><10.10.11.11></10.10.11.11><10.10.0.0></10.10.0.0><10.10.10.11></10.10.10.11></ips_in_list>
  </data>
  <metadata>

  <version>1</version>

  <reason>OK</reason>

  <result>1</result>

  <command>read_cphulk_records</command>
  </metadata>
</result>

```

Note:
Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
list_name	string	Required The cPHulk list's name.	<ul style="list-style-type: none"> • black • white 	white

- WHM API 1 Functions - create_cphulk_record — This function adds a new record or records to cPHulk's white list or black list.
- WHM API 1 Functions - delete_cphulk_record — This function deletes a record or records from cPHulk's white list or black list.

configurations

get_users_authn_linked_accounts

link_user_authn_provider

set_provider_client_configurations

set_provider_display_configurations

twofactorauth_disable_policy

twofactorauth_enable_policy

twofactorauth_generate_tfa_config

twofactorauth_get_issuer

twofactorauth_get_user_configs

twofactorauth_policy_status

twofactorauth_remove_user_config

twofactorauth_set_issuer

twofactorauth_set_tfa_config

unlink_user_authn_provider

validate_login_token

Backups

backup_config_get

backup_config_set

backup_data_list

backup_destination_add

backup_destination_delete

Returns

Return	Type	Description	Possible values	Example
list_name	string	The cPHulk list's name.	<ul style="list-style-type: none"> black white 	white
requester_ip	string	The requester's IP address.	A valid IP address.	10.1.4.228
requester_ip_is_whitelisted	Boolean	Whether the requester's IP address exists on cPHulk's whitelist.	<ul style="list-style-type: none"> 1 — The IP address exists on the whitelist. 0 — The IP address does not exist on the white list. 	1
warning_ip	string	A localized warning message, if the requester's IP address does not exist on the whitelist.	A valid localized string.	The IP address is not on the white list.
ips_in_list	hash	A hash of IP address information.	A hash of the IP address returns.	
IP address	string	The IP address' comment. <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p>Note : The IP address is the return's name.</p> </div> <p>The function returns this value in the <code>ips_in_list</code> hash.</p>	A valid string.	A helpful comment about the IP address.

- WHM API 1 Functions - disable_cphulk - This function disables the cPHulk service.

<ul style="list-style-type: none"> backup_dest_ination_get backup_dest_ination_list backup_dest_ination_set backup_dest_ination_validate backup_get_transport_status backup_list_transported backup_set_list backup_set_list_combined backup_skip_users_all backup_skip_users_all_status backup_user_list convert_and_migrate_from_legacy_config get_users_with_backup_metadata list_cparchive_files start_background_package toggle_user_backup_status 	<p>restart_ssh</p>	<p><i>Boolean</i></p>	<p>Whether you must restart the <code>sshd</code> daemon in order to implement changes.</p> <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : This return only appears if the <code>USEDNSSETTING</code> is yes in the <code>/etc/ssh/ssh_config</code> file.</p> <p>Because Use DNS and cPHulk are incompatible, the system sets the <code>USEDNSSETTING</code> to <code>no</code> when you enable cPHulk.</p> </div>	<ul style="list-style-type: none"> • 1 — You must restart the <code>sshd</code> daemon. • 0 — The system will implement changes without a restart. 	<p>1</p>
<p>▼ cPHulk</p> <ul style="list-style-type: none"> cphulk_status create_cphulk_record delete_cphulk_record disable_cphulk enable_cphulk flush_cphulk_login_history 					

flush_cphulk_login_history_for_ips	warning_ssh	string	A message that explains why you must restart SSH.	A valid string.	The system disabled the UseDNS setting for SSHD in order to add IP addresses to the whitelist. You must restart SSH to implement the change.
get_countries_with_known_ip_ranges			<div style="border: 1px solid orange; padding: 5px;"> <p>Note: This return only appears if the restart_ssh return's value is 1.</p> </div>		
get_cphulk_brutes					
get_cphulk_excessive_brutes					
get_cphulk_failed_logins					
get_cphulk_user_brutes					
load_cphulk_config					
read_cphulk_records					
save_cphulk_config					
set_cphulk_config_key					

▼ Databases

- background_mysql_upgrade_status
- current_mysql_version
- installable_mysql_versions
- latest_available_mysql_version
- list_database_users
- list_databases
- list_mysql_databases_and_users
- remote_mysql_create_profile
- remote_mysql_create_profile_via_ssh
- remote_mysql_delete_profile
- remote_mysql_initiate_profile_activation

ion

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

▼ DNS

adddns

addzonerecord

addzonerecord (Reverse DNS)

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns
listmxs
listzones
lookupnsip
lookupnsips
removezone
record
resetzone
resolvedom
ainname
savemxs
setresolvers
update_nam
eservers_co
nfig

▼ EasyApache

ea4_get_cur
rently_install
ed_packages

ea4_get_ea
_pkgs_state

ea4_list_pro
files

ea4_metainf
o

ea4_migrati
on

ea4_pre_mi
grate_check

ea4_recom
mendations

ea4_save_p
rofile

ea4_tomcat
85_add

ea4_tomcat
85_list

ea4_tomcat
85_rem

▼ Greylisting

cpgreylist_is
_server_net
block_truste
d

cpgreylist_li
st_entries_f
or_common
_mail_provid
er

cpgreylist_lo
ad_common
_mail_provid

ers_config

cpgreylist_s
ave_commo
n_mail_provi
ders_config

cpgreylist_st
atus

cpgreylist_tr
ust_entries_
for_common
_mail_provid
er

cpgreylist_u
ntrust_entrie
s_for_comm
on_mail_pro
vider

create_cpgr
eylist_truste
d_host

delete_cpgr
eylist_truste
d_host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyl
ist_config

read_cpgrey
list_deferred
_entries

read_cpgrey
list_trusted_
host

save_cpgrey
list_config

▼ Integration

batch

cpanel

create_integ
ration_group

create_integ
ration_link

get_integrati
on_link_user
_config

list_integrati
on_groups

list_integrati
on_links

remove_inte
gration_grou
p

remove_inte

gration_link

update_inte
gration_link
_token

▼ IP Addresses

addips

delip

get_public_i
p

get_shared_
ip

ipv6_disable
_account

ipv6_enable
_account

ipv6_range_
add

ipv6_range_
edit

ipv6_range_
list

ipv6_range_
remove

ipv6_range_
usage

listips

nat_checkip

nat_set_pub
lic_ip

setsiteip

▼ Mail

disable_dki
m

disable_mail
_sni

emailtrack_s
earch

emailtrack_s
tats

emailtrack_u
ser_stats

enable_dkim

enable_mail
_sni

ensure_dki
m_keys_exi
st

exim_config
uration_che
ck

expunge_m

mailbox_messages

expunge_messages_for_mailbox_guid

fetch_dkim_private_keys

fetch_mail_queue

generate_mobileconfig

get_mailbox_status

get_mailbox_status_list

get_unique_recipient_count_per_sender_for_user

get_unique_sender_recipient_count_per_user

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for

mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email

unsuspend_outgoing_email

validate_currency_installed_exim_configuration

validate_currency_dkims

validate_currency_ptrs

validate_currency_spfs

validate_exim_configuration_syntax

▼ Market

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

▼ ModSecurity™

modsec_added_rule

modsec_added_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_de
ploy_all_rule
_changes

modsec_de
ploy_rule_ch
anges

modsec_de
ploy_setting
s_changes

modsec_dis
able_rule

modsec_dis
able_vendor

modsec_dis
able_vendor
_configs

modsec_dis
able_vendor
_updates

modsec_dis
card_all_rul
e_changes

modsec_dis
card_rule_c
hanges

modsec_edit
_rule

modsec_en
able_vendor

modsec_en
able_vendor
_configs

modsec_en
able_vendor
_updates

modsec_get
_config_text

modsec_get
_configs

modsec_get
_configs_wit
h_changes_
pending

modsec_get
_log

modsec_get
_rules

modsec_get
_settings

modsec_get
_vendors

modsec_is_i
nstalled

modsec_ma
ke_config_a
ctive

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_disable_rule

modsec_update_vendor

▼ Packages

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_feature_relist

delete_feature_relist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featureli

sts

get_users_f
eatures_sett
ings

getfeaturelis
t

getpkginfo

killpkg

listpkgs

manage_fea
tures

matchpkgs

read_feature
list

remove_ove
rride_featu
res_for_user

update_feat
urelist

verify_user_
has_feature

▼ PHP

convert_all_
domains_to
_fpm

get_fpm_co
unt_and_util
ization

is_conversio
n_in_progre
ss

php_get_def
ault_accoun
ts_to_fpm

php_get_ha
ndlers

php_get_im
pacted_dom
ains

php_get_ins
talled_versio
ns

php_get_old
_fpm_flag

php_get_sys
tem_default
_version

php_get_vh
osts_by_ver
sion

php_get_vh
ost_versions

php_ini_get
_content

php_ini_get
_directives

php_ini_set
_content

php_ini_set
_directives

php_set_def
ault_accoun
ts_to_fpm

php_set_ha
ndler

php_set_old
_fpm_flag

php_set_ses
sion_save_p
ath

php_set_sys
tem_default
_version

php_set_vh
ost_versions

▼ Resellers

acctcounts

get_public_c
ontact

getresellerip
s

listacIs

listresellers

resellerstats

saveacllist

set_public_c
ontact

setacIs

setresellerip
s

setresellerli
mits

setresellerm
ainip

setresellern
ameservers

setresellerp
ackagelimit

setupreselle
r

suspendres
eller

terminateres
eller

unsetuprese

ller

unsuspendr
eseller

▼ RPM

delete_rpm_
version

edit_rpm_ve
rsion

get_rpm_ver
sion_data

install_rpm_
plugin

list_rpms

package_m
anager_fixc
ache

package_m
anager_get_
build_log

package_m
anager_get_
package_inf
o

package_m
anager_is_p
erforming_a
ctions

package_m
anager_list_
packages

package_m
anager_reso
lve_actions

package_m
anager_sub
mit_actions

package_m
anager_upgr
ade

uninstall_rp
m_plugin

▼ Script Hooks

delete_hook

edit_hook

list_hooks

reorder_hoo
ks

▼ Security

accesshash

authorizessh
key

check_remo
te_ssh_conn
ection

convertopen
sshtoputty

deletesshke
y

fetch_securi
ty_advice

generatessh
keypair

importsshke
y

listsshkeys

▼ Server

Administration

add_configcl
usterserver

configureba
ckgroundpro
cesskiller

configureser
vice

cors_proxy_
get

create_user
_session

delete_confi
gclusterserv
er

enable_mon
itor_all_ena
bled_service
s

get_all_cont
act_importa
nces

get_appconf
ig_applicatio
n_list

get_applicati
on_contact_
event_import
tance

get_applicati
on_contact_
importance

get_availabl
e_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_has
h

get_service_
config

get_service_
config_key

get_tcp4_so
ckets

get_tcp6_so
ckets

get_tweakse
tting

get_udp4_s
ockets

get_udp6_s
ockets

get_update_
availability

get_users_li
nks

getdiskusag
e

gethostname

is_role_ena
bled

list_configcl
usterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a
_license

reboot

remove_in_
progress_ex
im_config_e
dit

restartservic
e

restore_conf
ig_from_file

restore_conf
ig_from_upl
oad

run_cpkeyclt

send_test_p
osturl

send_test_p
ushbullet_n
ote

servicestatu

s

set_applicati
on_contact_
event_imp
ortance

set_applicati
on_contact_
importance

set_primary
_servernam
e

set_service_
config_key

set_tweakse
tting

sethostname

setminimum
passwordstr
engths

start_profile
_activation

system_nee
ds_reboot

systemloada
vg

update_conf
igclusterserv
er

update_cont
act_email

verify_aim_a
ccess

verify_icq_a
ccess

verify_oscar
_access

verify_postu
rl_access

verify_pushb
ullet_access

▼ SSL

disable_aut
ossl

fetch_servic
e_ssl_comp
onents

fetch_ssl_ce
rtificates_for
_fqdns

fetch_ssl_vh
osts

fetch_vhost
_ssl_compo
nents

fetchcrtinfo
fetchsslinfo
generatessl
get_autossl
_check_schedule
get_autossl
_log
get_autossl
_logs_catalog
get_autossl
_metadata
get_autossl
_pending_queue
get_autossl
_pending_queue_for_domain
get_autossl
_pending_queue_for_user
get_autossl
_problems_for_domain
get_autossl
_problems_for_user
get_autossl
_providers
get_best_ssl
domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall
edssldb
rebuildusers
sldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key

set_autossl_
provider

start_autossl_
check_for_
all_users

start_autossl_
check_for_
one_user

▼ Styles and Themes

generate_cp
anel_plugin

list_styles

load_style

remove_log
o

remove_styl
e

save_style

set_default

▼ Support Tickets

ticket_creat
e_stub_ticke
t

ticket_get_s
upport_agre
ement

ticket_get_s
upport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revok
e

ticket_ssh_t
est

ticket_ssh_t
est_start

ticket_updat
e_service_a
greement_a
pproval

ticket_valida
te_oauth2_c
ode

ticket_whitel
ist_check

ticket_whitel
ist_setup

ticket_whitel
ist_unsetup

▼ Transfers

abort_transf
er_session

analyze_tra
nsfer_sessio
n_remote

available_tr
ansfer_mod
ules

create_remo
te_root_tran
sfer_session

create_remo
te_user_tran
sfer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transf
er_session_l
og

get_transfer
_session_st
ate

pause_trans
fer_session

remote_basi
c_credential
_check

retrieve_tran
sfer_session
_remote_an
alysis

start_transfe
r_session

transfer_mo
dule_schem
a

validate_sys
tem_user

▼ Updates

accept_eula

get_availabl
e_tiers

get_current_
lts_expiratio
n_status

get_lts_wex
pire

getlongterm
support

installed_ver
sions

set_cpanel_
updates

set_tier

update_upd
ateconf

version