

cPanel API 2 Functions - MysqlFE::userdbprivs

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

AddonDomain:: adddondomain

main:: adddondomain

AddonDomain:: deladdondomain

AddonDomain:: listaddondomains

Backups

Backups:: listfullbackups

Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbwdata

Bandwidth:: gethourlyaveragebwoveryear

BoxTrapper

BoxTrapper:: accountmanagelist

Branding

Branding:: addbrandingobj

Branding:: applist

Branding:: brandingeditor

Branding:: createpkg

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpkg

Branding:: gensprites

Description

This function lists a user's privileges on a MySQL® database.

Warning:

- This function is currently deprecated and does not function. We **strongly** recommend that you use the `MysqlFE::getdbuserprivileges` function.
- We **strongly** recommend that you use UAPI instead of cPanel API 2. However, no equivalent UAPI function exists.

Important:

In cPanel & WHM version 76 and later, when you disable the MySQL role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

[Addondomain](#)

Examples

WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=MysqlFE&cpanel_jsonapi_function=userdbprivs&db=example_db1&dbuser=example_user1
```

Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

About this module

The MysqlFE module manages MySQL® databases, users, and services.

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpkgs

Branding:: spritelist

▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

CSVImport:: uploadimport

▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List privileges  
for "example_user1"  
on "example_db1"  
$list_privs =  
$cpanel->api2(  
    'MySQLFE',  
    'userdbprivs',  
    array(  
        'db' =>  
        'example_db1',  
        'dbuser' =>  
        'example_user1',  
    )  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

Notes:

- The
Fe

int
• Ur
mi
us
or
20
)'.
20
or
20
).

Find a function

- Contactus:: isenab led
 - Contactus:: sendc ontact
 - Cron:: add_line
 - Cron:: edit_line
 - Cron:: fetchcron
 - Cron:: get_email
 - Cron:: listcron
 - Cron:: remove_line
 - Cron:: set_email
 - CustInfo:: contacte mails
 - CustInfo:: contactp refs
 - CustInfo:: displayc ontactinfo
 - CustInfo:: savecon tactinfo
 - DBmap:: status
 - DBmap:: version
 - DKIMUI:: available
 - DKIMUI:: getrecor ds
 - DKIMUI:: install
 - DKIMUI:: installed
 - DKIMUI:: uninstall
 - DenyIp:: listdenyip s
 - DiskCounter:: disk _counter
 - DiskUsage:: buildc ache
 - DiskUsage:: clearc ache
 - DiskUsage:: fetch_ raw_disk_usage
 - DiskUsage:: fetchd iskusage
 - DiskUsage:: fetchd iskusagewithextras

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# List privileges for
"example_user1" on
"example_db1"
my $list_privs =
$cpliveapi->api2(
'MysqlFE',
'userdbprivs',
{
'db' =>
'example_db1',
'dbuser' =>
'example_user1',
}
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

cPanel Tag System (deprecated)

Warnings:

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecat ed**. We **strongly** recommend that you **only** use the LiveAPI system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our LiveAPI.
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Dep recated cPanel Tag Usage](#) docume ntation.

- cPan el API 2 Mod ules - Mysq lFE — The Mysq lFE mod ule man ages MyS QL® data base s, user s, and servi ces.
- cPan el API 2 Func tions - Mysq lFE:: auth orize host — This functi on auth orize s a host for remo te acce ss to the acco unt's data base .

▼ DnsLookup

DnsLookup:: name
2ip

▼ DomainLookup

DomainLookup:: c
ountbaseddomains

DomainLookup:: g
etbaseddomains

DomainLookup:: g
etdocroot

DomainLookup:: g
etdocroots

DomainLookup:: g
etmaindomain

▼ Email

Email:: accountna
me

Email:: adddomain
forward

Email:: addforward

Email:: addmx

Email:: addpop

Email:: browsebox
es

Email:: changemx

Email:: checkmain
discard

Email:: clearpopca
che

Email:: deletefilter

Email:: delforward

Email:: delmx

Email:: delpop

Email:: disablefilter

Email:: editquota

Email:: enablefilter

Email:: fetchautore
sponder

Email:: fetchcharm
aps

Email:: filteractions

Email:: filterlist

Email:: filtername

Email:: filterrules

Email:: get_archivi
ng_configuration

Email:: get_archivi
ng_default_configu

▼ Command Line

```
cpapi2
--user=username
MysqlFE userdbprivs
db=example_db1
dbuser=example_user1
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- You **must** run the --user=username command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the cpapi2 --help command.
- If you run CloudLinux™, you **must** use the full path of the cpapi2 command:

```
/usr/local
/cpanel/bi
n/cpapi2
```

▼ Output (JSON)

```
{
  "cpanelresult": {
    "apiversion": 2,
    "func":
    "userdbprivs",
    "data": [
      {
        "DELETE": 1,
        "EXECUTE": 1
      }
    ],
    "event": {
      "result": 1
    },
    "module":
    "MysqlFE"
  }
}
```

- cPanel API 2 Functions - MysqlFE:: changdbuser password

— This function changes a database user's password.

- cPanel API 2 Functions - MysqlFE:: create

edb — This function creates a database.

- cPanel API 2 Functions - MysqlFE:: create

eduser — This function creates a database user.

ration

Email: `get_archiving_types`

Email: `get_default_email_quota`

Email: `get_email_signing`

Email: `get_max_email_quota`

Email: `getabsbrowsedir`

Email: `getalwaysaccept`

Email: `getdiskusage`

Email: `getmxcheck`

Email: `has_delegated_mailman_lists`

Email: `list_system_filter_info`

Email: `listaliasesbackups`

Email: `listautoresponders`

Email: `listdefaultaddresses`

Email: `listdomainforwards`

Email: `listfilterbackups`

Email: `listfilters`

Email: `listforwards`

Email: `listlists`

Email: `listmaildomains`

Email: `listmx`

Email: `listmxs`

Email: `listpops`

Email: `listpopssingle`

Email: `listpopswithdisk`

Email: `listpopswithimage`

Email: `loadfilter`

Email: `passwdpop`

Email: `reorderfilters`

Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
db	<i>string</i>	Required The database name.	A valid database name.	example_db1
dbuser	<i>string</i>	Required The database username.	A valid database username	example_user1

Returns

Note:

This function's Boolean values only return if the database user has privileges for that database. If the value is 0, the function will not return that value.

Return	Type	Description	Possible values	Example
ALL PRIVILEGES	<i>Boolean</i>	Whether the user has all privileges on the database.	<ul style="list-style-type: none">1 — The user has all privileges.	1
ALTER	<i>Boolean</i>	Whether the user has this privilege on the database.	<ul style="list-style-type: none">1 — The user has this privilege.	1
ALTER ROUTINE	<i>Boolean</i>	Whether the user has this privilege on the database.	<ul style="list-style-type: none">1 — The user has this privilege.	1
CREATE	<i>Boolean</i>	Whether the user has this privilege on the database.	<ul style="list-style-type: none">1 — The user has this privilege.	1
CREATE ROUTINE	<i>Boolean</i>	Whether the user has this privilege on the database.	<ul style="list-style-type: none">1 — The user has this privilege.	1
CREATE TEMPORARY TABLES	<i>Boolean</i>	Whether the user has this privilege on the database.	<ul style="list-style-type: none">1 — The user has this privilege.	1

Email:: [set_archiving_configuration](#)

Email:: [set_archiving_default_configuration](#)

Email:: [set_email_signing](#)

Email:: [setalwaysaccept](#)

Email:: [setdefaultaddress](#)

Email:: [setmxcheck](#)

Email:: [storefilter](#)

Email:: [tracefilter](#)

▼ [EmailTrack](#)

EmailTrack:: [search](#)

EmailTrack:: [stats](#)

EmailTrack:: [trace](#)

▼ [Encoding](#)

Encoding:: [get_encodings](#)

Encoding:: [guess_file](#)

Encoding:: [guess_file_opts](#)

▼ [FSTest](#)

FSTest:: [dirisempty](#)

▼ [Fileman](#)

Fileman:: [autocomplete_dir](#)

Fileman:: [fileop](#)

Fileman:: [getabsdir](#)

Fileman:: [getdir](#)

Fileman:: [getdiractions](#)

Fileman:: [getdiskinfo](#)

Fileman:: [getedittype](#)

Fileman:: [getfileactions](#)

Fileman:: [getpath](#)

Fileman:: [listfiles](#)

Fileman:: [mkdir](#)

Fileman:: [mkfile](#)

Fileman:: [savefile](#)

CREATE VIEW	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
DELETE	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
DROP	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
EVENT	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
EXECUTE	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
INDEX	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
INSERT	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
LOCK TABLES	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
REFERENCES	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
SELECT	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
SHOW VIEW	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
TRIGGER	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1
UPDATE	<i>Boolean</i>	Whether the user has this privilege on the database.	• 1 — The user has this privilege.	1

- Fileman:: [search](#)
- Fileman:: [statfiles](#)
- Fileman:: [uploadfiles](#)
- Fileman:: [viewfile](#)
- ▼ [ForcePassword](#)
 - ForcePassword:: [get_force_password_flags](#)
 - ForcePassword:: [update_force_password_flags](#)
- ▼ [Frontpage](#)
 - Frontpage:: [fpenabled](#)
 - Frontpage:: [list](#)
- ▼ [Ftp](#)
 - Ftp:: [addftp](#)
 - Ftp:: [delftp](#)
 - Ftp:: [listftp](#)
 - Ftp:: [listftpsessions](#)
 - Ftp:: [listftpwithdisk](#)
 - Ftp:: [passwd](#)
 - Ftp:: [setquota](#)
- ▼ [Gpg](#)
 - Gpg:: [listpgpkeys](#)
 - Gpg:: [listsecretgpgkeys](#)
 - Gpg:: [number_of_private_keys](#)
 - Gpg:: [number_of_public_keys](#)
- ▼ [Htaccess](#)
 - Htaccess:: [listuser](#)
 - Htaccess:: [listusers](#)
- ▼ [HttpUtils](#)
 - HttpUtils:: [getdirindices](#)
- ▼ [ImageManager](#)
 - ImageManager:: [thumbnail](#)
- ▼ [LVEInfo](#)
 - LVEInfo:: [getUsage](#)
- ▼ [LangMods](#)
 - LangMods:: [getarcname](#)
 - LangMods:: [getkey](#)

reason	<i>string</i>	A reason for failure. <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;">Note : This function only returns a reason value if it failed.</div>	A string that describes the error.	This is an error message.
result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"> • 1 — The function succeeded. • 0 — The function failed. 	1

LangMods:: getpre
fix

LangMods:: install

LangMods:: langlis
t

LangMods:: list_av
ailable

LangMods:: list_in
stalled

LangMods:: magic
_status

LangMods:: pre_ru
n

LangMods:: search

LangMods:: setup

LangMods:: uninst
all

LangMods:: updat
e

▼ LeechProtect

LeechProtect:: set
up

▼ Locale

Locale:: get_encod
ing

Locale:: get_html_
dir_attr

Locale:: get_locale
_name

Locale:: get_user_
locale

Locale:: get_user_
locale_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse
r

Logaholic:: adduse
rprofile

Logaholic:: deleteu
ser

Logaholic:: deleteu
serprofile

Logaholic:: edituse
r

Logaholic:: fetchus
er

Logaholic:: listuser
profiles

Logaholic:: logahol
iclink

Logaholic:: proces
sstats

▼ Mime

Mime:: list_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectname

Mime:: redirecturlname

▼ MysqlFE

MysqlFE:: authorizehost

MysqlFE:: change
dbuserpassword

MysqlFE:: createdb

MysqlFE:: createdbuser

MysqlFE:: dbuserexists

MysqlFE:: deauthorizehost

MysqlFE:: deletedb

MysqlFE:: deletedbuser

MysqlFE:: getalldb
sinfo

MysqlFE:: getalldb
usersanddbs

MysqlFE:: getdbuserprivileges

MysqlFE:: getdbusers

MysqlFE:: gethosts

MysqlFE:: getmysqlprivileges

MysqlFE:: getmysqlserverprivileges

MysqlFE:: has_my
cnf_for_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsback
up

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers
indb

MysqlFE:: revoked
buserprivileges

MysqlFE:: setdbu
sprivileges

MysqlFE:: userdbp
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f
etch_slow_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does_news
_exist

News:: does_news
_type_exist

News:: get_news

▼ PHPINI

PHPINI:: getallopti
ons

PHPINI:: getoption
s

▼ Park

Park:: listaddondo
mains

Park:: listparkeddo
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change_
password

Passwd:: set_dige
st_auth

▼ PasswdStrength

PasswdStrength::
appstrengths

PasswdStrength::
get_password_stre
ngth

PasswdStrength::
get_required_stren
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers
indb

Postgres:: userexi
sts

▼ Rand

Rand:: getranddat
a

▼ Resellers

Resellers:: get_su
b_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewri
te

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartap
p

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: a
ddip

SourceIPCheck:: d
elip

SourceIPCheck:: g
etaccount

SourceIPCheck:: li
stips

SourceIPCheck:: l
oadsecquestions

SourceIPCheck:: r
esetsecquestions

SourceIPCheck:: s
amplequestions

SourceIPCheck:: s
avesecquestions

▼ SPFUJ

SPFUJ:: available

SPFUJ:: count_sett
ings

SPFUI:: entries_co
mplete

SPFUI:: get_raw_r
ecord

SPFUI:: getmainse
rverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settin
gs

SPFUI:: load_curr
ent_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopp
k

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_leg
acy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcabundl
e

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearc
ache

▼ Stats

Stats:: getmonthly

bandwidth

Stats:: getmonthly
domainbandwidth

Stats:: getthismont
hsbwusage

Stats:: lastapache
hits

Stats:: lastvisitors

Stats:: listanalog

Stats:: listawstats

Stats:: listlastvisito
rs

Stats:: listrawlogs

Stats:: listurchin

Stats:: listwebalize
r

▼ StatsBar

StatsBar:: getrowc
ounter

StatsBar:: rowcoun
ter

StatsBar:: setrowc
ounter

StatsBar:: stat

▼ SubDomain

SubDomain:: adds
ubdomain

SubDomain:: chan
gedocroot

SubDomain:: delsu
bdomain

SubDomain:: getre
servedsubdomains

SubDomain:: listsu
bdomains

SubDomain:: validr
egex

▼ Themes

Themes:: apply_n
ew_theme

Themes:: does_cp
anel_theme_exist

Themes:: get_avail
able_themes

Themes:: get_the
mes_list

Themes:: restore_
saved_theme

▼ UI

UI:: dynamicinclud
elist

UI:: includelist

UI:: listform

UI:: paginate

UI:: paginate_list

▼ UserHttpUtils

UserHttpUtils:: get
dirindices

▼ WebDisk

WebDisk:: addweb
disk

WebDisk:: delweb
disk

WebDisk:: hasdige
st

WebDisk:: listwebd
isks

WebDisk:: passwd
webdisk

WebDisk:: set_dig
est_auth

WebDisk:: set_ho
mdir

WebDisk:: set_per
ms

WebDisk:: setstatu
s

▼ WebmailApps

WebmailApps:: list
webmailapps

▼ ZoneEdit

ZoneEdit:: add_zo
ne_record

ZoneEdit:: edit_zo
ne_record

ZoneEdit:: fetch_c
panel_generated_
domains

ZoneEdit:: fetchzo
ne

ZoneEdit:: fetchzo
ne_records

ZoneEdit:: fetchzo
nes

ZoneEdit:: get_zon
e_record

ZoneEdit:: remove
_zone_record

ZoneEdit:: resetzo
ne

