

WHM API 1 Functions - restore_queue_clear_completed_task

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Call cPanel API 2 and UAPI](#)

Description

This function removes a single completed task from the restoration queue.

[restore_modules_summary](#)

[restore_queue_activate](#)

[restore_queue_add_task](#)

[restore_queue_clear_all_completed_tasks](#)

[restore_queue_clear_all_failed_tasks](#)

[restore_queue_clear_all_pending_tasks](#)

[restore_queue_clear_all_tasks](#)

[restore_queue_clear_completed_task](#)

[restore_queue_clear_pending_task](#)

[restore_queue_is_active](#)

[restore_queue_list_active](#)

[restore_queue_list_completed](#)

[restore_queue_list_pending](#)

[restore_queue_state](#)

[restoreaccount](#)

Function information

API

Version:

[WHM API 1](#)

Available in:

WHM 11.38+

Methods:

GET, POST

Required

Parameters:

user, start_time

Return

Format:

s:

JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

[verify_new_username_for_restore](#)
[accountsummary](#)
[applist](#)
[createacct](#)
[domainuserdata](#)
[editquota](#)
[forcepasswordchange](#)
[get_disk_usage](#)
[get_domain_info](#)
[getdomainowner](#)
[has_digest_auth](#)
[has_mycnf_for_cpuser](#)
[limitbw](#)
[list_users](#)
[listaccts](#)
[listlockedaccounts](#)
[listsuspended](#)
[modifyacct](#)
[myprivs](#)
[passwd](#)
[quota_enabled](#)
[removeacct](#)
[set_digest_auth](#)
[showbw](#)
[suspendacct](#)
[unsuspendacct](#)
[untrack_acct_id](#)
[verify_new_username](#)
[convert_addon_fetch_conversion_details](#)
[convert_addon_fetch_domain_details](#)

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/restore_queue_clear_completed_tasks?api.version=1&user=user&start_time=1396065600
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/restore_queue_clear_completed_tasks?api.version=1&user=user&start_time=1396065600
```

```
whmapil restore_queue_clear_completed_tasks user=user start_time=1396065600
```



Notes:

- Unless otherwise noted, you **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

```
{
  "metadata": {
    "version": 1,
    "reason": "OK",
    "result": "1",
    "command": "restore_queue_clear_completed_tasks"
  }
}
```

```
<result>
  <metadata>
    <version>1</version>
    <reason>OK</reason>
    <result>1</result>
    <command>restore_queue_clear_completed_tasks<
  /command>
  </metadata>
</result>
```



Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

• Some functions and parameters may require that you authenticate as the root user.

[convert_addon_get_conversion_status](#)

[convert_addon_initiate_conversion](#)

[convert_addon_list_addon_domains](#)

[convert_addon_list_conversions](#)

[api_token_create](#)

[api_token_list](#)

[api_token_revoke](#)

[api_token_update](#)

[disable_authentication_provider](#)

[disable_failing_authentication_providers](#)

[enable_authentication_provider](#)

[get_available_authentication_providers](#)

[get_login_url](#)

[get_provider_client_configurations](#)

[get_provider_configuration_fields](#)

[get_provider_display_configurations](#)

[get_users_authn_linked_accounts](#)

[link_user_authn_provider](#)

[set_provider_client_configurations](#)

[set_provider_display_configurations](#)

[twofactorauth_disable_policy](#)

[twofactorauth_enable_policy](#)

Parameters

Parameter	Type	Description	Possible values	Example
user	<i>string</i>	Required The account's username.	A valid cPanel account's username.	user
start_time	<i>integer</i>	Required When the restoration queue started the restoration.	A time in Unix time format.	1396065600

Returns

This function only returns metadata.

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

twofactorauth
_generate_tfa_config

twofactorauth
_get_issuer

twofactorauth
_get_user_config

twofactorauth
_policy_status

twofactorauth
_remove_user_config

twofactorauth
_set_issuer

twofactorauth
_set_tfa_config

unlink_user_auth_provider

validate_login_token

backup_config_get

backup_config_set

backup_date_list

backup_destination_add

backup_destination_delete

backup_destination_get

backup_destination_list

backup_destination_set

backup_destination_validate

backup_get_transport_status

backup_list_transported

backup_set_list

backup_set_list_combined

backup_skip_users_all

backup_skip_users_all_status

- [WHM API 1 Sections - Account Restoration](#) — Account Restoration functions allow you to restore cPanel accounts from backups and manage restoration queues.
- [WHM API 1 Functions - restore_queue_activate](#) — This function activates the restore queue.
- [WHM API 1 Functions - restore_queue_add_task](#) — This function restores a user's cPanel account from a backup file.
- [WHM API 1 Functions - restore_queue_clear_all_completed_tasks](#) — This function removes successfully completed tasks from the restoration queue.
- [WHM API 1 Functions - restore_queue_clear_all_failed_tasks](#) — This function removes any failed tasks from the restoration queue.

backup_user
_list

convert_and_
migrate_from
_legacy_conf
ig

get_users_wi
th_backup_m
etadata

list_cparchive
_files

start_backgro
und_pkgacct

toggle_user_
backup_state

cphulk_status

create_cphul
k_record

delete_cphul
k_record

disable_cphu
lk

enable_cphulk

flush_cphulk
_login_history

flush_cphulk
_login_histor
y_for_ips

get_countries
_with_known
_ip_ranges

get_cphulk_b
routes

get_cphulk_e
xcessive_bru
tes

get_cphulk_f
ailed_logins

get_cphulk_u
ser_brutes

load_cphulk_
config

read_cphulk_
records

save_cphulk
_config

set_cphulk_c
onfig_key

background_
mysql_upgra
de_status

current_mysq
l_version

installable_m
ysql_versions

latest_available_mysql_version

list_database_users

list_databases

list_mysql_databases_and_users

remote_mysql_create_profile

remote_mysql_create_profile_via_ssh

remote_mysql_delete_profile

remote_mysql_initiate_profile_activation

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user

rename_postgresql_database

rename_postgresql_user

set_local_mysql_root_password

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

adddns

addzonerecord

addzonerecord (Reverse DNS)
dumpzone
editzonerecord
get_nameserver_config
getzonerecord
has_local_authority
killdns
listmxs
listzones
lookupnsip
lookupnsips
removezonerecord
resetzone
resolvedomainname
savemxs
setresolvers
update_nameservers_config
ea4_get_currently_installed_packages
ea4_get_ea_pkgs_state
ea4_list_profiles
ea4_metainfo
ea4_migration
ea4_pre_migrate_check
ea4_recommendations
ea4_save_profile
ea4_tomcat85_add
ea4_tomcat85_list
ea4_tomcat85_remove
cpgreylist_is_server_netblock_trusted

cpgreylist_list
_entries_for_
common_mail_
provider

cpgreylist_load_
common_
mail_provider_
s_config

cpgreylist_save_
common_
mail_provider_
s_config

cpgreylist_status

cpgreylist_trust_
entries_for_
common_mail_
provider

cpgreylist_untrust_
entries_for_
common_mail_
provider

create_cpgreylist_
trusted_host

delete_cpgreylist_
trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_
config

read_cpgreylist_
deferred_entries

read_cpgreylist_
trusted_hosts

save_cpgreylist_
config

batch

cpanel

create_integration_
group

create_integration_
link

get_integration_
link_user_
config

list_integration_
groups

list_integration_
links

remove_integration_
group

remove_integ
ration_link

update_integ
ration_link_to
ken

addips

delip

get_public_ip

get_shared_ip

ipv6_disable
_account

ipv6_enable_
account

ipv6_range_a
dd

ipv6_range_e
dit

ipv6_range_li
st

ipv6_range_r
emove

ipv6_range_u
sage

listips

nat_checkip

nat_set_publi
c_ip

setsiteip

disable_dkim

disable_mail
_sni

emailtrack_s
earch

emailtrack_st
ats

emailtrack_u
ser_stats

enable_dkim

enable_mail_
sni

ensure_dkim
_keys_exist

exim_configu
ration_check

expunge_mai
lbox_messag
es

expunge_me
ssages_for_
mailbox_guid

fetch_dkim_p
rivate_keys

fetch_mail_queue

generate_mobileconfig

get_mailbox_status

get_mailbox_status_list

get_unique_recipient_count_per_sender_for_user

get_unique_sender_recipient_count_per_user

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for

mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email

unsuspend_outgoing_email

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

disable_market_provider

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

modsec_add_rule

modsec_add_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_deploy_all_rule_changes

modsec_deploy_rule_changes

modsec_deploy_settings_changes

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

modsec_discard_all_rule_changes

modsec_discard_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_upd
ate_vendor

_getpkgexten
sionform

add_override
_features_for
_user

addpkg

addpkgext

changepacka
ge

create_featur
elist

delete_featur
elist

delpkgext

editpkg

get_available
_applications

get_available
_featurelists

get_feature_
metadata

get_feature_
names

get_featurelis
t_data

get_featurelis
ts

get_users_fe
atures_settin
gs

getfeaturelist

getpkginfo

killpkg

listpkgs

manage_feat
ures

matchpkgs

read_featurel
ist

remove_over
ride_features
_for_user

update_featu
relist

verify_user_h
as_feature

convert_all_d
omains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_defaults_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_vhosts_by_version

php_get_vhost_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_set_defaults_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_path

php_set_system_default_version

php_set_vhost_versions

acctcounts

get_public_contact

getresellerips

listaccls

listresellers

resellerstats
saveacllist
set_public_contact
setacis
setresellerips
setresellerlimits
setresellermainip
setresellernameservers
setresellerpackage_limit
setupreseller
suspendresellers
terminatereseller
unsetupreseller
unsuspendreseller
delete_rpm_version
edit_rpm_version
get_rpm_version_data
install_rpm_plugin
list_rpms
package_manager_fixcache
package_manager_get_build_log
package_manager_get_package_info
package_manager_is_performing_actions
package_manager_list_packages
package_manager_resolve_actions
package_manager_submit_actions

package_m
anager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

enable_monit
or_all_enable
d_services

get_all_conta
ct_importanc
es

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_available_profiles
get_current_profile
get_password_strength
get_remote_access_hash
get_service_config
get_service_config_key
get_tcp4_sockets
get_tcp6_sockets
get_tweaksetting
get_udp4_sockets
get_udp6_sockets
get_update_availability
get_users_links
getdiskusage
gethostname
is_role_enabled
list_configclusterservers
loadavg
nvget
nvset
personalization_get
personalization_set
purchase_app_license
reboot
remove_in_progress_exim_config_edit
restartservice
restore_config_from_file
restore_config_from_upload

run_cpkeyctl
send_test_posturl
send_test_pushbullet_note
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_config_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
system_needs_reboot
systemloadavg
update_config_clusterserver
update_contact_email
verify_aim_access
verify_icq_access
verify_oscar_access
verify_posturl_access
verify_pushbullet_access
disable_auto_ssl
fetch_service_ssl_components
fetch_ssl_certificates_forfqdns
fetch_ssl_hosts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_
log

get_autossl_
logs_catalog

get_autossl_
metadata

get_autossl_
pending_que
ue

get_autossl_
pending_que
ue_for_doma
in

get_autossl_
pending_que
ue_for_user

get_autossl_
problems_for
_domain

get_autossl_
problems_for
_user

get_autossl_
providers

get_best_ssl
domain_for_s
ervice

install_servic
e_ssl_certific
ate

installssl

listcrts

rebuildinstall
edssldb

rebuilduserss
ldb

reset_autossl_
_provider

reset_service_
_ssl_certificate

set_autossl_
metadata

set_autossl_
metadata_key

set_autossl_
provider

start_autosl
_check_for_a
ll_users

start_autosl
_check_for_o
ne_user

generate_cp
anel_plugin

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_su
pport_agree
ment

ticket_get_su
pport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remo
te_user_trans
fer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

accept_eula

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version