

Edit MX Entry

(WHM >> Home >> DNS Functions >> Edit MX Entry)

- [Overview](#)
- [How to edit MX entries](#)
- [MX Entries](#)
- [Add and delete MX entry text boxes](#)
- [Additional documentation](#)

Overview

A mail exchanger (MX) entry determines which server receives mail for a domain name. The *Edit MX Entry* interface allows you to configure the entry for each destination mail server.

How to edit MX entries

To edit your server's MX entries, perform the following steps:

1. From the *Choose a Domain to Edit* menu, select the name of the domain for which you wish to configure MX entries.
2. Click *Edit*. A new interface will appear.
3. Select the *Email Routing* setting that you wish to use. For more information, see the [Email Routing](#) table below.
4. Enter the desired settings for each MX entry in the *MX Entries* section.
5. Click *Save*.

Email Routing

You can select any of the following *Email Routing* settings for your mail exchangers:

Setting	Description
<i>Automatically Detect Configuration</i>	<p>Select this setting to allow the system to choose the most appropriate <i>Email Routing</i> setting, based on a query of the MX record.</p> <p>The system queries the MX record and uses the following criteria to determine the <i>Email Routing</i> setting:</p> <ul style="list-style-type: none">• If the lowest priority mail exchanger points to an IP address on this server, the system selects the <i>Local Mail Exchanger</i> setting.• If a mail exchanger with a higher priority points to an IP address on this server, the system selects the <i>Backup Mail Exchanger</i> setting.• If there are no mail exchangers that point to an IP address on this server, the system selects the <i>Remote Mail Exchanger</i> setting. <div><p> Note:</p><p>The system cannot perform automatic detection for this setting if the MX entry does not resolve (for example, if you mistype a domain name or enter one that does not exist). If the MX entry does not resolve and the <i>Email Routing</i> setting is <i>Automatically Detect Configuration</i>, the system generates a warning and defaults to the last known <i>Email Routing</i> setting.</p></div>
<i>Local Mail Exchanger</i>	Select this setting to cause the server to always accept mail for the domain.
<i>Backup Mail Exchanger</i>	Select this setting to cause the server to accept mail for the domain and store it until a higher priority (lower number) mail server becomes available.
<i>Remote Mail Exchanger</i>	Select this setting to cause the server to never accept mail for the domain. <div><p> Note:</p><p>The system always assigns the lowest priority value to <i>Remote Mail Exchanger</i> mail servers.</p></div>

 **Note:**

For the *Automatically Detect Configuration* setting to treat additional IP addresses as local, you **must** add them to the list of local IP addresses. Add IP addresses to the list in WHM's [Configure Remote Service IPs](#) interface (WHM >> Home >> IP Functions >> Configure Remote Service IPs).

MX Entries

You can configure the following values for each MX entry:

Setting	Description
<i>TTL</i>	This integer value specifies the time to live (TTL). TTL indicates how long a particular record remains in memory, in seconds, before it refreshes. This value defaults to 14400.
<i>Priority</i>	This integer value represents the priority order of the mail server, in relation to other MX entries. The lower the <i>Priority</i> value, the higher the server's priority. This value defaults to a value that is 10 higher than the highest existing MX entry's priority. <ul style="list-style-type: none">• The servers with the lowest <i>Priority</i> values act as the primary mail servers.• Servers with higher <i>Priority</i> values serve as secondary mail servers.• If multiple mail servers have the same <i>Priority</i> value, the system distributes mail at that <i>Priority</i> value to those servers randomly.
<i>MX Destination</i>	Enter the name of the mail server (for example, mail.example.com).

Add and delete MX entry text boxes

- To add a new MX entry text box, click *Add Another MX Entry Field*. A new row will appear.
- To delete a row, click *Delete* next to that MX entry.



Note:

The bottom MX entry text box is **always** a new MX entry, and displays the label *(new)* in the furthest right column.

Additional documentation

- [Edit DNS Zone](#)
- [Edit MX Entry](#)
- [Add a DNS Zone](#)
- [Delete a DNS Zone](#)
- [Edit Zone Templates](#)