

# UAPI Functions - WebDisk::delete\_user

## Guide to UAPI

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Calls from the WHM API](#)

[Custom UAPI Modules](#)

Backup:: [fullbackup\\_to\\_ftp](#)

Backup:: [fullbackup\\_to\\_homedir](#)

Backup:: [fullbackup\\_to\\_scp\\_with\\_key](#)

Backup:: [fullbackup\\_to\\_scp\\_with\\_password](#)

Backup:: [list\\_backups](#)

Bandwidth:: [get\\_enabled\\_protocols](#)

Bandwidth:: [get\\_retention\\_periods](#)

Bandwidth:: [query](#)

Batch:: [strict](#)

Brand:: [read](#)

Branding:: [file](#)

Branding:: [get\\_applications](#)

Branding:: [get\\_application\\_information](#)

Branding:: [get\\_available\\_applications](#)

Branding:: [get\\_information\\_for\\_applications](#)

Branding:: [image](#)

Branding:: [include](#)

Branding:: [spritelist](#)

CacheBuster:: [read](#)

CacheBuster:: [update](#)

Chkservd:: [get\\_exim\\_ports](#)

## Description

This function deletes a Web Disk account.



### Important:

In cPanel & WHM version 76 and later, when you disable the `webDisk` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

## Examples

```
https://hostname.example.com:2083/cpsess#####/execute/WebDisk/delete_user?user=example1%40example.com&destroy=1
```



### Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.

// Delete the example1 Web Disk user.
$new_password = $cpanel->uapi(
    'WebDisk', 'delete_user',
    array(
        'user' =>
        'example1@example.com',
        'destroy' => '1'
    )
);
```



### Note:

For more information, read our [Guide to the LiveAPI System](#).

## Function information

**Module:**  
WebDisk

**API Version:**  
[UAPI](#)

**Available in:**  
cPanel 54+

**Methods:**  
GET, POST

**Required**

**Parameters:**

user, destroy

**Return Format:**

JSON, XML

**Legacy Equivalents:**

- [WebDisk::delwebdisk](#)

## About this module

The WebDisk module manages Web Disk users, connections, and services.

## About UAPI

UAPI accesses and modifies data for cPanel accounts.



### Notes:

Chkserverd:: [get\\_exit\\_ports\\_ssl](#)

Chrome:: [get\\_domain](#)

Contactus:: [is\\_enabled](#)

cPAddons:: [get\\_available\\_addons](#)

cPAddons:: [get\\_instance\\_settings](#)

cPAddons:: [list\\_addon\\_instances](#)

cPGreyList:: [disable\\_all\\_domains](#)

cPGreyList:: [disable\\_domains](#)

cPGreyList:: [enable\\_all\\_domains](#)

cPGreyList:: [enable\\_domains](#)

cPGreyList:: [has\\_greylisting\\_enabled](#)

cPGreyList:: [list\\_domains](#)

DAV:: [disable\\_shared\\_global\\_addressbook](#)

DAV:: [enable\\_shared\\_global\\_addressbook](#)

DAV:: [get\\_calendar\\_contacts\\_config](#)

DAV:: [has\\_shared\\_global\\_addressbook](#)

DAV:: [is\\_dav\\_service\\_enabled](#)

DAV:: [is\\_horde\\_enabled](#)

DCV:: [check\\_domains\\_via\\_dns](#)

DCV:: [check\\_domains\\_via\\_http](#)

DCV:: [ensure\\_domains\\_can\\_pass\\_dcv](#)

DomainInfo:: [domains\\_data](#)

DomainInfo:: [list\\_domains](#)

DomainInfo:: [main\\_domain\\_builtin\\_subdomain\\_aliases](#)

DomainInfo:: [single\\_domain\\_data](#)

DNS:: [ensure\\_domains\\_reside\\_only\\_locally](#)

```
my $cpliveapi = Cpanel::LiveAPI->new(); # Connect to
cPanel - only do this once.

# Delete the example1 Web Disk user.
my $set_password = $cpliveapi->uapi(
    'WebDisk', 'delete_user',
    {
        'user' =>
        'example1@example.com',
        'destroy' => '1'
    }
);
```



**Note:**

For more information, read our [Guide to the LiveAPI System](#).

```
<!-- Delete the example1 Web Disk user. -->
[% execute( 'WebDisk', 'delete_user', { user =>
'example1@example.com', destroy => '1' } ); %]
```



**Note:**

For more information, read our [Guide to Template Toolkit documentation](#).

```
uapi --user=username WebDisk delete_user user=example1%
40example.com destroy=1
```



**Notes:**

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local/cpanel/bin/uapi
```

• These functions may require specific features. To enable or disable features, use WHM's [Feature Manager](#) interface.

• Unless you call this API with the WHM

[DNS:: has\\_local\\_authority](#)  
[DNSSEC:: disable\\_dnssec](#)  
[DNSSEC:: enable\\_dnssec](#)  
[DNSSEC:: fetch\\_ds\\_records](#)  
[DNSSEC:: set\\_nsec3](#)  
[DNSSEC:: unset\\_nsec3](#)  
[Email:: account\\_name](#)  
[Email:: add\\_auto\\_responder](#)  
[Email:: add\\_domain\\_forwarder](#)  
[Email:: add\\_forwarder](#)  
[Email:: add\\_list](#)  
[Email:: add\\_mailman\\_delegates](#)  
[Email:: add\\_mx](#)  
[Email:: add\\_pop](#)  
[Email:: add\\_spam\\_filter](#)  
[Email:: browse\\_mailbox](#)  
[Email:: change\\_mx](#)  
[Email:: check\\_fastmail](#)  
[Email:: check\\_pipe\\_forwarder](#)  
[Email:: delete\\_auto\\_responder](#)  
[Email:: delete\\_domain\\_forwarder](#)  
[Email:: delete\\_filter](#)  
[Email:: delete\\_forwarder](#)  
[Email:: delete\\_held\\_messages](#)  
[Email:: delete\\_list](#)  
[Email:: delete\\_mx](#)  
[Email:: delete\\_pop](#)  
[Email:: disable\\_filter](#)  
[Email:: disable\\_mailbox\\_autocreate](#)  
[Email:: disable\\_spam\\_assassin](#)

```

{
  "messages":null,
  "errors":null,
  "status":1,
  "metadata":{

  },
  "data":null
}

```

**Note:**

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

## Parameters

Parameter	Type	Description	Possible values	Example
user	string	<b>Required</b> The Web Disk account username.	The username of a Web Disk account on the cPanel account.	example1@example.com
destroy	Boolean	<b>Required</b> Whether to delete the WebDisk account.	<ul style="list-style-type: none"> <li>1 — Confirm deletion of the WebDisk account.</li> <li>0 — Do <b>not</b> delete the WebDisk account.</li> </ul>	1

## Returns

This function only returns metadata.

M  
A  
P  
I  
,  
y  
o  
u  
m  
u  
s  
t  
u  
s  
e  
t  
h  
e  
a  
p  
p  
r  
o  
p  
r  
i  
e  
t  
e  
c  
P  
a  
n  
e  
l  
p  
o  
r  
t  
s  
(  
2  
0  
8  
2  
o  
r  
2  
0  
8  
3  
)  
Y  
o  
u  
c  
a  
n  
a  
l  
s  
o  
c  
a  
l  
l  
s  
o  
m  
e  
f  
u  
n  
c  
t  
i  
o  
n  
s  
v  
i  
a  
c  
P  
a  
n  
e  
l's  
W  
e  
b  
m  
a  
i  
l  
p  
o  
r  
t  
s  
(  
2  
0  
9  
5  
o  
r  
2  
0  
9  
6  
)

Email:: [disable\\_spam\\_autodelete](#)

Email:: [disable\\_spam\\_box](#)

Email:: [dispatch\\_client\\_settings](#)

Email:: [edit\\_pop\\_quota](#)

Email:: [enable\\_filter](#)

Email:: [enable\\_mailbox\\_autocreate](#)

Email:: [enable\\_spam\\_assassin](#)

Email:: [enable\\_spam\\_box](#)

Email:: [fetch\\_charmaps](#)

Email:: [fts\\_rescan\\_mailbox](#)

Email:: [generate\\_mailman\\_opt](#)

Email:: [get\\_auto\\_responder](#)

Email:: [get\\_charsets](#)

Email:: [get\\_client\\_settings](#)

Email:: [get\\_default\\_email\\_quota](#)

Email:: [get\\_default\\_email\\_quota\\_mib](#)

Email:: [get\\_disk\\_usage](#)

Email:: [get\\_filter](#)

Email:: [get\\_held\\_message\\_count](#)

Email:: [get\\_mailbox\\_autocreate](#)

Email:: [get\\_mailman\\_delegates](#)

Email:: [get\\_main\\_account\\_disk\\_usage](#)

Email:: [get\\_main\\_account\\_disk\\_usage\\_bytes](#)

Email:: [get\\_max\\_email\\_quota](#)

Email:: [get\\_max\\_email\\_quota\\_mib](#)

Email:: [get\\_pop\\_quota](#)

Email:: [get\\_spam\\_settings](#)

## Find a function

## Related functions

- [UAPI Modules - WebDisk](#) — The `WebDisk` module manages Web Disk users, connections, and services.
- [UAPI Functions - WebDisk::set\\_homedir](#) — This function changes the home directory for a Web Disk account.
- [UAPI Functions - WebDisk::set\\_password](#) — This function changes the Web Disk account's password.
- [UAPI Functions - WebDisk::set\\_permissions](#) — This function changes the Web Disk home directory's permissions.
- [UAPI Functions - WebDisk::delete\\_user](#) — This function deletes a Web Disk account.

Email: [get\\_webmail\\_settings](#)

Email: [has\\_delegated\\_mailman\\_lists](#)

Email: [has\\_plaintext\\_authentication](#)

Email: [hold\\_outgoing](#)

Email: [is\\_integer](#)

Email: [list\\_auto\\_responders](#)

Email: [list\\_default\\_address](#)

Email: [list\\_domain\\_forwarders](#)

Email: [list\\_filters](#)

Email: [list\\_filters\\_backups](#)

Email: [list\\_forwarders](#)

Email: [list\\_forwarders\\_backups](#)

Email: [list\\_lists](#)

Email: [list\\_mail\\_domains](#)

Email: [list\\_mx](#)

Email: [list\\_pops](#)

Email: [list\\_pops\\_with\\_disk](#)

Email: [list\\_system\\_filter\\_info](#)

Email: [passwd\\_list](#)

Email: [passwd\\_pop](#)

Email: [release\\_outgoing](#)

Email: [remove\\_mailman\\_delegates](#)

Email: [reorder\\_filters](#)

Email: [set\\_always\\_accept](#)

Email: [set\\_default\\_address](#)

Email: [set\\_list\\_privacy\\_options](#)

Email: [stats\\_db\\_status](#)

Email: [store\\_filter](#)

Email: [suspend\\_incoming](#)

Email: [suspend\\_login](#)

Email:: suspend\_outgoing

Email:: trace\_filter

Email:: unsuspend\_incoming

Email:: unsuspend\_login

Email:: unsuspend\_outgoing

Email:: verify\_password

EmailAuth:: disable\_dkim

EmailAuth:: enable\_dkim

EmailAuth:: ensure\_dkim\_keys\_exist

EmailAuth:: fetch\_dkim\_private\_keys

EmailAuth:: install\_dkim\_private\_keys

EmailAuth:: install\_spf\_records

EmailAuth:: validate\_current\_dkims

EmailAuth:: validate\_current\_ptrs

EmailAuth:: validate\_current\_spfs

ExternalAuthentication:: add\_authn\_link

ExternalAuthentication:: configured\_modules

ExternalAuthentication:: get\_authn\_links

ExternalAuthentication:: has\_external\_auth\_modules\_configured

ExternalAuthentication:: remove\_authn\_link

Features:: get\_feature\_metadata

Features:: has\_feature

Features:: list\_features

Fileman:: autocomplete\_dir

Fileman:: empty\_trash

Fileman:: get\_file\_content

Fileman:: [get\\_file\\_information](#)

Fileman:: [list\\_files](#)

Fileman:: [save\\_file\\_content](#)

Fileman:: [transcode](#)

Fileman:: [upload\\_files](#)

Ftp:: [add\\_ftp](#)

Ftp:: [allows\\_anonymous\\_ftp](#)

Ftp:: [allows\\_anonymous\\_ftp\\_incoming](#)

Ftp:: [delete\\_ftp](#)

Ftp:: [ftp\\_exists](#)

Ftp:: [get\\_ftp\\_daemon\\_info](#)

Ftp:: [get\\_port](#)

Ftp:: [get\\_quota](#)

Ftp:: [get\\_welcome\\_message](#)

Ftp:: [kill\\_session](#)

Ftp:: [list\\_ftp](#)

Ftp:: [list\\_ftp\\_with\\_disk](#)

Ftp:: [list\\_sessions](#)

Ftp:: [passwd](#)

Ftp:: [server\\_name](#)

Ftp:: [set\\_anonymous\\_ftp](#)

Ftp:: [set\\_anonymous\\_ftp\\_incoming](#)

Ftp:: [set\\_homedir](#)

Ftp:: [set\\_quota](#)

Ftp:: [set\\_welcome\\_message](#)

Integration:: [fetch\\_url](#)

KnownHosts:: [create](#)

KnownHosts:: [delete](#)

KnownHosts:: [update](#)

KnownHosts:: [verify](#)

LangPHP:: [php\\_get\\_domain\\_handler](#)

LangPHP:: [php\\_get\\_impacted\\_domains](#)

LangPHP:: [php\\_get\\_installed\\_versions](#)

LangPHP:: php\_get  
\_system\_default\_ve  
rsion

LangPHP:: php\_get  
\_vhost\_versions

LangPHP:: php\_ini\_  
get\_user\_basic\_dire  
ctives

LangPHP:: php\_ini\_  
get\_user\_content

LangPHP:: php\_ini\_  
get\_user\_paths

LangPHP:: php\_ini\_  
set\_user\_basic\_dire  
ctives

LangPHP:: php\_ini\_  
set\_user\_content

LangPHP:: php\_set  
\_vhost\_versions

LastLogin:: get\_last  
\_or\_current\_logged  
\_in\_ip

Locale:: get\_attribut  
es

Mailboxes:: expung  
e\_mailbox\_messag  
es

Mailboxes:: expung  
e\_messages\_for\_m  
ailbox\_guid

Mailboxes:: get\_mai  
lbox\_status

Mailboxes:: has\_utf  
8\_mailbox\_names

Mailboxes:: set\_utf8  
\_mailbox\_names

Market:: cancel\_pen  
ding\_ssl\_certificate

Market:: create\_sho  
pping\_cart

Market:: get\_all\_pro  
ducts

Market:: get\_certific  
ate\_status\_details

Market:: get\_login\_u  
rl

Market:: get\_pendin  
g\_ssl\_certificates

Market:: get\_provid  
er\_specific\_dcv\_con  
straints

Market:: get\_provid  
ers\_list

Market:: get\_ssl\_cer  
tificate\_if\_available



Market:: process\_ssl\_pending\_queue

Market:: request\_ssl\_certificates

Market:: set\_status\_of\_pending\_queue\_items

Market:: set\_url\_after\_checkout

Market:: validate\_login\_token

Mime:: add\_handler

Mime:: add\_hotlink

Mime:: add\_mime

Mime:: add\_redirect

Mime:: delete\_handler

Mime:: delete\_hotlink

Mime:: delete\_mime

Mime:: delete\_redirect

Mime:: list\_handlers

Mime:: list\_hotlinks

Mime:: list\_mime

Mime:: list\_redirects

Mime:: redirect\_info

ModSecurity:: disable\_all\_domains

ModSecurity:: disable\_domains

ModSecurity:: enable\_all\_domains

ModSecurity:: enable\_domains

ModSecurity:: has\_modsecurity\_installed

ModSecurity:: list\_domains

Mysql:: add\_host

Mysql:: add\_host\_note

Mysql:: check\_database

Mysql:: create\_database

Mysql:: create\_user

Mysql:: delete\_database

Mysql:: delete\_host

Mysql:: delete\_user

Mysql:: get\_host\_notes

Mysql:: get\_privileges\_on\_database

Mysql:: get\_restrictions

Mysql:: get\_server\_information

Mysql:: locate\_server

Mysql:: rename\_database

Mysql:: rename\_user

Mysql:: repair\_database

Mysql:: revoke\_access\_to\_database

Mysql:: set\_password

Mysql:: set\_privileges\_on\_database

Notifications:: get\_notifications\_count

NVData:: get

NVData:: set

Parser:: firstfile\_relative\_uri

PassengerApps:: disable\_application

PassengerApps:: edit\_application

PassengerApps:: enable\_application

PassengerApps:: ensure\_deps

PassengerApps:: list\_applications

PassengerApps:: register\_application

PassengerApps:: unregister\_application

PasswdStrength:: get\_required\_strength

Personalization::set

Personalization ::get

Postgresql:: create\_database

Postgresql:: create\_user

Postgresql:: delete\_database

Postgresql: [get\\_restrictions](#)

Postgresql: [grant\\_all\\_privileges](#)

Postgresql: [rename\\_database](#)

Postgresql: [rename\\_user](#)

Postgresql: [rename\\_user\\_no\\_password](#)

Postgresql: [revoke\\_all\\_privileges](#)

Postgresql: [set\\_password](#)

Pushbullet: [send\\_test\\_message](#)

Quota: [get\\_quota\\_info](#)

Resellers: [list\\_accounts](#)

ResourceUsage: [get\\_usages](#)

Restore: [directory\\_listing](#)

Restore: [get\\_users](#)

Restore: [query\\_file\\_info](#)

Restore: [restore\\_file](#)

Session: [create\\_temp\\_user](#)

SiteTemplates: [list\\_site\\_templates](#)

SiteTemplates: [list\\_user\\_settings](#)

SiteTemplates: [publish](#)

SpamAssassin: [clear\\_spam\\_box](#)

SpamAssassin: [get\\_symbolic\\_test\\_names](#)

SpamAssassin: [get\\_user\\_preferences](#)

SpamAssassin: [update\\_user\\_preference](#)

SSH: [get\\_port](#)

SSL: [add\\_autossl\\_excluded\\_domains](#)

SSL: [can\\_ssl\\_redirect](#)

SSL: [check\\_shared\\_cert](#)

SSL:: delete\_cert  
SSL:: delete\_csr  
SSL:: delete\_key  
SSL:: delete\_ssl  
SSL:: disable\_mail\_sni  
SSL:: enable\_mail\_sni  
SSL:: fetch\_best\_for\_domain  
SSL:: fetch\_cert\_info  
SSL:: fetch\_certificates\_for\_fqdns  
SSL:: fetch\_key\_and\_cabundle\_for\_certificate  
SSL:: find\_certificates\_for\_key  
SSL:: find\_csrs\_for\_key  
SSL:: generate\_cert  
SSL:: generate\_csr  
SSL:: generate\_key  
SSL:: get\_autossl\_excluded\_domains  
SSL:: get\_autossl\_pending\_queue  
SSL:: get\_autossl\_problems  
SSL:: get\_cabundle  
SSL:: get\_cn\_name  
SSL:: install\_ssl  
SSL:: installed\_host  
SSL:: installed\_hosts  
SSL:: is\_autossl\_check\_in\_progress  
SSL:: is\_mail\_sni\_supported  
SSL:: is\_sni\_supported  
SSL:: list\_certs  
SSL:: list\_csrs  
SSL:: list\_keys  
SSL:: list\_ssl\_items  
SSL:: mail\_sni\_status  
SSL:: rebuild\_mail\_sni\_config

SSL:: rebuildssldb

SSL:: remove\_autossl\_excluded\_domains

SSL:: set\_autossl\_excluded\_domains

SSL:: set\_cert\_friendly\_name

SSL:: set\_csr\_friendly\_name

SSL:: set\_key\_friendly\_name

SSL:: set\_primary\_ssl

SSL:: set\_ssl\_share

SSL:: show\_cert

SSL:: show\_csr

SSL:: show\_key

SSL:: start\_autossl\_check

SSL:: toggle\_ssl\_directs\_for\_domains

SSL:: upload\_cert

SSL:: upload\_key

StatsBar:: get\_stats

Styles:: current

Styles:: list

Styles:: set\_default

Styles:: update

SubDomain:: addsubdomain

Themes:: get\_theme\_base

Themes:: list

Themes:: update

Tokens:: create\_full\_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

TwoFactorAuth:: generate\_user\_configuration

TwoFactorAuth:: get\_user\_configuration

TwoFactorAuth:: remove\_user\_configuration

TwoFactorAuth:: [set\\_user\\_configuration](#)

UserManager:: [check\\_account\\_conflicts](#)

UserManager:: [create\\_user](#)

UserManager:: [delete\\_user](#)

UserManager:: [dismiss\\_user](#)

UserManager:: [edit\\_user](#)

UserManager:: [list\\_users](#)

UserManager:: [lookup\\_service\\_account](#)

UserManager:: [lookup\\_user](#)

UserManager:: [merge\\_service\\_account](#)

UserManager:: [unlink\\_service\\_account](#)

UserTasks:: [delete](#)

UserTasks:: [retrieve](#)

VersionControl:: [create](#)

VersionControl:: [delete](#)

VersionControl:: [retrieve](#)

VersionControl:: [update](#)

VersionControlDeployment:: [create](#)

VersionControlDeployment:: [delete](#)

VersionControlDeployment:: [retrieve](#)

WebDisk:: [delete\\_user](#)

WebDisk:: [set\\_home\\_dir](#)

WebDisk:: [set\\_password](#)

WebDisk:: [set\\_permissions](#)

WebmailApps:: [list\\_emailapps](#)

WebVhost:: [list\\_domains](#)

WebVhost:: [list\\_ssl\\_capable\\_domains](#)

WordPressBackup::  
[any\\_running](#)

WordPressBackup::  
[cancel](#)

WordPressBackup::  
[cleanup](#)

WordPressBackup::  
[get\\_available\\_backups](#)

WordPressBackup::  
[is\\_running](#)

WordPressBackup::  
[start](#)

WordPressInstance  
Manager::[cancel\\_scan](#)

WordPressInstance  
Manager::[cleanup\\_scan](#)

WordPressInstance  
Manager::[change\\_admin\\_password](#)

WordPressInstance  
Manager::[configure\\_autoupdate](#)

WordPressInstance  
Manager::[get\\_api\\_version](#)

WordPressInstance  
Manager::[get\\_instance\\_by\\_id](#)

WordPressInstance  
Manager::[get\\_instances](#)

WordPressInstance  
Manager::[get\\_latest\\_wordpress\\_version\\_from\\_wordpress\\_org](#)

WordPressInstance  
Manager::[get\\_scan\\_results](#)

WordPressInstance  
Manager::[is\\_installable\\_addon\\_available](#)

WordPressInstance  
Manager::[start\\_scan](#)

WordPressRestore::  
[any\\_running](#)

WordPressRestore::  
[cleanup](#)

WordPressRestore::  
[start](#)

