

Guide to WHM Plugins - Uninstall Plugins

Guide to WHM Plugins

Plugin Files

[Installation Scripts](#)

[Interfaces](#)

[Access Control Lists](#)

[ACL Metadata Perl Module](#)

[ACL Object Perl Module](#)

[ACL Reference Chart](#)

[AppConfig Plugin Registration](#)

[Add Plugins](#)

[Checks](#)

[Configuration File](#)

[Uninstall Plugins](#)

Introduction

WHM plugins can include uninstallation scripts, or system administrators can remove them manually. Uninstallation scripts should perform all of the same actions as manual uninstallation.



Note:

cPanel plugin requirements and WHM plugin requirements are **not** identical. For information about cPanel plugins, read our [Guide to cPanel Plugins](#) documentation.

Uninstall a plugin manually

To uninstall or remove a plugin from a cPanel & WHM server, perform the following steps:

1. Manually remove all of the plugin's files **except** for the AppConfig configuration file.
 - We recommend that plugin developers store most plugin files in subdirectories within the `/usr/local/cpanel/3rdparty/` directory. However, many plugins also use or create files outside of this directory.
 - For help to find and remove plugin files, system administrators should contact the plugin's developers.



Important:

If you do **not** remove the plugin's files, the plugin will continue to appear in WHM's interface.

2. Run the following command, where `app` represents either the absolute path to the application's AppConfig configuration file, or the application's internal name:

```
/usr/local/cpanel/bin/unregister_appconfig app
```

This script unregisters applications with AppConfig and removes the application's configuration file from the `/var/cpanel/apps/` directory.



Important:

This script **only** removes third-party applications. It **cannot** remove applications that ship with cPanel & WHM.

Example uninstallation script

The following example BASH uninstallation script performs the necessary actions to uninstall a WHM plugin:

WHM Plugins

About WHM Plugins

- *WHM plugins add custom features to the WHM interface.*
- *In WHM 11.38.1+, you **must** use the AppConfig system to register plugins.*

Compatible with:

- WHM 11.32+

Related Documentation

- [Configure ClamAV Scanner](#)
- [Manage Plugins](#)
- [Guide to WHM Plugins — WHM plugins add new functionality to the WHM interface.](#)
- [Guide to WHM Plugins - AppConfig Registration — Use AppConfig to register plugins with the WHM interface.](#)
- [Guide to WHM Plugins - Access Control Lists — Access Control Lists \(ACLs\) limit the features that WHM users can access.](#)

```
#!/usr/bin/bash

# Remove plugin icons.
/bin/rm -f /usr/local/cpanel/whostmgr/docroot/addon_plugins
/whm_plugin_example.png

# Removing plugin directories
/bin/rm -rf /usr/local/cpanel/whostmgr/docroot/cgi
/whm_example_plugin
/bin/rm -rf /usr/local/cpanel/whostmgr/docroot/templates
/whm_example_plugin

# Unregister the plugin with AppConfig
/usr/local/cpanel/bin/unregister_appconfig /var/cpanel/apps
/whm_example_plugin.conf
```

- Line 4 removes the plugin's icons.
- Lines 7 and 8 remove the plugin's directories.
- Line 11 unregisters the plugin with AppConfig.



Important:

Make **certain** that your script removes **all** of the files for your plugin **except** for the AppConfig configuration file before it unregisters the plugin.