

WHM API 1 Functions - modsec_disable_rule

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Call cPanel API 2 and UAPI](#)

[restore_modules_summary](#)

[restore_queue_activate](#)

[restore_queue_add_task](#)

[restore_queue_clear_all_completed_tasks](#)

[restore_queue_clear_all_failed_tasks](#)

[restore_queue_clear_all_pending_tasks](#)

[restore_queue_clear_all_tasks](#)

[restore_queue_clear_completed_task](#)

[restore_queue_clear_pending_task](#)

[restore_queue_is_active](#)

[restore_queue_list_active](#)

[restore_queue_list_completed](#)

[restore_queue_list_pending](#)

[restore_queue_state](#)

[restoreaccount](#)

[verify_new_username_for_restore](#)

[accountsummary](#)

Description

This function disables a ModSecurity™ rule.



Important:

In cPanel & WHM version 76 and later, when you disable the `webServer` role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/modsec_disable_rule?api.version=1&config=modsec_vendor_configs%2Fexample.conf&id=1234567890
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/modsec_disable_rule?api.version=1&config=modsec_vendor_configs%2Fexample.conf&id=1234567890
```

```
whmapil modsec_disable_rule config=modsec_vendor_configs%5C%2Fexample.conf id=1234567890
```

```
{  "data": {},  "metadata": {    "version": 1,    "reason": "OK",    "result": 1,    "command": "modsec_disable_rule"  }}
```

```
<result>  <data></data>  <metadata>    <command>modsec_disable_rule</command>    <reason>OK</reason>    <result>1</result>    <version>1</version>  </metadata></result>
```



Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Function information

API Version:
WHM API 1
Available in:
WHM 11.46+
Methods:
GET, POST
Required Parameters:
config, id
Return Format:
JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

[applist](#)
[createacct](#)
[domainuserdata](#)
[editquota](#)
[forcepasswordchange](#)
[get_disk_usage](#)
[get_domain_info](#)
[getdomainowner](#)
[has_digest_auth](#)
[has_mycnf_for_cpuser](#)
[limitbw](#)
[list_users](#)
[listaccts](#)
[listlockedaccounts](#)
[listsuspended](#)
[modifyacct](#)
[myprivs](#)
[passwd](#)
[quota_enabled](#)
[removeacct](#)
[set_digest_auth](#)
[showbw](#)
[suspendacct](#)
[unsuspendacct](#)
[untrack_acct_id](#)
[verify_new_username](#)
[convert_addon_fetch_conversion_details](#)
[convert_addon_fetch_domain_details](#)
[convert_addon_get_conversion_status](#)
[convert_addon_initiate_conversion](#)

Parameter	Type	Description	Possible values	Example
config	string	Required The ModSecurity configuration file.	A ModSecurity configuration file's path, relative to the /usr/local/apache/conf/ directory.	modsec_vendor_configs/example.conf
id	string	Required The ModSecurity rule's ID.	A valid ModSecurity rule ID.	1234567890

Returns

This function only returns metadata.

- Some functions and parameters may require that you authenticate as the user.

[convert_addon_list_addons_domains](#)

[convert_addon_list_conversions](#)

[api_token_create](#)

[api_token_list](#)

[api_token_revoke](#)

[api_token_update](#)

[disable_authentication_provider](#)

[disable_failing_authentication_providers](#)

[enable_authentication_provider](#)

[get_available_authentication_providers](#)

[get_login_url](#)

[get_provider_client_configurations](#)

[get_provider_configuration_fields](#)

[get_provider_display_configurations](#)

[get_users_authn_linked_accounts](#)

[link_user_authn_provider](#)

[set_provider_client_configurations](#)

[set_provider_display_configurations](#)

[twofactorauth_disable_policy](#)

[twofactorauth_enable_policy](#)

[twofactorauth_generate_tfa_config](#)

[twofactorauth_get_issuer](#)

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

twofactorauth
_get_user_co
nfigs

twofactorauth
_policy_status

twofactorauth
_remove_use
r_config

twofactorauth
_set_issuer

twofactorauth
_set_tfa_conf
ig

unlink_user_
authn_provid
er

validate_logi
n_token

backup_conf
ig_get

backup_conf
ig_set

backup_date
_list

backup_desti
nation_add

backup_desti
nation_delete

backup_desti
nation_get

backup_desti
nation_list

backup_desti
nation_set

backup_desti
nation_valida
te

backup_get_t
ransport_stat
us

backup_list_t
ransported

backup_set_l
ist

backup_set_l
ist_combined

backup_skip
_users_all

backup_skip
_users_all_st
atus

backup_user
_list

- [WHM API 1 Sections - ModSecurity](#) — ModSecurity functions allow you to manage ModSecurity rules and vendors on your server.
- [WHM API 1 Functions - modsec_add_rule](#) — This function adds a new rule to a ModSecurity™ configuration staging file.
- [WHM API 1 Functions - modsec_add_vendor](#) — This function adds a new ModSecurity™ vendor rule set to the server.
- [WHM API 1 Functions - modsec_batch_settings](#) — This function adds, updates, and removes global ModSecurity™ configuration directives.
- [WHM API 1 Functions - modsec_clone_rule](#) — This function copies a ModSecurity™ rule with a new rule ID.

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

cphulk_status

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk_login_history

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brutes

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_user_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

background_mysql_upgrade_status

current_mysql_version

installable_mysql_versions

latest_available_mysql_version

list_database
_users

list_databases

list_mysql_da
tabases_and
_users

remote_mysq
l_create_profi
le

remote_mysq
l_create_profi
le_via_ssh

remote_mysq
l_delete_profi
le

remote_mysq
l_initiate_prof
ile_activation

remote_mysq
l_monitor_pr
ofile_activation

remote_mysq
l_read_profile

remote_mysq
l_read_profiles

remote_mysq
l_update_pro
file

remote_mysq
l_validate_pr
ofile

rename_mys
ql_database

rename_mys
ql_user

rename_post
gresql_datab
ase

rename_post
gresql_user

set_local_my
sql_root_pas
sword

set_mysql_p
assword

set_postgres
ql_password

start_backgro
und_mysql_u
pgrade

adddns

addzonereco
rd

addzonereco
rd (Reverse
DNS)

dumpzone
editzonerecord
get_nameserver_config
getzonerecord
has_local_authority
killdns
listmxs
listzones
lookupnsip
lookupnsips
removezonerecord
resetzone
resolvedomainname
savemxs
setresolvers
update_nameservers_config
ea4_get_currently_installed_packages
ea4_get_ea_pkgs_state
ea4_list_profiles
ea4_metainfo
ea4_migration
ea4_pre_migrate_check
ea4_recommendations
ea4_save_profile
ea4_tomcat85_add
ea4_tomcat85_list
ea4_tomcat85_remove
cpgreylist_is_server_netblock_trusted
cpgreylist_list_entries_for_common_mail_provider

cpgreylist_lo
ad_common_
mail_provider
s_config

cpgreylist_sa
ve_common_
mail_provider
s_config

cpgreylist_st
atus

cpgreylist_tru
st_entries_for
_common_m
ail_provider

cpgreylist_un
trust_entries_
for_common_
_mail_provid
er

create_cpgr
eylist_trusted_
host

delete_cpgr
eylist_trusted_
host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyli
st_config

read_cpgreyli
st_deferred_
entries

read_cpgreyli
st_trusted_ho
st

save_cpgreyli
st_config

batch

cpanel

create_integr
ation_group

create_integr
ation_link

get_integratio
n_link_user_
config

list_integratio
n_groups

list_integratio
n_links

remove_integ
ration_group

remove_integ
ration_link

update_integ
ration_link_to
ken

addips

delip

get_public_ip

get_shared_ip

ipv6_disable
_account

ipv6_enable_
account

ipv6_range_a
dd

ipv6_range_e
dit

ipv6_range_li
st

ipv6_range_r
emove

ipv6_range_u
sage

listips

nat_checkip

nat_set_publi
c_ip

setsiteip

disable_dkim

disable_mail
_sni

emailtrack_s
earch

emailtrack_st
ats

emailtrack_u
ser_stats

enable_dkim

enable_mail_
sni

ensure_dkim
_keys_exist

exim_configu
ration_check

expunge_mai
lbox_messag
es

expunge_me
ssages_for_
mailbox_guid

fetch_dkim_p
rivate_keys

fetch_mail_q
ueue

generate_mailbox_config

get_mailbox_status

get_mailbox_status_list

get_unique_recipient_count_per_sender_for_user

get_unique_sender_recipient_count_per_user

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for

mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email

unsuspend_outgoing_email

validate_current_installed_exim_config

validate_current_dkims

validate_current_ptrs

validate_current_spfs

validate_exim_configuration_syntax

disable_marketing_provider

enable_mark
et_provider

get_adjusted
_market_pro
viders_produ
cts

get_market_
providers_co
mmission_co
nfig

get_market_
providers_list

get_market_
providers_pr
oduct_metad
ata

get_market_
providers_pr
oducts

set_market_p
roduct_attri
bute

set_market_p
rovider_com
mission_id

modsec_add
_rule

modsec_add
_vendor

modsec_ass
emble_config
_text

modsec_batc
h_settings

modsec_che
ck_rule

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_discard_all_rule_changes

modsec_discard_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_upd
ate_vendor

_getpkgexten
sionform

add_override
_features_for
_user

addpkg

addpkgext

changepacka
ge

create_featur
elist

delete_featur
elist

delpkgext

editpkg

get_available
_applications

get_available
_featurelists

get_feature_
metadata

get_feature_
names

get_featurelis
t_data

get_featurelis
ts

get_users_fe
atures_settin
gs

getfeaturelist

getpkginfo

killpkg

listpkgs

manage_feat
ures

matchpkgs

read_featurel
ist

remove_over
ride_features
_for_user

update_featu
relist

verify_user_h
as_feature

convert_all_d
omains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_defaults_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_versions_by_version

php_get_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_set_defaults_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_path

php_set_system_default_version

php_set_versions

acctcounts

get_public_contact

getresellerips

listaccls

listresellers

resellerstats
saveacllist
set_public_contact
setacis
setresellerips
setresellerlimits
setresellermainip
setresellernameservers
setresellerpackagelimit
setupreseller
suspendresellers
terminatereseller
unsetupreseller
unsuspendreseller
delete_rpm_version
edit_rpm_version
get_rpm_version_data
install_rpm_plugin
list_rpms
package_manager_fixcache
package_manager_get_build_log
package_manager_get_package_info
package_manager_is_performing_actions
package_manager_list_packages
package_manager_resolve_actions
package_manager_submit_actions

package_m
anager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

enable_monit
or_all_enable
d_services

get_all_conta
ct_importanc
es

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_available_profiles
get_current_profile
get_password_strength
get_remote_access_hash
get_service_config
get_service_config_key
get_tcp4_sockets
get_tcp6_sockets
get_tweaksetting
get_udp4_sockets
get_udp6_sockets
get_update_availability
get_users_links
getdiskusage
gethostname
is_role_enabled
list_configclusterservers
loadavg
nvget
nvset
personalization_get
personalization_set
purchase_app_license
reboot
remove_in_progress_exim_config_edit
restartservice
restore_config_from_file
restore_config_from_upload

run_cpkeyctl
send_test_posturl
send_test_pushbullet_note
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_config_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
system_needs_reboot
systemloadavg
update_config_clusterserver
update_contact_email
verify_aim_access
verify_icq_access
verify_oscar_access
verify_posturl_access
verify_pushbullet_access
disable_auto_ssl
fetch_service_ssl_components
fetch_ssl_certificates_forfqdns
fetch_ssl_vhosts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_
log

get_autossl_
logs_catalog

get_autossl_
metadata

get_autossl_
pending_que
ue

get_autossl_
pending_que
ue_for_doma
in

get_autossl_
pending_que
ue_for_user

get_autossl_
problems_for
_domain

get_autossl_
problems_for
_user

get_autossl_
providers

get_best_ssl
domain_for_s
ervice

install_servic
e_ssl_certific
ate

installssl

listcrts

rebuildinstall
edssldb

rebuilduserss
ldb

reset_autossl_
_provider

reset_service_
_ssl_certificate

set_autossl_
metadata

set_autossl_
metadata_key

set_autossl_
provider

start_autosl
_check_for_a
ll_users

start_autosl
_check_for_o
ne_user

generate_cp
anel_plugin

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_su
pport_agree
ment

ticket_get_su
pport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remo
te_user_trans
fer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

accept_eula

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version