

cPanel API 2 Functions - SSH::importkey

Guide to cPanel API 2

[Return Data](#)

[Filter and Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Calls from the WHM API](#)

[cPanel Tags \(deprecated\)](#)

AddonDomain:: [add addondomain](#)

AddonDomain:: [dela ddomdomain](#)

AddonDomain:: [lista ddomdomains](#)

Backups:: [listfullbackups](#)

Bandwidth:: [addhttp bandwidth](#)

Bandwidth:: [getbwdata](#)

Bandwidth:: [gethourlyaveragebwoveryear](#)

BoxTrapper:: [accountmanagelist](#)

Branding:: [addbrandingobj](#)

Branding:: [applist](#)

Branding:: [branding editor](#)

Branding:: [createpkg](#)

Branding:: [cssmerge](#)

Branding:: [delbrandingobj](#)

Branding:: [delpkg](#)

Branding:: [gensprites](#)

Branding:: [getbrandingpkg](#)

Branding:: [getbrandingpkgstatus](#)

Branding:: [getdefaultbrandingpkg](#)

Branding:: [installbrandingpkgs](#)

Branding:: [installimages](#)

Description

This function imports an SSH key.



Important:

This function **will** overwrite any existing keys that use the same name as the imported key.



Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?
cpanel_jsonapi_user=user&cpanel_jsonapi_apiversion=2&cpanel_jsonapi_module=SSH&cpanel_jsonapi_func=importkey&key=-----BEGIN%20RSA%20PRIVATE%20KEY-----%5CnProc-Type%3A%204%2CEncrypted%5CnDEK-Info%3A%20DES-EDE3-CBC%2C8B36FD4196F9015D%5Cn%5CnRttykPEmZu4jTfPzIZkSsfkZaTTXOt3Ho%2BJCqG6HplaCm%2FKibiEBkVUXkC4QLrUL%5CnB%2B%2FifvJN%2BiXYwiYvXLSB5EnVyEuPIjFnnugSIN1Cp84mUlRSyO4DfhPTdWLwr5tP%5CnIYqzPB0cxL2zqX%2BGB8BCx%2FS2NDQ%2FnQWmepKZrod3kasza%2FH580F5103fJlU%2B3WQb%5Cn1YqgOMKeDcatCDgrlc%2FS%2Fqz6xjk%2BHrivnzL%2BETS0av8ZtWEjsjCwvn9N0Gb1TOW%5Cni8uv%2FhPpu6SVZkLub7RUsIEXW44%2B%2FSa6PsSjTq5SLu8C%2FDV8K6x63R%2FRszLES%2BXi%5CnDb1%2BIGPY2JGPjBnje3X4D8QwzEFzFMx24VuwglT21IbYmhyrc5h0oye1mVLGwbV9%5Cn%2FxoLX9iQEjRMzB67zHTU%2F6WfVPhYFSiSoBSCwegtO14R4ZLMby5sdXycKME4wCyJ%5Cn3UFkrI6NH4H0FGte%2BMFjz0SwUy18IO%2Fpxs%2FhScg0ZUK4LbpiA9feB%2FImkxrDW19t%5Cn9b26RWHI%2FK4tT4NUDSB%2BT08UM0hb%2BQ2%2BMbYLDrANTvb4NqazlJsa%2BrwYD3X8%2BHj%5CneTxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfqOwn3D4eltscOS%2B%2BTvATTgo3Qr%5CnXpAmCQ8mfeZjzVDPiWp7XO3EBg3uDqfVe9gPh%2FQ1mTwYOBYHMk3dWNbx1cuovXvc%5CnCFwjJHD8FGHBS%2BEJhscRYW9YfVyuIcb3arZn%2BNk6a8p%2B%2BnLu8yojh5P6iGJviMq%5Cn2Pkk2tgu6Cshy66tFJy0joDo5jsXh5d4WEB1aKojrLI%3D%5Cn-----END%20RSA%20PRIVATE%20KEY-----&name=user&pass=12345luggage
```



Note:

For more information, read our [Calls from the WHM API](#) documentation.

Function information

Module: SSH
API Version: [cPanel API 2](#)
Available in: cPanel 11+
Methods: GET, POST
Required Parameters: key
Return Format: JSON, XML



Notes:

- XML output
- [call this](#)
- [cPanel deprecated XML output](#)

Legacy Equivalents: (none)

About this module

The SSH module manages SSH keys.

About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.



Notes:

Branding:: [killings](#)

Branding:: [listimgtypes](#)

Branding:: [listobjecttypes](#)

Branding:: [preloadconf](#)

Branding:: [resetall](#)

Branding:: [resetcss](#)

Branding:: [resethtml](#)

Branding:: [resolvefile](#)

Branding:: [resolvelocalcss](#)

Branding:: [savelocalcss](#)

Branding:: [setbrandingpkgstatus](#)

Branding:: [showpkgs](#)

Branding:: [spritelist](#)

CSVImport:: [columnchoices](#)

CSVImport:: [configimport](#)

CSVImport:: [data](#)

CSVImport:: [fetchimporadata](#)

CSVImport:: [isenabled](#)

CSVImport:: [loaddata](#)

CSVImport:: [processdata](#)

CSVImport:: [sendcontact](#)

CSVImport:: [uploadimport](#)

Contactus:: [isenabled](#)

Contactus:: [sendcontact](#)

Cron:: [add_line](#)

Cron:: [edit_line](#)

Cron:: [fetchcron](#)

Cron:: [get_email](#)

Cron:: [listcron](#)


Cron:: [remove_line](#)

Cron:: [set_email](#)

CustInfo:: [contactemails](#)

```
$cpanel = new CPANEL(); // Connect to cPanel - only do
this once.

// Import an SSH key
$import_key = $cpanel->api2(
    'SSH', 'importkey',
    array(
        'key' => '-----BEGIN RSA PRIVATE KEY-----\nProc-
Type: 4, ENCRYPTED\nDEK-Info: DES-EDE3-CBC,
8B36FD4196F9015D\n\nRtTykPEmZu4jTfPzIZkSsfkZaTTXOt3Ho+JCqG
6HplaCm/KibiEBkVUXkC4QLrUL\nB+
/IfvJN+iXYwiYvXLSB5EnVyEuPIjFnnugSIN1Cp84mU1RSyO4DfhPTdWLw
r5tP\nIYqzpb0cxL2zqX+GB8BCx/S2NDQ/nQWMepKZrod3kasza
/H580F5103fJlU+3WQb\nlYqgOMKeDcatCDgrlc/S
/qz6xjk+HrivnZL+EQTS0av8ZtWEjsjCwvn9N0Gb1TOW\ni8uv
/hPpu6SVZkLub7RUsIEXW44+/Sa6PssjTq5SLu8C/DV8K6x63R
/RszLES+Xi\nDb1+IGPY2JGPjBnje3X4D8QwzEFzFMx24VuwglT21IbYmh
yrc5h0oyelmVLGwbV9\n/xo1X9iQEjRMzB67zHTU
/6WfVpNYFSiSoBSCwgcgtO14R4ZLMby5sdXycKME4wCyJ\n3UFkrI6NH4H0
FGte+MFjZ0SwUy18IO/pxs/hScg0ZUK4LbpiA9feB
/ImkxrdW19t\n9b26RWHI
/K4tT4NUDSB+T08UM0Hb+Q2+MbYLDranTvb4NqxazlJsa+rwyD3X8+Hj\n
eTxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfqOwn3D4eltscOS++TvAT
Tgo3Qr\nXpAmCQ8mfeZJzVDPiWP7XO3EBg3uDqfVe9gPh
/QlmTWYOBYHMk3dWNbxlcuovXvC\nCFwjJHD8FGHbsC+EJhscRYW9YfVyu
Icb3arZn+Nk6a8p++nLu8yojh5P6iGJviMq\n2Pkk2tgu6Cshy66tFJy0j
oDo5jsXh5d4WEB1aKojrLI=\n-----END RSA PRIVATE KEY-----',
        'name' => 'user',
        'pass' => '12345luggage'
    )
);
```

 **Note:**
For more information, read our [Guide to the LiveAPI System](#).

- These functions may require a feature list. To view with the available features list on a cPanel installation, view the WHM's [Feature Manager](#) interface.
- Unless you can

CustInfo:: [contactprefs](#)

CustInfo:: [displaycontactinfo](#)

CustInfo:: [savecontactinfo](#)

DBmap:: [status](#)

DBmap:: [version](#)

Denylp:: [listdenyips](#)

DiskCounter:: [diskcounter](#)

DiskUsage:: [buildcache](#)

DiskUsage:: [clearcache](#)

DiskUsage:: [fetch_raw_disk_usage](#)

DiskUsage:: [fetchdiskusage](#)

DiskUsage:: [fetchdiskusagewithextras](#)

DKIMUI:: [available](#)

DKIMUI:: [getrecords](#)

DKIMUI:: [install](#)

DKIMUI:: [installed](#)

DKIMUI:: [uninstall](#)

DnsLookup:: [name2ip](#)

DomainLookup:: [countbaseddomains](#)

DomainLookup:: [getbaseddomains](#)

DomainLookup:: [getdocroot](#)

DomainLookup:: [getdocroots](#)

DomainLookup:: [getmaindomain](#)

Email:: [accountname](#)

Email:: [adddomainforward](#)

Email:: [addforward](#)

Email:: [addmx](#)

Email:: [addpop](#)


Email:: [browseboxes](#)


Email:: [changemx](#)

Email:: [checkmaindiscard](#)

```
my $cpliveapi = Cpanel::LiveAPI->new(); # Connect to
cPanel - only do this once.

# Import an SSH key
my $import_key = $cpliveapi->api2(
    'SSH', 'importkey'
    {
        'key' => '-----BEGIN RSA PRIVATE KEY-----\nProc-
Type: 4, ENCRYPTED\nDEK-Info: DES-EDE3-CBC,
8B36FD4196F9015D\n\nRttykPEmZu4jTfPzIZkSsfkZaTTXOt3Ho+JCqG
6HplaCm/KibiEBkVUXkC4QLrUL\nB+
/ifuJN+iXYwiYvXLSB5EnVyEuPIjFnnugSIN1Cp84mU1RSyO4DfhPTdWLw
r5tP\nIYqzpb0cxL2zqX+GB8BCx/S2NDQ/nQWmepKZrod3kasza
/H580F5103fJlU+3WQb\nlYqgOMKeDcatCDgrlc/S
/qz6xjk+HrivnZL+EQTS0av8ZtWEjsjCwvn9N0Gb1TOW\ni8uv
/hPpu6SVZkLub7RUsIEXW44+/Sa6PssjTq5SLu8C/DV8K6x63R
/RszLES+Xi\nDb1+IGPY2JGPjBnje3X4D8QwzEFzFMx24VuwglT21IbYmh
yrc5h0oyelmVLGwbV9\n/xolX9iQEjRMzB67zHTU
/6WfVpNYFSiSoBSCwgcgtO14R4ZLMby5sdXycKME4wCyJ\n3n3VUFkrI6NH4H0
FGte+MFjZ0SwUy18IO/pxs/hScg0ZUk4LbpiA9feB
/ImkxrdW19t\n9b26RWHI
/K4tT4NUDSB+T08UM0Hb+Q2+MbYLDranTvb4NqxazlJsa+rwYD3X8+Hj\n
eTxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfqOwn3D4eltscOS++TvAT
Tgo3Qr\nXpAmCQ8mfeZJzVDPiWP7XO3EBg3uDqfVe9gPh
/QlmTWyOBYHmK3dWNbxlcuovXvC\nCFwjJHD8FGHbsC+EJhscRYW9YfVyu
Icb3arZn+Nk6a8p++nLu8yojh5P6iGJviMq\n2Pkk2tgu6Cshy66tFJy0j
oDo5jsXh5d4WEB1aKojrLI=\n-----END RSA PRIVATE KEY-----',
        'name' => 'user',
        'pass' => '12345luggage'
    }
);
```

 **Note:**
For more information, read our [Guide to the LiveAPI System](#).

 **Warnings:**

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the **LiveAPI** system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

ll
th
s
A
P
I
v
i
a
t
h
e
W
H
M
A
P
I
,
y
o
u
m
u
s
t
u
s
e
t
h
e
a
p
p
r
o
p
r
i
a
t
e
c
P
a
n
e
l
p
o
r
t
s
(
2
0
8
2
o
r
2
0
8
3
).
Y
o
u
c
a
n
a
l
s
o
c
a
l
l
s
o
m
e
f
u
n
c
t
i
o
n
s
v
i
a
c
P
a
n
e
l
s
W
e
b
m
a
i
l
p
o
r

Email: [clearpopcac](#)
[he](#)

Email: [deletefilter](#)

Email: [delforward](#)

Email: [delmx](#)

Email: [delpop](#)

Email: [disablefilter](#)

Email: [editquota](#)

Email: [enablefilter](#)

Email: [fetchautoresponder](#)

Email: [fetchcharmaps](#)

Email: [filteractions](#)

Email: [filterlist](#)

Email: [filtername](#)

Email: [filterrules](#)

Email: [get_archiving_configuration](#)

Email: [get_archiving_default_configuration](#)

Email: [get_archiving_types](#)

Email: [get_default_email_quota](#)

Email: [get_email_sizing](#)

Email: [get_max_email_quota](#)

Email: [getabsbrowse](#)
[edir](#)

Email: [getalwaysaccept](#)

Email: [getdiskusage](#)

Email: [getmxcheck](#)

Email: [has_delegated_mailman_lists](#)

Email: [list_system_filter_info](#)

Email: [listaliasbackups](#)

Email: [listautoresponders](#)

Email: [listdefaultaddresses](#)

Email: [listdomainforwards](#)

Email: [listfilterbackups](#)

```
cpapi2 --user=username SSH importkey key=-----BEGIN RSA
PRIVATE KEY-----\nProc-Type: 4,ENCRYPTED\nDEK-Info: DES-
EDE3-CBC,
8B36FD4196F9015D\n\nRttykPEmZu4jTfPzIzkSsfkZaTtXOt3Ho+JC
qG6HplaCm/KibiEBkVUXkC4QLrUL\nnB+
/ifuVjN+iXYwiYvXLSB5EnVyEuPijFnnugSIN1Cp84mUlRSyO4DfhPTDwLW
r5tP\niYqzpB0cxL2zqX+GB8BCx/S2NDQ/nQWmepKZrod3kasza
/H580F5103fJlU+3WQb\nlYqgOMKeDcatCDgrlc/S
/qz6xjk+HrivnZL+EQTS0av8ZtWEjsjCwvn9N0Gb1TOW\ni8uv
/hPpu6SVZkLub7RUsIEXW44+/Sa6PsSjTq5SLu8C/DV8K6x63R
/Rsz1ES+Xi\nDbl+IGPY2JGPjBnje3X4D8QwzEFzFMx24VuwglT21IbYmh
yrc5h0oyelmVLGwbV9\n/xo1X9iQEjRMzB67zHTU
/6WfVPnyFSiSoBSCwgcgt014R4ZLMby5sdXycKME4wCyJ\nn3UFkrI6NH4H0
FGte+MFjZ0SwUy18IO/pxs/hScg0ZUk4LbpiA9feB
/ImkxrdW19t\n9b26RWHI
/K4tT4NUDSB+T08UM0Hb+Q2+MbYLDrANTvb4NqxazlJsa+rwyD3X8+Hj\n
eTxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfQOwn3D4eltscOS++TvAT
Tgo3Qr\nXpAmCQ8mfeZJzVDPiWP7XO3EBg3uqdfVe9gPh
/QlmTwYOBYHmk3dWNbxlcuovXvC\nCFWjJHD8FGHBS+C+EJhscRYW9YfVyu
Icb3arZn+Nk6a8p++nLu8yojh5P6iGJviMq\nn2Pkk2tgu6Cshy66tFJy0j
oDo5jsXh5d4WEB1aKojrLI=\n-----END RSA PRIVATE KEY-----
name=user pass=12345luggage
```



Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local/cpanel/bin/cpapi2
```

```
{
  "cpanelresult": {
    "apiversion": 2,
    "func": "importkey",
    "data": [
      {
        "name": "bob",
      }
    ],
    "event": {
      "result": 1
    },
    "module": "SSH"
  }
}
```



Note:

Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

```
ts
(2
0
95
o
r
2
0
96
).
```

Find a function

Related functions

- [cPanel API 2 Modules - SSH](#) — The SSH module manages SSH keys.
- [cPanel API 2 Functions - SSH::authkey](#) — This function authorizes an SSH key.
- [cPanel API 2 Functions - SSH::converttoppk](#) — This function converts an SSH key to PuTTY's PPK file format.
- [cPanel API 2 Functions - SSH::delkey](#) — This function deletes an SSH key.
- [cPanel API 2 Functions - SSH::fetchkey](#) — This function retrieves an SSH key.

Email: [listfilters](#)

Email: [listforwards](#)

Email: [listlists](#)

Email: [listmaildomains](#)

Email: [listmx](#)

Email: [listmxs](#)

Email: [listpops](#)

Email: [listpopssingle](#)

Email: [listpopswithdisk](#)

Email: [listpopswithimage](#)

Email: [loadfilter](#)

Email: [passwdpop](#)

Email: [reorderfilters](#)

Email: [set_archiving_configuration](#)

Email: [set_archiving_default_configuration](#)

Email: [set_email_signing](#)

Email: [setalwaysaccept](#)

Email: [setdefaultaddress](#)

Email: [setmxcheck](#)

Email: [storefilter](#)

Email: [tracefilter](#)

EmailTrack: [search](#)

EmailTrack: [stats](#)

EmailTrack: [trace](#)

Encoding: [get_encodings](#)

Encoding: [guess_file](#)

Encoding: [guess_file_opts](#)

Fileman: [autocomplete_dir](#)

Fileman: [fileop](#)

Fileman: [getabsdir](#)

Fileman: [getdir](#)

Fileman: [getdiractions](#)

Fileman: [getdiskinfo](#)

Fileman: [getedittype](#)

Parameters

Parameter	Type	Description	Possible values	Example
key	string	Required The contents of the key file.	A valid SSH key file.	-----BEGIN RSA PRIVATE KEY----- Proc-Type: 4, ENCRYPTED\nDEK-Info: DES-EDE3-CBC, 8B36FD4196F9015D\n\nRttykPEmZu4jTfPzIZkSsfkZaTTXOT3Ho+JCqG6HpIaCm /KibiEBkVUXkC4QLrUL\nB+ /ifvjN+iXYwiYvXLSB5EnVyEuPIjFnnugSINLCP84mU1RSyO4DfhPTdWLwr5tP\nIYqzpb0cxL2zqX+GB8BCx/S2NDQ /nQWMepKZrod3kasza /H580F5103fJlU+3WQb\nlYqgOMKeDcatCDgrlc/S /qz6xjk+HrivnZL+EQTS0av8ZtWEjsjCwvn9N0Gb1TOW\ni8uv /hPpu6SVZkLub7RUsIEXW44+ /Sa6PsSjTq5SLu8C/DV8K6x63R /Rsz1ES+Xi\nDb1+IGPY2JGPjBnje3X4D8QwzEFzFMx24Vuwg1T21IbYmhyrc5h0oyelmVLGwbV9\n\n/xolX9iQEjRMzB67zHTU /6WfVPnYFSiSoBSCwgcg014R4ZLMby5sdXycKME4wCyJ\n3UFkRI6NH4H0FGte+MFjz0SwUy18IO/pxs /hScg0ZUk4LbpiA9feB /ImkxrdW19t\n9b26RWHI /K4tT4NUDSB+T08UM0Hb+Q2+MbyLDrANTvb4NxqazlJsa+rwyD3X8+Hj\nneTxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfQOwn3D4e1tscOS++TvATTgo3Qr\nXpAmCQ8mfeZJzVDPiWp7X03EBg3uDqfVe9gPh /Q1mTwYOBYHMk3dWNbxlcuovXvc\nnCFwJjHD8FGHbSc+EJhscRYW9YfVyuIcb3arZn+Nk6a8p++nLu8yojh5P6iGJviMq\n2Pkk2tgu6Cshy66tFJy0j0Do5jsXh5d4WEB1aKojrLI=\n-----END RSA PRIVATE KEY-----
EmailTrack: search EmailTrack: stats EmailTrack: trace Encoding: get_encodings Encoding: guess_file Encoding: guess_file_opts Fileman: autocomplete_dir Fileman: fileop Fileman: getabsdir Fileman: getdir Fileman: getdiractions Fileman: getdiskinfo Fileman: getedittype	string	The SSH key's filename. If you do not use either the name or pass parameters, the function returns all of the account's keys.	A valid string.	user

Fileman:: [getfileactions](#)

Fileman:: [getpath](#)

Fileman:: [listfiles](#)

Fileman:: [mkdir](#)

Fileman:: [mkfile](#)

Fileman:: [savefile](#)

Fileman:: [search](#)

Fileman:: [statfiles](#)

Fileman:: [uploadfiles](#)

Fileman:: [viewfile](#)

ForcePassword:: [get_force_password_flags](#)

ForcePassword:: [update_force_password_flags](#)

Frontpage:: [fpenabled](#)

Frontpage:: [list](#)

FSTest:: [dirisempty](#)

Ftp:: [addftp](#)

Ftp:: [delftp](#)

Ftp:: [listftp](#)

Ftp:: [listftpsessions](#)

Ftp:: [listftpwithdisk](#)

Ftp:: [passwd](#)

Ftp:: [setquota](#)

Gpg:: [listgpgkeys](#)

Gpg:: [listsecretgpgkeys](#)

Gpg:: [number_of_private_keys](#)

Gpg:: [number_of_public_keys](#)

Htaccess:: [listuser](#)

Htaccess:: [listusers](#)

HttpUtils:: [getdirindices](#)

ImageManager:: [thumbnail](#)

LangMods:: [getarchname](#)

LangMods:: [getkey](#)

LangMods:: [getprefix](#)

LangMods:: [install](#)

LangMods:: [langlist](#)



Note:

You cannot use the following values:

- `confign`
- `known`
- `authentication`
- `authorized`
- `authorizedkeys`
- `environment`
- `rc`
- `identity`



Remember:

This function will overwrite any existing keys that use the same name as the imported key.

LangMods:: [list_available](#)

LangMods:: [list_installed](#)

LangMods:: [magic_status](#)

LangMods:: [pre_run](#)

LangMods:: [search](#)

LangMods:: [setup](#)

LangMods:: [uninstall](#)

LangMods:: [update](#)

LeechProtect:: [setup](#)

Locale:: [get_encoding](#)

Locale:: [get_html_dir_attr](#)

Locale:: [get_locale_name](#)

Locale:: [get_user_locale](#)

Locale:: [get_user_locale_name](#)

Locale:: [numf](#)

Logaholic:: [adduser](#)

Logaholic:: [adduser_profile](#)

Logaholic:: [deleteuser](#)

Logaholic:: [deleteuser_profile](#)

Logaholic:: [edituser](#)

Logaholic:: [fetchuser](#)

Logaholic:: [listuser_profiles](#)

Logaholic:: [logaholic_link](#)

Logaholic:: [process_stats](#)

LVEInfo:: [getUsage](#)

Mime:: [list_hotlinks](#)

Mime:: [listhandlers](#)

Mime:: [listmime](#)

Mime:: [listredirects](#)


Mime:: [redirectname](#)

Mime:: [redirecturlname](#)

MySQLFE:: [authorize_host](#)

pass	<i>string</i>	The SSH key's password. If you do not use either the name or password parameters, the function returns all of the account's keys.	A secure password.	123451uggage
------	---------------	---	--------------------	--------------

Returns

Return	Type	Description	Possible values	Example
name	<i>string</i>	The SSH key's name.	A valid filename.	user
reason	<i>string</i>	A reason for failure. <div style="border: 1px solid #ccc; padding: 5px; margin: 5px 0;"> Note: This function only returns a <code>reason</code> value if it failed.</div>	A string that describes the error.	This is an error message.
result	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none">• 1 — The function succeeded.• 0 — The function failed.	1

MysqlFE:: [changed
buserpassword](#)

MysqlFE:: [createdb](#)

MysqlFE:: [createdb
user](#)

MysqlFE:: [dbuserexi
sts](#)

MysqlFE:: [deauthori
zehost](#)

MysqlFE:: [deletedb](#)

MysqlFE:: [deletedb
user](#)

MysqlFE:: [getalldb
info](#)

MysqlFE:: [getalldb
usersanddbs](#)

MysqlFE:: [getdbuse
rprivileges](#)

MysqlFE:: [getdbuse
rs](#)

MysqlFE:: [gethosts](#)

MysqlFE:: [getmysql
privileges](#)

MysqlFE:: [getmysql
serverprivileges](#)

MysqlFE:: [has_myc
nf_for_cpuser](#)

MysqlFE:: [listdbs](#)

MysqlFE:: [listdbsba
ckup](#)

MysqlFE:: [listhosts](#)

MysqlFE:: [listusers](#)

MysqlFE:: [listusers
ndb](#)

MysqlFE:: [revokedb
userprivileges](#)

MysqlFE:: [setdbuse
rprivileges](#)

MysqlFE:: [userdbpri
vs](#)

MysqlOptimizer:: [fet
ch_slow_queries](#)

Net:: [dnszone](#)

Net:: [traceroute](#)

News:: [does_news_
exist](#)

News:: [does_news_
type_exist](#)

News:: [get_news](#)

NVData:: [get](#)

NVData:: [set](#)

NVData:: [setall](#)

Park:: [listaddondomains](#)

Park:: [listparkedomains](#)

Park:: [park](#)

Park:: [unpark](#)

Passwd:: [change_password](#)

Passwd:: [set_digest_auth](#)

PasswdStrength:: [appstrengths](#)

PasswdStrength:: [get_password_strength](#)

PasswdStrength:: [get_required_strength](#)

PHPINI:: [getaloptions](#)

PHPINI:: [getoptions](#)

Postgres:: [listdbs](#)

Postgres:: [listusers](#)

Postgres:: [listusersinndb](#)

Postgres:: [userexists](#)

Rand:: [getranddata](#)

Resellers:: [get_sub_accounts](#)

RoR:: [addapp](#)

RoR:: [changeapp](#)

RoR:: [importrails](#)

RoR:: [listapps](#)

RoR:: [listrewrites](#)

RoR:: [needsimport](#)

RoR:: [removeapp](#)

RoR:: [removerewrite](#)

RoR:: [restartapp](#)

RoR:: [setuprewrite](#)

RoR:: [softrestartapp](#)

RoR:: [startapp](#)

RoR:: [stopapp](#)

SetLang:: [setlocale](#)

SourceIPCheck:: [addip](#)

SourceIPCheck:: de
lip

SourceIPCheck:: ge
taccount

SourceIPCheck:: list
ips

SourceIPCheck:: lo
adsecquestions

SourceIPCheck:: re
setsecquestions

SourceIPCheck:: sa
mplequestions

SourceIPCheck:: sa
vesecquestions

SPFUI:: available

SPFUI:: count_setti
ngs

SPFUI:: entries_co
mplete

SPFUI:: get_raw_re
cord

SPFUI:: getmainser
verip

SPFUI:: install

SPFUI:: installed

SPFUI:: list_settings

SPFUI:: load_curren
t_values

SPFUI:: uninstall

SSH:: authkey

SSH:: converttoppk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey_legacy

SSH:: importkey

SSH:: listkeys

SSL:: fetchcabundle

SSL:: fetchinfo

SSL:: gencrt

SSL:: genscr

SSL:: genkey

SSL:: getcname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys
SSL:: listsslitems
SSL:: uploadcrt
SSL:: uploadkey
SSLInfo:: fetchinfo
StatCache:: clearcache
Stats:: getmonthlybandwidth
Stats:: getmonthlydomainbandwidth
Stats:: getthismonthsbwusage
Stats:: lastapachehits
Stats:: lastvisitors
Stats:: listanalog
Stats:: listawstats
Stats:: listlastvisitors
Stats:: listrawlogs
Stats:: listurchin
Stats:: listwebalizer
StatsBar:: getrowcounter
StatsBar:: rowcounter
StatsBar:: setrowcounter
StatsBar:: stat
SubDomain:: addsubdomain
SubDomain:: changedocroot
SubDomain:: delsubdomain
SubDomain:: getreservedsubdomains
SubDomain:: listsubdomains
SubDomain:: validategex
Themes:: apply_new_theme
Themes:: does_panel_theme_exist
Themes:: get_available_themes
Themes:: get_themes_list

Themes:: [restore_saved_theme](#)

UI:: [dynamicincludelist](#)

UI:: [includelist](#)

UI:: [listform](#)

UI:: [paginate](#)

UI:: [paginate_list](#)

UserHttpUtils:: [getdirindices](#)

WebDisk:: [addwebdisk](#)

WebDisk:: [delwebdisk](#)

WebDisk:: [hasdigest](#)

WebDisk:: [listwebdisks](#)

WebDisk:: [passwordebdisk](#)

WebDisk:: [set_digest_auth](#)

WebDisk:: [set_home_dir](#)

WebDisk:: [set_perms](#)

WebDisk:: [setstatus](#)

WebmailApps:: [listwebmailapps](#)

ZoneEdit:: [add_zone_record](#)

ZoneEdit:: [edit_zone_record](#)

ZoneEdit:: [fetch_cpanel_generated_domains](#)

ZoneEdit:: [fetchzone](#)

ZoneEdit:: [fetchzone_records](#)

ZoneEdit:: [fetchzones](#)

ZoneEdit:: [get_zone_record](#)

ZoneEdit:: [remove_zone_record](#)

ZoneEdit:: [resetzone](#)